District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico

Submit Original to Appropriate District Office

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

GAS CAPTURE PLAN

ONLINE AFTER FRAC

NA

GAS CAPTURE PLAN

Dat	e: 11-20-18					•	•	
☑ Original			Operator & OGRID No.: Mewbourne Oil Company - 14744					
	Amended - Reason for	Amendment:						
	s Gas Capture Plan ou completion (new drill			-	o reduce we	ll/production	facility flaring/venting	g fo
Note	e: Form C-129 must be su	bmitted and app	proved prior to excee	ding 60 days d	ıllowed by Rul	e (Subsection A	of 19.15.18.12 NMAC).	
We	ll(s)/Production Facil	ity – Name of	facility					
The	well(s) that will be lo	cated at the pro	oduction facility a	re shown in	the table bel	ow.		
	Well Name	API	Well Location	Footages	Expected	Flared or	Comments	
			(ULSTR)		MCF/D	Vented		

Gathering System and Pipeline Notification

Charolais 21/28 B2BO State Com #1H

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in
place. The gas produced from production facility is dedicated to western and will be connected to
Western low/high pressure gathering system located in EDDY County, New Mexico. It will require
3,400 of pipeline to connect the facility to low/high pressure gathering system. Mewbourne Oil Company provides
(periodically) to Western a drilling, completion and estimated first production date for wells that are scheduled to
be drilled in the foreseeable future. In addition, Mewbourne Oil Company and Western have periodic
conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at
Western Processing Plant located in Sec. 36 , Blk. 58 T1S , Culberson County, Texas. The actual flow
of the gas will be based on compression operating parameters and gathering system pressures.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on western system at that time. Based on current information, it is Operator's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - o Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines