Form 3160-5 (June 2015)

## **UNITED STATES** DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED OMB NO. 1004-0137 2018

	Expires: January	31, 2
Lease	Serial No.	
NMN	M136226	

6	If Indian	Allottee or Tribe Name	

Ri	UREAU OF LAND MANAC	REMENT						
SUNDRY NOTICES AND REPORTS ON WELLS  Do not use this form for proposals to drill or to re-enter an					5. Lease Serial No. NMNM136226			
					6. If Indian, Allottee or Tribe Name			
SUBMIT IN 1	TRIPLICATE - Other instr	ructions on	page	1 6 10 18	7. If Unit or CA/Agree	ment, Name and	Vor No.	
I. Type of Well  ☑ Oil Well ☐ Gas Well ☐ Oth			40,1	CEN	8. Well Name and No. BIGGERS FEDER			
2. Name of Operator	Contact:	MMY R LI	NK 🔞	The state of the s	9. API Well No.	0.74		
MATADÓR PRODUCTION CO	JMPANYE-Mail: tiink@matao							
3a. Address 5400 LBJ FREEWAY SUITE 1 DALLAS, TX 75240	1500	Ph: 575-62	(include area code) 7-2465  10. Field and Pool or Exploratory Area DOGIE DRAW-DELAWARE					
4. Location of Well (Footage, Sec., T.	., R., M., or Survey Description)				11. County or Parish,	State		
Sec 18 T25S R35E 353FSL 5 32.124153 N Lat, 103.413445		LEA COUNTY, NM						
12. CHECK THE AF	PPROPRIATE BOX(ES)	TO INDICA	TE NATURE O	F NOTICE,	REPORT, OR OTH	ER DATA		
TYPE OF SUBMISSION			TYPE OF	F ACTION				
☐ Notice of Intent	☐ Acidize	☐ Dee	pen	☐ Product	ion (Start/Resume)	☐ Water Sh	ut-Off	
	☐ Alter Casing	☐ Hyd	raulic Fracturing	ing Reclamation		■ Well Inte	grity	
Subsequent Report	□ Casing Repair	□ New	Construction	□ Recomp	lete	Other		
☐ Final Abandonment Notice	☐ Change Plans	Plug	and Abandon	☐ Tempor	arily Abandon	Drilling Ope	rations	
	☐ Convert to Injection	Plug	Back	☐ Water D	Disposal			
13. Describe Proposed or Completed Ope If the proposal is to deepen directiona Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi	ally or recomplete horizontally, g it will be performed or provide to operations. If the operation rest pandonment Notices must be file	pive subsurface he Bond No. or ults in a multipl	locations and measu a file with BLM/BIA e completion or reco	ared and true ve A. Required sub completion in a r	rtical depths of all pertin sequent reports must be new interval, a Form 316	ent markers and filed within 30 d 0-4 must be filed	zones. lays l once	
BLM BOND NO:NMB0001079 Surety Bond No:RLB0015172			was view Chics					
Drilling Sundry	,		Artesia					
5/25/18 Spud Well					,			
5/26/2018 Surface casing set @ 1,007' 13 3/8" 54.5# J-55. Bump plug 1050 psi good. LD sx 772, LD Yield 1.75, TL SX 501, TL Yield 1.33, TTL SX 1273 Class C. Circulated 176 bbls cmt to surface.  Test casing to 1500 psi; good test.  NIM OIL CONSERV ARTESIA DISTRIC								
5/31/2018 Intermediate 1 @ 5,462', 9 5/8" 40# J-55 bump plug 2050 psi; good test. LD SX 1205, LD NOV 1 4 2018							18	
14. I hereby certify that the foregoing is	true and correct.					RECEIVED	)	
•	Electronic Submission #4 For MATADOR PF	42607 verifie RODUCTION	d by the BLM Well COMPANY, sent	II Information to the Hobbs	System			
Name (Printed/Typed) TAMMY R	nmitted to AFMSS for proces	ssing by PKI		n 11/05/2018 JCTION ANA				
Signature (Electronic S	Submission)		Date 11/05/2	018				
	THIS SPACE FO	R FEDERA	L OR STATE	OFFICE U	SE			
Approved By ACCEPTED			ZOTA STEVENS TitlePETROLEUM ENGINEER Date 1			1/07/2018		
Conditions of approval, if any, are attached certify that the applicant holds legal or equivalent would entitle the applicant to conduct the conduction of t	Office Hobbs							
Title 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent s	U.S.C. Section (\$12, make it a c	rime for any pe	rson knowingly and	willfully to ma	ike to any department or	agency of the Ur	nited	

## Additional data for EC transaction #442607 that would not fit on the form

## 32. Additional remarks, continued

Yield 1.88, TL SX 471, TL Yield 1.38, TTL SX 1676 Class C. Circulated 192 bbls cmt to surface. Test casing to 1500 psi held(good test).

6/10/2018 Intermediate 2 Top, @4448', 7 5/8" 29.70 P-110,LD SX 605, LD Yield 2.21, TL SX 365, TL Yield 1.37, TTL SX 970 Class C and Top of Cement at 3620'. Test casing to 1500 psi and held (good test).

6/10/2018 Intermediate 2M, top of casing @4448, 7 5/8" 29.70 P-110, depth set @12,037'.

6/10/2018 Intermediate 2 BTM, top of casing set at 12,037' and depth set @ 13,000', 7" 29# P-110. Bump plug w/2400 psi. Test casing to 1500 psi, good test.

6/13/2018 RU and pressure test BOP to 250 psi low and 10,000 psi high IBOP, TIW valve, annular preventer to 250 psi low and 5000 psi high, and stand pipe, top drive and mud lines back to pumps at 250 psi low and 6500 psi high. Test casing at 1500 psi for 30 minutes, good test.

6/20/2018 Production top depth set @ 11,956' 5 1/2" 20#, P-110,TL SX 520, TL Yield 1.17, TTL SX 520 Class C. Bump plug w/6,300 psi, Top of Cement @11,500'.

6/20/2018 Production BTM, top of casing @11,956 and depth set @ 17,546', 4 1/2" 13.50# P-110.

6/23/2018 Release Rig.