

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-041-20975
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Amigos de Pancho 11 Fee
8. Well Number 1
9. OGRID Number 372658
10. Pool name or Wildcat Chaveroo; Permo Penn, North

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>	
2. Name of Operator Yates Industries LLC	
3. Address of Operator 403 W. San Francisco St., NM 87505	
4. Well Location Unit Letter O : 330 feet from the South line and 2310 feet from the East line Section 11 Township 7S Range 33E NMPM Roosevelt County	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4360 GL	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

Approved for Plugging of wellbore only. Liability under bond is retained pending restoration and completion of the C-103, Specific for Subsequent Report of Well Plugging, which may be found on the OCD web page under forms.
Restoration Due By **09-25-2019**

☐
☐
☐
☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Drill out intermediate w/ 7 7/8" bit to TD of 8460', and run electric logs. Call Maxey Brown w/ Hobbs NMOCD and discuss P&A on 9/23/2018. Set cmt plugs: 35 sx class H plug @ 8460-8360, 55 sx class H plug @ 6460-6360, 40 sx class H plug 4460-4360, 35 sx class H plug @ 3550-3450, 30 sx class H plug 1910-1810, 30 sx class H plug 475-375, 18 sx surface plug 60 to surface. Cut off wellhead 4' below ground level and weld plate on per conservation agreement w/ pertinent well information. Back fill cellar and clean location, ready for inspection.

All plugs calculated based upon open hole log caliper. All displacement fluid and wellbore fluid between plugs is 10.5 ppg 55 vis mud.

PA'd 09/25/2018

Spud Date:

Rig Release Date:

9/25/2018

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE *John C. May Jr.* TITLE Consulting Pet Engr DATE 11/1/2018

Type or print name _____ E-mail address: _____ PHONE: _____
For State Use Only

APPROVED BY: *Mark Whitelam* TITLE PES DATE 11/27/2018

Conditions of Approval (if any):

* Operator submitted photo of belowground DHM. Info correct.