District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy, Minerals and Natural Resources Department

Submit Original to Appropriate District Office

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

DEC 182018

Date: 12/17/18	r		GAS CA	PTURE PL	AN	F	RECEIVED	
☑ Original □ Amended - F		Amendment:		& OGRID	No.: <u>Manz</u>	AHO, LLC	- 231429	
-			to be taken by the onew zone, re-fra	-	to reduce we	ell/production	n facility flaring/ventin	ıg for
Note: Form C-129	must be sub	mitted and app	proved prior to excee	ding 60 days d	allowed by Rui	le (Subsection)	A of 19.15.18.12 NMAC).	
Well(s)/Produc	tion Facili	ty – Name of	facility					
			oduction facility a	re chown in	the table be	low		
Well Name		API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments	
West Cross San Andre	roads s. Unit		C-5-105-36e	1284, M	200	Flares	WILL NEED TO WANT FOR GAS CONNER	chor-
	30	-029-49	433				No current GAS Connection available	
Gathering Syst	em and Pir	neline Natifi	ration					_
				oack operation	ons are com	olete, if gas tr	ansporter system is in p	olace.
							to Gas Transporter low	
							of pipeline to connec	
							ter a drilling, completion	
estimated first pr	oduction da	ite for wells th	nat are scheduled to	o be drilled in	n the foresee	able future. In	n addition, Operator and	d <u>Gas</u>
	-		_	_	-		Gas from these wells w	
processed at Gas	Transporter	Processing P	lant located in Sec.	, Twn.	, Rng.	,	County, New Mexico). The

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on <u>Gas Transporter</u> system at that time. Based on current information, it is <u>Operator's</u> belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

actual flow of the gas will be based on compression operating parameters and gathering system pressures.

- Power Generation On lease
 - o Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines