Submit 1 Copy To Appropriate District Office	Energy, Minerals and Natural Resources		Form C-103		
<u>District I</u> – (575) 393-6161 1625 N. French Dr., Hobbs, NM 88240			Revised August 1, 2011 WELL API NO.		
<u>District II</u> – (575) 748-1283			30-005-10122		
811 S. First St., Artesia, NM 88210 District III – (505) 334-6178			5. Indicate Type of		
1000 Rio Brazos Rd., Aztec, NM 87410	Santa Fe NM 87505		STATE 🛛 6. State Oil & Gas		
<u>District IV</u> – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM 87505		385 00	B-8638	Lease No.	
(DO NOT USE THIS FORM FOR PROPO	ICES AND REPORTS ON WELL'S DSALS TO DRILL OR TO DEEPEN OR PLU ICATION FOR PERMIT" (FORM C-101) FO	IG BACK TO A	7. Lease Name or U LEVICK STAT		t Name
1. Type of Well: Oil Well	Gas Well 🔲 Other	RECE	8. Well Number	1	
2. Name of Operator ENDEAVORENERGY RESOURCES, LP			9. OGRID Number	190595	
3. Address of Operator			10. Pool name or W	Vildcat	
110 N. MARIENFELD, STE 200 MIDLAND, TX 79701			TOBAC		
4. Well Location				T 4 G/T	
Unit Letter I : Section 20	_1980feet from theSOUTH Township 8S		60 feet from the		line
Section 20	Township 8S 11. Elevation (Show whether DR,	Range 33E	NMPM	CHAVES	County /
	4391' DF	MAD, MI, OA, EIC.)			
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON PULL OR ALTER CASING CHANGE PLANS PULL OR ALTER CASING MULTIPLE COMPL					
DOWNHOLE COMMINGLE					
OTHER:		OTHER:			
 Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 					
 NOTIFY NMOCD 24 HRS. BEFORE MIRU. MIRU. ND WH, NU BOPE. TAG CEMENT PLUG@3575' CIRCULATE 9.5 PPG MLF AND TEST CASING. SPOT 40SX OF CLASS "C" CEMENT FROM 2402'-2302'. WOC&TAG. (B.SALT) SPOT 40SX OF CLASS "C" CEMENT FROM 1860'-1760'. WOC&TAG. (T.SALT) SPOT 40SX OF CLASS "C" CEMENT FROM 436'-336'. WOC&TAG. (SHOE/FW) SPOT 10SX OF CLASS "C" CEMENT FROM 30'-SURFACE. VERIFY CEMENT TO SURFACE. (SURFACE). CUTOFF WELLHEAD, ANCHORS 3' BELOW SURFACE AND INSTALL DRYHOLE MARKER, TURN OVER FOR RECLAMATION. CLOSED LOOP CONTAINMENT SYSTEM WILL BE USED FOR FLUIDS. 					
				_	
Spud Date:	Rig Release Da	ite:	/		
I haraby cartify that the information	above is true and complete to the be	et of my knowlade	a and haliaf		
Thereby certify that the information	above is true and complete to the be	est of my knowledge	e and benef.		
SIGNATURE					
Type or print name <u>JAN SOUTH</u> E-mail address: <u>JSOUTH@EERONLINE.COM</u> PHONE: (432)685-1575					
For State Use Only					
APPROVED BY: Kiny Conditions of Approval (if any):	Forther TITLE Com	pliance Off	icen A DAT	E 2-1-1	9



