Subn	nit I Copy To Appropriate District	State of 1			. (A)	Form C-103			
Distr	ict I - (575) 393-6161 N. French Dr., Hobbs, NM 88240	Energy, Minerals		ા	WELL API NO.	Revised July 18, 2013			
Dist	<u>igt II</u> = (575) 748-1283 S. First St., Artesia, NM 88210	OIL CONSERV	'ATION	DIVISION	30-02	25-20720			
Distr	ict III - (505) 334-6178 Rio Brazos Rd., Aztec, NM 87410	1220 South	St. Frai	icis Mil	5 Chidicate Type of STATE	FEE			
Distr	<u>ńct IV</u> ~ (505) 476-3460	Santa Fo	, NM 87	7505 👫 程度	6. Stafe Off & Gas				
8750					C	-1320			
(DO	SUNDRY NO NOT USE THIS FORM FOR PRO	TICES AND REPORTS OF POSALS TO DRILL OR TO DEED			Init Agreement Name				
	IFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH ROPOSALS.)				8. Well Number				
1. 1	Type of Well: Oil Well 🗵 Gas Well 🗌 Other					01			
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	Name of Operator C	onocoPhillips Company			9. OGRID Number 2	17817			
3. 7	Address of Operator				10. Pool name or W	ildeat			
1 1	3300 N. 'A'	St, Ste. 6-100 Midland, T	X 79705		Vacuur	n; Glorieta			
_ **. `	Unit Letter B :	330 feet from the	North	line and 23	06 feet from the	East line			
	Section 32	Township 17-S	R	ange 35-E	NMPM	County Lea			
	建工业业工业	11. Elevation (Show wh				e (i)			
			3964	GL					
	12. Check	Appropriate Box to In	dicate N	ature of Notice,	Report or Other D	ata			
	NOTICE OF INTENTION TO:								
	RFORM REMEDIAL WORK	PLUG AND ABANDON	K ALTERING CASING						
	TEMPORARILY ABANDON					AND A			
	WNHOLE COMMINGLE	·	tunut						
			П	OTHER:		П			
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date									
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.									
		J. ND WH, NU BOP. POOI IBP @ 5854' – Circ hole w			pot 25sx cmt @ 5854	' <i></i> 5554'.			
	Spot	30sx cmt @ 4367' - 3968'.		_					
		25sx cmt @ 3697' – 3397' 40sx cmt @ 3052' – 2563'.	WOC-Ta	Ę	S	ee Attached			
Perf & Sqz 60sx cmt @ 1630' - 1433'. WOC-Tag Conditions of An									
	POO!	& Sqz 25sx cmt @ 60' – 3' H. Fill wellbore. Verify cmt	@ surfac	e in all annuli		- Phoon			
Cut off WH & anchors. Install DH marker 4"d:a 4" above ground									
	A closed-loop system	n will be used for all fluids fro	om this we	llbore and disposed o	of required by OCD R	ile 19.15.17			
					······································	٦			
Spud	Date:	Rig I	Release D	ate:					
1 here	eby certify that the information	on above is true and comple	e to the b	est of my knowledg	e and belief.				
SIGN	NATURE	₹ TITLE	Agent	t – Basic Energy Sc	rvices DATE	2/8/19			
			4.	-					
	or print nameGreg B State Use Only	ryant E-mail add	ress:		PHONE:	432-563-3355			
		1t.	r Cm	oliona OM	A DAT	E_2-14-19			
APPI Cond	ROVED BY: Xerry interest (if appr):	J rypur IIII	E OUM	minuce office	VAI	E <u> </u>			

WELLBORE SKETCH ConocoPhillips Company -- Permian Basin Business Unit

			Date: 2/5	i/2019
RKB @	3978'			
DF @	3978		50 at a se (50 a s)	
GL @	3967'	Subarea : Lease & Woll No	Buckeye (East)	4
	1 Surface	Legal Descriptio		
161 1	\$6/780', 24#/ff, to 1580'	County:		Aexico
	Cmt'd w/ 750 SX	Field :	Lea State: New!	viexico
	TOC @ Surface	Date Spudded:	6/9/1964	
Ш	I III roo g sunce		30-025-20720	
	Squeezed on 5/28/1994 750 SX	Ar i Humber .	55-725-20120	
	750 SX		Operator Number:	
F1	TOC - Unknown (Near Surface)		Leaso ID:	
			Field Number	
- 181			, ,	
	Production			
	4-1/2", 9.5# & 11.6/h, to 6223"			
	Cmt'd w/ 900 SX			
	TOC @ 2701' by TS			
	 			
	i M			
	Tubing - 2 3/3, 4.7#, J-55			
2	<u>니</u> []			
	ESP Discharge @-5742			
	H \mathbb{N}			
	W 🕷			
	H			
	!- 			
8				
	高 []			
	0 			
18				
	o ESP Press Sensor/EOT @-5912			
134				
Ξ	<u> </u>			
=	=			
=	=			
=	San Andres / Paddock	•		
	Perf d 5954' - 6172'			
=				
(S)				
	PBTD @ 6218'			
132	TO @ 6225			
	·			

WELLBORE SKETCH ConocoPhillips Company -- Permian Basin Business Unit

RKB @ 3978' DF @ 3978' GL @ 3967'

> P&S 25sx cmt @ 60'-3' 8-5/8", 24#/ft, to 1580' Cmt'd w/ 750 SX TOC @ Surface P&S 60sx cmt @ 1630'-1433' - Tag Squeezed on 5/28/1994 750 SX TOC - Unknown (Near Surface) Spot 40sx cmt @ 3052'-2563' - Tag 4-1/2", 9.5# & 11.6/11, to 6223' Cmt'd w/ 900 SX TOC @ 2701' by TS Spot 26sx cmt @ 3697'-3397' Spot 30sx cmt @ 4387'-3968' - Tag Spot 25sx cmt @ 5854'-5554' Set CIBP @ 5854' San Andres / Paddock PBTD @ 6218

TD @ 6225'

 Subarea
 Buckeye (East)

 Lease & Well No.
 Vacuum Glorieta East Unit
 02
 No. 01

 Legal Description
 Sec. 32N, T-17S, R-35-E
 2306' FEL, 330' FNL

 County
 Lea
 State
 New Mexico

 Field
 Vacuum

 Date Spudded
 6/9/1964

 API Number
 30-025-20720

Operator Number: Lease ID: Field Number:

Date: 2/5/2019

GENERAL CONDITIONS OF APPROVAL:

- Insure all bradenheads have been exposed, identified, and valves are operational prior to rigging up on well.
- 2) Contact the appropriate NMOCD District Office no later than 24 hours prior to moving in and rigging up.
- 3) A copy of the approved C103 intent to P&A should be distributed to the onsite company and plugging representatives. Approved procedures are good for a period of one year from approved date, unless otherwise specified on the C103 intent. Approvals past this date will require the submission and approval of a new C103 intent.
- 4) A company representative is required to be present to witness all operations including setting CIBP's, circulation of mud laden fluids, perforating, squeezing or spotting cement plugs, tags, or any other operations approved on the C103 intent to P&A. Company representative should contact the NMOCD and report all operations.
- 5) Any changes that may be required during plugging operations should be approved by the NMOCD before proceeding.
- 6) A closed loop system is to be used for all plugging operations. Contents of the steel pits to be hauled to a NMOCD permitted disposal facility.
- 7) Mud laden fluids must be placed between all cement plugs mixed at 25 sacks of salt gel per 100 barrels of brine.
- 8) All cement plugs will be 100' or 25 sacks cement, whichever is greater. Class 'C' cement will be used above 7500' and Class 'H' below 7500'. Plugs should be no more than 3000' apart
- 9) Site remediation due within one year of well plugging completion.