District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 1220 S. St. Francis Dr., Santa Fe, NM 87505

pec 1/31/19 State of New Mexico Energy, Minerals and Natural Resources Department

Submit Original to Appropriate District Office

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Date:_	1/31/19		GAS CA	PTURE PL	AN		•
☑ Original ☐ Amended - Reason for Amendment:				& OGRID	No.: Маи	PANO, LLC	231429
new co <i>Note: F</i>	mpletion (new drill, form C-129 must be sub	recomplete to	o new zone, re-fra	ac) activity.		•	n facility flaring/venting for
	/Production Facilitels) It is that will be located the locates of			ıre shown in	the table bel	low.	
W	ell Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
2	orrison san andre Unit \$ 942 H 30-		C-16-6s-34e	1050' FAL	100	FlareD	There is no current outlet FOR GAS -
	70-	041-20	985				Hopefully, if successful we will be able to get a line into Line
Gathering System and Pipeline Notification Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place							
The gas pressur	s produced from produced from produced from 1	luction facilit located in	y is dedicated to C	Gas Transpor New Mexico	ter and will tec	be connected Juire	to Gas Transporter low/high of pipeline to connect the
estimate	ed first production da	te for wells th	nat are scheduled to	o be drilled in	n the foresee	able future. I	ter a drilling, completion and n addition, <u>Operator</u> and <u>Gas</u> Gas from these wells will be
process		Processing Pl	lant located in Sec.	, Twn.	, Rng	,	County, New Mexico. The
Flowh	ack Strategy						

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on Gas Transporter system at that time. Based on current information, it is Operator's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines