District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

11/1/2010

State of New Mexico Energy, Minerals and Natural Resources Department

Submit Original to Appropriate District Office

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

GAS CAPTURE PLAN

Date. 11/1/2016				
☑ Original	Operator & OGRID No.:	Devon Energy Prod. Co., L.P. (6137)		
☐ Amended - Reason for Amendment:				
This Gas Capture Plan outlines actions to be new completion (new drill, recomplete to ne		e well/production facility flaring/venting for		

Note: Form C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15.18.12 NMAC).

Well(s)/Production Facility – Name of facility

The well(s) that will be located at the production facility are shown in the table below

Wel	ll Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
Chine 234H	coteague 8-5 Fed Com	25-45702	Unit E, Sec 8-T25S- R32E	2314 FNL 2120 FEL			Chincoteague 8 CTB 1
		, , , ,					

Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, if DCP system is in place. The gas produced from production facility is dedicated to DCP and will be connected to DCP low/high pressure gathering system located in Lea County, New Mexico. It will require 4500' of pipeline to connect the facility to low/high pressure gathering system. Devon provides (periodically) to DCP a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, Devon and DCP have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at <u>DCP</u> Processing Plant located in Sec. 19, Two 19S, Rng. 32E, Lea County, New Mexico. The actual flow of the gas will be based on compression operating process and gathering system pressures. MAR 082019

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on DCP system at that time. Based on current information, it is Devon's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- - Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines