	BI	EPARTMENT OF THE I UREAU OF LAND MANA	gmarisdad Ky		OMB NO. 1004-0137 Expires: January 31, 2018 Serial No.	
	SUNDRY Do not use thi	NOTICES AND REPO is form for proposals to	RTS ON WELL SAN drill or to release an Control D) for such proposal Control		NM136226 dian, Allottee or Tribe Name	
	abandoned we	II. Use form 3160-3 (AP	D) for such proposal	o. If Inc	dian, Allottee or Tribe Name	
-	SUBMIT IN TRIPLICATE - Other instructions on page				nit or CA/Agreement, Name and/or 1	
-	1. Type of Well			8. Well	Name and No. LIE FED COM 217H	
-	2. Name of Operator Contact: TAMMY R LINK MATADOR PRODUCTION COMPANYE-Mail: tlink@matadorresources.com				Well No. 025-44547-00-X1	
• •	3a. Address 3b. Phone No. (inclination of the second of the				ld and Pool or Exploratory Area GIE DRAW-DELAWARE	
-	4. Location of Well (Footage, Sec., T.)	11. Cou	inty or Parish, State		
	Sec 17 T25S R35E SWSE 30 32.123959 N Lat, 103.387756		LEA	COUNTY, NM		
-	12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA					
-	TYPE OF SUBMISSION		TYPE OI	TYPE OF ACTION		
-	Notice of Intent	Acidize	Deepen	D Production (Star	t/Resume) 🔲 Water Shut-C	
	□ Notice of Intent	Alter Casing	Hydraulic Fracturing	Reclamation	🗖 Well Integrity	
	🛛 Subsequent Report	Casing Repair	□ New Construction	Recomplete	🛛 Other	
	Final Abandonment Notice	Change Plans	Plug and Abandon	□ Temporarily Aba	andon Production Star	
		Convert to Injection	Plug Back	□ Water Disposal		
	following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi	operations. If the operation re- bandonment Notices must be fil	the Bond No. on file with BLM/BIA sults in a multiple completion or reco	. Required subsequent r mpletion in a new interv	ths of all pertinent markers and zone eports must be filed within 30 days al, a Form 3160-4 must be filed onc en completed and the operator has	
	following completion of the involved testing has been completed. Final Ab	operations. If the operation re- pandonment Notices must be fil inal inspection.	the Bond No. on file with BLM/BIA sults in a multiple completion or reco	. Required subsequent r mpletion in a new interv	eports must be filed within 30 days al, a Form 3160-4 must be filed once	
	following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi BLM Bond No:NMB001079	operations. If the operation re- pandonment Notices must be fil inal inspection.	the Bond No. on file with BLM/BIA sults in a multiple completion or reco	. Required subsequent r mpletion in a new interv	eports must be filed within 30 days al, a Form 3160-4 must be filed once	
	following completion of the involved testing has been completed. Final At determined that the site is ready for fi BLM Bond No:NMB001079 Surety Bond No:RLB0015172	c meeting. Pressure test est to 5,600 psi for 30 min psi. Displace 2,000 gals m. SICP @ 5,300 psi, tot to 9,500 psi; begin frac s stage 21. Total Sand Pro	the Bond No. on file with BLM/BIA sults in a multiple completion or recc ed only after all requirements, includ stack to 12,500 psi, chart 5 m nutes; lost 74 psi. Applied 2,00 of 15% HCL Acid, max press tal bbls pumped 482 bbls. stage 1 17,103-16,940'. SI afto opant 12,596,000 lbs. total flu	A. Required subsequent n mpletion in a new interv ing reclamation, have be inutes, good 00 psi to ure; 10,781 psi. er frac @ id 170.249	eports must be filed within 30 days al, a Form 3160-4 must be filed once	
	following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi BLM Bond No:NMB001079 Surety Bond No:RLB0015172 Production Sundry 9/12/2018 - MIRU held pre fra test. Perform casing integrity t backside w/pop offset at 2,500 Final pressure 9,000 psi 13 bp 9/15/2018 - Test WL lubricator 00:06 hrs thru 9/21/2018 frac s bbls. Total Acid 469 bbls. Tota	operations. If the operation re bandonment Notices must be fil inal inspection. est to 5,600 psi for 30 min psi. Displace 2,000 gals om. SICP @ 5,300 psi, tot r to 9,500 psi; begin frac s stage 21. Total Sand Proj al 100 mesh 987,000 lbs,	the Bond No. on file with BLM/BIA sults in a multiple completion or recc ed only after all requirements, includ stack to 12,500 psi, chart 5 m nutes; lost 74 psi. Applied 2,00 of 15% HCL Acid, max press tal bbls pumped 482 bbls. stage 1 17,103-16,940'. SI afto opant 12,596,000 lbs. total flu	A. Required subsequent n mpletion in a new interv ing reclamation, have be inutes, good 00 psi to ure; 10,781 psi. er frac @ id 170.249	eports must be filed within 30 days al, a Form 3160-4 must be filed once	
····	following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi BLM Bond No:NMB001079 Surety Bond No:RLB0015172 Production Sundry 9/12/2018 - MIRU held pre fra test. Perform casing integrity t backside w/pop offset at 2,500 Final pressure 9,000 psi 13 bp 9/15/2018 - Test WL lubricator 00:06 hrs thru 9/21/2018 frac s bbls. Total Acid 469 bbls. Tota	operations. If the operation re pandonment Notices must be fil inal inspection. c meeting. Pressure test est to 5,600 psi for 30 min psi. Displace 2,000 gals om. SICP @ 5,300 psi, tot r to 9,500 psi; begin frac s stage 21. Total Sand Prop al 100 mesh 987,000 lbs, true and correct. Electronic Submission # For MATADOR P	the Bond No. on file with BLM/BIA sults in a multiple completion or recc ed only after all requirements, includ stack to 12,500 psi, chart 5 m nutes; lost 74 psi. Applied 2,00 of 15% HCL Acid, max press tal bbls pumped 482 bbls. stage 1 17,103-16,940'. SI after ppant 12,596,000 lbs, total flui Total 40/70 mesh 11,609,000	A. Required subsequent n impletion in a new interv img reclamation, have be inutes, good D0 psi to ure; 10,781 psi. er frac @ id 170,249 lbs. II Information System to the Hobbs	eports must be filed within 30 days al, a Form 3160-4 must be filed onc en completed and the operator has	
····	following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi BLM Bond No:NMB001079 Surety Bond No:RLB0015172 Production Sundry 9/12/2018 - MIRU held pre fra test. Perform casing integrity t backside w/pop offset at 2,500 Final pressure 9,000 psi 13 bp 9/15/2018 - Test WL lubricator 00:06 hrs thru 9/21/2018 frac s bbls. Total Acid 469 bbls. Tota	c meeting. Pressure test est to 5,600 psi for 30 min psi. Displace 2,000 gals om. SICP @ 5,300 psi, to to 9,500 psi; begin frac s stage 21. Total Sand Proj al 100 mesh 987,000 lbs, true and correct. Electronic Submission # For MATADOR P mitted to AFMSS for proce	the Bond No. on file with BLM/BIA sults in a multiple completion or recc ed only after all requirements, includ stack to 12,500 psi, chart 5 m nutes; lost 74 psi. Applied 2,00 of 15% HCL Acid, max press tal bbls pumped 482 bbls. stage 1 17,103-16,940'. SI afte ppant 12,596,000 lbs, total flui Total 40/70 mesh 11,609,000 455055 verified by the BLM Wei RODUCTION COMPANY, sent essing by PRISCILLA PEREZ of	A. Required subsequent n impletion in a new interv img reclamation, have be inutes, good D0 psi to ure; 10,781 psi. er frac @ id 170,249 lbs. II Information System to the Hobbs	eports must be filed within 30 days al, a Form 3160-4 must be filed onc en completed and the operator has	
· · · · · · · · · · · · · · · · · · ·	following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi BLM Bond No:NMB001079 Surety Bond No:RLB0015172 Production Sundry 9/12/2018 - MIRU held pre fra test. Perform casing integrity t backside w/pop offset at 2,500 Final pressure 9,000 psi 13 bp 9/15/2018 - Test WL lubricator 00:06 hrs thru 9/21/2018 frac s bbls. Total Acid 469 bbls. Tota 14. I hereby certify that the foregoing is Name (Printed/Typed) TAMMY R	c meeting. Pressure test est to 5,600 psi for 30 min psi. Displace 2,000 gals om. SICP @ 5,300 psi, tot to 9,500 psi; begin frac s stage 21. Total Sand Proj al 100 mesh 987,000 lbs, true and correct. Electronic Submission # For MATADOR P mitted to AFMSS for process	the Bond No. on file with BLM/BIA sults in a multiple completion or recc ed only after all requirements, includ stack to 12,500 psi, chart 5 m nutes; lost 74 psi. Applied 2,00 of 15% HCL Acid, max press tal bbls pumped 482 bbls. stage 1 17,103-16,940'. SI afte ppant 12,596,000 lbs, total flu Total 40/70 mesh 11,609,000 455055 verified by the BLM Wei RODUCTION COMPANY, sent essing by PRISCILLA PEREZ of Title PRODL	A. Required subsequent n mpletion in a new interv img reclamation, have be of psi to ure; 10,781 psi. er frac @ id 170,249 lbs. Il Information System to the Hobbs n 02/22/2019 (19PP10 JCTION ANALYST	eports must be filed within 30 days al, a Form 3160-4 must be filed onc en completed and the operator has	
	following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi BLM Bond No:NMB001079 Surety Bond No:RLB0015172 Production Sundry 9/12/2018 - MIRU held pre fra test. Perform casing integrity t backside w/pop offset at 2,500 Final pressure 9,000 psi 13 bp 9/15/2018 - Test WL lubricator 00:06 hrs thru 9/21/2018 frac s bbls. Total Acid 469 bbls. Tota	c meeting. Pressure test est to 5,600 psi for 30 min psi. Displace 2,000 gals om. SICP @ 5,300 psi, tot to 9,500 psi; begin frac s stage 21. Total Sand Proj al 100 mesh 987,000 lbs, true and correct. Electronic Submission # For MATADOR P amitted to AFMSS for process LINK	the Bond No. on file with BLM/BIA sults in a multiple completion or recc ed only after all requirements, includ stack to 12,500 psi, chart 5 m nutes; lost 74 psi. Applied 2,00 of 15% HCL Acid, max press tal bbls pumped 482 bbls. stage 1 17,103-16,940'. SI afte ppant 12,596,000 lbs, total flui Total 40/70 mesh 11,609,000 455055 verified by the BLM Wei RODUCTION COMPANY, sent essing by PRISCILLA PEREZ of	A. Required subsequent n mpletion in a new interv ing reclamation, have be inutes, good 20 psi to ure; 10,781 psi. er frac @ id 170,249 lbs. Il Information System to the Hobbs n 02/22/2019 (19PP10 JCTION ANALYST 019	eports must be filed within 30 days al, a Form 3160-4 must be filed onc en completed and the operator has	
	following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi BLM Bond No:NMB001079 Surety Bond No:RLB0015172 Production Sundry 9/12/2018 - MIRU held pre fra test. Perform casing integrity t backside w/pop offset at 2,500 Final pressure 9,000 psi 13 bp 9/15/2018 - Test WL lubricator 00:06 hrs thru 9/21/2018 frac s bbls. Total Acid 469 bbls. Tota 14. I hereby certify that the foregoing is Name (Printed/Typed) TAMMY R	c meeting. Pressure test est to 5,600 psi for 30 min psi. Displace 2,000 gals om. SICP @ 5,300 psi, tot to 9,500 psi; begin frac s stage 21. Total Sand Proj al 100 mesh 987,000 lbs, true and correct. Electronic Submission # For MATADOR P amitted to AFMSS for process LINK	the Bond No. on file with BLM/BIA sults in a multiple completion or recc ed only after all requirements, includ stack to 12,500 psi, chart 5 m nutes; lost 74 psi. Applied 2,00 of 15% HCL Acid, max press tal bbls pumped 482 bbls. stage 1 17,103-16,940'. SI afte ppant 12,596,000 lbs, total flu Total 40/70 mesh 11,609,000 455055 verified by the BLM Wel RODUCTION COMPANY, sent essing by PRISCILLA PEREZ of Title PRODU Date 02/19/2 DR FEDERAL OR STATE	A. Required subsequent n mpletion in a new interv ing reclamation, have be inutes, good 00 psi to ure; 10,781 psi. er frac @ id 170,249 lbs. Il Information System to the Hobbs n 02/22/2019 (19PP10 JCTION ANALYST 019 OFFICE USE	eports must be filed within 30 days al, a Form 3160-4 must be filed onc en completed and the operator has 80SE)	
_	following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi BLM Bond No:NMB001079 Surety Bond No:RLB0015172 Production Sundry 9/12/2018 - MIRU held pre fra test. Perform casing integrity t backside w/pop offset at 2,500 Final pressure 9,000 psi 13 bp 9/15/2018 - Test WL lubricator 00:06 hrs thru 9/21/2018 frac s bbls. Total Acid 469 bbls. Tota 14. I hereby certify that the foregoing is Com Name (Printed/Typed) TAMMY R Signature (Electronic S Approved By	c meeting. Pressure test est to 5,600 psi for 30 min) psi. Displace 2,000 gals om. SICP @ 5,300 psi, tot r to 9,500 psi; begin frac s stage 21. Total Sand Proj al 100 mesh 987,000 lbs, true and correct. Electronic Submission # For MATADOR P mitted to AFMSS for proce LINK Submission)	the Bond No. on file with BLM/BIA sults in a multiple completion or recc ed only after all requirements, includ stack to 12,500 psi, chart 5 m nutes; lost 74 psi. Applied 2,00 of 15% HCL Acid, max press tal bbls pumped 482 bbls. stage 1 17,103-16,940'. SI afte ppant 12,596,000 lbs, total flui Total 40/70 mesh 11,609,000 455055 verified by the BLM Wei RODUCTION COMPANY, sent essing by PRISCILLA PEREZ of Title PRODU Date 02/19/2 DR FEDERAL OR STATE	A. Required subsequent r impletion in a new interv img reclamation, have be inutes, good 00 psi to ure; 10,781 psi. er frac @ id 170,249 lbs. Il Information System to the Hobbs n 02/22/2019 (19PP10 JCTION ANALYST 019 OFFICE USE ited for Reco	eports must be filed within 30 days al, a Form 3160-4 must be filed onc en completed and the operator has 80SE)	
- 0	following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi BLM Bond No:NMB001079 Surety Bond No:RLB0015172 Production Sundry 9/12/2018 - MIRU held pre fra test. Perform casing integrity t backside w/pop offset at 2,500 Final pressure 9,000 psi 13 bp 9/15/2018 - Test WL lubricator 00:06 hrs thru 9/21/2018 frac s bbls. Total Acid 469 bbls. Tota 14. I hereby certify that the foregoing is Corr Name (<i>Printed/Typed</i>) TAMMY R Signature (Electronic S	c meeting. Pressure test est to 5,600 psi for 30 min) psi. Displace 2,000 gals om. SICP @ 5,300 psi, tot r to 9,500 psi; begin frac s stage 21. Total Sand Proj al 100 mesh 987,000 lbs, true and correct. Electronic Submission # For MATADOR P mitted to AFMSS for process LINK Submission) THIS SPACE FC	the Bond No. on file with BLM/BIA sults in a multiple completion or recc ed only after all requirements, includ stack to 12,500 psi, chart 5 m nutes; lost 74 psi. Applied 2,00 of 15% HCL Acid, max press tal bbls pumped 482 bbls. stage 1 17,103-16,940'. SI afte ppant 12,596,000 lbs, total flui Total 40/70 mesh 11,609,000 455055 verified by the BLM Wei RODUCTION COMPANY, sent essing by PRISCILLA PEREZ of Title PRODU Date 02/19/2 DR FEDERAL OR STATE	A. Required subsequent n mpletion in a new interv ing reclamation, have be inutes, good 00 psi to ure; 10,781 psi. er frac @ id 170,249 lbs. Il Information System to the Hobbs n 02/22/2019 (19PP10 JCTION ANALYST 019 OFFICE USE	eports must be filed within 30 days al, a Form 3160-4 must be filed onc en completed and the operator has 80SE)	
- - - - 	following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi BLM Bond No:NMB001079 Surety Bond No:RLB0015172 Production Sundry 9/12/2018 - MIRU held pre fra test. Perform casing integrity to backside w/pop offset at 2,500 Final pressure 9,000 psi 13 bp 9/15/2018 - Test WL lubricator 00:06 hrs thru 9/21/2018 frac so bbls. Total Acid 469 bbls. Tota 14. I hereby certify that the foregoing is Com Name (<i>Printed/Typed</i>) TAMMY R Signature (Electronic S Conditions of approval, if any, are attached certify that the applicant holds legal or equ	c meeting. Pressure test est to 5,600 psi for 30 min psi. Displace 2,000 gals om. SICP @ 5,300 psi, tot to 9,500 psi; begin frac s stage 21. Total Sand Prop al 100 mesh 987,000 lbs, true and correct. Electronic Submission # For MATADOR P mitted to AFMSS for proce LINK Submission) THIS SPACE FC	the Bond No. on file with BLM/BIA sults in a multiple completion or recc ed only after all requirements, includ stack to 12,500 psi, chart 5 m nutes; lost 74 psi. Applied 2,00 of 15% HCL Acid, max press tal bbls pumped 482 bbls. stage 1 17,103-16,940'. SI aftr ppant 12,596,000 lbs, total flui Total 40/70 mesh 11,609,000 455055 verified by the BLM Wei RODUCTION COMPANY, sent essing by PRISCILLA PEREZ of Title PRODU Date 02/19/2 DR FEDERAL OR STATE	A. Required subsequent n mpletion in a new interv img reclamation, have be of psi to ure; 10,781 psi. er frac @ id 170,249 lbs. Il Information System to the Hobbs in 02/22/2019 (19PP10 JCTION ANALYST 019 OFFICE USE ited for Reco athon Shepard sbad Field Office	eports must be filed within 30 days al, a Form 3160-4 must be filed onc en completed and the operator has 80SE) 80SE) FEBat2 7 2	

Additional data for EC transaction #455055 that would not fit on the form

32. Additional remarks, continued

9/22/2018 - NU Wellhead @ 11:00 hrs. Pressure test CTU equipment, lines plug catcher and manifold to 8,000 psi; good test. Test to 8,000 psi, good test. 9/24/2018 - ND slips and blind shear BOP's, RD 2 3/8" CTU and Support equipment. 9/30/2018 - RDMO GR WL and support equipment NU single BOP on top of Flowcross w/2 3/8" pipe rams.

9/30/2018 - RDMO GR WL and support equipment NU single BOP on top of Flowcross w/2 3/8" pipe ra Tested blind shear ran to 8,000 psi.
10/5/2018 - RD Equipment. Rig crew prepped equipment to be moved off location.
10/7/2018 - Flowing well to OTT, trace of oil, trace of gas.
10/16/2018 - Gas to flare, 10/17/2018 gas back to sales.
11/3/2018 - Turned well over to production, well off flowback.
12/7/2018 - MIRU WSU and set pipe racks. Unloaded 2 7/8" 8RDL-80 production tubing.
12/8/2018 - ND production tree and NU BOP MU 8' 2 7/8" 8RD tubing sub to tubing hanger and load tubing hanger. MU 5.5" ASL-X packer BHA. TIH w/372 joints of 2 7/8" tubing to 11,520' and 14 GLV's.
Pumped 180 bbls of packer fluid down casing at 2.5 bpm NU production tree to flowline. Tested voids to 5K w/no loss of pressure. Packer @ 11,533.51.