

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

OCD Hobbs

FORM APPROVED
OMB NO. 1004-0137
Expires: January 31, 2018**SUNDRY NOTICES AND REPORTS ON WELLS**
*Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.*5. Lease Serial No.
NMNM104724

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.
NMNM103145X8. Well Name and No.
WEST TEAS UNIT 9229. API Well No.
30-025-29900-00-S110. Field and Pool or Exploratory Area
TEAS11. County or Parish, State
LEA COUNTY, NM**SUBMIT IN TRIPLICATE - Other instructions on page 2**

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

CHEVRON USA INCORPORATED

Contact: NICK GLANN

E-Mail: NGLANN@CHEVRON.COM

3a. Address

6301 DEAUVILLE BLVD
MIDLAND, TX 79706

3b. Phone No. (include area code)

Ph: 661-599-5062

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Sec 9 T20S R33E SENW 1980FNL 1650FWL

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☒ Notice of Intent☐ Subsequent Report☐ Final Abandonment Notice☐ Acidize☐ Alter Casing☐ Casing Repair☐ Change Plans☐ Convert to Injection☐ Deepen*☐ Hydraulic Fracturing☐ New Construction☒ Plug and Abandon☐ Plug Back☐ Production (Start/Resume)☐ Reclamation☐ Recomplete☐ Temporarily Abandon☐ Water Disposal☐ Water Shut-Off☐ Well Integrity☐ Other

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleate horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleation in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.

1. Provide BLM with 24 hour notification prior to MIRU in accordance with applicable COAs

2. MIRU, pull rods, N/U BOP, pull tubing

3. Set CIBP @ 3050', fill well with fresh water, pressure test casing to 500 psi for 10 minutes.

If test passes, spot MLF.

4. Spot 140 sx CL C cmt f/ 3050' U 1161' (Yates, Potash Area, Shoe). If casing test in step 3 was successful, do not WOC & tag. If casing test in step 3 was unsuccessful, WOC, tag, pressure test, and spot MLF.

5. Spot 30 sx CL C cmt f/ 400' t/ surface (Fresh Water)

6. Verify cement to surface and RDMO

SEE ATTACHED FOR
CONDITIONS OF APPROVAL

14. I hereby certify that the foregoing is true and correct.

Electronic Submission #458470 verified by the BLM Well Information System

For CHEVRON USA INCORPORATED, sent to the Hobbs

Committed to AFMSS for processing by DEBORAH MCKINNEY on 03/19/2019 (19DLM0285SE)

Name (Printed/Typed) NICK GLANN

Title P&A ENGINEER

Signature

(Electronic Submission)

Date 03/19/2019

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved By

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED **

X7 NMOLD 4-25-19

FOR RECORD ONLY

Well: WTU 922
Field: West Teas
Reservoir: Yates

Current
Wellbore Diagram

Location:
32.589340/-103.6711000
Section: 9
Township: 20
Range: 33
County: Lea State: NM

Well ID Info:
Chevno: II4580
API No: 3002529900
Spud Date: 4/29/87
Compl. Date: 8/1/87

Surface Csg: 8.625", 32#, Unk
Set: @ 1261' w/ 600 sks **1256**
Hole Size: 12.25"
Circ: Yes **TOC:** Surface
TOC By: Circulated

Prod. Csg: 4.5", 9.5#
Set: @ 3400' w/ 900 sks
Hole Size: 7 7/8"
Circ: yes **TOC:** surface
TOC By: circ

Formation Name	TD, ft
	Top
Potash Area	
yates	3,075
Seven Rivers	3,325

T/Salt 1500 +/-
B/Salt 2800 +/- **AAD**
Yates 2992 +/-

Tubing Detail (Top - Down)

Date	Part Type	Tubing Component	Joints	Max OD	Min ID	Weight	Grade	Top Depth
4/29/1987	Tubing - OD 2.375	Unknown Grade/Thread/Weight 2.375 OD	95	2.375	1.995	0	Unknown	11
4/29/1987	Tubing Anchor/Catcher	Tubing Anchor/Catcher 2.375	1	2.375	1.995	0	N/A	3026.5
4/29/1987	Tubing - OD 2.375	Unknown Grade/Thread/Weight 2.375 OD	7	2.375	1.995	0	Unknown	3029.5
4/29/1987	Seat Nipple / Shoes	Seat Nipple - Standard (2.375) Cup Type	1	2.375	0	0	N/A	3250
4/29/1987	Tubing Sub - OD 2.375	Perforated Tubing Sub 2.375	1	2.375	1.995	0	Unknown	3251
4/29/1987	Tubing - OD 2.375	Unknown Grade/Thread/Weight 2.375 OD	1	2.375	1.995	0	Unknown	3251
4/29/1987	Tubing - OD 2.375	Unknown Grade/Thread/Weight 2.375 OD	1	2.375	1.995	0	Unknown	3251
4/29/1987	Tubing - OD 2.375	Unknown Grade/Thread/Weight 2.375 OD	1	2.375	1.995	0	Unknown	3251
4/29/1987	Perforation Hole/Slot Detail	Tubing Perforation	1	0	0	0	N/A	3251
4/29/1987	Tubing - OD 2.375	Unknown Grade/Thread/Weight 2.375 OD	1	2.375	1.995	0	Unknown	3255

Rod Detail (Top - Down)

Date	Part Type	Rod Component	Count	Size	Grade	Length	Top Depth	Bottom Depth
4/29/1987	Polished Rod	1.250 (1 1/4 in.) Spray Metal x 16	1	1.25	C	16	11	27
4/29/1987	Rod (Sub)	0.750 (3/4 in.) D Rod Sub(s)	9	0.75	Unknown	18	27	45
4/29/1987	Rod	0.750 (3/4 in.) D x 25 Rod	128	0.75	D	3200	45	3245

Yates Perfs @ 3092'-3147' 3201'-3275'

3-27-19 OK to Set
LIAPQ 3052-2992.
To Michael Steel.
432.528-8564

Cement plug at 3348'

PBTD: 3348'
TD: 3400'

Well: **WTU 922**

Field: **West Teas**

Reservoir: **Yates**

Proposed
Wellbore Diagram

Location:
32.589340/-103.6711000
Section: 9
Township: 20
Range: 33
County: Lea **State:** NM

Well ID Info:
Chevno: II4580
API No: 3002529900

Spud Date: 4/29/87
Compl. Date: 8/1/87

Surface Csg: 8.625", 32#, Unk
Set: @ 1261' w/ 600 sks
Hole Size: 12.25"
Circ: Yes **TOC:** Surface
TOC By: Circulated

Prod. Csg: 4.5", 9.5#
Set: @ 3400' w/ 900 sks
Hole Size: 7 7/8"
Circ: yes **TOC:** surface
TOC By: circ

Formation Name	TD, ft
	Top
Potash Area	
yates	3,075
Seven Rivers	3,325

Spot 30 sx CL C cmt f/ 400' t/ surface

Yates Perfs @ 3092'-3147' 3201'-3275'

Spot 140 sx CL C cmt f/ 3050' t/ 1161' (Yates, Potash Area, Shoe)
Set CIBP @ 3050'

PBTD: 3348'
TD: 3400'

Cement plug at 3348'

BUREAU OF LAND MANAGEMENT
Carlsbad Field Office
620 East Greene Street
Carlsbad, New Mexico 88220
575-234-5972

Permanent Abandonment of Federal Wells
Conditions of Approval (LPC Habitat)

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within ninety (90) days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

2. Notification: Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.

3. Blowout Preventers: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.

4. Mud Requirement: Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of brine water. Minimum nine (9) pounds per gallon.

5. Cement Requirement: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. Below Ground Level Cap (Lesser Prairie-Chicken Habitat): All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off. Upon the plugging and subsequent abandonment of wells that are located in lesser prairie-chicken habitat, the casings shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The well bore shall then be covered with a metal plate at least ¼ inch thick and welded in place. A weep hole shall be left in the plate and/or casing.

NMOCD also requires the operator to notify NMOCD when this type of dry hole marker is used. This can be done on the subsequent report of abandonment which is submitted to the BLM after the well is plugged. State that a below ground cap was installed as required in the COA's from the BLM.

7. Subsequent Plugging Reporting: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. Show date well was plugged.

8. Trash: All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.

Timing Limitation Stipulation/ Condition of Approval for Lesser Prairie-Chicken:

From March 1st through June 15th annually, abandonment activities will be allowed except between the hours from 3:00 am and 9:00 am. Normal vehicle use on existing roads will not be restricted