

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
APPLICATION FOR PERMIT TO DRILL OR REENTER

HOBBS OGD
MAY 08 2019
RECEIVED

FORM APPROVED
OMB No. 1004-0137
Expires: January 31, 2018

F/A
(H)

1a. Type of work: ☒ DRILL ☐ REENTER
1b. Type of Well: ☒ Oil Well ☐ Gas Well ☐ Other
1c. Type of Completion: ☐ Hydraulic Fracturing ☒ Single Zone ☐ Multiple Zone

5. Lease Serial No.
NMNM023199

6. If Indian, Allottee or Tribe Name

7. If Unit or CA Agreement, Name and No.

8. Lease Name and Well No.

CAMELLIA FED COM 26 36 21
121H (325400)

2. Name of Operator
AMEREDEV OPERATING LLC (372224)

9. API Well No.

30-025-45897 (98234)
JAL / WOLFCAMP WEST WOLFCAMP

3a. Address
5707 Southwest Parkway, Building 1, Suite 275 Austin TX

3b. Phone No. (include area code)
(737)300-4700

4. Location of Well (Report location clearly and in accordance with any State requirements. *)

At surface LOT M / 283 FSL / 270 FWL / LAT 32.0222961 / LONG -103.2777208

At proposed prod. zone LOT D / 50 FNL / 200 FWL / LAT 32.05041 / LONG -103.27796

11. Sec., T. R. M. or Blk. and Survey or Area
SEC 21 / T26S / R36E / NMP

14. Distance in miles and direction from nearest town or post office*
5 miles

12. County or Parish
LEA

13. State
NM

15. Distance from proposed*
location to nearest
property or lease line, ft.
(Also to nearest drig. unit line, if any)
270 feet

16. No of acres in lease
320

17. Spacing Unit dedicated to this well
320

18. Distance from proposed location*
to nearest well, drilling, completed,
applied for, on this lease, ft.
720 feet

19. Proposed Depth
12560 feet / 23283 feet

20. BLM/BIA Bond No. in file
FED: NMB001478

21. Elevations (Show whether DF, KDB, RT, GL, etc.)
2924 feet

22. Approximate date work will start*
03/15/2019

23. Estimated duration
90 days

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, and the Hydraulic Fracturing rule per 43 CFR 3162.3-3 (as applicable)

1. Well plat certified by a registered surveyor.

2. A Drilling Plan.

3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office).

4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).

5. Operator certification.

6. Such other site specific information and/or plans as may be requested by the BLM.

25. Signature
(Electronic Submission)

Name (Printed/Typed)
Christie Hanna / Ph: (737)300-4723

Date
04/10/2018

Title
Senior Engineering Technician

Approved by (Signature)
(Electronic Submission)

Name (Printed/Typed)
Cody Layton / Ph: (575)234-5959

Date
05/03/2019

Title
Assistant Field Manager Lands & Minerals

Office
CARLSBAD

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

GEP Rec 05/06/19

KZ 05/06/19

REQUIRER NPL

(Continued on page 2)

APPROVED WITH CONDITIONS

Approval Date: 05/03/2019

*(Instructions on page 2)

INSTRUCTIONS

GENERAL: This form is designed for submitting proposals to perform certain well operations, as indicated on Federal and Indian lands and leases for action by appropriate Federal agencies, pursuant to applicable Federal laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from local Federal offices.

ITEM 1: If the proposal is to redrill to the same reservoir at a different subsurface location or to a new reservoir, use this form with appropriate notations. Consult applicable Federal regulations concerning subsequent work proposals or reports on the well.

ITEM 4: Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local Federal offices for specific instructions.

ITEM 14: Needed only when location of well cannot readily be found by road from the land or lease description. A plat, or plats, separate or on the reverse side, showing the roads to, and the surveyed location of, the well, and any other required information, should be furnished when required by Federal agency offices.

ITEMS 15 AND 18: If well is to be, or has been directionally drilled, give distances for subsurface location of hole in any present or objective productive zone.

ITEM 22: Consult applicable Federal regulations, or appropriate officials, concerning approval of the proposal before operations are started.

ITEM 24: If the proposal will involve hydraulic fracturing operations, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

NOTICES

The Privacy Act of 1974 and regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 25 U.S.C. 396; 43 CFR 3160

PRINCIPAL PURPOSES: The information will be used to: (1) process and evaluate your application for a permit to drill a new oil, gas, or service well or to reenter a plugged and abandoned well; and (2) document, for administrative use, information for the management, disposal and use of National Resource Lands and resources including (a) analyzing your proposal to discover and extract the Federal or Indian resources encountered; (b) reviewing procedures and equipment and the projected impact on the land involved; and (c) evaluating the effects of the proposed operation on the surface and subsurface water and other environmental impacts.

ROUTINE USE: Information from the record and/or the record will be transferred to appropriate Federal, State, and local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecution, in connection with congressional inquiries and for regulatory responsibilities.

EFFECT OF NOT PROVIDING INFORMATION: Filing of this application and disclosure of the information is mandatory only if you elect to initiate a drilling or reentry operation on an oil and gas lease.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM connects this information to an evaluation of the technical, safety, and environmental factors involved with drilling for oil and/or gas on Federal and Indian oil and gas leases. This information will be used to analyze and approve applications. Response to this request is mandatory only if the operator elects to initiate drilling or reentry operations on an oil and gas lease. The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Connection Clearance Officer (WO-630), 1849 C Street, N.W., Mail Stop 401 LS, Washington, D.C. 20240.

Additional Operator Remarks

Location of Well

1. SHL: LOT M / 283 FSL / 270 FWL / TWSP: 26S / RANGE: 36E / SECTION: 21 / LAT: 32.0222961 / LONG: -103.2777208 (TVD: 0 feet, MD: 0 feet)
PPP: LOT D / 50 FNL / 200 FWL / TWSP: 26S / RANGE: 36E / SECTION: 16 / LAT: 32.05041 / LONG: -103.27796 (TVD: 12560 feet, MD: 23283 feet)
BHL: LOT D / 50 FNL / 200 FWL / TWSP: 26S / RANGE: 36E / SECTION: 16 / LAT: 32.05041 / LONG: -103.27796 (TVD: 12560 feet, MD: 23283 feet)

BLM Point of Contact

Name: Priscilla Perez

Title: Legal Instruments Examiner

Phone: 5752345934

Email: pperez@blm.gov

Review and Appeal Rights

A person contesting a decision shall request a State Director review. This request must be filed within 20 working days of receipt of the Notice with the appropriate State Director (see 43 CFR 3165.3). The State Director review decision may be appealed to the Interior Board of Land Appeals, 801 North Quincy Street, Suite 300, Arlington, VA 22203 (see 43 CFR 3165.4). Contact the above listed Bureau of Land Management office for further information.

PECOS DISTRICT DRILLING CONDITIONS OF APPROVAL

OPERATOR'S NAME:	Ameredev Operating LLC
LEASE NO.:	NMNM023199
WELL NAME & NO.:	Camellia Fed Com 26 36 21 121H
SURFACE HOLE FOOTAGE:	283'S & 270'/W
BOTTOM HOLE FOOTAGE:	50'/N & 200'/W
LOCATION:	Section 21, T.26 S., R.36 E., NMPM
COUNTY:	Lea County, New Mexico

COA

H2S	<input type="radio"/> Yes	<input checked="" type="radio"/> No	
Potash	<input checked="" type="radio"/> None	<input type="radio"/> Secretary	<input type="radio"/> R-111-P
Cave/Karst Potential	<input checked="" type="radio"/> Low	<input type="radio"/> Medium	<input type="radio"/> High
Variance	<input type="radio"/> None	<input checked="" type="radio"/> Flex Hose	<input type="radio"/> Other
Wellhead	<input type="radio"/> Conventional	<input checked="" type="radio"/> Multibowl	<input type="radio"/> Both
Other	<input type="checkbox"/> 4 String Area	<input checked="" type="checkbox"/> Capitan Reef	<input type="checkbox"/> WIPP

A. HYDROGEN SULFIDE

Hydrogen Sulfide (H2S) monitors shall be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the Hydrogen Sulfide area shall meet Onshore Order 6 requirements, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, provide measured values and formations to the BLM.

B. CASING

Primary Casing Design:

1. The 13-3/8 inch surface casing shall be set at approximately **1925** feet (a minimum of 25 feet into the Rustler Anhydrite and above the salt) and cemented to the surface.
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
 - b. Wait on cement (WOC) time for a primary cement job will be a minimum of **8 hours** or 500 pounds compressive strength, whichever is greater. (This is to include the lead cement)
 - c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours

after bringing cement to surface or 500 pounds compressive strength, whichever is greater.

- d. If cement falls back, remedial cementing will be done prior to drilling out that string.

❖ **Special Capitan Reef requirements.** If lost circulation (50% or greater) occurs below the Base of the Salt, the operator shall do the following:

- Switch to fresh water mud to protect the Capitan Reef and use fresh water mud until setting the intermediate casing. The appropriate BLM office is to be notified for a PET to witness the switch to fresh water.
- Daily drilling reports from the Base of the Salt to the setting of the intermediate casing are to be submitted to the BLM CFO engineering staff via e-mail by 0800 hours each morning. Any lost circulation encountered is to be recorded on these drilling reports. The daily drilling report should show mud volume per shift/tour. Failure to submit these reports will result in an Incidence of Non-Compliance being issued for failure to comply with the Conditions of Approval. If not already planned, the operator shall run a caliper survey for the intermediate well bore and submit to the appropriate BLM office.

Intermediate casing must be kept fluid filled to meet BLM minimum collapse requirement.

2. The minimum required fill of cement behind the **9-5/8 inch 1st intermediate** casing is:

Operator has proposed a DV tool, the depth may be adjusted as long as the cement is changed proportionally. The DV tool may be cancelled if cement circulates to surface on the first stage.

- a. First stage to DV tool: Cement to circulate. If cement does not circulate off the DV tool, contact the appropriate BLM office before proceeding with second stage cement job.
- b. Second stage above DV tool:
 - Cement should tie-back at least **200 feet** into previous casing string. Operator shall provide method of verification.
Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst or potash.
 - Cement to surface. If cement does not circulate, contact the appropriate BLM office.

Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst or potash. Excess calculates to 22% - additional cement might be required.

3. The minimum required fill of cement behind the 5-1/2 inch production casing is:
 - Cement should tie-back at least 50 feet on top of Capitan Reef Top. Operator shall provide method of verification. **Excess calculates to 17% - additional cement might be required.**

Alternate Casing Design:

2nd Intermediate casing must be kept fluid filled to meet BLM minimum collapse requirement.

3. The minimum required fill of cement behind the 7-5/8 inch 2nd intermediate casing is:
 - Cement to surface. If cement does not circulate see B.1.a, c-d above. **Excess calculates to 14% - additional cement might be required.**

In the case of lost circulation, operator has proposed to pump down 9 5/8" X 7 5/8" annulus. Operator must run a CBL from TD of the 7 5/8" casing to surface. Submit results to the BLM.

Pilot hole is required to have a plug at the bottom of the hole. If two plugs are set, the BLM is to be contacted (575-361-2822) prior to tag of bottom plug, which must be a minimum of 200' in length. Operator can set one plug from bottom of pilot hole to kick-off point and save the WOC time for tagging the first plug. Note plug tops on subsequent drilling report.

4. The minimum required fill of cement behind the 5-1/2 inch production casing is:
 - Cement should tie-back at least 50 feet on top of Capitan Reef Top. Operator shall provide method of verification. **Excess calculates to 15% - additional cement might be required.**

C. PRESSURE CONTROL

1. Variance approved to use flex line from BOP to choke manifold. Manufacturer's specification to be readily available. No external damage to flex line. Flex line to be installed as straight as possible (no hard bends).'
- 2.

Option 1:

Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **10,000 (10M) psi.**

Option 2:

Operator has proposed a multi-bowl wellhead assembly. This assembly will only be tested when installed on the surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be 10,000 (10M) psi.

- a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
- b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
- c. Manufacturer representative shall install the test plug for the initial BOP test.
- d. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
- e. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.

Variance approved to use a 5M annular. The annular must be tested to full working pressure (5000 psi.)

D. SPECIAL REQUIREMENT(S)

Communitization Agreement

- The operator will submit a Communitization Agreement to the Carlsbad Field Office, 620 E Greene St. Carlsbad, New Mexico 88220, at least 90 days before the anticipated date of first production from a well subject to a spacing order issued by the New Mexico Oil Conservation Division. The Communitization Agreement will include the signatures of all working interest owners in all Federal and Indian leases subject to the Communitization Agreement (i.e., operating rights owners and lessees of record), or certification that the operator has obtained the written signatures of all such owners and will make those signatures available to the BLM immediately upon request.
- If the operator does not comply with this condition of approval, the BLM may take enforcement actions that include, but are not limited to, those specified in 43 CFR 3163.1.
- In addition, the well sign shall include the surface and bottom hole lease numbers. When the Communitization Agreement number is known, it shall also be on the sign.

GENERAL REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

☒ Chaves and Roosevelt Counties

Call the Roswell Field Office, 2909 West Second St., Roswell NM 88201.

During office hours call (575) 627-0272.

After office hours call (575)

☒ Eddy County

Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220,
(575) 361-2822

☒ Lea County

Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240, (575)
393-3612

1. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
 - a. In the event the operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).
 - b. When the operator proposes to set surface casing with Spudder Rig
 - Notify the BLM when moving in and removing the Spudder Rig.
 - Notify the BLM when moving in the 2nd Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
 - BOP/BOPE test to be conducted per Onshore Oil and Gas Order No. 2 as soon as 2nd Rig is rigged up on well.
2. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.
3. The record of the drilling rate along with the GR/N well log (one log per well pad is acceptable) run from TD to surface (horizontal well – vertical portion of hole) shall

be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.

A. CASING

1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.
2. Wait on cement (WOC) for Potash Areas: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends, 2) until cement has been in place at least 24 hours. WOC time will be recorded in the driller's log. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
3. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.
6. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.

7. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.
8. Whenever a casing string is cemented in the R-111-P potash area, the NMOCD requirements shall be followed.

B. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.
2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: The flex line must meet the requirements of API 16C. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.
3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
 - e. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.
5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.

- a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead when specified), whichever is greater. However, if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).
- b. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the plug. However, **no tests** shall commence until the cement has had a minimum of 24 hours setup time, except the casing pressure test can be initiated immediately after bumping the plug (only applies to single stage cement jobs).
- c. The tests shall be done by an independent service company utilizing a test plug. The results of the test shall be reported to the appropriate BLM office.
- d. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
- e. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
- f. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes. This test shall be performed prior to the test at full stack pressure.
- g. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per Onshore Order No. 2.

C. DRILLING MUD

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

D. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

Waste Minimization Plan (WMP)

In the interest of resource development, submission of additional well gas capture development plan information is deferred but may be required by the BLM Authorized Officer at a later date.

NMK4282019

Cap

13 3/8	surface csg in a	17 1/2	inch hole.	Design Factors			SURFACE		
Segment	#/ft	Grade	Coupling	Body	Collapse	Burst	Length	Weight	
"A"	68.00	J 55	BUTT	8.17	2.27	0.65	1,925	130,900	
"B"							0	0	
w/8.4#/g mud, 30min Sfc Csg Test psig: 1,500			Tail Cmt	does not	circ to sfc.	Totals:	1,925	130,900	
Comparison of Proposed to Minimum Required Cement Volumes									
Hole	Annular	1 Stage	1 Stage	Min	1 Stage	Drilling	Calc	Req'd	Min Dist
Size	Volume	Cmt Sx	CuFt Cmt	Cu Ft	% Excess	Mud Wt	MASP	BOPE	Hole-Cplg
17 1/2	0.6946	1231	2083	1390	50	8.60	2933	3M	1.56
Burst Frac Gradient(s) for Segment(s) A, B = , b All > 0.70, OK. Alt Burst = 1.18 > 0.7									

9 5/8 casing inside the 13 3/8				Design Factors			INTERMEDIATE		
Segment	#/ft	Grade	Coupling	Body	Collapse	Burst	Length	Weight	
"A"	40.00	HCL 80	BUTT	2.10	0.79	0.84	10,931	437,240	
"B"							0	0	
w/8.4#/g mud, 30min Sfc Csg Test psig:						Totals:	10,931	437,240	
The cement volume(s) are intended to achieve a top of				0	ft from surface or a		1925	overlap.	
Hole	Annular	1 Stage	1 Stage	Min	1 Stage	Drilling	Calc	Req'd	Min Dist
Size	Volume	Cmt Sx	CuFt Cmt	Cu Ft	% Excess	Mud Wt	MASP	BOPE	Hole-Cplg
12 1/4	0.3132	look	0	3485		9.40	4088	5M	0.81
D V Tool(s):			5002				sum of sx	Σ CuFt	Σ%excess
t by stage % :			127	22			2756	6210	78
Class 'H' tail cmt yld > 1.20									
Burst Frac Gradient(s) for Segment(s): A, B, C, D = 0.53, b, c, d									
<0.70 a Problem!!									
Alt Burst = 1.50 > 1 Alt Collapse = 1.19 > 1.125									

Tail cmt									
5 1/2	casing inside the	9 5/8	Design Factors				PRODUCTION		
Segment	#/ft	Grade	Coupling	Body	Collapse	Burst	Length	Weight	
"A"	20.00	HCP 110	BUTT	2.55	1.68	1.8	12,095	241,894	
"B"	20.00	HCP 110	BUTT	7.16	1.48	1.8	11,105	222,106	
w/8.4#/g mud, 30min Sfc Csg Test psig: 2,661						Totals:	23,200	464,000	
The cement volume(s) are intended to achieve a top of				0	ft from surface or a		10931	overlap.	
Hole	Annular	1 Stage	1 Stage	Min	1 Stage	Drilling	Calc	Req'd	Min Dist
Size	Volume	Cmt Sx	CuFt Cmt	Cu Ft	% Excess	Mud Wt	MASP	BOPE	Hole-Cplg
8 1/2	0.2291	4829	6471	5666	14	10.50			1.23
Class 'H' tail cmt yld > 1.20									

0	5 1/2				Design Factors				
Segment	#/ft	Grade	Coupling	Joint	Collapse	Burst	Length	Weight	
"A"							0	0	
"B"							0	0	
w/8.4#/g mud, 30min Sfc Csg Test psig:							Totals:	0	0
Cmt vol calc below includes this csg, TOC intended					0	ft from surface or a		23200	overlap.
Hole	Annular	1 Stage	1 Stage	Min	1 Stage	Drilling	Calc	Req'd	Min Dist
Size	Volume	Cmt Sx	CuFt Cmt	Cu Ft	% Excess	Mud Wt	MASP	BOPE	Hole-Cplg
0			0	0					

Cap

13 3/8	surface csg in a	17 1/2	inch hole.	Design Factors			SURFACE		
Segment	#/ft	Grade	Coupling	Body	Collapse	Burst	Length	Weight	
"A"	54.50	J 55	BUTT	8.13	1.31	1.12	1,925	104,913	
"B"							0	0	
w/8.4#/g mud, 30min Sfc Csg Test psig: 1,071			Tail Cmt	does not	circ to sfc.	Totals:	1,925	104,913	
Comparison of Proposed to Minimum Required Cement Volumes									
Hole	Annular	1 Stage	1 Stage	Min	1 Stage	Drilling	Calc	Req'd	Min Dist
Size	Volume	Cmt Sx	CuFt Cmt	Cu Ft	% Excess	Mud Wt	MASP	BOPE	Hole-Cplg
17 1/2	0.6946			1391		8.60	1345	2M	1.56

9 5/8 casing inside the 13 3/8					Design Factors			INTERMEDIATE	
Segment	#/ft	Grade	Coupling	Body	Collapse	Burst	Length	Weight	
"A"	40.00	HCL 80	BUTT	4.57	1.73	0.82	5,013	200,520	
"B"							0	0	
w/8.4#/g mud, 30min Sfc Csg Test psig:						Totals:	5,013	200,520	
The cement volume(s) are intended to achieve a top of				0	ft from surface or a		1925	overlap.	
Hole	Annular	1 Stage	1 Stage	Min	1 Stage	Drilling	Calc	Req'd	Min Dist
Size	Volume	Cmt Sx	CuFt Cmt	Cu Ft	% Excess	Mud Wt	MASP	BOPE	Hole-Cplg
12 1/4	0.3132	look ↘	0	1684		9.40	4161	5M	0.81
D V Tool(s):			3262				sum of sx	Σ CuFt	Σ%excess
t by stage % :		315	37				1357	3882	130
Burst Frac Gradient(s) for Segment(s): A, B, C, D = 1.15, b, c, d					Alt Burst = 1.38 > 1				
All > 0.70, OK.									

7 5/8	casing inside the	9 5/8	A Buoyant		Design Factors		INTERMEDIATE		
Segment	#/ft	Grade	Coupling	Joint	Collapse	Burst	Length	Weight	
"A"	29.70	HCL 80	BUTT	2.13	1.1	1.36	11,147	331,066	
"B"							0	0	
w/8.4#/g mud, 30min Sfc Csg Test psig: 2,452						Totals:	11,147	331,066	
The cement volume(s) are intended to achieve a top of				0	ft from surface or a		5013	overlap.	
Hole	Annular	1 Stage	1 Stage	Min	1 Stage	Drilling	Calc	Req'd	Min Dist
Size	Volume	Cmt Sx	CuFt Cmt	Cu Ft	% Excess	Mud Wt	MASP	BOPE	Hole-Cplg
8 3/4	0.1005	683	1339	1172	14	10.50	4088	5M	0.56
Class 'H' tail cmt yld > 1.20									
Alt Collapse = 1.65 > 1.125									

Tail cmt						Design Factors		PRODUCTION	
5 1/2	casing inside the	7 5/8	-						
Segment	#/ft	Grade	Coupling	Joint	Collapse	Burst	Length	Weight	
"A"	20.00	P 110	BUTT	2.61	2.1	2.1	11,147	222,940	
"B"	20.00	P 110	BUTT	6.03	1.70	2.1	12,053	241,060	
w/8.4#/g mud, 30min Sfc Csg Test psig: 2,452						Totals:	23,200	464,000	
B segment Design Factors would be:				23.18	1.87	if it were a vertical wellbore.			
No Pilot Hole Planned		MTD	Max VTD	Csg VD	Curve KOP	Dogleg°	Severity°	MEOC	
		23200	12560	12560	12095	90	12	12871.5	
The cement volume(s) are intended to achieve a top of					0	ft from surface or a		11147	overlap.
Hole	Annular	1 Stage	1 Stage	Min	1 Stage	Drilling	Calc	Req'd	Min Dist
Size	Volume	Cmt Sx	CuFt Cmt	Cu Ft	% Excess	Mud Wt	MASP	BOPE	Hole-Cplg
6 3/4	0.0835	1751	2346	2047	15	10.50			0.49
Class 'H' tail cmt yld > 1.20									

**PECOS DISTRICT
SURFACE USE
CONDITIONS OF APPROVAL**

Camellia Federal Com 26 36 21 81H:

Surface Hole Location: 283' FSL & 290' FWL, Section 21, T. 26 S., R. 36 E.
Bottom Hole Location: 200' FNL & 660' FWL, Section 16, T. 26 S., R. 36 E.

Camellia Federal Com 26 36 21 91H:

Surface Hole Location: 283' FSL & 310' FWL, Section 21, T. 26 S., R. 36 E.
Bottom Hole Location: 200' FNL & 660' FWL, Section 16, T. 26 S., R. 36 E.

Camellia Federal Com 26 36 21 101H:

Surface Hole Location: 283' FSL & 230' FWL, Section 21, T. 26 S., R. 36 E.
Bottom Hole Location: 200' FNL & 380' FWL, Section 16, T. 26 S., R. 36 E.

Camellia Federal Com 26 36 21 111H:

Surface Hole Location: 283' FSL & 250' FWL, Section 21, T. 26 S., R. 36 E.
Bottom Hole Location: 200' FNL & 380' FWL, Section 16, T. 26 S., R. 36 E.

Camellia Federal Com 26 36 21 121H:

Surface Hole Location: 283' FSL & 270' FWL, Section 21, T. 26 S., R. 36 E.
Bottom Hole Location: 200' FNL & 380' FWL, Section 16, T. 16 S., R. 36 E.

TABLE OF CONTENTS

Standard Conditions of Approval (COA) apply to this APD. If any deviations to these standards exist or special COAs are required, the section with the deviation or requirement will be checked below.

- ☐ **General Provisions**
- ☐ **Permit Expiration**
- ☐ **Archaeology, Paleontology, and Historical Sites**
- ☐ **Noxious Weeds**
- ☒ **Special Requirements**
 - Lesser Prairie-Chicken Timing Stipulations
 - Timing Limitation Exception
 - Ground-level Abandoned Well Marker
 - Hydrology
- ☒ **Construction**
 - Notification
 - Topsoil
 - Closed Loop System
 - Federal Mineral Material Pits
 - Well Pads
 - Roads
- ☐ **Road Section Diagram**
- ☒ **Production (Post Drilling)**
 - Well Structures & Facilities
 - Pipelines
 - Electric Lines
- ☐ **Interim Reclamation**
- ☐ **Final Abandonment & Reclamation**

I. GENERAL PROVISIONS

The approval of the Application For Permit To Drill (APD) is in compliance with all applicable laws and regulations: 43 Code of Federal Regulations 3160, the lease terms, Onshore Oil and Gas Orders, Notices To Lessees, New Mexico Oil Conservation Division (NMOCD) Rules, National Historical Preservation Act As Amended, and instructions and orders of the Authorized Officer. Any request for a variance shall be submitted to the Authorized Officer on Form 3160-5, Sundry Notices and Report on Wells.

II. PERMIT EXPIRATION

If the permit terminates prior to drilling and drilling cannot be commenced within 60 days after expiration, an operator is required to submit Form 3160-5, Sundry Notices and Reports on Wells, requesting surface reclamation requirements for any surface disturbance. However, if the operator will be able to initiate drilling within 60 days after the expiration of the permit, the operator must have set the conductor pipe in order to allow for an extension of 60 days beyond the expiration date of the APD. (Filing of a Sundry Notice is required for this 60 day extension.)

III. ARCHAEOLOGICAL, PALEONTOLOGY & HISTORICAL SITES

Any cultural and/or paleontological resource discovered by the operator or by any person working on the operator's behalf shall immediately report such findings to the Authorized Officer. The operator is fully accountable for the actions of their contractors and subcontractors. The operator shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery shall be made by the Authorized Officer to determine the appropriate actions that shall be required to prevent the loss of significant cultural or scientific values of the discovery. The operator shall be held responsible for the cost of the proper mitigation measures that the Authorized Officer assesses after consultation with the operator on the evaluation and decisions of the discovery. Any unauthorized collection or disturbance of cultural or paleontological resources may result in a shutdown order by the Authorized Officer.

IV. NOXIOUS WEEDS

The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

V. SPECIAL REQUIREMENT(S)

Timing Limitation Stipulation / Condition of Approval for lesser prairie-chicken:

Oil and gas activities including 3-D geophysical exploration, and drilling will not be allowed in lesser prairie-chicken habitat during the period from March 1st through June 15th annually. During that period, other activities that produce noise or involve human activity, such as the maintenance of oil and gas facilities, pipeline, road, and well pad construction, will be allowed except between 3:00 am and 9:00 am. The 3:00 am to 9:00 am restriction will not apply to normal, around-the-clock operations, such as venting, flaring, or pumping, which do not require a human presence during this period. Additionally, no new drilling will be allowed within up to 200 meters of leks known at the time of permitting. Normal vehicle use on existing roads will not be restricted. Exhaust noise from pump jack engines must be muffled or otherwise controlled so as not to exceed 75 db measured at 30 feet from the source of the noise.

Timing Limitation Exceptions:

The Carlsbad Field Office will publish an annual map of where the LPC timing and noise stipulations and conditions of approval (Limitations) will apply for the identified year (between March 1 and June 15) based on the latest survey information. The LPC Timing Area map will identify areas which are Habitat Areas (HA), Isolated Population Area (IPA), and Primary Population Area (PPA). The LPC Timing Area map will also have an area in red crosshatch. The red crosshatch area is the only area where an operator is required to submit a request for exception to the LPC Limitations. If an operator is operating outside the red crosshatch area, the LPC Limitations do not apply for that year and an exception to LPC Limitations is not required.

Ground-level Abandoned Well Marker to avoid raptor perching: Upon the plugging and subsequent abandonment of the well, the well marker will be installed at ground level on a plate containing the pertinent information for the plugged well. For more installation details, contact the Carlsbad Field Office at 575-234-5972.

Hydrology

- The entire well pad will be bermed to prevent oil, salt, and other chemical contaminants from leaving the well pad. Topsoil shall not be used to construct the berm. No water flow from the uphill side(s) of the pad shall be allowed to enter the well pad. The berm shall be maintained through the life of the well and after interim reclamation has been completed.
- Any water erosion that may occur due to the construction of the well pad during the life of the well will be quickly corrected and proper measures will be taken to prevent future erosion.
- Exhaust noise from pump jack engines must be muffled or otherwise controlled so as not to exceed 75 db measured at 30 ft. from the source of the noise.

- Tank battery locations will be lined and bermed. A 20 mil permanent liner will be installed with a 4 oz. felt backing to prevent tears or punctures. Tank battery berms must be large enough to contain 1 ½ times the content of the largest tank.
- Automatic shut off, check valves, or similar systems will be installed for tanks to minimize the effects of catastrophic line failures used in production or drilling.
- A leak detection plan will be submitted to the BLM Carlsbad Field Office for approval prior to pipeline installation. The method could incorporate gauges to detect pressure drops, siting valves and lines so they can be visually inspected periodically or installing electronic sensors to alarm when a leak is present. The leak detection plan will incorporate an automatic shut off system that will be installed for proposed pipelines to minimize the effects of an undesirable event.

VI. CONSTRUCTION

A. NOTIFICATION

The BLM shall administer compliance and monitor construction of the access road and well pad. Notify the Carlsbad Field Office at (575) 234-5909 at least 3 working days prior to commencing construction of the access road and/or well pad.

When construction operations are being conducted on this well, the operator shall have the approved APD and Conditions of Approval (COA) on the well site and they shall be made available upon request by the Authorized Officer.

B. TOPSOIL

The operator shall strip the top portion of the soil (root zone) from the entire well pad area and stockpile the topsoil along the edge of the well pad as depicted in the APD. The root zone is typically six (6) inches in depth. All the stockpiled topsoil will be redistributed over the interim reclamation areas. Topsoil shall not be used for berming the pad or facilities. For final reclamation, the topsoil shall be spread over the entire pad area for seeding preparation.

Other subsoil (below six inches) stockpiles must be completely segregated from the topsoil stockpile. Large rocks or subsoil clods (not evident in the surrounding terrain) must be buried within the approved area for interim and final reclamation.

C. CLOSED LOOP SYSTEM

Tanks are required for drilling operations: No Pits.

The operator shall properly dispose of drilling contents at an authorized disposal site.

D. FEDERAL MINERAL MATERIALS PIT

Payment shall be made to the BLM prior to removal of any federal mineral materials. Call the Carlsbad Field Office at (575) 234-5972.

E. WELL PAD SURFACING

Surfacing of the well pad is not required.

If the operator elects to surface the well pad, the surfacing material may be required to be removed at the time of reclamation. The well pad shall be constructed in a manner which creates the smallest possible surface disturbance, consistent with safety and operational needs.

F. EXCLOSURE FENCING (CELLARS & PITS)

Exclosure Fencing

The operator will install and maintain exclosure fencing for all open well cellars to prevent access to public, livestock, and large forms of wildlife before and after drilling operations until the pit is free of fluids and the operator initiates backfilling. (For examples of exclosure fencing design, refer to BLM's Oil and Gas Gold Book, Exclosure Fence Illustrations, Figure 1, Page 18.)

G. ON LEASE ACCESS ROADS**Road Width**

The access road shall have a driving surface that creates the smallest possible surface disturbance and does not exceed fourteen (14) feet in width. The maximum width of surface disturbance, when constructing the access road, shall not exceed twenty-five (25) feet.

Surfacing

Surfacing material is not required on the new access road driving surface. If the operator elects to surface the new access road or pad, the surfacing material may be required to be removed at the time of reclamation.

Where possible, no improvements should be made on the unsurfaced access road other than to remove vegetation as necessary, road irregularities, safety issues, or to fill low areas that may sustain standing water.

The Authorized Officer reserves the right to require surfacing of any portion of the access road at any time deemed necessary. Surfacing may be required in the event the road deteriorates, erodes, road traffic increases, or it is determined to be beneficial for future field development. The surfacing depth and type of material will be determined at the time of notification.

Crowning

Crowning shall be done on the access road driving surface. The road crown shall have a grade of approximately 2% (i.e., a 1" crown on a 14' wide road). The road shall conform to Figure 1; cross section and plans for typical road construction.

Ditching

Ditching shall be required on both sides of the road.

Turnouts


Vehicle turnouts shall be constructed on the road. Turnouts shall be intervisible with interval spacing distance less than 1000 feet. Turnouts shall conform to Figure 1; cross section and plans for typical road construction.

Drainage

Drainage control systems shall be constructed on the entire length of road (e.g. ditches, sidehill outslowing and insloping, lead-off ditches, culvert installation, and low water crossings).

A typical lead-off ditch has a minimum depth of 1 foot below and a berm of 6 inches above natural ground level. The berm shall be on the down-slope side of the lead-off ditch.

Cross Section of a Typical Lead-off Ditch



All lead-off ditches shall be graded to drain water with a 1 percent minimum to 3 percent maximum ditch slope. The spacing interval are variable for lead-off ditches and shall be determined according to the formula for spacing intervals of lead-off ditches, but may be amended depending upon existing soil types and centerline road slope (in %);

Formula for Spacing Interval of Lead-off Ditches

Example - On a 4% road slope that is 400 feet long, the water flow shall drain water into a lead-off ditch. Spacing interval shall be determined by the following formula:

$$400 \text{ foot road with } 4\% \text{ road slope: } \frac{400'}{4\%} + 100' = 200' \text{ lead-off ditch interval}$$

Cattle guards

An appropriately sized cattle guard sufficient to carry out the project shall be installed and maintained at fence/road crossings. Any existing cattle guards on the access road route shall be repaired or replaced if they are damaged or have deteriorated beyond practical use. The operator shall be responsible for the condition of the existing cattle guards that are in place and are utilized during lease operations.

Fence Requirement

Where entry is granted across a fence line, the fence shall be braced and tied off on both sides of the passageway prior to cutting. The operator shall notify the private surface landowner or the grazing allotment holder prior to crossing any fences.

Public Access

Public access on this road shall not be restricted by the operator without specific written approval granted by the Authorized Officer.

Construction Steps

1. Salvage topsoil
2. Construct road

3. Redistribute topsoil
4. Revegetate slopes




Figure 1. Cross-sections and plans for typical road sections representative of BLM resource or FS local and higher-class roads.

VII. PRODUCTION (POST DRILLING)

A. WELL STRUCTURES & FACILITIES

Placement of Production Facilities

Production facilities should be placed on the well pad to allow for maximum interim recontouring and revegetation of the well location.

Exclosure Netting (Open-top Tanks)

Immediately following active drilling or completion operations, the operator will take actions necessary to prevent wildlife and livestock access, including avian wildlife, to all open-topped tanks that contain or have the potential to contain salinity sufficient to cause harm to wildlife or livestock, hydrocarbons, or Resource Conservation and Recovery Act of 1976-exempt hazardous substances. At a minimum, the operator will net, screen, or cover open-topped tanks to exclude wildlife and livestock and prevent mortality. If the operator uses netting, the operator will cover and secure the open portion of the tank to prevent wildlife entry. The operator will net, screen, or cover the tanks until the operator removes the tanks from the location or the tanks no longer contain substances that could be harmful to wildlife or livestock. Use a maximum netting mesh size of 1 ½ inches. The netting must not be in contact with fluids and must not have holes or gaps.

Chemical and Fuel Secondary Containment and Exclosure Screening

The operator will prevent all hazardous, poisonous, flammable, and toxic substances from coming into contact with soil and water. At a minimum, the operator will install and maintain an impervious secondary containment system for any tank or barrel containing hazardous, poisonous, flammable, or toxic substances sufficient to contain the contents of the tank or barrel and any drips, leaks, and anticipated precipitation. The operator will dispose of fluids within the containment system that do not meet applicable state or U. S. Environmental Protection Agency livestock water standards in accordance with state law; the operator must not drain the fluids to the soil or ground. The operator will design, construct, and maintain all secondary containment systems to prevent wildlife and livestock exposure to harmful substances. At a minimum, the operator will install effective wildlife and livestock exclosure systems such as fencing, netting, expanded metal mesh, lids, and grate covers. Use a maximum netting mesh size of 1 ½ inches.

Open-Vent Exhaust Stack Exclosures

The operator will construct, modify, equip, and maintain all open-vent exhaust stacks on production equipment to prevent birds and bats from entering, and to discourage perching, roosting, and nesting. (*Recommended exclosure structures on open-vent exhaust stacks are in the shape of a cone.*) Production equipment includes, but may not be limited to, tanks, heater-treaters, separators, dehydrators, flare stacks, in-line units, and compressor mufflers.

Containment Structures

Proposed production facilities such as storage tanks and other vessels will have a secondary containment structure that is constructed to hold the capacity of 1.5 times the largest tank, plus freeboard to account for precipitation, unless more stringent protective requirements are deemed necessary.

Painting Requirement

All above-ground structures including meter housing that are not subject to safety requirements shall be painted a flat non-reflective paint color, **Shale Green** from the BLM Standard Environmental Color Chart (CC-001: June 2008).

B. PIPELINES

STANDARD STIPULATIONS FOR SURFACE INSTALLED PIPELINES

A copy of the application (Grant, Sundry Notice, APD) and attachments, including stipulations, survey plat and/or map, will be on location during construction. BLM personnel may request to you a copy of your permit during construction to ensure compliance with all stipulations.

Holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer:

1. The holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant.
2. The holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976 as amended, 15 USC 2601 et seq. (1982) with regards to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized under this right-of-way grant. (See 40 CFR, Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR, Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation, and Liability Act, section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the authorized officer concurrent with the filing of the reports to the involved Federal agency or State government.
3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, et seq. or the Resource Conservation and Recovery Act, 42 U.S.C. 6901, et seq.) on the Right-of-Way (unless the release or threatened release is wholly unrelated to activity of the Right-of-Way holder's activity on the Right-of-Way), or resulting from the activity of the Right-of-Way holder on the Right-of-Way. This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

4. The holder shall be liable for damage or injury to the United States to the extent provided by 43 CFR Sec. 2883.1-4. The holder shall be held to a standard of strict liability for damage or injury to the United States resulting from pipe rupture, fire, or spills caused or substantially aggravated by any of the following within the right-of-way or permit area:

- a. Activities of the holder including, but not limited to construction, operation, maintenance, and termination of the facility.
- b. Activities of other parties including, but not limited to:
 - (1) Land clearing.
 - (2) Earth-disturbing and earth-moving work.
 - (3) Blasting.
 - (4) Vandalism and sabotage.
- c. Acts of God.

The maximum limitation for such strict liability damages shall not exceed one million dollars (\$1,000,000) for any one event, and any liability in excess of such amount shall be determined by the ordinary rules of negligence of the jurisdiction in which the damage or injury occurred.

This section shall not impose strict liability for damage or injury resulting primarily from an act of war or from the negligent acts or omissions of the United States.

5. If, during any phase of the construction, operation, maintenance, or termination of the pipeline, any oil, salt water, or other pollutant should be discharged from the pipeline system, impacting Federal lands, the control and total removal, disposal, and cleaning up of such oil, salt water, or other pollutant, wherever found, shall be the responsibility of the holder, regardless of fault. Upon failure of the holder to control, dispose of, or clean up such discharge on or affecting Federal lands, or to repair all damages resulting therefrom, on the Federal lands, the Authorized Officer may take such measures as he deems necessary to control and clean up the discharge and restore the area, including, where appropriate, the aquatic environment and fish and wildlife habitats, at the full expense of the holder. Such action by the Authorized Officer shall not relieve the holder of any responsibility as provided herein.

6. All construction and maintenance activity will be confined to the authorized right-of-way width of 20 feet. If the pipeline route follows an existing road or buried pipeline right-of-way, the surface pipeline must be installed no farther than 10 feet from the edge of the road or buried pipeline right-of-way. If existing surface pipelines prevent this distance, the proposed surface pipeline must be installed immediately adjacent to the outer surface pipeline. All construction and maintenance activity will be confined to existing roads or right-of-ways.

7. No blading or clearing of any vegetation will be allowed unless approved in writing by the Authorized Officer.

8. The holder shall install the pipeline on the surface in such a manner that will minimize suspension of the pipeline across low areas in the terrain. In hummocky or dune areas, the pipeline will be "snaked" around hummocks and dunes rather than suspended across these features.

9. The pipeline shall be buried with a minimum of 24 inches under all roads, "two-tracks," and trails. Burial of the pipe will continue for 20 feet on each side of each crossing. The condition of the road, upon completion of construction, shall be returned to at least its former state with no bumps or dips remaining in the road surface.

10. The holder shall minimize disturbance to existing fences and other improvements on public lands. The holder is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the owner of any improvements prior to disturbing them. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting of the fence. No permanent gates will be allowed unless approved by the Authorized Officer.

11. In those areas where erosion control structures are required to stabilize soil conditions, the holder will install such structures as are suitable for the specific soil conditions being encountered and which are in accordance with sound resource management practices.

12. Excluding the pipe, all above-ground structures not subject to safety requirement shall be painted by the holder to blend with the natural color of the landscape. The paint used shall be a color which simulates "Standard Environmental Colors" – **Shale Green**, Munsell Soil Color No. 5Y 4/2; designated by the Rocky Mountain Five State Interagency Committee.

13. The pipeline will be identified by signs at the point of origin and completion of the right-of-way and at all road crossings. At a minimum, signs will state the holder's name, BLM serial number, and the product being transported. Signs will be maintained in a legible condition for the life of the pipeline.

14. The holder shall not use the pipeline route as a road for purposes other than routine maintenance as determined necessary by the Authorized Officer in consultation with the holder. The holder will take whatever steps are necessary to ensure that the pipeline route is not used as a roadway.

15. Any cultural and/or paleontological resource (historic or prehistoric site or object) discovered by the holder, or any person working on his behalf, on public or Federal land shall be immediately reported to the authorized officer. Holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the authorized officer. An evaluation of the discovery will be made by the authorized officer to determine appropriate cultural or scientific values. The holder will

be responsible for the cost of evaluation and any decision as to proper mitigation measures will be made by the authorized officer after consulting with the holder.

16. The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, powerline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

17. Surface pipelines must be less than or equal to 4 inches and a working pressure below 125 psi.

18. Special Stipulations:

- a. **Lesser Prairie-Chicken:** Oil and gas activities will not be allowed in lesser prairie-chicken habitat during the period from March 1st through June 15th annually. During that period, other activities that produce noise or involve human activity, such as the maintenance of oil and gas facilities and pipeline, road, and well pad construction, will be allowed except between 3:00 am and 9:00 am. The 3:00 am to 9:00 am restriction will not apply to normal, around-the-clock operations, such as venting, flaring, or pumping, which do not require a human presence during this period. Normal vehicle use on existing roads will not be restricted.
- b. This authorization is subject to your Certificate of Participation and/or Certificate of Inclusion under the New Mexico Candidate Conservation Agreement. Because it involves surface disturbing activities covered under your Certificate, your Habitat Conservation Fund Account with the Center of Excellence for Hazardous Materials Management (CEHMM) will be debited according to Exhibit B Part 2 of the Certificate of Participation.

BURIED PIPELINE STIPULATIONS

A copy of the application (Grant, APD, or Sundry Notice) and attachments, including conditions of approval, survey plat and/or map, will be on location during construction. BLM personnel may request to you a copy of your permit during construction to ensure compliance with all stipulations.

Holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer:

1. The Holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant.

2. The Holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976 as amended, 15 USC 2601 et seq. (1982) with regards to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized under this right-of-way grant. (See 40 CFR Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation, and Liability Act, section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the authorized officer concurrent with the filing of the reports to the involved Federal agency or State government.

3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, et seq. or the Resource Conservation and Recovery Act, 42 U.S.C. 6901, et seq.) on the Right-of-Way (unless the release or threatened release is wholly unrelated to the Right-of-Way holder's activity on the Right-of-Way), or resulting from the activity of the Right-of-Way holder on the Right-of-Way. This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

4. If, during any phase of the construction, operation, maintenance, or termination of the pipeline, any oil or other pollutant should be discharged from the pipeline system, impacting Federal lands, the control and total removal, disposal, and cleaning up of such oil or other pollutant, wherever found, shall be the responsibility of holder, regardless of fault. Upon failure of holder to control, dispose of, or clean up such discharge on or affecting Federal lands, or to repair all damages resulting therefrom, on the Federal lands, the Authorized Officer may take such measures as he deems necessary to control and clean up the discharge and restore the area, including where appropriate, the aquatic environment and fish and wildlife habitats, at the full expense of the holder. Such action by the Authorized Officer shall not relieve holder of any responsibility as provided herein.

5. All construction and maintenance activity will be confined to the authorized right-of-way.
6. The pipeline will be buried with a minimum cover of 36 inches between the top of the pipe and ground level.
7. The maximum allowable disturbance for construction in this right-of-way will be 30 feet:
- Blading of vegetation within the right-of-way will be allowed: maximum width of blading operations will not exceed 20 feet. The trench is included in this area. (*Blading is defined as the complete removal of brush and ground vegetation.*)
 - Clearing of brush species within the right-of-way will be allowed: maximum width of clearing operations will not exceed 30 feet. The trench and bladed area are included in this area. (*Clearing is defined as the removal of brush while leaving ground vegetation (grasses, weeds, etc.) intact. Clearing is best accomplished by holding the blade 4 to 6 inches above the ground surface.*)
 - The remaining area of the right-of-way (if any) shall only be disturbed by compressing the vegetation. (*Compressing can be caused by vehicle tires, placement of equipment, etc.*)
8. The holder shall stockpile an adequate amount of topsoil where blading is allowed. The topsoil to be stripped is approximately 6 inches in depth. The topsoil will be segregated from other spoil piles from trench construction. The topsoil will be evenly distributed over the bladed area for the preparation of seeding.
9. The holder shall minimize disturbance to existing fences and other improvements on public lands. The holder is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the owner of any improvements prior to disturbing them. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting of the fence. No permanent gates will be allowed unless approved by the Authorized Officer.
10. Vegetation, soil, and rocks left as a result of construction or maintenance activity will be randomly scattered on this right-of-way and will not be left in rows, piles, or berms, unless otherwise approved by the Authorized Officer. The entire right-of-way shall be recontoured to match the surrounding landscape. The backfilled soil shall be compacted and a 6 inch berm will be left over the ditch line to allow for settling back to grade.
11. In those areas where erosion control structures are required to stabilize soil conditions, the holder will install such structures as are suitable for the specific soil conditions being encountered and which are in accordance with sound resource management practices.

12. The holder will reseed all disturbed areas. Seeding will be done according to the attached seeding requirements, using the following seed mix.

- | | |
|--|--|
| <input type="checkbox"/> seed mixture 1 | <input type="checkbox"/> seed mixture 3 |
| <input type="checkbox"/> seed mixture 2 | <input type="checkbox"/> seed mixture 4 |
| <input checked="" type="checkbox"/> seed mixture 2/LPC | <input type="checkbox"/> Aplomado Falcon Mixture |

13. All above-ground structures not subject to safety requirements shall be painted by the holder to blend with the natural color of the landscape. The paint used shall be color which simulates "Standard Environmental Colors" – **Shale Green**, Munsell Soil Color No. 5Y 4/2.

14. The pipeline will be identified by signs at the point of origin and completion of the right-of-way and at all road crossings. At a minimum, signs will state the holder's name, BLM serial number, and the product being transported. All signs and information thereon will be posted in a permanent, conspicuous manner, and will be maintained in a legible condition for the life of the pipeline.

15. The holder shall not use the pipeline route as a road for purposes other than routine maintenance as determined necessary by the Authorized Officer in consultation with the holder before maintenance begins. The holder will take whatever steps are necessary to ensure that the pipeline route is not used as a roadway. As determined necessary during the life of the pipeline, the Authorized Officer may ask the holder to construct temporary deterrence structures.

16. Any cultural and/or paleontological resources (historic or prehistoric site or object) discovered by the holder, or any person working on his behalf, on public or Federal land shall be immediately reported to the Authorized Officer. Holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery will be made by the Authorized Officer to determine appropriate actions to prevent the loss of significant cultural or scientific values. The holder will be responsible for the cost of evaluation and any decision as to proper mitigation measures will be made by the Authorized Officer after consulting with the holder.

17. The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes associated roads, pipeline corridor and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

18. Escape Ramps - The operator will construct and maintain pipeline/utility trenches [that are not otherwise fenced, screened, or netted] to prevent livestock, wildlife, and humans from becoming entrapped. At a minimum, the operator will construct and maintain escape ramps,

ladders, or other methods of avian and terrestrial wildlife escape in the trenches according to the following criteria:

- a. Any trench left open for eight (8) hours or less is not required to have escape ramps; however, before the trench is backfilled, the contractor/operator shall inspect the trench for wildlife, remove all trapped wildlife, and release them at least 100 yards from the trench.
- b. For trenches left open for eight (8) hours or more, earthen escape ramps (built at no more than a 30 degree slope and spaced no more than 500 feet apart) shall be placed in the trench.

19. Special Stipulations:

Lesser Prairie-Chicken

Oil and gas activities will not be allowed in lesser prairie-chicken habitat during the period from March 1st through June 15th annually. During that period, other activities that produce noise or involve human activity, such as the maintenance of oil and gas facilities, geophysical exploration other than 3-D operations, and pipeline, road, and well pad construction, will be allowed except between 3:00 am and 9:00 am. The 3:00 am to 9:00 am restriction will not apply to normal, around-the-clock operations, such as venting, flaring, or pumping, which do not require a human presence during this period. Normal vehicle use on existing roads will not be restricted. Exhaust noise from pump jack engines must be muffled or otherwise controlled so as not to exceed 75 db measured at 30 ft. from the source of the noise.

C. ELECTRIC LINES

STANDARD STIPULATIONS FOR OVERHEAD ELECTRIC DISTRIBUTION LINES

A copy of the grant and attachments, including stipulations, survey plat and/or map, will be on location during construction. BLM personnel may request to you a copy of your permit during construction to ensure compliance with all stipulations.

Holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer:

1. The holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant.
2. The holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976 as amended, 15 USC 2601 et seq. (1982) with regards to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized under this right-of-way grant. (See 40 CFR, Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR, Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation, and Liability Act, section 102b.

A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the authorized officer concurrent with the filing of the reports to the involved Federal agency or State government.

3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, et seq. or the Resource Conservation and Recovery Act, 42 U.S.C. 6901, et seq.) on the Right-of-Way (unless the release or threatened release is wholly unrelated to the Right-of-Way holder's activity on the Right-of-Way), or resulting from the activity of the Right-of-Way holder on the Right-of-Way. This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

4. There will be no clearing or blading of the right-of-way unless otherwise agreed to in writing by the Authorized Officer.

5. Power lines shall be constructed and designed in accordance to standards outlined in "Suggested Practices for Avian Protection on Power lines: The State of the Art in 2006" Edison Electric Institute, APLIC, and the California Energy Commission 2006 . The holder shall assume the burden and expense of proving that pole designs not shown in the above publication deter raptor perching, roosting, and nesting. Such proof shall be provided by a raptor expert approved by the Authorized Officer. The BLM reserves the right to require modification or additions to all powerline structures placed on this right-of-way, should they be necessary to ensure the safety of large perching birds. Such modifications and/or additions shall be made by the holder without liability or expense to the United States.

Raptor deterrence will consist of but not limited to the following: triangle perch discouragers shall be placed on each side of the cross arms and a nonconductive perching deterrence shall be placed on all vertical poles that extend past the cross arms.

6. The holder shall minimize disturbance to existing fences and other improvements on public lands. The holder is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the owner of any improvements prior to disturbing them. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting the fence. No permanent gates will be allowed unless approved by the Authorized Officer.

7. The BLM serial number assigned to this authorization shall be posted in a permanent, conspicuous manner where the power line crosses roads and at all serviced facilities. Numbers will be at least two inches high and will be affixed to the pole nearest the road crossing and at the facilities served.

8. Upon cancellation, relinquishment, or expiration of this grant, the holder shall comply

with those abandonment procedures as prescribed by the Authorized Officer.

9. All surface structures (poles, lines, transformers, etc.) shall be removed within 180 days of abandonment, relinquishment, or termination of use of the serviced facility or facilities or within 180 days of abandonment, relinquishment, cancellation, or expiration of this grant, whichever comes first. This will not apply where the power line extends service to an active, adjoining facility or facilities.

10. Any cultural and/or paleontological resource (historic or prehistoric site or object) discovered by the holder, or any person working on his behalf, on public or Federal land shall be immediately reported to the Authorized Officer. Holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery will be made by the Authorized Officer to determine appropriate actions to prevent the loss of significant cultural or scientific values. The holder will be responsible for the cost of evaluation and any decision as to proper mitigation measures will be made by the Authorized Officer after consulting with the holder.

11. Special Stipulations:

- For reclamation remove poles, lines, transformer, etc. and dispose of properly.
- Fill in any holes from the poles removed.

Timing Limitation Stipulation/Condition of Approval for Lesser Prairie-Chicken:

Oil and gas activities including 3-D geophysical exploration, and drilling will not be allowed in lesser prairie-chicken habitat during the period from March 1st through June 15th annually. During that period, other activities that produce noise or involve human activity, such as the maintenance of oil and gas facilities, geophysical exploration other than 3-D operations, and pipeline, road, and well pad construction, will be allowed except between 3:00 am and 9:00 am. The 3:00 am to 9:00 am restriction will not apply to normal, around-the-clock operations, such as venting, flaring, or pumping, which do not require a human presence during this period. Additionally, no new drilling will be allowed within up to 200 meters of leks known at the time of permitting. Normal vehicle use on existing roads will not be restricted. Exhaust noise from pump jack engines must be muffled or otherwise controlled so as not to exceed 75 db measured at 30 ft. from the source of the noise.

VIII. INTERIM RECLAMATION

During the life of the development, all disturbed areas not needed for active support of production operations should undergo interim reclamation in order to minimize the environmental impacts of development on other resources and uses.

Within six (6) months of well completion, operators should work with BLM surface management specialists (Jim Amos: 575-234-5909) to devise the best strategies to reduce the size of the location. Interim reclamation should allow for remedial well operations, as well as safe and efficient removal of oil and gas.

During reclamation, the removal of caliche is important to increasing the success of revegetating the site. Removed caliche that is free of contaminants may be used for road repairs, fire walls or for building other roads and locations. In order to operate the well or complete workover operations, it may be necessary to drive, park and operate on restored interim vegetation within the previously disturbed area. Disturbing revegetated areas for production or workover operations will be allowed. If there is significant disturbance and loss of vegetation, the area will need to be revegetated. Communicate with the appropriate BLM office for any exceptions/exemptions if needed.

All disturbed areas after they have been satisfactorily prepared need to be reseeded with the seed mixture provided below.

Upon completion of interim reclamation, the operator shall submit a Sundry Notices and Reports on Wells, Subsequent Report of Reclamation (Form 3160-5).

IX. FINAL ABANDONMENT & RECLAMATION

At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land are restored.

Earthwork for final reclamation must be completed within six (6) months of well plugging. All pads, pits, facility locations and roads must be reclaimed to a satisfactory revegetated, safe, and stable condition, unless an agreement is made with the landowner or BLM to keep the road and/or pad intact.

After all disturbed areas have been satisfactorily prepared, these areas need to be revegetated with the seed mixture provided below. Seeding should be accomplished by drilling on the contour whenever practical or by other approved methods. Seeding may need to be repeated until revegetation is successful, as determined by the BLM.

Operators shall contact a BLM surface protection specialist prior to surface abandonment operations for site specific objectives (Jim Amos: 575-234-5909).

Ground-level Abandoned Well Marker to avoid raptor perching: Upon the plugging and subsequent abandonment of the well, the well marker will be installed at ground level on a plate containing the pertinent information for the plugged well.

Seed Mixture for LPC Sand/Shinnery Sites

Holder shall seed all disturbed areas with the seed mixture listed below. The seed mixture shall be planted in the amounts specified in pounds of pure live seed (PLS)* per acre. There shall be no primary or secondary noxious weeds in the seed mixture. Seed will be tested and the viability testing of seed shall be done in accordance with State law(s) and within nine (9) months prior to purchase. Commercial seed shall be either certified or registered seed. The seed container shall be tagged in accordance with State law(s) and available for inspection by the Authorized Officer.

Seed will be planted using a drill equipped with a depth regulator to ensure proper depth of planting where drilling is possible. The seed mixture will be evenly and uniformly planted over the disturbed area (smaller/heavier seeds have a tendency to drop the bottom of the drill and are planted first). Holder shall take appropriate measures to ensure this does not occur. Where drilling is not possible, seed will be broadcast and the area shall be raked or chained to cover the seed. When broadcasting the seed, the pounds per acre are to be doubled. Seeding shall be repeated until a satisfactory stand is established as determined by the Authorized Officer. Evaluation of growth may not be made before completion of at least one full growing season after seeding.

Species to be planted in pounds of pure live seed* per acre:

<u>Species</u>	<u>lb/acre</u>
Plains Bristlegrass	5lbs/A
Sand Bluestem	5lbs/A
Little Bluestem	3lbs/A
Big Bluestem	6lbs/A
Plains Coreopsis	2lbs/A
Sand Dropseed	1lbs/A

*Pounds of pure live seed:

Pounds of seed x percent purity x percent germination = pounds pure live seed



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Operator Certification Data Report

05/03/2019

Operator Certification

I hereby certify that I, or someone under my direct supervision, have inspected the drill site and access route proposed herein; that I am familiar with the conditions which currently exist; that I have full knowledge of state and Federal laws applicable to this operation; that the statements made in this APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for the operations conducted under this application. These statements are subject to the provisions of 18 U.S.C. 1001 for the filing of false statements.

NAME: Christie Hanna

Signed on: 04/04/2019

Title: Senior Engineering Technician

Street Address: 5707 Southwest Parkway, Building 1, Suite 275

City: Austin

State: TX

Zip: 78735

Phone: (737)300-4723

Email address: channa@ameredev.com

Field Representative

Representative Name: Zachary Boyd

Street Address: 5707 Southwest Parkway, Building 1, Suite 275

City: Austin

State: TX

Zip: 78735

Phone: (432)385-6996

Email address: zboyd@ameredev.com



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Application Data Report

05/03/2019

APD ID: 10400029259

Submission Date: 04/10/2018

Operator Name: AMEREDEV OPERATING LLC

Well Name: CAMELLIA FED COM 26 36 21

Well Number: 121H

Well Type: OIL WELL

Well Work Type: Drill

[Show Final Text](#)

Section 1 - General

APD ID: 10400029259

Tie to previous NOS?

Submission Date: 04/10/2018

BLM Office: CARLSBAD

User: Christie Hanna

Title: Senior Engineering Technician

Federal/Indian APD: FED

Is the first lease penetrated for production Federal or Indian? FED

Lease number: NMNM023199

Lease Acres: 320

Surface access agreement in place?

Allotted?

Reservation:

Agreement in place? NO

Federal or Indian agreement:

Agreement number:

Agreement name:

Keep application confidential? NO

Permitting Agent? NO

APD Operator: AMEREDEV OPERATING LLC

Operator letter of designation:

Operator Info

Operator Organization Name: AMEREDEV OPERATING LLC

Operator Address: 5707 Southwest Parkway, Building 1, Suite 275

Zip: 78735

Operator PO Box:

Operator City: Austin

State: TX

Operator Phone: (737)300-4700

Operator Internet Address:

Section 2 - Well Information

Well in Master Development Plan? NO

Master Development Plan name:

Well in Master SUPO? NO

Master SUPO name:

Well in Master Drilling Plan? NO

Master Drilling Plan name:

Well Name: CAMELLIA FED COM 26 36 21

Well Number: 121H

Well API Number:

Field/Pool or Exploratory? Field and Pool

Field Name: JAL

Pool Name: WOLFCAMP
WEST

Is the proposed well in an area containing other mineral resources? USFARI F WATER

Operator Name: AMEREDEV OPERATING LLC

Well Name: CAMELLIA FED COM 26 36 21

Well Number: 121H

Describe other minerals:

Is the proposed well in a Helium production area? N **Use Existing Well Pad?** NO **New surface disturbance?**

Type of Well Pad: MULTIPLE WELL

Multiple Well Pad Name:

Number: 1N

Well Class: HORIZONTAL

CAM/AZE

Number of Legs: 1

Well Work Type: Drill

Well Type: OIL WELL

Describe Well Type:

Well sub-Type: INFILL

Describe sub-type:

Distance to town: 5 Miles

Distance to nearest well: 720 FT

Distance to lease line: 270 FT

Reservoir well spacing assigned acres Measurement: 320 Acres

Well plat: CAMELLIA_FED_COM_26_36_21_121H__BLM_LEASE_MAP_20190313125605.pdf

CAMELLIA_FED_COM_26_36_21_121H__VICINITY_MAP_20190313125609.pdf

CAMELLIA_FED_COM_26_36_21_121H__EXH_2AB_20190313125608.pdf

CAMELLIA_FED_COM_26_36_21_121H__GAS_CAPTURE_PLAN_20190313125621.pdf

CAMELLIA_FED_COM_26_36_21_121H__C_102_SIG_20190313145131.pdf

Well work start Date: 03/15/2019

Duration: 90 DAYS

Section 3 - Well Location Table

Survey Type: RECTANGULAR

Describe Survey Type:

Datum: NAD83

Vertical Datum: NAVD88

Survey number: 19642

	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	MD	TVD
SHL Leg #1	283	FSL	270	FWL	26S	36E	21	Lot M	32.02229 61	- 103.2777 208	LEA	NEW MEXI CO	NEW MEXI CO	F	NMNM 023199	292 4	0	0

Operator Name: AMEREDEV OPERATING LLC

Well Name: CAMELLIA FED COM 26 36 21

Well Number: 121H

	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	MD	TVD
KOP Leg #1	379	FNL	270	FWL	26S	36E	28	Aliquot NWN W	32.02047	- 103.2777 4	LEA	NEW MEXI CO	NEW MEXI CO	S	STATE	- 907 6	120 34	120 00
PPP Leg #1	50	FNL	200	FWL	26S	36E	16	Lot D	32.05041	- 103.2779 6	LEA	NEW MEXI CO	NEW MEXI CO	S	STATE	- 963 6	232 83	125 60
EXIT Leg #1	50	FNL	200	FWL	26S	36E	16	Lot D	32.05041	- 103.2779 6	LEA	NEW MEXI CO	NEW MEXI CO	S	STATE	- 963 6	232 83	125 60
BHL Leg #1	50	FNL	200	FWL	26S	36E	16	Lot D	32.05041	- 103.2779 6	LEA	NEW MEXI CO	NEW MEXI CO	S	STATE	- 963 6	232 83	125 60



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Drilling Plan Data Report

05/03/2019

APD ID: 10400029259

Submission Date: 04/10/2018

Operator Name: AMEREDEV OPERATING LLC

Well Name: CAMELLIA FED COM 26 36 21

Well Number: 121H

Well Type: OIL WELL

Well Work Type: Drill

[Show Final Text](#)

Section 1 - Geologic Formations

Formation ID	Formation Name	Elevation	True Vertical Depth	Measured Depth	Lithologies	Mineral Resources	Producing Formation
1	RUSTLER ANHYDRITE	1054	1876	1876	ANHYDRITE	NONE	No
2	SALADO	-1170	2224	2224	SALT	NONE	No
3	TANSILL	-2152	3206	3206	LIMESTONE	NONE	No
4	CAPITAN REEF	-2567	3621	3621	LIMESTONE	USEABLE WATER	No
5	LAMAR	-3898	4952	4952	LIMESTONE	NONE	No
6	BELL CANYON	-4032	5086	5086	SANDSTONE	NATURAL GAS,OIL	No
7	BRUSHY CANYON	-6051	7105	7105	SANDSTONE	NATURAL GAS,OIL	No
8	BONE SPRING LIME	-7075	8129	8129	LIMESTONE	NONE	No
9	BONE SPRING 1ST	-8577	9631	9631	SANDSTONE	NATURAL GAS,OIL	No
10	BONE SPRING 2ND	-9221	10275	10275	SANDSTONE	NATURAL GAS,OIL	No
11	BONE SPRING 3RD	-9752	10806	10806	LIMESTONE	NATURAL GAS,OIL	No
12	BONE SPRING 3RD	-10468	11522	11522	SANDSTONE	NATURAL GAS,OIL	No
13	WOLFCAMP	-10701	11755	11755	SHALE	NATURAL GAS,OIL	No
14	WOLFCAMP	-11156	12210	12210	SHALE	NATURAL GAS,OIL	Yes

Section 2 - Blowout Prevention

Operator Name: AMEREDEV OPERATING LLC

Well Name: CAMELLIA FED COM 26 36 21

Well Number: 121H

Pressure Rating (PSI): 10M

Rating Depth: 15000

Equipment: 10M BOPE SYSTEM WILL BE USED AFTER THE SURFACE CASING IS SET. A KELLY COCK WILL BE KEPT IN THE DRILL STRING AT ALL TIMES. A FULL OPENING DRILL PIPE STABBING VALVE WITH PROPER DRILL PIPE CONNECTIONS WILL BE ON THE RIG FLOOR AT ALL TIMES.

Requesting Variance? YES

Variance request: Co-Flex Choke Line, 5M Annular Preventer

Testing Procedure: See attachment

Choke Diagram Attachment:

10M_Choke_Manifold_REV_20190313141742.pdf

BOP Diagram Attachment:

5M_Annular_Preventer_Variance_and_Well_Control_Plan_20190313141808.pdf

5M_BOP_System_20190313141809.pdf

Pressure_Control_Plan_Single_Well_MB4_3String_Big_Hole_BLM_20190313141809.pdf

4_String_MB_Ameredev_Wellhead_Drawing_net_REV_20190313141921.pdf

Section 3 - Casing

Casing ID	String Type	Hole Size	Csg Size	Condition	Standard	Tapered String	Top Set MD	Bottom Set MD	Top Set TVD	Bottom Set TVD	Top Set MSL	Bottom Set MSL	Calculated casing length MD	Grade	Weight	Joint Type	Collapse SF	Burst SF	Joint SF Type	Joint SF	Body SF Type	Body SF
1	SURFACE	17.5	13.375	NEW	API	N	0	2001	0	2001	2924		2001	J-55	68	OTHER - BTC	4.59	0.65	DRY	6.72	DRY	7.86
2	INTERMEDIATE	12.25	9.625	NEW	API	N	0	10931	0	10931	2924		10931	HCL-80	40	OTHER - BTC	1.26	1.16	DRY	2.19	DRY	2.15
3	PRODUCTION	8.5	5.5	NEW	API	N	0	23283	0	12560	2924		23283	HCP-110	20	OTHER - BTC	1.64	1.76	DRY	2.61	DRY	2.9

Casing Attachments

Operator Name: AMEREDEV OPERATING LLC

Well Name: CAMELLIA FED COM 26 36 21

Well Number: 121H

Casing Attachments

Casing ID: 1 **String Type:** SURFACE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

13.375_54.50_J55_SEAH_20190313142821.pdf

Camellia_Fed_Com_26_36_21_121H___Wellbore_Diagram_and_CDA_20190404092302.pdf

Casing ID: 2 **String Type:** INTERMEDIATE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

9.625_40_SeAH80HC_4100_Collapse_20190313143012.pdf

Camellia_Fed_Com_26_36_21_121H___Wellbore_Diagram_and_CDA_20190404092350.pdf

Casing ID: 3 **String Type:** PRODUCTION

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

5.5_20_P110HP_Eagle_SFH_20190313143217.pdf

Camellia_Fed_Com_26_36_21_121H___Wellbore_Diagram_and_CDA_20190404092409.pdf

Operator Name: AMEREDEV OPERATING LLC

Well Name: CAMELLIA FED COM 26 36 21

Well Number: 121H

Section 4 - Cement

String Type	Lead/Tail	Stage Tool Depth	Top MD	Bottom MD	Quantity(sx)	Yield	Density	Cu Ft	Excess%	Cement type	Additives
SURFACE	Lead		0	1615	1031	1.76	13.5	1815.28	50	CLASS C	Bentonite, Accelerator, Kolseal, Defoamer, Celloflake
SURFACE	Tail		1615	2001	200	1.34	14.8	268	100	CLASS C	Salt
INTERMEDIATE	Lead	5002	0	4152	684	2.47	11.9	1690.63	25	Class C	Salt, Bentonite, Kolseal, Defoamer, Celloflake, Anti-Settling Expansion Additive
INTERMEDIATE	Tail		4152	5002	200	1.33	14.8	266	25	Class C	Retarder
INTERMEDIATE	Lead	5002	0	9675	1572	2.47	11.9	3882.88	25	CLASS H	Bentonite, Salt, Kolseal, Defoamer, Celloflake, Retarder, Anti-Settling Expansion Additive
INTERMEDIATE	Tail		9675	10931	300	1.24	14.5	371.1	25	CLASS H	Salt, Bentonite, Retarder, Dispersant, Fluid Loss
PRODUCTION	Lead		0	23283	4971	1.34	14.2	6661.58	25	Class H	Salt, Bentonite, Fluid Loss, Dispersant, Retarder, Defoamer

Section 5 - Circulating Medium

Mud System Type: Closed

Will an air or gas system be Used? NO

Description of the equipment for the circulating system in accordance with Onshore Order #2:

Diagram of the equipment for the circulating system in accordance with Onshore Order #2:

Describe what will be on location to control well or mitigate other conditions: All necessary supplies (e.g. bentonite, cedar bark) for fluid control will be on site.

Describe the mud monitoring system utilized: An electronic pit volume totalizer (PVT) will be utilized on the circulating system to monitor pit volume, flow rate, pump pressure, and pump rate.

Circulating Medium Table

Operator Name: AMEREDEV OPERATING LLC

Well Name: CAMELLIA FED COM 26 36 21

Well Number: 121H

Top Depth	Bottom Depth	Mud Type	Min Weight (lbs/gal)	Max Weight (lbs/gal)	Density (lbs/cu ft)	Gel Strength (lbs/100 sqft)	PH	Viscosity (CP)	Salinity (ppm)	Filtration (cc)	Additional Characteristics
0	2001	WATER-BASED MUD	8.4	8.6							
2001	1093 1	OTHER : Diesel Brine Emulsion	8.5	9.4							
1093 1	1256 0	OIL-BASED MUD	10.5	12.5							

Section 6 - Test, Logging, Coring

List of production tests including testing procedures, equipment and safety measures:

A directional survey, measurement while drilling and a mudlog/geologic lithology log will all be run from surface to TD.

List of open and cased hole logs run in the well:

DS,MWD,MUDLOG

Coring operation description for the well:

No coring will be done on this well.

Section 7 - Pressure

Anticipated Bottom Hole Pressure: 5000

Anticipated Surface Pressure: 2236.8

Anticipated Bottom Hole Temperature(F): 160

Anticipated abnormal pressures, temperatures, or potential geologic hazards? NO

Describe:

Contingency Plans geohazards description:

Contingency Plans geohazards attachment:

Hydrogen Sulfide drilling operations plan required? YES

Hydrogen sulfide drilling operations plan:

H2S_Plan_20180410080524.pdf

Operator Name: AMEREDEV OPERATING LLC

Well Name: CAMELLIA FED COM 26 36 21

Well Number: 121H

Section 8 - Other Information

Proposed horizontal/directional/multi-lateral plan submission:

Cam121_DR_20190313144503.pdf

Cam121_LLR_20190313144503.pdf

5M_Annular_Preventer_Variance_and_Well_Control_Plan_20190313144523.pdf

Pressure_Control_Plan_Single_Well_MB4_3String_Big_Hole_BLM_20190313144523.pdf

Other proposed operations facets description:

4-String contingency plan attached

Other proposed operations facets attachment:

CAPITAN_PROTECTION_CONTINGENCY_PLAN_20190313144643.pdf

Other Variance attachment:

R616__CoC_for_hoses_12_18_17_20190313144734.pdf

Requested_Exceptions__3_String_Revised_01312019_20190313144735.pdf

5M Annular Preventer Variance Request and Well Control Procedures

Note: A copy of the Well Control Plan must be available at multiple locations on the rig for review by rig personnel, as well as review by the BLM PET/PE, and a copy must be maintained on the rig floor.

Dual Isolation Design for 5M Annular Exception

Ameredev will utilize 13-5/8" 10M (5M Annular) BOPE System consisting of:

- 13-5/8" 5M Annular
- 13-5/8" 10M Upper Pipe Rams
 - 3-1/2" – 5-1/2" Variable Bore Ram
- 13-5/8" 10M Blind Rams
- 13-5/8" 10M Drilling Spool /w 2 - 4" 10M Outlets Double 10M Isolation Valves
- 13-5/8" 10M Lower Blind Rams
 - 3-1/2" – 5-1/2" Variable Bore Ram

All drilling components and casing associated to exposure > 5000 psi BHP requiring a 10M system will have a double isolation (secondary barrier) below the 5M Annular that would provide a barrier to flow. The mud system will always be primary barrier, it will be maintained by adjusting values based on tourly mud tests and monitoring a PVT System to maintain static wellbore conditions, displacement procedures will be followed and recorded on daily drilling reports during tripping operations. Surge and swab pressure values will be calculated and maintained and static flow check will be monitored at previous casing shoe and verified static well conditions prior to tripping out of hole and again prior to pulling last joint of drill pipe through BOPE. The below table, documents that two barriers to flow can be maintained at all times, independent of the rating of the annular preventer.

Drill Components	Size	Primary Barrier	Secondary Barrier	Third Barrier
Drillpipe	3-1/2"-5-1/2"	Drilling Fluid	Upper Pipe Rams	Lower Pipe Rams
HWDP Drillpipe	3-1/2"-5-1/2"	Drilling Fluid	Upper Pipe Rams	Lower Pipe Rams
Drill Collars	3-1/2"-5-1/2"	Drilling Fluid	Upper Pipe Rams	Lower Pipe Rams
Production Casing	3-1/2"-5-1/2"	Drilling Fluid	Upper Pipe Rams	Lower Pipe Rams
Open Hole	13-5/8	Drilling Fluid	Blind Rams	
All Drilling Components in 10M Environment will have OD that will allow full Operational RATED WORKING PRESSURE for system design. Kill line with minimum 2" ID will be available outside substructure with 10M Check Valve for OOH Kill Operations				

Well Control Procedures

Proper well control procedures are dependent to differentiating well conditions, to cover the basic well control operations there are will be standard drilling ahead, tripping pipe, tripping BHA, running casing, and pipe out of the hole/open hole scenarios that will be defined by procedures below. Initial Shut In Pressure can be taken against the Uppermost BOPE component the 5M Annular, pressure control can be transferred from the lesser 5M Annular to the 10M Upper Pipe Rams if needed. Shut In Pressures may be equal to or less than the Rated Working Pressure but at no time will the pressure on the annular preventer exceed the Rated Working Pressure of the annular. The annular will be tested to 5,000 psi. This will be the Rated Working Pressure of the annular preventer. All scenarios will be written such as shut in will be performed by closing the 10,000 psi Upper Pipe Rams for faster Accumulator pressure recovery to allow safer reaction to controlling wellbore pressure.

Shutting In While Drilling

1. Sound alarm signaling well control event to Rig Crew
2. Space out drill string to allow FOSV installation
3. Shut down pumps
4. Shut in Upper Pipe Rams and open HCR against Open Chokes and Valves
Open to working pressure gauge
5. Install open, full open safety valve and close valve, Close Chokes
6. Verify well is shut-in and flow has stopped
7. Notify supervisory personnel
8. Record data (SIDP, SICP, Pit Gain, and Time)
9. Hold pre-job safety meeting and discuss kill procedure

Shutting In While Running Casing

1. Sound alarm signaling well control event to Rig Crew
2. Space out casing to allow circulating swedge installation
3. Shut in Upper Pipe Rams and open HCR against Open Chokes and Valves
Open to working pressure gauge
4. Install circulating swedge, Close high pressure, low torque valves, Close Chokes
5. Verify well is shut-in and flow has stopped
6. Notify supervisory personnel
7. Record data (SIDP, SICP, Pit Gain, and Time)
8. Hold Pre-job safety meeting and discuss kill procedure

Shutting in while out of hole

1. Sound alarm signaling well control event to Rig Crew
2. Shut-in well: close blind rams and open HCR against Open Chokes and Valves
Open to working pressure gauge
3. Close Chokes, Verify well is shut-in and monitor pressures
4. Notify supervisory personnel
5. Record data (SIDP, SICP, Pit Gain, and Time)
6. Hold Pre-job safety meeting and discuss kill procedure

Shutting in prior to pulling BHA through stack

Prior to pulling last joint of drill pipe thru the stack space out and check flow

Shutting in while BHA is in the stack and ram preventer and combo immediately available

1. Sound alarm signaling well control event to Rig Crew
2. Space out BHA with upset just beneath the compatible pipe ram
3. Shut in upper compatible pipe ram and open HCR against Open Chokes and Valves Open to working pressure gauge
4. Install open, full open safety valve and close valve, Close Chokes
5. Verify well is shut-in and flow has stopped
6. Notify supervisory personnel
7. Record data (SIDP, SICP, Pit Gain, and Time)
8. Hold pre-job safety meeting and discuss kill procedure

*FOSV will be on rig floor in open position with operating handle for each type of connection utilized and tested to 10,000 psi

Shutting in while BHA is in the stack and no ram preventer or combo immediately available

1. Sound alarm signaling well control event to Rig Crew
2. If possible pick up high enough, to pull string clear and follow "Open Hole" scenario

If not possible to pick up high enough:

3. Stab Crossover, make up one joint/stand of drill pipe, and install open, full open safety valve (Leave Open)
4. Space out drill string with upset just beneath the compatible pipe ram.
5. Shut in upper compatible pipe ram and open HCR against Open Chokes and Valves Open to working pressure gauge
6. Close FOSV, Close Chokes, Verify well is shut-in and flow has stopped
7. Notify supervisory personnel
8. Record data (SIDP, SICP, Pit Gain, and Time)
9. Hold pre-job safety meeting and discuss kill procedure


13 5/8" 5M BOP
Configuration

CO-FLEX LINE TO
CHOKE MANIFOLD

2" KILL LINE

4" 10M VALVES &

10M Check Valve




Pressure Control Plan

Pressure Control Equipment

- Following setting of 13-3/8" Surface Casing Ameredev will install 13-5/8 MB4 Multi Bowl Casing Head by welding on a 13-5/8 SOW x 13-5/8" 5M in combination with 13-5/8 5M x 13-5/8 10M B-Sec to Land Intm #1 and a 13-5/8 10M x 13-5/8 10M shouldered to land C-Sec to Land Intm #2 (Installation procedure witnessed and verified by a manufacturer's representative).
- Casing will be tested to 1500 psi or .22 psi/ft whichever is greater for 30 minutes with <10% leak off, but will not exceed 70% of the burst rating per Onshore Order No. 2.
- Ameredev will install a 5M System Blowout Preventer (BOPE) with a 5M Annular Preventer and related equipment (BOPE). Full testing will be performed utilizing a full isolation test plug and limited to 5,000 psi MOP of MB4 Multi Bowl Casing Head. Pressure will be held for 10 min or until provisions of test are met on all valves and rams. The 5M Annular Preventer will be tested to 50% of approved working pressure (2,500 psi). Casing will be tested to 1500 psi or .22 psi/ft whichever is greater for 30 minutes with <10% leak off, but will not exceed 70% of the burst rating per Onshore Order No. 2.
- Setting of 9-5/8" Intermediate will be done by landing a wellhead hanger in the 13-5/8" 5M Bowl, Cementing and setting Well Head Packing seals and testing same. (Installation procedure witnessed and verified by a manufacturer's representative) Casing will be tested to 1500 psi or .22 psi/ft whichever is greater for 30 minutes with <10% leak off, but will not exceed 70% of the burst rating per Onshore Order No. 2.
- Full testing will be performed utilizing a full isolation test plug to 10,000 psi MOP of MB4 Multi Bowl B-Section. Pressure will be held for 10 min or until provisions of test are met on all valves and rams. The 5M Annular Preventer will be tested to 100% of approved working pressure (5,000 psi).
- Before drilling >20ft of new formation under the 9-5/8" Casing Shoe a pressure integrity test of the Casing Shoe will be performed to minimum of the MWE anticipated to control formation pressure to the next casing depth.
- Following setting of 5-1/2" Production Casing and adequate WOC time Ameredev will break 10M System Blowout Preventer (BOP) from 10M DOL-2 Casing Head, install annulus casing slips and test same (Installation procedure witnessed and verified by a manufacturer's representative) and install 11" 10M x 5-1/8" 15M Tubing Head (Installation procedure witnessed and verified by a manufacturer's representative). Ameredev will test head to 70% casing design and install Dry Hole cap with needle valve and pressure gauge to monitor well awaiting completion.

Pressure Control Plan

- Slow pump speeds will be taken daily by each crew and recorded on Daily Drilling Report after mudding up.
- A choke manifold and accumulator with floor and remote operating stations will be functional and in place after installation of BOPE, as well as full functioning mud gas separator.
- Weekly BOPE pit level drills will be conducted by each crew and recorded on Daily Drilling Report.
- BOP will be fully operated when out of hole and will be documented on the daily drilling log.
- All B.O.P.s and associated equipment will be tested in accordance with Onshore Order #2
- All B.O.P. testing will be done by an independent service company.
- The B.O.P. will be tested within 21 days of the original test if drilling takes more time than planned.
- Ameredev requests a variance to connect the B.O.P. choke outlet to the choke manifold using a co-flex hose with a 10,000 psi working pressure that has been tested to 15,000psi and is built to API Spec 16C. Once the flex line is installed it will be tied down with safety clamps. (certifications will be sent to Carlsbad BLM Office prior to install)
- Ameredev requests a variance to install a 5M Annular Preventer on the 10M System to drill the Production Hole below the 9-5/8" Intermediate Section. 5M Annular will be tested to 100% working pressure (5,000 psi). A full well control procedure will be included to isolate well bore.



Quotation

Downing Wellhead Equipment

Oklahoma City,
Oklahoma - USA

Reference Data:

16925 AMEREDEV

Proprietary and Confidential

The information contained in this drawing is the sole property of Downing Wellhead Equipment, any reproduction in part or in whole without the written permission of Downing Wellhead Equipment is prohibited.

TITLE:

AMEREDEV

DRAWN

CHECKED

APPROVED

SIZE

A

DWG. NO.

Scale:

Weight:

REV.

Sheet:

Wellbore Schematic

Well: Camellia Fed Com 26-36-21 121H
SHL: Sec. 21 26S-36E 283' FSL & 270' FWL
BHL: Sec. 16 26S-36E 50' FNL 200' FWL
 Lea, NM
Wellhead: A - 13-5/8" 10M x 13-5/8" SOW
 B - 13-5/8" 10M x 13-5/8" 10M
 C - 13-5/8" 10M x 13-5/8" 10M
 Tubing Spool - 5-1/8" 15M x 13-3/8" 10M
Xmas Tree: 2-9/16" 10M
Tubing: 2-7/8" L-80 6.5# 8rd EUE

Co. Well ID: 40921
AFE No.: 2017-066
API No.: xxxxxxxxxxxx
GL: 2,924'
Field: Delaware
Objective: Wolfcamp B
TVD: 12,560'
MD: 23,283'
Rig: TBD **KB:** 27'
E-Mail: Wellsite2@ameredev.com

Hole Size	Formation Tops	Logs Cement	Mud Weight
17.5"	Rustler 1,876' 13.375" 68# J-55 BTC 2,001'	1,231 Sacks TOC 0' 100% Excess	8.4-8.6 ppg WBM
12.25"	Salado 2,224' Tansill 3,206' Capitan Reef 3,621' Lamar 4,952' DV Tool 5,002' Bell Canyon 5,086' Brushy Canyon 7,105' Bone Spring Lime 8,129' First Bone Spring 9,631' Second Bone Spring 10,275' Third Bone Spring Upper 10,806' 9.625" 40# L-80HC BTC 10,931'	884 Sacks TOC 0' 50% Excess 1,723 Sacks TOC 0' 50% Excess	8.5 - 9.4 ppg Diesel Brine Emulsion
8.5"	Third Bone Spring 11,522' Wolfcamp A 11,755' Wolfcamp B 12,210' 5.5" 20# P-110CYHP BTC 23,283' Target Wolfcamp B 12560 TVD // 23283 MD	4,971 Sacks TOC 0' 25% Excess	10.5 - 12.5 ppg OBM

Casing Design and Safety Factor Check

Casing Specifications						
Segment	Hole ID	Depth	OD	Weight	Grade	Coupling
Surface	17.5	2,001'	13.375	68	J-55	BTC
Intermediate	12.25	10,931'	9.625	40	HCL-80	BTC
Prod Segment A	8.5	12,034'	5.5	20	CYHP-110	BTC
Prod Segment B	8.5	23,283'	5.5	20	CYHP-110	BTC

Check Surface Casing				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
14.375	1,069	915	4,100	3,450
Safety Factors				
1.56	7.86	6.72	4.59	0.65
Check Intermediate Casing				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
7.625	940	558	6700	9460
Safety Factors				
2.31	2.15	2.19	1.26	1.16
Check Prod Casing, Segment A				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
5.777	728	655	12780	14360
Safety Factors				
1.36	2.90	2.61	1.64	1.76
Check Prod Casing, Segment B				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
5.777	728	655	12780	14360
Safety Factors				
1.36	69.20	62.26	1.57	1.76

Wellbore Schematic

Well: Camellia Fed Com 26-36-21 121H
SHL: Sec. 21 26S-36E 283' FSL & 270' FWL
BHL: Sec. 16 26S-36E 50' FNL 200' FWL
 Lea, NM
Wellhead: A - 13-5/8" 10M x 13-5/8" SOW
 B - 13-5/8" 10M x 13-5/8" 10M
 C - 13-5/8" 10M x 13-5/8" 10M
 Tubing Spool - 5-1/8" 15M x 13-3/8" 10M
Xmas Tree: 2-9/16" 10M
Tubing: 2-7/8" L-80 6.5# 8rd EUE

Co. Well ID: 40921
AFE No.: 2017-066
API No.: xxxxxxxxxxxx
GL: 2,924'
Field: Delaware
Objective: Wolfcamp B
TVD: 12,560'
MD: 23,283'
Rig: TBD **KB:** 27'
E-Mail: Wellsite2@ameredev.com

Hole Size	Formation Tops	Logs Cement	Mud Weight
17.5"	Rustler 1,876'	1,231 Sacks TOC 0'	8.4-8.6 ppg WBM
	13.375" 68# J-55 BTC 2,001'		
12.25"	Salado 2,224'		
	Tansill 3,206'		
	Capitan Reef 3,621'		
	Lamar 4,952'	884 Sacks TOC 0'	50% Excess
	DV Tool 5,002'		
	Bell Canyon 5,086'		
	Brushy Canyon 7,105'		
	Bone Spring Lime 8,129'		
	First Bone Spring 9,631'		
	Second Bone Spring 10,275'		
	Third Bone Spring Upper 10,806'		
	9.625" 40# L-80HC BTC 10,931'	1,723 Sacks TOC 0'	50% Excess
8.5"	Third Bone Spring 11,522'		
	Wolfcamp A 11,755'		
	Wolfcamp B 12,210'		
12° Build @ 12,034' MD thru 12,872' MD	5.5" 20# P-110CYHP BTC 23,283'		
	Target Wolfcamp B 12560 TVD // 23283 MD	4,971 Sacks TOC 0'	25% Excess
			10.5 - 12.5 ppg OBM

Casing Design and Safety Factor Check

Casing Specifications						
Segment	Hole ID	Depth	OD	Weight	Grade	Coupling
Surface	17.5	2,001'	13.375	68	J-55	BTC
Intermediate	12.25	10,931'	9.625	40	HCL-80	BTC
Prod Segment A	8.5	12,034'	5.5	20	CYHP-110	BTC
Prod Segment B	8.5	23,283'	5.5	20	CYHP-110	BTC

Check Surface Casing				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
14.375	1,069	915	4,100	3,450
Safety Factors				
1.56	7.86	6.72	4.59	0.65
Check Intermediate Casing				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
7.625	940	558	6700	9460
Safety Factors				
2.31	2.15	2.19	1.26	1.16
Check Prod Casing, Segment A				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
5.777	728	655	12780	14360
Safety Factors				
1.36	2.90	2.61	1.64	1.76
Check Prod Casing, Segment B				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
5.777	728	655	12780	14360
Safety Factors				
1.36	69.20	62.26	1.57	1.76

Wellbore Schematic

Well: Camellia Fed Com 26-36-21 121H
SHL: Sec. 21 26S-36E 283' FSL & 270' FWL
BHL: Sec. 16 26S-36E 50' FNL 200' FWL
 Lea, NM
Wellhead: A - 13-5/8" 10M x 13-5/8" SOW
 B - 13-5/8" 10M x 13-5/8" 10M
 C - 13-5/8" 10M x 13-5/8" 10M
 Tubing Spool - 5-1/8" 15M x 13-3/8" 10M
Xmas Tree: 2-9/16" 10M
Tubing: 2-7/8" L-80 6.5# 8rd EUE

Co. Well ID: 40921
AFE No.: 2017-066
API No.: xxxxxxxxxxxx
GL: 2,924'
Field: Delaware
Objective: Wolfcamp B
TVD: 12,560'
MD: 23,283'
Rig: TBD **KB:** 27'
E-Mail: Wellsite2@ameredev.com

Hole Size	Formation Tops	Logs Cement	Mud Weight
17.5"	Rustler 1,876'	1,231 Sacks TOC 0'	8.4-8.6 ppg WBM
	13.375" 68# J-55 BTC 2,001'		
12.25"	Salado 2,224'		
	Tansill 3,206'		
	Capitan Reef 3,621'		
	Lamar 4,952'	884 Sacks TOC 0'	50% Excess
	DV Tool 5,002'		
	Bell Canyon 5,086'		
	Brushy Canyon 7,105'		
	Bone Spring Lime 8,129'		
	First Bone Spring 9,631'		
	Second Bone Spring 10,275'		
	Third Bone Spring Upper 10,806'		
	9.625" 40# L-80HC BTC 10,931'	1,723 Sacks TOC 0'	50% Excess
8.5"	Third Bone Spring 11,522'		
	Wolfcamp A 11,755'		
	Wolfcamp B 12,210'		
12° Build @ 12,034' MD thru 12,872' MD	5.5" 20# P-110CYHP BTC 23,283'		
	Target Wolfcamp B 12560 TVD // 23283 MD	4,971 Sacks TOC 0'	25% Excess
			10.5 - 12.5 ppg OBM

Casing Design and Safety Factor Check

Casing Specifications						
Segment	Hole ID	Depth	OD	Weight	Grade	Coupling
Surface	17.5	2,001'	13.375	68	J-55	BTC
Intermediate	12.25	10,931'	9.625	40	HCL-80	BTC
Prod Segment A	8.5	12,034'	5.5	20	CYHP-110	BTC
Prod Segment B	8.5	23,283'	5.5	20	CYHP-110	BTC

Check Surface Casing				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
14.375	1,069	915	4,100	3,450
Safety Factors				
1.56	7.86	6.72	4.59	0.65
Check Intermediate Casing				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
7.625	940	558	6700	9460
Safety Factors				
2.31	2.15	2.19	1.26	1.16
Check Prod Casing, Segment A				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
5.777	728	655	12780	14360
Safety Factors				
1.36	2.90	2.61	1.64	1.76
Check Prod Casing, Segment B				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
5.777	728	655	12780	14360
Safety Factors				
1.36	69.20	62.26	1.57	1.76

H₂S Drilling Operation Plan

1. **All Company and Contract personnel admitted on location must be trained by a qualified H₂S safety instructor to the following:**
 - a. Characteristics of H₂S
 - b. Physical effects and hazards
 - c. Principal and operation of H₂S detectors, warning system and briefing areas
 - d. Evacuation procedure, routes and first aid
 - e. Proper use of safety equipment and life support systems
 - f. Essential personnel meeting Medical Evaluation criteria will receive additional training on the proper use of 30 minute pressure demand air packs.
2. **Briefing Area:**
 - a. Two perpendicular areas will be designated by signs and readily accessible.
 - b. Upon location entry there will be a designated area to establish all safety compliance criteria (1.) has been met.
3. **H₂S Detection and Alarm Systems:**
 - a. H₂S sensors/detectors shall be located on the drilling rig floor, in the base of the sub structure/cellar area, and on the mud pits in the shale shaker area. Additional H₂S detectors may be placed as deemed necessary. All detectors will be set to initiate visual alarm at 10 ppm and visual with audible at 14 ppm and all equipment will be calibrated every 30 days or as needed.
 - b. An audio alarm will be installed on the derrick floor and in the top doghouse.
4. **Protective Equipment for Essential Personnel:**
 - a. **Breathing Apparatus:**
 - i. Rescue Packs (SCBA) - 1 Unit shall be placed at each briefing area.
 - ii. Two (SCBA) Units will be stored in safety trailer on location.
 - iii. Work/Escapes packs - 1 Unit will be available on rig floor in doghouse for emergency evacuation for driller.
 - b. **Auxiliary Rescue Equipment:**
 - i. Stretcher
 - ii. 2 - OSHA full body harnesses
 - iii. 100 ft. 5/8" OSHA approved rope
 - iv. 1 - 20# class ABC fire extinguisher
5. **Windsock and/or Wind Streamers:**
 - a. Windsock at mud pit area should be high enough to be visible.
 - b. Windsock on the rig floor should be high enough to be visible.
6. **Communication:**
 - a. While working under mask scripting boards will be used for communication where applicable.
 - b. Hand signals will be used when script boards are not applicable.

H₂S Drilling Operation Plan

- c. Two way radios will be used to communicate off location in case of emergency help is required. In most cases cellular telephones will be available at Drilling Foreman's Office.

7. **Drill Stem Testing:** - No Planned DST at this time.

8. **Mud program:**

- a. If H₂S is encountered, mud system will be altered if necessary to maintain control of formation. A mud gas separator will be brought into service along with H₂S scavengers if necessary.

9. **Metallurgy:**

- a. All drill strings, casing, tubing, wellhead, blowout preventer, drilling spool, kill lines, choke manifold and lines, and valves shall be suitable for H₂S service.
- b. Drilling Contractor supervisor will be required to be familiar with the effect H₂S has on tubular goods and other mechanical equipment provided through contractor.

H₂S Contingency Plan

Emergency Procedures

In the event of a release of H₂S, the first responder(s) must:

- Isolate the area and prevent entry by other persons into the 100 ppm ROE.
- Evacuate any public places encompassed by the 100 ppm ROE.
- Be equipped with H₂S monitors and air packs in order to control the release.
- Use the "buddy system" to ensure no injuries occur during the response.
- Take precautions to avoid personal injury during this operation.
- Contact Operator and/or local officials the aid in operation. See list of phone numbers attached.
- Have received training in the:
 - Detection of H₂S and
 - Measures for protection against the gas,
 - Equipment used for protection and emergency response.

Ignition of Gas Source

Should control of the well be considered lost and ignition considered, take care to protect against exposure to Sulfur Dioxide (SO₂). Intentional ignition must be coordinated with the NMOCD and local officials. Additionally, the NM State Police may become involved. NM State Police shall be the Incident Command on scene of any major release. Take care to protect downwind whenever there is an ignition of the gas.

Characteristics of H₂S and SO₂

Common Name	Chemical Formula	Specific Gravity	Threshold Limit	Hazardous Limit	Lethal Concentration
Hydrogen Sulfide	H ₂ S	1.189 Air=1	10 ppm	100 ppm/hr	600 ppm
Sulfur Dioxide	SO ₂	2.21 Air=1	2 ppm	N/A	1000 ppm

Contacting Authorities

Ameredev Operating LLC personnel must liaise with local and state agencies to ensure a proper response to a major release. Additionally, the OCD must be notified of the release as soon as possible but no later than 4 hours. Agencies will ask for information such as type and volume of release, wind direction, location of release, etc. Be prepared with all information available including direction to site. The following call list of essential and potential responders has been prepared for use during a release. Ameredev Operating LLC's response must be in coordination with the State of New Mexico's "Hazardous Materials Emergency Response Plan" (HMER)

H₂S Contingency Plan

Ameredev Operating LLC – Emergency Phone 737-300-4799			
Key Personnel:			
Name	Title	Office	Mobile
Floyd Hammond	Chief Operating officer	737-300-4724	512-783-6810
Zachary Boyd	Operations Superintendent	737-300-4725	432-385-6996
Blake Estrada	Construction Foreman		432-385-5831

<u>Artesia</u>			
Ambulance			911
State Police			575-746-2703
City Police			575-746-2703
Sheriff's Office			575-746-9888
Fire Department			575-746-2701
Local Emergency Planning Committee			575-746-2122
New Mexico Oil Conservation Division			575-748-1283
<u>Carlsbad</u>			
Ambulance			911
State Police			575-885-3137
City Police			575-885-2111
Sheriff's Office			575-887-7551
Fire Department			575-887-3798
Local Emergency Planning Committee			575-887-6544
US Bureau of Land Management			575-887-6544
<u>Santa Fe</u>			
New Mexico Emergency Response Commission (Santa Fe)			505-476-9600
New Mexico Emergency Response Commission (Santa Fe) 24 Hrs			505-827-9126
New Mexico State Emergency Operations Center			505-476-9635
<u>National</u>			
National Emergency Response Center (Washington, D.C.)			800-424-8802
<u>Medical</u>			
Flight for Life - 4000 24th St.; Lubbock, TX			806-743-9911
Aerocare - R3, Box 49F; Lubbock, TX			806-747-8923
Med Flight Air Amb - 2301 Yale Blvd S.E., #D3; Albuquerque, NM			505-842-4433
'SB Air Med Service - 2505 Clark Carr Loop S.E.; Albuquerque, NM			505-842-4949

AMEREDEV

Ameredev Operating, LLC.

CAM/AZ

CAM/AZ #1N

Camellia 121H

Wellbore #1

Plan: Design #1

Standard Planning Report

16 January, 2019

Database: EDM5000
Company: Ameredev Operating, LLC.
Project: CAM/AZ
Site: CAM/AZ #1N
Well: Camellia 121H
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well Camellia 121H
TVD Reference: KB @ 2951.0usft
MD Reference: KB @ 2951.0usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature

Project	CAM/AZ		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	New Mexico Eastern Zone		

Site	CAM/AZ #1N		
Site Position:		Northing:	373,448.30 usft
From:	Lat/Long	Easting:	868,493.74 usft
Position Uncertainty:	0.0 usft	Slot Radius:	13-3/16 "
		Latitude:	32° 1' 20.266 N
		Longitude:	103° 16' 39.795 W
		Grid Convergence:	0.56 °

Well	Camellia 121H		
Well Position	+N-S	0.0 usft	Northing:
	+E-W	0.0 usft	Easting:
Position Uncertainty	0.0 usft	Wellhead Elevation:	
		Latitude:	32° 1' 20.266 N
		Longitude:	103° 16' 39.795 W
		Ground Level:	2,924.0 usft

Wellbore	Wellbore #1		
Magnetics	Model Name	Sample Date	Declination
			(°)
	IGRF2015	1/11/2019	6.63
			Dip Angle
			(°)
			59.90
			Field Strength
			(nT)
			47,691.06803742

Design	Design #1		
Audit Notes:			
Version:	Phase:	PROTOTYPE	Tie On Depth:
			0.0
Vertical Section:	Depth From (TVD)	+N-S	+E-W
	(usft)	(usft)	(usft)
	0.0	0.0	0.0
			Direction
			(°)
			359.02

Plan Survey Tool Program	Date 1/16/2019		
Depth From	Depth To	Survey (Wellbore)	Tool Name
(usft)	(usft)		
1	0.0	23,283.4 Design #1 (Wellbore #1)	MWD
			OWSG MWD - Standard
			Remarks

Database: EDM5000
Company: Ameredev Operating, LLC.
Project: CAM/AZ
Site: CAM/AZ #1N
Well: Camellia 121H
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well Camellia 121H
TVD Reference: KB @ 2951.0usft
MD Reference: KB @ 2951.0usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature

Plan Sections

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
2,000.0	0.00	0.00	2,000.0	0.0	0.0	0.00	0.00	0.00	0.00	
2,300.0	6.00	180.00	2,299.5	-15.7	0.0	2.00	2.00	0.00	180.00	
6,724.8	6.00	180.00	6,700.0	-478.2	0.0	0.00	0.00	0.00	0.00	
7,024.8	0.00	0.00	6,999.5	-493.9	0.0	2.00	-2.00	0.00	180.00	
8,525.3	0.00	0.00	8,500.0	-493.9	0.0	0.00	0.00	0.00	0.00	
8,825.3	6.00	180.00	8,799.5	-509.6	0.0	2.00	2.00	0.00	180.00	
10,133.0	6.00	180.00	10,100.0	-646.3	0.0	0.00	0.00	0.00	0.00	
10,433.0	0.00	0.00	10,399.5	-662.0	0.0	2.00	-2.00	0.00	180.00	
12,033.6	0.00	0.00	12,000.0	-662.0	0.0	0.00	0.00	0.00	0.00	
12,094.7	7.29	248.11	12,061.0	-663.4	-3.6	11.93	11.93	0.00	248.11	
12,871.5	90.00	359.42	12,560.0	-184.1	-68.0	11.93	10.65	14.33	111.14	Cam121 FTP
23,283.4	90.00	359.42	12,560.0	10,227.1	-174.3	0.00	0.00	0.00	0.00	Cam121 BHL

Database: EDM5000
Company: Ameredev Operating, LLC.
Project: CAM/AZ
Site: CAM/AZ #1N
Well: Camellia 121H
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well Camellia 121H
TVD Reference: KB @ 2951.0usft
MD Reference: KB @ 2951.0usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00
300.0	0.00	0.00	300.0	0.0	0.0	0.0	0.00	0.00	0.00
400.0	0.00	0.00	400.0	0.0	0.0	0.0	0.00	0.00	0.00
500.0	0.00	0.00	500.0	0.0	0.0	0.0	0.00	0.00	0.00
600.0	0.00	0.00	600.0	0.0	0.0	0.0	0.00	0.00	0.00
700.0	0.00	0.00	700.0	0.0	0.0	0.0	0.00	0.00	0.00
800.0	0.00	0.00	800.0	0.0	0.0	0.0	0.00	0.00	0.00
900.0	0.00	0.00	900.0	0.0	0.0	0.0	0.00	0.00	0.00
1,000.0	0.00	0.00	1,000.0	0.0	0.0	0.0	0.00	0.00	0.00
1,100.0	0.00	0.00	1,100.0	0.0	0.0	0.0	0.00	0.00	0.00
1,200.0	0.00	0.00	1,200.0	0.0	0.0	0.0	0.00	0.00	0.00
1,300.0	0.00	0.00	1,300.0	0.0	0.0	0.0	0.00	0.00	0.00
1,400.0	0.00	0.00	1,400.0	0.0	0.0	0.0	0.00	0.00	0.00
1,500.0	0.00	0.00	1,500.0	0.0	0.0	0.0	0.00	0.00	0.00
1,600.0	0.00	0.00	1,600.0	0.0	0.0	0.0	0.00	0.00	0.00
1,700.0	0.00	0.00	1,700.0	0.0	0.0	0.0	0.00	0.00	0.00
1,800.0	0.00	0.00	1,800.0	0.0	0.0	0.0	0.00	0.00	0.00
1,900.0	0.00	0.00	1,900.0	0.0	0.0	0.0	0.00	0.00	0.00
2,000.0	0.00	0.00	2,000.0	0.0	0.0	0.0	0.00	0.00	0.00
2,100.0	2.00	180.00	2,100.0	-1.7	0.0	-1.7	2.00	2.00	0.00
2,200.0	4.00	180.00	2,199.8	-7.0	0.0	-7.0	2.00	2.00	0.00
2,300.0	6.00	180.00	2,299.5	-15.7	0.0	-15.7	2.00	2.00	0.00
2,400.0	6.00	180.00	2,398.9	-26.1	0.0	-26.1	0.00	0.00	0.00
2,500.0	6.00	180.00	2,498.4	-36.6	0.0	-36.6	0.00	0.00	0.00
2,600.0	6.00	180.00	2,597.8	-47.1	0.0	-47.0	0.00	0.00	0.00
2,700.0	6.00	180.00	2,697.3	-57.5	0.0	-57.5	0.00	0.00	0.00
2,800.0	6.00	180.00	2,796.7	-68.0	0.0	-67.9	0.00	0.00	0.00
2,900.0	6.00	180.00	2,896.2	-78.4	0.0	-78.4	0.00	0.00	0.00
3,000.0	6.00	180.00	2,995.6	-88.9	0.0	-88.9	0.00	0.00	0.00
3,100.0	6.00	180.00	3,095.1	-99.3	0.0	-99.3	0.00	0.00	0.00
3,200.0	6.00	180.00	3,194.5	-109.8	0.0	-109.8	0.00	0.00	0.00
3,300.0	6.00	180.00	3,294.0	-120.2	0.0	-120.2	0.00	0.00	0.00
3,400.0	6.00	180.00	3,393.4	-130.7	0.0	-130.7	0.00	0.00	0.00
3,500.0	6.00	180.00	3,492.9	-141.1	0.0	-141.1	0.00	0.00	0.00
3,600.0	6.00	180.00	3,592.3	-151.6	0.0	-151.6	0.00	0.00	0.00
3,700.0	6.00	180.00	3,691.8	-162.0	0.0	-162.0	0.00	0.00	0.00
3,800.0	6.00	180.00	3,791.2	-172.5	0.0	-172.5	0.00	0.00	0.00
3,900.0	6.00	180.00	3,890.7	-182.9	0.0	-182.9	0.00	0.00	0.00
4,000.0	6.00	180.00	3,990.1	-193.4	0.0	-193.4	0.00	0.00	0.00
4,100.0	6.00	180.00	4,089.6	-203.8	0.0	-203.8	0.00	0.00	0.00
4,200.0	6.00	180.00	4,189.0	-214.3	0.0	-214.3	0.00	0.00	0.00
4,300.0	6.00	180.00	4,288.5	-224.8	0.0	-224.7	0.00	0.00	0.00
4,400.0	6.00	180.00	4,387.9	-235.2	0.0	-235.2	0.00	0.00	0.00
4,500.0	6.00	180.00	4,487.4	-245.7	0.0	-245.6	0.00	0.00	0.00
4,600.0	6.00	180.00	4,586.9	-256.1	0.0	-256.1	0.00	0.00	0.00
4,700.0	6.00	180.00	4,686.3	-266.6	0.0	-266.5	0.00	0.00	0.00
4,800.0	6.00	180.00	4,785.8	-277.0	0.0	-277.0	0.00	0.00	0.00
4,900.0	6.00	180.00	4,885.2	-287.5	0.0	-287.4	0.00	0.00	0.00
5,000.0	6.00	180.00	4,984.7	-297.9	0.0	-297.9	0.00	0.00	0.00
5,100.0	6.00	180.00	5,084.1	-308.4	0.0	-308.3	0.00	0.00	0.00
5,200.0	6.00	180.00	5,183.6	-318.8	0.0	-318.8	0.00	0.00	0.00
5,300.0	6.00	180.00	5,283.0	-329.3	0.0	-329.2	0.00	0.00	0.00

Database: EDM5000
Company: Ameredev Operating, LLC.
Project: CAM/AZ
Site: CAM/AZ #1N
Well: Camellia 121H
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well Camellia 121H
TVD Reference: KB @ 2951.0usft
MD Reference: KB @ 2951.0usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
5,400.0	6.00	180.00	5,382.5	-339.7	0.0	-339.7	0.00	0.00	0.00
5,500.0	6.00	180.00	5,481.9	-350.2	0.0	-350.1	0.00	0.00	0.00
5,600.0	6.00	180.00	5,581.4	-360.6	0.0	-360.6	0.00	0.00	0.00
5,700.0	6.00	180.00	5,680.8	-371.1	0.0	-371.0	0.00	0.00	0.00
5,800.0	6.00	180.00	5,780.3	-381.5	0.0	-381.5	0.00	0.00	0.00
5,900.0	6.00	180.00	5,879.7	-392.0	0.0	-391.9	0.00	0.00	0.00
6,000.0	6.00	180.00	5,979.2	-402.4	0.0	-402.4	0.00	0.00	0.00
6,100.0	6.00	180.00	6,078.6	-412.9	0.0	-412.8	0.00	0.00	0.00
6,200.0	6.00	180.00	6,178.1	-423.4	0.0	-423.3	0.00	0.00	0.00
6,300.0	6.00	180.00	6,277.5	-433.8	0.0	-433.7	0.00	0.00	0.00
6,400.0	6.00	180.00	6,377.0	-444.3	0.0	-444.2	0.00	0.00	0.00
6,500.0	6.00	180.00	6,476.4	-454.7	0.0	-454.6	0.00	0.00	0.00
6,600.0	6.00	180.00	6,575.9	-465.2	0.0	-465.1	0.00	0.00	0.00
6,700.0	6.00	180.00	6,675.3	-475.6	0.0	-475.5	0.00	0.00	0.00
6,724.8	6.00	180.00	6,700.0	-478.2	0.0	-478.1	0.00	0.00	0.00
6,800.0	4.50	180.00	6,774.9	-485.1	0.0	-485.0	2.00	-2.00	0.00
6,900.0	2.50	180.00	6,874.7	-491.2	0.0	-491.1	2.00	-2.00	0.00
7,000.0	0.50	180.00	6,974.7	-493.8	0.0	-493.7	2.00	-2.00	0.00
7,024.8	0.00	0.00	6,999.5	-493.9	0.0	-493.8	2.00	-2.00	0.00
7,100.0	0.00	0.00	7,074.7	-493.9	0.0	-493.8	0.00	0.00	0.00
7,200.0	0.00	0.00	7,174.7	-493.9	0.0	-493.8	0.00	0.00	0.00
7,300.0	0.00	0.00	7,274.7	-493.9	0.0	-493.8	0.00	0.00	0.00
7,400.0	0.00	0.00	7,374.7	-493.9	0.0	-493.8	0.00	0.00	0.00
7,500.0	0.00	0.00	7,474.7	-493.9	0.0	-493.8	0.00	0.00	0.00
7,600.0	0.00	0.00	7,574.7	-493.9	0.0	-493.8	0.00	0.00	0.00
7,700.0	0.00	0.00	7,674.7	-493.9	0.0	-493.8	0.00	0.00	0.00
7,800.0	0.00	0.00	7,774.7	-493.9	0.0	-493.8	0.00	0.00	0.00
7,900.0	0.00	0.00	7,874.7	-493.9	0.0	-493.8	0.00	0.00	0.00
8,000.0	0.00	0.00	7,974.7	-493.9	0.0	-493.8	0.00	0.00	0.00
8,100.0	0.00	0.00	8,074.7	-493.9	0.0	-493.8	0.00	0.00	0.00
8,200.0	0.00	0.00	8,174.7	-493.9	0.0	-493.8	0.00	0.00	0.00
8,300.0	0.00	0.00	8,274.7	-493.9	0.0	-493.8	0.00	0.00	0.00
8,400.0	0.00	0.00	8,374.7	-493.9	0.0	-493.8	0.00	0.00	0.00
8,500.0	0.00	0.00	8,474.7	-493.9	0.0	-493.8	0.00	0.00	0.00
8,525.3	0.00	0.00	8,500.0	-493.9	0.0	-493.8	0.00	0.00	0.00
8,600.0	1.49	180.00	8,574.7	-494.9	0.0	-494.8	2.00	2.00	0.00
8,700.0	3.49	180.00	8,674.6	-499.2	0.0	-499.2	2.00	2.00	0.00
8,800.0	5.49	180.00	8,774.2	-507.1	0.0	-507.0	2.00	2.00	0.00
8,825.3	6.00	180.00	8,799.5	-509.6	0.0	-509.5	2.00	2.00	0.00
8,900.0	6.00	180.00	8,873.7	-517.4	0.0	-517.3	0.00	0.00	0.00
9,000.0	6.00	180.00	8,973.2	-527.9	0.0	-527.8	0.00	0.00	0.00
9,100.0	6.00	180.00	9,072.6	-538.3	0.0	-538.2	0.00	0.00	0.00
9,200.0	6.00	180.00	9,172.1	-548.8	0.0	-548.7	0.00	0.00	0.00
9,300.0	6.00	180.00	9,271.5	-559.2	0.0	-559.1	0.00	0.00	0.00
9,400.0	6.00	180.00	9,371.0	-569.7	0.0	-569.6	0.00	0.00	0.00
9,500.0	6.00	180.00	9,470.4	-580.1	0.0	-580.0	0.00	0.00	0.00
9,600.0	6.00	180.00	9,569.9	-590.6	0.0	-590.5	0.00	0.00	0.00
9,700.0	6.00	180.00	9,669.3	-601.0	0.0	-600.9	0.00	0.00	0.00
9,800.0	6.00	180.00	9,768.8	-611.5	0.0	-611.4	0.00	0.00	0.00
9,900.0	6.00	180.00	9,868.2	-621.9	0.0	-621.8	0.00	0.00	0.00
10,000.0	6.00	180.00	9,967.7	-632.4	0.0	-632.3	0.00	0.00	0.00
10,100.0	6.00	180.00	10,067.1	-642.8	0.0	-642.7	0.00	0.00	0.00
10,133.0	6.00	180.00	10,100.0	-646.3	0.0	-646.2	0.00	0.00	0.00
10,200.0	4.66	180.00	10,166.7	-652.5	0.0	-652.4	2.00	-2.00	0.00

Database: EDM5000
Company: Ameredev Operating, LLC.
Project: CAM/AZ
Site: CAM/AZ #1N
Well: Camellia 121H
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well Camellia 121H
TVD Reference: KB @ 2951.0usft
MD Reference: KB @ 2951.0usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
10,300.0	2.66	180.00	10,266.5	-658.9	0.0	-658.8	2.00	-2.00	0.00
10,400.0	0.66	180.00	10,366.4	-661.8	0.0	-661.7	2.00	-2.00	0.00
Sec 28									
10,433.0	0.00	0.00	10,399.5	-662.0	0.0	-661.9	2.00	-2.00	0.00
10,500.0	0.00	0.00	10,466.4	-662.0	0.0	-661.9	0.00	0.00	0.00
10,600.0	0.00	0.00	10,566.4	-662.0	0.0	-661.9	0.00	0.00	0.00
10,700.0	0.00	0.00	10,666.4	-662.0	0.0	-661.9	0.00	0.00	0.00
10,800.0	0.00	0.00	10,766.4	-662.0	0.0	-661.9	0.00	0.00	0.00
10,900.0	0.00	0.00	10,866.4	-662.0	0.0	-661.9	0.00	0.00	0.00
11,000.0	0.00	0.00	10,966.4	-662.0	0.0	-661.9	0.00	0.00	0.00
11,100.0	0.00	0.00	11,066.4	-662.0	0.0	-661.9	0.00	0.00	0.00
11,200.0	0.00	0.00	11,166.4	-662.0	0.0	-661.9	0.00	0.00	0.00
11,300.0	0.00	0.00	11,266.4	-662.0	0.0	-661.9	0.00	0.00	0.00
11,400.0	0.00	0.00	11,366.4	-662.0	0.0	-661.9	0.00	0.00	0.00
11,500.0	0.00	0.00	11,466.4	-662.0	0.0	-661.9	0.00	0.00	0.00
11,600.0	0.00	0.00	11,566.4	-662.0	0.0	-661.9	0.00	0.00	0.00
11,700.0	0.00	0.00	11,666.4	-662.0	0.0	-661.9	0.00	0.00	0.00
11,800.0	0.00	0.00	11,766.4	-662.0	0.0	-661.9	0.00	0.00	0.00
11,800.6	0.00	0.00	11,767.0	-662.0	0.0	-661.9	0.00	0.00	0.00
Sec 21									
11,900.0	0.00	0.00	11,866.4	-662.0	0.0	-661.9	0.00	0.00	0.00
12,000.0	0.00	0.00	11,966.4	-662.0	0.0	-661.9	0.00	0.00	0.00
12,033.6	0.00	0.00	12,000.0	-662.0	0.0	-661.9	0.00	0.00	0.00
12,094.7	7.29	248.11	12,061.0	-663.4	-3.6	-663.3	11.93	11.93	0.00
12,100.0	7.09	252.88	12,066.2	-663.7	-4.2	-663.5	11.93	-3.84	90.26
12,200.0	12.00	325.31	12,165.1	-656.9	-16.1	-656.5	11.93	4.91	72.43
12,300.0	22.82	342.96	12,260.4	-629.7	-27.7	-629.1	11.93	10.82	17.65
12,400.0	34.36	349.38	12,348.1	-583.3	-38.6	-582.5	11.93	11.54	6.41
12,500.0	46.08	352.83	12,424.3	-519.5	-48.4	-518.7	11.93	11.72	3.45
12,600.0	57.87	355.12	12,485.8	-441.3	-56.5	-440.3	11.93	11.79	2.30
12,700.0	69.69	356.89	12,529.9	-352.0	-62.7	-350.9	11.93	11.82	1.76
12,800.0	81.53	358.40	12,554.7	-255.4	-66.6	-254.2	11.93	11.84	1.51
12,871.5	90.00	359.42	12,560.0	-184.1	-68.0	-183.0	11.93	11.84	1.42
Cam121 FTP									
12,900.0	90.00	359.42	12,560.0	-155.7	-68.3	-154.5	0.00	0.00	0.00
13,000.0	90.00	359.42	12,560.0	-55.7	-69.3	-54.5	0.00	0.00	0.00
13,100.0	90.00	359.42	12,560.0	44.3	-70.3	45.5	0.00	0.00	0.00
13,200.0	90.00	359.42	12,560.0	144.3	-71.3	145.5	0.00	0.00	0.00
13,300.0	90.00	359.42	12,560.0	244.3	-72.3	245.5	0.00	0.00	0.00
13,400.0	90.00	359.42	12,560.0	344.3	-73.4	345.5	0.00	0.00	0.00
13,500.0	90.00	359.42	12,560.0	444.3	-74.4	445.5	0.00	0.00	0.00
13,600.0	90.00	359.42	12,560.0	544.3	-75.4	545.5	0.00	0.00	0.00
13,700.0	90.00	359.42	12,560.0	644.3	-76.4	645.5	0.00	0.00	0.00
13,800.0	90.00	359.42	12,560.0	744.3	-77.5	745.5	0.00	0.00	0.00
13,900.0	90.00	359.42	12,560.0	844.3	-78.5	845.5	0.00	0.00	0.00
14,000.0	90.00	359.42	12,560.0	944.3	-79.5	945.5	0.00	0.00	0.00
14,100.0	90.00	359.42	12,560.0	1,044.3	-80.5	1,045.5	0.00	0.00	0.00
14,200.0	90.00	359.42	12,560.0	1,144.3	-81.5	1,145.5	0.00	0.00	0.00
14,300.0	90.00	359.42	12,560.0	1,244.3	-82.6	1,245.5	0.00	0.00	0.00
14,400.0	90.00	359.42	12,560.0	1,344.2	-83.6	1,345.5	0.00	0.00	0.00
14,500.0	90.00	359.42	12,560.0	1,444.2	-84.6	1,445.5	0.00	0.00	0.00
14,600.0	90.00	359.42	12,560.0	1,544.2	-85.6	1,545.5	0.00	0.00	0.00
14,700.0	90.00	359.42	12,560.0	1,644.2	-86.6	1,645.5	0.00	0.00	0.00

Database: EDM5000
 Company: Ameredev Operating, LLC.
 Project: CAM/AZ
 Site: CAM/AZ #1N
 Well: Camellia 121H
 Wellbore: Wellbore #1
 Design: Design #1

Local Co-ordinate Reference: Well Camellia 121H
 TVD Reference: KB @ 2951.0usft
 MD Reference: KB @ 2951.0usft
 North Reference: Grid
 Survey Calculation Method: Minimum Curvature

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
14,800.0	90.00	359.42	12,560.0	1,744.2	-87.7	1,745.5	0.00	0.00	0.00
14,900.0	90.00	359.42	12,560.0	1,844.2	-88.7	1,845.5	0.00	0.00	0.00
15,000.0	90.00	359.42	12,560.0	1,944.2	-89.7	1,945.5	0.00	0.00	0.00
15,100.0	90.00	359.42	12,560.0	2,044.2	-90.7	2,045.5	0.00	0.00	0.00
15,200.0	90.00	359.42	12,560.0	2,144.2	-91.7	2,145.5	0.00	0.00	0.00
15,300.0	90.00	359.42	12,560.0	2,244.2	-92.8	2,245.5	0.00	0.00	0.00
15,400.0	90.00	359.42	12,560.0	2,344.2	-93.8	2,345.5	0.00	0.00	0.00
15,500.0	90.00	359.42	12,560.0	2,444.2	-94.8	2,445.5	0.00	0.00	0.00
15,600.0	90.00	359.42	12,560.0	2,544.2	-95.8	2,545.5	0.00	0.00	0.00
15,700.0	90.00	359.42	12,560.0	2,644.2	-96.9	2,645.4	0.00	0.00	0.00
15,800.0	90.00	359.42	12,560.0	2,744.2	-97.9	2,745.4	0.00	0.00	0.00
15,900.0	90.00	359.42	12,560.0	2,844.2	-98.9	2,845.4	0.00	0.00	0.00
16,000.0	90.00	359.42	12,560.0	2,944.2	-99.9	2,945.4	0.00	0.00	0.00
16,100.0	90.00	359.42	12,560.0	3,044.2	-100.9	3,045.4	0.00	0.00	0.00
16,200.0	90.00	359.42	12,560.0	3,144.2	-102.0	3,145.4	0.00	0.00	0.00
16,300.0	90.00	359.42	12,560.0	3,244.2	-103.0	3,245.4	0.00	0.00	0.00
16,400.0	90.00	359.42	12,560.0	3,344.1	-104.0	3,345.4	0.00	0.00	0.00
16,500.0	90.00	359.42	12,560.0	3,444.1	-105.0	3,445.4	0.00	0.00	0.00
16,600.0	90.00	359.42	12,560.0	3,544.1	-106.0	3,545.4	0.00	0.00	0.00
16,700.0	90.00	359.42	12,560.0	3,644.1	-107.1	3,645.4	0.00	0.00	0.00
16,800.0	90.00	359.42	12,560.0	3,744.1	-108.1	3,745.4	0.00	0.00	0.00
16,900.0	90.00	359.42	12,560.0	3,844.1	-109.1	3,845.4	0.00	0.00	0.00
17,000.0	90.00	359.42	12,560.0	3,944.1	-110.1	3,945.4	0.00	0.00	0.00
17,100.0	90.00	359.42	12,560.0	4,044.1	-111.1	4,045.4	0.00	0.00	0.00
17,200.0	90.00	359.42	12,560.0	4,144.1	-112.2	4,145.4	0.00	0.00	0.00
17,300.0	90.00	359.42	12,560.0	4,244.1	-113.2	4,245.4	0.00	0.00	0.00
17,400.0	90.00	359.42	12,560.0	4,344.1	-114.2	4,345.4	0.00	0.00	0.00
17,500.0	90.00	359.42	12,560.0	4,444.1	-115.2	4,445.4	0.00	0.00	0.00
17,600.0	90.00	359.42	12,560.0	4,544.1	-116.2	4,545.4	0.00	0.00	0.00
17,700.0	90.00	359.42	12,560.0	4,644.1	-117.3	4,645.4	0.00	0.00	0.00
17,800.0	90.00	359.42	12,560.0	4,744.1	-118.3	4,745.4	0.00	0.00	0.00
17,900.0	90.00	359.42	12,560.0	4,844.1	-119.3	4,845.4	0.00	0.00	0.00
18,000.0	90.00	359.42	12,560.0	4,944.1	-120.3	4,945.4	0.00	0.00	0.00
18,053.2	90.00	359.42	12,560.0	4,997.2	-120.9	4,998.5	0.00	0.00	0.00
Sec 16									
18,100.0	90.00	359.42	12,560.0	5,044.1	-121.4	5,045.4	0.00	0.00	0.00
18,200.0	90.00	359.42	12,560.0	5,144.1	-122.4	5,145.4	0.00	0.00	0.00
18,300.0	90.00	359.42	12,560.0	5,244.0	-123.4	5,245.4	0.00	0.00	0.00
18,400.0	90.00	359.42	12,560.0	5,344.0	-124.4	5,345.4	0.00	0.00	0.00
18,500.0	90.00	359.42	12,560.0	5,444.0	-125.4	5,445.4	0.00	0.00	0.00
18,600.0	90.00	359.42	12,560.0	5,544.0	-126.5	5,545.4	0.00	0.00	0.00
18,700.0	90.00	359.42	12,560.0	5,644.0	-127.5	5,645.4	0.00	0.00	0.00
18,800.0	90.00	359.42	12,560.0	5,744.0	-128.5	5,745.4	0.00	0.00	0.00
18,900.0	90.00	359.42	12,560.0	5,844.0	-129.5	5,845.4	0.00	0.00	0.00
19,000.0	90.00	359.42	12,560.0	5,944.0	-130.5	5,945.4	0.00	0.00	0.00
19,100.0	90.00	359.42	12,560.0	6,044.0	-131.6	6,045.4	0.00	0.00	0.00
19,200.0	90.00	359.42	12,560.0	6,144.0	-132.6	6,145.4	0.00	0.00	0.00
19,300.0	90.00	359.42	12,560.0	6,244.0	-133.6	6,245.4	0.00	0.00	0.00
19,400.0	90.00	359.42	12,560.0	6,344.0	-134.6	6,345.4	0.00	0.00	0.00
19,500.0	90.00	359.42	12,560.0	6,444.0	-135.6	6,445.4	0.00	0.00	0.00
19,600.0	90.00	359.42	12,560.0	6,544.0	-136.7	6,545.4	0.00	0.00	0.00
19,700.0	90.00	359.42	12,560.0	6,644.0	-137.7	6,645.4	0.00	0.00	0.00
19,800.0	90.00	359.42	12,560.0	6,744.0	-138.7	6,745.4	0.00	0.00	0.00

Database: EDM5000
Company: Ameredev Operating, LLC.
Project: CAM/AZ
Site: CAM/AZ #1N
Well: Camellia 121H
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well Camellia 121H
TVD Reference: KB @ 2951.0usft
MD Reference: KB @ 2951.0usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
19,900.0	90.00	359.42	12,560.0	6,844.0	-139.7	6,845.3	0.00	0.00	0.00
20,000.0	90.00	359.42	12,560.0	6,944.0	-140.7	6,945.3	0.00	0.00	0.00
20,100.0	90.00	359.42	12,560.0	7,044.0	-141.8	7,045.3	0.00	0.00	0.00
20,200.0	90.00	359.42	12,560.0	7,143.9	-142.8	7,145.3	0.00	0.00	0.00
20,300.0	90.00	359.42	12,560.0	7,243.9	-143.8	7,245.3	0.00	0.00	0.00
20,400.0	90.00	359.42	12,560.0	7,343.9	-144.8	7,345.3	0.00	0.00	0.00
20,500.0	90.00	359.42	12,560.0	7,443.9	-145.9	7,445.3	0.00	0.00	0.00
20,600.0	90.00	359.42	12,560.0	7,543.9	-146.9	7,545.3	0.00	0.00	0.00
20,700.0	90.00	359.42	12,560.0	7,643.9	-147.9	7,645.3	0.00	0.00	0.00
20,800.0	90.00	359.42	12,560.0	7,743.9	-148.9	7,745.3	0.00	0.00	0.00
20,900.0	90.00	359.42	12,560.0	7,843.9	-149.9	7,845.3	0.00	0.00	0.00
21,000.0	90.00	359.42	12,560.0	7,943.9	-151.0	7,945.3	0.00	0.00	0.00
21,100.0	90.00	359.42	12,560.0	8,043.9	-152.0	8,045.3	0.00	0.00	0.00
21,200.0	90.00	359.42	12,560.0	8,143.9	-153.0	8,145.3	0.00	0.00	0.00
21,300.0	90.00	359.42	12,560.0	8,243.9	-154.0	8,245.3	0.00	0.00	0.00
21,400.0	90.00	359.42	12,560.0	8,343.9	-155.0	8,345.3	0.00	0.00	0.00
21,500.0	90.00	359.42	12,560.0	8,443.9	-156.1	8,445.3	0.00	0.00	0.00
21,600.0	90.00	359.42	12,560.0	8,543.9	-157.1	8,545.3	0.00	0.00	0.00
21,700.0	90.00	359.42	12,560.0	8,643.9	-158.1	8,645.3	0.00	0.00	0.00
21,800.0	90.00	359.42	12,560.0	8,743.9	-159.1	8,745.3	0.00	0.00	0.00
21,900.0	90.00	359.42	12,560.0	8,843.9	-160.1	8,845.3	0.00	0.00	0.00
22,000.0	90.00	359.42	12,560.0	8,943.9	-161.2	8,945.3	0.00	0.00	0.00
22,100.0	90.00	359.42	12,560.0	9,043.8	-162.2	9,045.3	0.00	0.00	0.00
22,200.0	90.00	359.42	12,560.0	9,143.8	-163.2	9,145.3	0.00	0.00	0.00
22,300.0	90.00	359.42	12,560.0	9,243.8	-164.2	9,245.3	0.00	0.00	0.00
22,400.0	90.00	359.42	12,560.0	9,343.8	-165.3	9,345.3	0.00	0.00	0.00
22,500.0	90.00	359.42	12,560.0	9,443.8	-166.3	9,445.3	0.00	0.00	0.00
22,600.0	90.00	359.42	12,560.0	9,543.8	-167.3	9,545.3	0.00	0.00	0.00
22,700.0	90.00	359.42	12,560.0	9,643.8	-168.3	9,645.3	0.00	0.00	0.00
22,800.0	90.00	359.42	12,560.0	9,743.8	-169.3	9,745.3	0.00	0.00	0.00
22,900.0	90.00	359.42	12,560.0	9,843.8	-170.4	9,845.3	0.00	0.00	0.00
23,000.0	90.00	359.42	12,560.0	9,943.8	-171.4	9,945.3	0.00	0.00	0.00
23,100.0	90.00	359.42	12,560.0	10,043.8	-172.4	10,045.3	0.00	0.00	0.00
23,200.0	90.00	359.42	12,560.0	10,143.8	-173.4	10,145.3	0.00	0.00	0.00
Cam121 LTP									
23,283.4	90.00	359.42	12,560.0	10,227.1	-174.3	10,228.6	0.00	0.00	0.00
Cam121 BHL									

Database: EDM5000
Company: Ameredev Operating, LLC.
Project: CAMIAZ
Site: CAMIAZ #1N
Well: Camellia 121H
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well Camellia 121H
TVD Reference: KB @ 2951.0usft
MD Reference: KB @ 2951.0usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature

Design Targets**Target Name**

- hit/miss target - Shape	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
Sec 28	0.00	0.00	10,236.0	-5,570.2	-214.7	367,878.13	868,279.00	32° 0' 25.171 N	103° 16' 42.920 W
- plan misses target center by 4914.8usft at 10400.0usft MD (10366.4 TVD, -661.8 N, 0.0 E)									
- Polygon									
Point 1			10,236.0	0.0	0.0	367,878.13	868,279.00		
Point 2			10,236.0	5,283.8	-52.1	373,161.93	868,226.90		
Point 3			10,236.0	5,342.2	5,232.0	373,220.33	873,511.00		
Point 4			10,236.0	60.2	5,286.0	367,938.33	873,565.00		
Sec 21	0.00	0.00	11,767.0	-286.4	-266.9	373,161.95	868,226.87	32° 1' 17.458 N	103° 16' 42.927 W
- plan misses target center by 460.8usft at 11800.6usft MD (11767.0 TVD, -662.0 N, 0.0 E)									
- Polygon									
Point 1			11,767.0	0.0	0.0	373,161.95	868,226.87		
Point 2			11,767.0	5,281.5	-54.5	378,443.45	868,172.37		
Point 3			11,767.0	5,336.0	5,230.6	378,497.95	873,457.47		
Point 4			11,767.0	58.4	5,284.2	373,220.35	873,511.07		
Sec 16	0.00	0.00	11,767.0	4,995.2	-321.4	378,443.47	868,172.36	32° 2' 9.723 N	103° 16' 42.961 W
- plan misses target center by 818.0usft at 18053.2usft MD (12560.0 TVD, 4997.2 N, -120.9 E)									
- Polygon									
Point 1			11,767.0	0.0	0.0	378,443.47	868,172.36		
Point 2			11,767.0	5,280.0	-53.4	383,723.47	868,118.96		
Point 3			11,767.0	5,332.5	5,230.8	383,775.97	873,403.16		
Point 4			11,767.0	54.4	5,285.1	378,497.87	873,457.46		
Cam121 LTP	0.00	0.00	12,560.0	10,177.2	-173.8	383,625.46	868,319.96	32° 3' 0.982 N	103° 16' 40.658 W
- plan misses target center by 33.4usft at 23200.0usft MD (12560.0 TVD, 10143.8 N, -173.4 E)									
- Point									
Cam121 BHL	0.00	0.00	12,560.0	10,227.1	-174.3	383,675.45	868,319.47	32° 3' 1.477 N	103° 16' 40.658 W
- plan hits target center									
- Point									
Cam121 FTP	0.00	0.00	12,560.0	-184.1	-68.0	373,264.16	868,425.77	32° 1' 18.450 N	103° 16' 40.605 W
- plan hits target center									
- Point									



AMEREDEV

Ameredev Operating, LLC.

CAM/AZ

CAM/AZ #1N

Camellia 121H

Wellbore #1

Plan: Design #1

Lease Penetration Section Line Footages

16 January, 2019



Ameredev Operating, LLC
Lease Penetration Section Line Footages

Company: Ameredev Operating, LLC.
Project: CAM/AZ
Site: CAM/AZ #1N
Well: Camellia 121H
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well Camellia 121H
TVD Reference: KB @ 2951.0usft
MD Reference: KB @ 2951.0usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: EDM5000

Project CAM/AZ

Map System: US State Plane 1983
Geo Datum: North American Datum 1983
Map Zone: New Mexico Eastern Zone

System Datum: Mean Sea Level

Site CAM/AZ #1N

Site Position:		Northing:	373,448.30 usft	Latitude:	32° 1' 20.266 N
From:	Lat/Long	Easting:	868,493.74 usft	Longitude:	103° 16' 39.795 W
Position Uncertainty:	0.0 usft	Slot Radius:	13-3/16 "	Grid Convergence:	0.56 °

Well Camellia 121H

Well Position	+N/-S	0.0 usft	Northing:	373,448.30 usft	Latitude:	32° 1' 20.266 N
	+E/-W	0.0 usft	Easting:	868,493.74 usft	Longitude:	103° 16' 39.795 W
Position Uncertainty		0.0 usft	Wellhead Elevation:	usft	Ground Level:	2,924.0 usft

Wellbore Wellbore #1

Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2015	1/11/2019	6.63	59.90	47,691.06803742

Design Design #1

Audit Notes:

Version: Phase: PROTOTYPE Tie On Depth: 0.0

Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)
	0.0	0.0	0.0	359.02

Survey Tool Program Date 1/16/2019

From (usft)	To (usft)	Survey (Wellbore)	Tool Name	Description
0.0	23,283.4	Design #1 (Wellbore #1)	MWD	OWSG MWD - Standard

Ameredev Operating, LLC
Lease Penetration Section Line Footages

Company: Ameredev Operating, LLC.
Project: CAM/AZ
Site: CAM/AZ #1N
Well: Camellia 121H
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well Camellia 121H
TVD Reference: KB @ 2951.0usft
MD Reference: KB @ 2951.0usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: EDM5000

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	+FSL/-FNL (usft)	+FWL/-FEL (usft)	V. Sec (usft)	DLeg (°/100usft)	Build (°/100usft)	Turn (°/100usft)
0.0	0.00	0.00	0.0	283.0	270.0	0.0	0.00	0.00	0.00
100.0	0.00	0.00	100.0	283.0	270.0	0.0	0.00	0.00	0.00
200.0	0.00	0.00	200.0	283.0	270.0	0.0	0.00	0.00	0.00
300.0	0.00	0.00	300.0	283.0	270.0	0.0	0.00	0.00	0.00
400.0	0.00	0.00	400.0	283.0	270.0	0.0	0.00	0.00	0.00
500.0	0.00	0.00	500.0	283.0	270.0	0.0	0.00	0.00	0.00
600.0	0.00	0.00	600.0	283.0	270.0	0.0	0.00	0.00	0.00
700.0	0.00	0.00	700.0	283.0	270.0	0.0	0.00	0.00	0.00
800.0	0.00	0.00	800.0	283.0	270.0	0.0	0.00	0.00	0.00
900.0	0.00	0.00	900.0	283.0	270.0	0.0	0.00	0.00	0.00
1,000.0	0.00	0.00	1,000.0	283.0	270.0	0.0	0.00	0.00	0.00
1,100.0	0.00	0.00	1,100.0	283.0	270.0	0.0	0.00	0.00	0.00
1,200.0	0.00	0.00	1,200.0	283.0	270.0	0.0	0.00	0.00	0.00
1,300.0	0.00	0.00	1,300.0	283.0	270.0	0.0	0.00	0.00	0.00
1,400.0	0.00	0.00	1,400.0	283.0	270.0	0.0	0.00	0.00	0.00
1,500.0	0.00	0.00	1,500.0	283.0	270.0	0.0	0.00	0.00	0.00
1,600.0	0.00	0.00	1,600.0	283.0	270.0	0.0	0.00	0.00	0.00
1,700.0	0.00	0.00	1,700.0	283.0	270.0	0.0	0.00	0.00	0.00
1,800.0	0.00	0.00	1,800.0	283.0	270.0	0.0	0.00	0.00	0.00
1,900.0	0.00	0.00	1,900.0	283.0	270.0	0.0	0.00	0.00	0.00
2,000.0	0.00	0.00	2,000.0	283.0	270.0	0.0	0.00	0.00	0.00
2,100.0	2.00	180.00	2,100.0	281.3	270.0	-1.7	2.00	2.00	0.00
2,200.0	4.00	180.00	2,199.8	276.0	270.0	-7.0	2.00	2.00	0.00
2,300.0	6.00	180.00	2,299.5	267.3	270.0	-15.7	2.00	2.00	0.00
2,400.0	6.00	180.00	2,398.9	256.9	270.0	-26.1	0.00	0.00	0.00
2,500.0	6.00	180.00	2,498.4	246.4	270.0	-36.6	0.00	0.00	0.00
2,600.0	6.00	180.00	2,597.8	235.9	270.0	-47.0	0.00	0.00	0.00

Company: Ameredev Operating, LLC.
 Project: CAM/AZ
 Site: CAM/AZ #1N
 Well: Camellia 121H
 Wellbore: Wellbore #1
 Design: Design #1

Local Co-ordinate Reference: Well Camellia 121H
 TVD Reference: KB @ 2951.0usft
 MD Reference: KB @ 2951.0usft
 North Reference: Grid
 Survey Calculation Method: Minimum Curvature
 Database: EDM5000

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	+FSL/-FNL (usft)	+FWL/-FEL (usft)	V. Sec (usft)	DLeg (°/100usft)	Build (°/100usft)	Turn (°/100usft)
2,700.0	6.00	180.00	2,697.3	225.5	270.0	-57.5	0.00	0.00	0.00
2,800.0	6.00	180.00	2,796.7	215.0	270.0	-67.9	0.00	0.00	0.00
2,900.0	6.00	180.00	2,896.2	204.6	270.0	-78.4	0.00	0.00	0.00
3,000.0	6.00	180.00	2,995.6	194.1	270.0	-88.9	0.00	0.00	0.00
3,100.0	6.00	180.00	3,095.1	183.7	270.0	-99.3	0.00	0.00	0.00
3,200.0	6.00	180.00	3,194.5	173.2	270.0	-109.8	0.00	0.00	0.00
3,300.0	6.00	180.00	3,294.0	162.8	270.0	-120.2	0.00	0.00	0.00
3,400.0	6.00	180.00	3,393.4	152.3	270.0	-130.7	0.00	0.00	0.00
3,500.0	6.00	180.00	3,492.9	141.9	270.0	-141.1	0.00	0.00	0.00
3,600.0	6.00	180.00	3,592.3	131.4	270.0	-151.6	0.00	0.00	0.00
3,700.0	6.00	180.00	3,691.8	121.0	270.0	-162.0	0.00	0.00	0.00
3,800.0	6.00	180.00	3,791.2	110.5	270.0	-172.5	0.00	0.00	0.00
3,900.0	6.00	180.00	3,890.7	100.1	270.0	-182.9	0.00	0.00	0.00
4,000.0	6.00	180.00	3,990.1	89.6	270.0	-193.4	0.00	0.00	0.00
4,100.0	6.00	180.00	4,089.6	79.2	270.0	-203.8	0.00	0.00	0.00
4,200.0	6.00	180.00	4,189.0	68.7	270.0	-214.3	0.00	0.00	0.00
4,300.0	6.00	180.00	4,288.5	58.2	270.0	-224.7	0.00	0.00	0.00
4,400.0	6.00	180.00	4,387.9	47.8	270.0	-235.2	0.00	0.00	0.00
4,500.0	6.00	180.00	4,487.4	37.3	270.0	-245.6	0.00	0.00	0.00
4,600.0	6.00	180.00	4,586.9	26.9	270.0	-256.1	0.00	0.00	0.00
4,700.0	6.00	180.00	4,686.3	16.4	270.0	-266.5	0.00	0.00	0.00
4,800.0	6.00	180.00	4,785.8	6.0	270.0	-277.0	0.00	0.00	0.00
4,900.0	6.00	180.00	4,885.2	-4.5	270.0	-287.4	0.00	0.00	0.00
5,000.0	6.00	180.00	4,984.7	-14.9	270.0	-297.9	0.00	0.00	0.00
5,100.0	6.00	180.00	5,084.1	-25.4	270.0	-308.3	0.00	0.00	0.00
5,200.0	6.00	180.00	5,183.6	-35.8	270.0	-318.8	0.00	0.00	0.00
5,300.0	6.00	180.00	5,283.0	-46.3	270.0	-329.2	0.00	0.00	0.00

Ameredev Operating, LLC
Lease Penetration Section Line Footages

Company: Ameredev Operating, LLC.
Project: CAM/AZ
Site: CAM/AZ #1N
Well: Camellia 121H
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well Camellia 121H
TVD Reference: KB @ 2951.0usft
MD Reference: KB @ 2951.0usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: EDM5000

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	+FSL/-FNL (usft)	+FWL/-FEL (usft)	V. Sec (usft)	DLeg (°/100usft)	Build (°/100usft)	Turn (°/100usft)
5,400.0	6.00	180.00	5,382.5	-56.7	270.0	-339.7	0.00	0.00	0.00
5,500.0	6.00	180.00	5,481.9	-67.2	270.0	-350.1	0.00	0.00	0.00
5,600.0	6.00	180.00	5,581.4	-77.6	270.0	-360.6	0.00	0.00	0.00
5,700.0	6.00	180.00	5,680.8	-88.1	270.0	-371.0	0.00	0.00	0.00
5,800.0	6.00	180.00	5,780.3	-98.5	270.0	-381.5	0.00	0.00	0.00
5,900.0	6.00	180.00	5,879.7	-109.0	270.0	-391.9	0.00	0.00	0.00
6,000.0	6.00	180.00	5,979.2	-119.4	270.0	-402.4	0.00	0.00	0.00
6,100.0	6.00	180.00	6,078.6	-129.9	270.0	-412.8	0.00	0.00	0.00
6,200.0	6.00	180.00	6,178.1	-140.4	270.0	-423.3	0.00	0.00	0.00
6,300.0	6.00	180.00	6,277.5	-150.8	270.0	-433.7	0.00	0.00	0.00
6,400.0	6.00	180.00	6,377.0	-161.3	270.0	-444.2	0.00	0.00	0.00
6,500.0	6.00	180.00	6,476.4	-171.7	270.0	-454.6	0.00	0.00	0.00
6,600.0	6.00	180.00	6,575.9	-182.2	270.0	-465.1	0.00	0.00	0.00
6,700.0	6.00	180.00	6,675.3	-192.6	270.0	-475.5	0.00	0.00	0.00
6,724.8	6.00	180.00	6,700.0	-195.2	270.0	-478.1	0.00	0.00	0.00
6,800.0	4.50	180.00	6,774.9	-202.1	270.0	-485.0	2.00	-2.00	0.00
6,900.0	2.50	180.00	6,874.7	-208.2	270.0	-491.1	2.00	-2.00	0.00
7,000.0	0.50	180.00	6,974.7	-210.8	270.0	-493.7	2.00	-2.00	0.00
7,024.8	0.00	0.00	6,999.5	-210.9	270.0	-493.8	2.00	-2.00	0.00
7,100.0	0.00	0.00	7,074.7	-210.9	270.0	-493.8	0.00	0.00	0.00
7,200.0	0.00	0.00	7,174.7	-210.9	270.0	-493.8	0.00	0.00	0.00
7,300.0	0.00	0.00	7,274.7	-210.9	270.0	-493.8	0.00	0.00	0.00
7,400.0	0.00	0.00	7,374.7	-210.9	270.0	-493.8	0.00	0.00	0.00
7,500.0	0.00	0.00	7,474.7	-210.9	270.0	-493.8	0.00	0.00	0.00
7,600.0	0.00	0.00	7,574.7	-210.9	270.0	-493.8	0.00	0.00	0.00
7,700.0	0.00	0.00	7,674.7	-210.9	270.0	-493.8	0.00	0.00	0.00
7,800.0	0.00	0.00	7,774.7	-210.9	270.0	-493.8	0.00	0.00	0.00

Company: Ameredev Operating, LLC.
Project: CAM/AZ
Site: CAM/AZ #1N
Well: Camellia 121H
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well Camellia 121H
TVD Reference: KB @ 2951.0usft
MD Reference: KB @ 2951.0usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: EDM5000

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	+FSL/-FNL (usft)	+FWL/-FEL (usft)	V. Sec (usft)	DLeg (°/100usft)	Build (°/100usft)	Turn (°/100usft)
7,900.0	0.00	0.00	7,874.7	-210.9	270.0	-493.8	0.00	0.00	0.00
8,000.0	0.00	0.00	7,974.7	-210.9	270.0	-493.8	0.00	0.00	0.00
8,100.0	0.00	0.00	8,074.7	-210.9	270.0	-493.8	0.00	0.00	0.00
8,200.0	0.00	0.00	8,174.7	-210.9	270.0	-493.8	0.00	0.00	0.00
8,300.0	0.00	0.00	8,274.7	-210.9	270.0	-493.8	0.00	0.00	0.00
8,400.0	0.00	0.00	8,374.7	-210.9	270.0	-493.8	0.00	0.00	0.00
8,500.0	0.00	0.00	8,474.7	-210.9	270.0	-493.8	0.00	0.00	0.00
8,525.3	0.00	0.00	8,500.0	-210.9	270.0	-493.8	0.00	0.00	0.00
8,600.0	1.49	180.00	8,574.7	-211.9	270.0	-494.8	2.00	2.00	0.00
8,700.0	3.49	180.00	8,674.6	-216.2	270.0	-499.2	2.00	2.00	0.00
8,800.0	5.49	180.00	8,774.2	-224.1	270.0	-507.0	2.00	2.00	0.00
8,825.3	6.00	180.00	8,799.5	-226.6	270.0	-509.5	2.00	2.00	0.00
8,900.0	6.00	180.00	8,873.7	-234.4	270.0	-517.3	0.00	0.00	0.00
9,000.0	6.00	180.00	8,973.2	-244.9	270.0	-527.8	0.00	0.00	0.00
9,100.0	6.00	180.00	9,072.6	-255.3	270.0	-538.2	0.00	0.00	0.00
9,200.0	6.00	180.00	9,172.1	-265.8	270.0	-548.7	0.00	0.00	0.00
9,300.0	6.00	180.00	9,271.5	-276.2	270.0	-559.1	0.00	0.00	0.00
9,400.0	6.00	180.00	9,371.0	-286.7	270.0	-569.6	0.00	0.00	0.00
9,500.0	6.00	180.00	9,470.4	-297.1	270.0	-580.0	0.00	0.00	0.00
9,600.0	6.00	180.00	9,569.9	-307.6	270.0	-590.5	0.00	0.00	0.00
9,700.0	6.00	180.00	9,669.3	-318.0	270.0	-600.9	0.00	0.00	0.00
9,800.0	6.00	180.00	9,768.8	-328.5	270.0	-611.4	0.00	0.00	0.00
9,900.0	6.00	180.00	9,868.2	-338.9	270.0	-621.8	0.00	0.00	0.00
10,000.0	6.00	180.00	9,967.7	-349.4	270.0	-632.3	0.00	0.00	0.00
10,100.0	6.00	180.00	10,067.1	-359.8	270.0	-642.7	0.00	0.00	0.00
10,133.0	6.00	180.00	10,100.0	-363.3	270.0	-646.2	0.00	0.00	0.00
10,200.0	4.66	180.00	10,166.7	-369.5	270.0	-652.4	2.00	-2.00	0.00

Company: Ameredev Operating, LLC.
 Project: CAM/AZ
 Site: CAM/AZ #1N
 Well: Camellia 121H
 Wellbore: Wellbore #1
 Design: Design #1

Local Co-ordinate Reference: Well Camellia 121H
 TVD Reference: KB @ 2951.0usft
 MD Reference: KB @ 2951.0usft
 North Reference: Grid
 Survey Calculation Method: Minimum Curvature
 Database: EDM5000

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	+FSL/-FNL (usft)	+FWL/-FEL (usft)	V. Sec (usft)	DLeg (°/100usft)	Build (°/100usft)	Turn (°/100usft)
10,300.0	2.66	180.00	10,266.5	-375.9	270.0	-658.8	2.00	-2.00	0.00
10,400.0	0.66	180.00	10,366.4	-378.8	270.0	-661.7	2.00	-2.00	0.00
Sec 28									
10,433.0	0.00	0.00	10,399.5	-379.0	270.0	-661.9	2.00	-2.00	0.00
10,500.0	0.00	0.00	10,466.4	-379.0	270.0	-661.9	0.00	0.00	0.00
10,600.0	0.00	0.00	10,566.4	-379.0	270.0	-661.9	0.00	0.00	0.00
10,700.0	0.00	0.00	10,666.4	-379.0	270.0	-661.9	0.00	0.00	0.00
10,800.0	0.00	0.00	10,766.4	-379.0	270.0	-661.9	0.00	0.00	0.00
10,900.0	0.00	0.00	10,866.4	-379.0	270.0	-661.9	0.00	0.00	0.00
11,000.0	0.00	0.00	10,966.4	-379.0	270.0	-661.9	0.00	0.00	0.00
11,100.0	0.00	0.00	11,066.4	-379.0	270.0	-661.9	0.00	0.00	0.00
11,200.0	0.00	0.00	11,166.4	-379.0	270.0	-661.9	0.00	0.00	0.00
11,300.0	0.00	0.00	11,266.4	-379.0	270.0	-661.9	0.00	0.00	0.00
11,400.0	0.00	0.00	11,366.4	-379.0	270.0	-661.9	0.00	0.00	0.00
11,500.0	0.00	0.00	11,466.4	-379.0	270.0	-661.9	0.00	0.00	0.00
11,600.0	0.00	0.00	11,566.4	-379.0	270.0	-661.9	0.00	0.00	0.00
11,700.0	0.00	0.00	11,666.4	-379.0	270.0	-661.9	0.00	0.00	0.00
11,800.0	0.00	0.00	11,766.4	-379.0	270.0	-661.9	0.00	0.00	0.00
11,800.6	0.00	0.00	11,767.0	-379.0	270.0	-661.9	0.00	0.00	0.00
Sec 21									
11,900.0	0.00	0.00	11,866.4	-379.0	270.0	-661.9	0.00	0.00	0.00
12,000.0	0.00	0.00	11,966.4	-379.0	270.0	-661.9	0.00	0.00	0.00
12,033.6	0.00	0.00	12,000.0	-379.0	270.0	-661.9	0.00	0.00	0.00
12,094.7	7.29	248.11	12,061.0	-380.4	266.4	-663.3	11.93	11.93	0.00
12,100.0	7.09	252.88	12,066.2	-380.7	265.8	-663.5	11.93	-3.84	90.26
12,200.0	12.00	325.31	12,165.1	-373.9	253.9	-656.5	11.93	4.91	72.43
12,300.0	22.82	342.96	12,260.4	-346.7	242.3	-629.1	11.93	10.82	17.65

Ameredev Operating, LLC

Lease Penetration Section Line Footages

Company: Ameredev Operating, LLC.
 Project: CAM/AZ
 Site: CAM/AZ #1N
 Well: Camellia 121H
 Wellbore: Wellbore #1
 Design: Design #1

Local Co-ordinate Reference: Well Camellia 121H
 TVD Reference: KB @ 2951.0usft
 MD Reference: KB @ 2951.0usft
 North Reference: Grid
 Survey Calculation Method: Minimum Curvature
 Database: EDM5000

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	+FSL-FNL (usft)	+FWL-FEL (usft)	V. Sec (usft)	DLeg (°/100usft)	Build (°/100usft)	Turn (°/100usft)
12,400.0	34.36	349.38	12,348.1	-300.3	231.4	-582.5	11.93	11.54	6.41
12,500.0	46.08	352.83	12,424.3	-236.5	221.6	-518.7	11.93	11.72	3.45
12,600.0	57.87	355.12	12,485.8	-158.3	213.5	-440.3	11.93	11.79	2.30
12,700.0	69.69	356.89	12,529.9	-69.0	207.3	-350.9	11.93	11.82	1.76
12,800.0	81.53	358.40	12,554.7	27.6	203.4	-254.2	11.93	11.84	1.51
12,871.5	90.00	359.42	12,560.0	98.9	202.0	-183.0	11.93	11.84	1.42
Cam121 FTP									
12,900.0	90.00	359.42	12,560.0	127.3	201.7	-154.5	0.00	0.00	0.00
13,000.0	90.00	359.42	12,560.0	227.3	200.7	-54.5	0.00	0.00	0.00
13,100.0	90.00	359.42	12,560.0	327.3	199.7	45.5	0.00	0.00	0.00
13,200.0	90.00	359.42	12,560.0	427.3	198.7	145.5	0.00	0.00	0.00
13,300.0	90.00	359.42	12,560.0	527.3	197.7	245.5	0.00	0.00	0.00
13,400.0	90.00	359.42	12,560.0	627.3	196.6	345.5	0.00	0.00	0.00
13,500.0	90.00	359.42	12,560.0	727.3	195.6	445.5	0.00	0.00	0.00
13,600.0	90.00	359.42	12,560.0	827.3	194.6	545.5	0.00	0.00	0.00
13,700.0	90.00	359.42	12,560.0	927.3	193.6	645.5	0.00	0.00	0.00
13,800.0	90.00	359.42	12,560.0	1,027.3	192.5	745.5	0.00	0.00	0.00
13,900.0	90.00	359.42	12,560.0	1,127.3	191.5	845.5	0.00	0.00	0.00
14,000.0	90.00	359.42	12,560.0	1,227.3	190.5	945.5	0.00	0.00	0.00
14,100.0	90.00	359.42	12,560.0	1,327.3	189.5	1,045.5	0.00	0.00	0.00
14,200.0	90.00	359.42	12,560.0	1,427.3	188.5	1,145.5	0.00	0.00	0.00
14,300.0	90.00	359.42	12,560.0	1,527.3	187.4	1,245.5	0.00	0.00	0.00
14,400.0	90.00	359.42	12,560.0	1,627.2	186.4	1,345.5	0.00	0.00	0.00
14,500.0	90.00	359.42	12,560.0	1,727.2	185.4	1,445.5	0.00	0.00	0.00
14,600.0	90.00	359.42	12,560.0	1,827.2	184.4	1,545.5	0.00	0.00	0.00
14,700.0	90.00	359.42	12,560.0	1,927.2	183.4	1,645.5	0.00	0.00	0.00
14,800.0	90.00	359.42	12,560.0	2,027.2	182.3	1,745.5	0.00	0.00	0.00

Company: Ameredev Operating, LLC.
Project: CAM/AZ
Site: CAM/AZ #1N
Well: Camellia 121H
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well Camellia 121H
TVD Reference: KB @ 2951.0usft
MD Reference: KB @ 2951.0usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: EDM5000

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	+FSL/-FNL (usft)	+FWL/-FEL (usft)	V. Sec (usft)	DLeg (°/100usft)	Build (°/100usft)	Turn (°/100usft)
14,900.0	90.00	359.42	12,560.0	2,127.2	181.3	1,845.5	0.00	0.00	0.00
15,000.0	90.00	359.42	12,560.0	2,227.2	180.3	1,945.5	0.00	0.00	0.00
15,100.0	90.00	359.42	12,560.0	2,327.2	179.3	2,045.5	0.00	0.00	0.00
15,200.0	90.00	359.42	12,560.0	2,427.2	178.3	2,145.5	0.00	0.00	0.00
15,300.0	90.00	359.42	12,560.0	2,527.2	177.2	2,245.5	0.00	0.00	0.00
15,400.0	90.00	359.42	12,560.0	2,627.2	176.2	2,345.5	0.00	0.00	0.00
15,500.0	90.00	359.42	12,560.0	2,727.2	175.2	2,445.5	0.00	0.00	0.00
15,600.0	90.00	359.42	12,560.0	2,827.2	174.2	2,545.5	0.00	0.00	0.00
15,700.0	90.00	359.42	12,560.0	2,927.2	173.1	2,645.4	0.00	0.00	0.00
15,800.0	90.00	359.42	12,560.0	3,027.2	172.1	2,745.4	0.00	0.00	0.00
15,900.0	90.00	359.42	12,560.0	3,127.2	171.1	2,845.4	0.00	0.00	0.00
16,000.0	90.00	359.42	12,560.0	3,227.2	170.1	2,945.4	0.00	0.00	0.00
16,100.0	90.00	359.42	12,560.0	3,327.2	169.1	3,045.4	0.00	0.00	0.00
16,200.0	90.00	359.42	12,560.0	3,427.2	168.0	3,145.4	0.00	0.00	0.00
16,300.0	90.00	359.42	12,560.0	3,527.2	167.0	3,245.4	0.00	0.00	0.00
16,400.0	90.00	359.42	12,560.0	3,627.1	166.0	3,345.4	0.00	0.00	0.00
16,500.0	90.00	359.42	12,560.0	3,727.1	165.0	3,445.4	0.00	0.00	0.00
16,600.0	90.00	359.42	12,560.0	3,827.1	164.0	3,545.4	0.00	0.00	0.00
16,700.0	90.00	359.42	12,560.0	3,927.1	162.9	3,645.4	0.00	0.00	0.00
16,800.0	90.00	359.42	12,560.0	4,027.1	161.9	3,745.4	0.00	0.00	0.00
16,900.0	90.00	359.42	12,560.0	4,127.1	160.9	3,845.4	0.00	0.00	0.00
17,000.0	90.00	359.42	12,560.0	4,227.1	159.9	3,945.4	0.00	0.00	0.00
17,100.0	90.00	359.42	12,560.0	4,327.1	158.9	4,045.4	0.00	0.00	0.00
17,200.0	90.00	359.42	12,560.0	4,427.1	157.8	4,145.4	0.00	0.00	0.00
17,300.0	90.00	359.42	12,560.0	4,527.1	156.8	4,245.4	0.00	0.00	0.00
17,400.0	90.00	359.42	12,560.0	4,627.1	155.8	4,345.4	0.00	0.00	0.00
17,500.0	90.00	359.42	12,560.0	4,727.1	154.8	4,445.4	0.00	0.00	0.00

Company: Ameredev Operating, LLC.
 Project: CAM/AZ
 Site: CAM/AZ #1N
 Well: Camellia 121H
 Wellbore: Wellbore #1
 Design: Design #1

Local Co-ordinate Reference: Well Camellia 121H
 TVD Reference: KB @ 2951.0usft
 MD Reference: KB @ 2951.0usft
 North Reference: Grid
 Survey Calculation Method: Minimum Curvature
 Database: EDM5000

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	+FSL/-FNL (usft)	+FWL/-FEL (usft)	V. Sec (usft)	DLeg (°/100usft)	Build (°/100usft)	Turn (°/100usft)
17,600.0	90.00	359.42	12,560.0	4,827.1	153.8	4,545.4	0.00	0.00	0.00
17,700.0	90.00	359.42	12,560.0	4,927.1	152.7	4,645.4	0.00	0.00	0.00
17,800.0	90.00	359.42	12,560.0	5,027.1	151.7	4,745.4	0.00	0.00	0.00
17,900.0	90.00	359.42	12,560.0	5,127.1	150.7	4,845.4	0.00	0.00	0.00
18,000.0	90.00	359.42	12,560.0	5,227.1	149.7	4,945.4	0.00	0.00	0.00
18,053.2	90.00	359.42	12,560.0	5,280.2	149.1	4,998.5	0.00	0.00	0.00
Sec 16									
18,100.0	90.00	359.42	12,560.0	5,327.1	148.6	5,045.4	0.00	0.00	0.00
18,200.0	90.00	359.42	12,560.0	5,427.1	147.6	5,145.4	0.00	0.00	0.00
18,300.0	90.00	359.42	12,560.0	5,527.0	146.6	5,245.4	0.00	0.00	0.00
18,400.0	90.00	359.42	12,560.0	5,627.0	145.6	5,345.4	0.00	0.00	0.00
18,500.0	90.00	359.42	12,560.0	5,727.0	144.6	5,445.4	0.00	0.00	0.00
18,600.0	90.00	359.42	12,560.0	5,827.0	143.5	5,545.4	0.00	0.00	0.00
18,700.0	90.00	359.42	12,560.0	5,927.0	142.5	5,645.4	0.00	0.00	0.00
18,800.0	90.00	359.42	12,560.0	6,027.0	141.5	5,745.4	0.00	0.00	0.00
18,900.0	90.00	359.42	12,560.0	6,127.0	140.5	5,845.4	0.00	0.00	0.00
19,000.0	90.00	359.42	12,560.0	6,227.0	139.5	5,945.4	0.00	0.00	0.00
19,100.0	90.00	359.42	12,560.0	6,327.0	138.4	6,045.4	0.00	0.00	0.00
19,200.0	90.00	359.42	12,560.0	6,427.0	137.4	6,145.4	0.00	0.00	0.00
19,300.0	90.00	359.42	12,560.0	6,527.0	136.4	6,245.4	0.00	0.00	0.00
19,400.0	90.00	359.42	12,560.0	6,627.0	135.4	6,345.4	0.00	0.00	0.00
19,500.0	90.00	359.42	12,560.0	6,727.0	134.4	6,445.4	0.00	0.00	0.00
19,600.0	90.00	359.42	12,560.0	6,827.0	133.3	6,545.4	0.00	0.00	0.00
19,700.0	90.00	359.42	12,560.0	6,927.0	132.3	6,645.4	0.00	0.00	0.00
19,800.0	90.00	359.42	12,560.0	7,027.0	131.3	6,745.4	0.00	0.00	0.00
19,900.0	90.00	359.42	12,560.0	7,127.0	130.3	6,845.3	0.00	0.00	0.00
20,000.0	90.00	359.42	12,560.0	7,227.0	129.3	6,945.3	0.00	0.00	0.00

Ameredev Operating, LLC
Lease Penetration Section Line Footages

Company: Ameredev Operating, LLC.
Project: CAM/AZ
Site: CAM/AZ #1N
Well: Camellia 121H
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well Camellia 121H
TVD Reference: KB @ 2951.0usft
MD Reference: KB @ 2951.0usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: EDM5000

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	+FSL/-FNL (usft)	+FWL/-FEL (usft)	V. Sec (usft)	DLeg (°/100usft)	Build (°/100usft)	Turn (°/100usft)
20,100.0	90.00	359.42	12,560.0	7,327.0	128.2	7,045.3	0.00	0.00	0.00
20,200.0	90.00	359.42	12,560.0	7,426.9	127.2	7,145.3	0.00	0.00	0.00
20,300.0	90.00	359.42	12,560.0	7,526.9	126.2	7,245.3	0.00	0.00	0.00
20,400.0	90.00	359.42	12,560.0	7,626.9	125.2	7,345.3	0.00	0.00	0.00
20,500.0	90.00	359.42	12,560.0	7,726.9	124.1	7,445.3	0.00	0.00	0.00
20,600.0	90.00	359.42	12,560.0	7,826.9	123.1	7,545.3	0.00	0.00	0.00
20,700.0	90.00	359.42	12,560.0	7,926.9	122.1	7,645.3	0.00	0.00	0.00
20,800.0	90.00	359.42	12,560.0	8,026.9	121.1	7,745.3	0.00	0.00	0.00
20,900.0	90.00	359.42	12,560.0	8,126.9	120.1	7,845.3	0.00	0.00	0.00
21,000.0	90.00	359.42	12,560.0	8,226.9	119.0	7,945.3	0.00	0.00	0.00
21,100.0	90.00	359.42	12,560.0	8,326.9	118.0	8,045.3	0.00	0.00	0.00
21,200.0	90.00	359.42	12,560.0	8,426.9	117.0	8,145.3	0.00	0.00	0.00
21,300.0	90.00	359.42	12,560.0	8,526.9	116.0	8,245.3	0.00	0.00	0.00
21,400.0	90.00	359.42	12,560.0	8,626.9	115.0	8,345.3	0.00	0.00	0.00
21,500.0	90.00	359.42	12,560.0	8,726.9	113.9	8,445.3	0.00	0.00	0.00
21,600.0	90.00	359.42	12,560.0	8,826.9	112.9	8,545.3	0.00	0.00	0.00
21,700.0	90.00	359.42	12,560.0	8,926.9	111.9	8,645.3	0.00	0.00	0.00
21,800.0	90.00	359.42	12,560.0	9,026.9	110.9	8,745.3	0.00	0.00	0.00
21,900.0	90.00	359.42	12,560.0	9,126.9	109.9	8,845.3	0.00	0.00	0.00
22,000.0	90.00	359.42	12,560.0	9,226.9	108.8	8,945.3	0.00	0.00	0.00
22,100.0	90.00	359.42	12,560.0	9,326.8	107.8	9,045.3	0.00	0.00	0.00
22,200.0	90.00	359.42	12,560.0	9,426.8	106.8	9,145.3	0.00	0.00	0.00
22,300.0	90.00	359.42	12,560.0	9,526.8	105.8	9,245.3	0.00	0.00	0.00
22,400.0	90.00	359.42	12,560.0	9,626.8	104.7	9,345.3	0.00	0.00	0.00
22,500.0	90.00	359.42	12,560.0	9,726.8	103.7	9,445.3	0.00	0.00	0.00
22,600.0	90.00	359.42	12,560.0	9,826.8	102.7	9,545.3	0.00	0.00	0.00
22,700.0	90.00	359.42	12,560.0	9,926.8	101.7	9,645.3	0.00	0.00	0.00

Company: Ameredev Operating, LLC.
Project: CAM/AZ
Site: CAM/AZ #1N
Well: Camellia 121H
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well Camellia 121H
TVD Reference: KB @ 2951.0usft
MD Reference: KB @ 2951.0usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: EDM5000

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	+FSL/FNL (usft)	+FWL/FEL (usft)	V. Sec (usft)	DLeg (°/100usft)	Build (°/100usft)	Turn (°/100usft)
22,800.0	90.00	359.42	12,560.0	10,026.8	100.7	9,745.3	0.00	0.00	0.00
22,900.0	90.00	359.42	12,560.0	10,126.8	99.6	9,845.3	0.00	0.00	0.00
23,000.0	90.00	359.42	12,560.0	10,226.8	98.6	9,945.3	0.00	0.00	0.00
23,100.0	90.00	359.42	12,560.0	10,326.8	97.6	10,045.3	0.00	0.00	0.00
23,200.0	90.00	359.42	12,560.0	10,426.8	96.6	10,145.3	0.00	0.00	0.00
Cam121 LTP 23,283.4	90.00	359.42	12,560.0	10,510.1	95.7	10,228.6	0.00	0.00	0.00
Cam121 BHL									

Pressure Control Plan

Pressure Control Equipment

- Following setting of 13-3/8" Surface Casing Ameredev will install 13-5/8 MB4 Multi Bowl Casing Head by welding on a 13-5/8 SOW x 13-5/8" 5M in combination with 13-5/8 5M x 13-5/8 10M B-Sec to Land Intm #1 and a 13-5/8 10M x 13-5/8 10M shouldered to land C-Sec to Land Intm #2 (Installation procedure witnessed and verified by a manufacturer's representative).
- Casing will be tested to 1500 psi or .22 psi/ft whichever is greater for 30 minutes with <10% leak off, but will not exceed 70% of the burst rating per Onshore Order No. 2.
- Ameredev will install a 5M System Blowout Preventer (BOPE) with a 5M Annular Preventer and related equipment (BOPE). Full testing will be performed utilizing a full isolation test plug and limited to 5,000 psi MOP of MB4 Multi Bowl Casing Head. Pressure will be held for 10 min or until provisions of test are met on all valves and rams. The 5M Annular Preventer will be tested to 50% of approved working pressure (2,500 psi). Casing will be tested to 1500 psi or .22 psi/ft whichever is greater for 30 minutes with <10% leak off, but will not exceed 70% of the burst rating per Onshore Order No. 2.
- Setting of 9-5/8" Intermediate will be done by landing a wellhead hanger in the 13-5/8" 5M Bowl, Cementing and setting Well Head Packing seals and testing same. (Installation procedure witnessed and verified by a manufacturer's representative) Casing will be tested to 1500 psi or .22 psi/ft whichever is greater for 30 minutes with <10% leak off, but will not exceed 70% of the burst rating per Onshore Order No. 2.
- Full testing will be performed utilizing a full isolation test plug to 10,000 psi MOP of MB4 Multi Bowl B-Section. Pressure will be held for 10 min or until provisions of test are met on all valves and rams. The 5M Annular Preventer will be tested to 100% of approved working pressure (5,000 psi).
- Before drilling >20ft of new formation under the 9-5/8" Casing Shoe a pressure integrity test of the Casing Shoe will be performed to minimum of the MWE anticipated to control formation pressure to the next casing depth.
- Following setting of 5-1/2" Production Casing and adequate WOC time Ameredev will break 10M System Blowout Preventer (BOP) from 10M DOL-2 Casing Head, install annulus casing slips and test same (Installation procedure witnessed and verified by a manufacturer's representative) and install 11" 10M x 5-1/8" 15M Tubing Head (Installation procedure witnessed and verified by a manufacturer's representative). Ameredev will test head to 70% casing design and install Dry Hole cap with needle valve and pressure gauge to monitor well awaiting completion.

Pressure Control Plan

- Slow pump speeds will be taken daily by each crew and recorded on Daily Drilling Report after mudding up.
- A choke manifold and accumulator with floor and remote operating stations will be functional and in place after installation of BOPE, as well as full functioning mud gas separator.
- Weekly BOPE pit level drills will be conducted by each crew and recorded on Daily Drilling Report.
- BOP will be fully operated when out of hole and will be documented on the daily drilling log.
- All B.O.P.s and associated equipment will be tested in accordance with Onshore Order #2
- All B.O.P. testing will be done by an independent service company.
- The B.O.P. will be tested within 21 days of the original test if drilling takes more time than planned.
- Ameredev requests a variance to connect the B.O.P. choke outlet to the choke manifold using a co-flex hose with a 10,000 psi working pressure that has been tested to 15,000psi and is built to API Spec 16C. Once the flex line is installed it will be tied down with safety clamps. (certifications will be sent to Carlsbad BLM Office prior to install)
- Ameredev requests a variance to install a 5M Annular Preventer on the 10M System to drill the Production Hole below the 9-5/8" Intermediate Section. 5M Annular will be tested to 100% working pressure (5,000 psi). A full well control procedure will be included to isolate well bore.

Ameredev Drilling Plan: 3 String with 4 String Contingency

- Contingency Plan If Losses Exceed 50% in Intermediate Interval
 - We will utilize a MB4 wellhead that will enable us to convert a 3 string design to a 4 string design. (Schematic Attached)
 - We will displace well with FW and drill or condition to run 9-5/8" Casing at the Lamar Limestone, we will utilize DV Tool w/ ACP @ the Tansill to Isolate Capitan Reef and cement to surface.
 - Casing will be tested to 1500 psi or .22 psi/ft whichever is greater for 30 minutes with <10% leak off, but will not exceed 70% of the burst rating per Onshore Order No. 2.
- 7.625 Casing will be Additional 4th String
 - Drill remaining hole section to 10,670'
 - Run 7.625 29.7# HCL80 FJM Casing

4-String Contingency Wellbore Schematic

Well:	(Well Name)	Co. Well ID:	xxxxxx
SHL:	(SHL)	AFE No.:	xxxx-xxx
BHL:	(BHL)	API No.:	xxxxxxxxxxx
	Lea, NM	GL:	(Elevation)'
Wellhead:	A - 13-5/8" 10M x 13-5/8" SOW	Field:	Delaware
	B - 13-5/8" 10M x 13-5/8" 10M	Objective:	Wolfcamp B
	C - 13-5/8" 10M x 13-5/8" 10M	TVD:	(TVD)'
	Tubing Spool - 5-1/8" 15M x 13-3/8" 10M	MD:	(MD)'
Xmas Tree:	2-9/16" 10M	Rig:	TBD KB 27'
Tubing:	2-7/8" L-80 6.5# 8rd EUE	E-Mail:	Wellsite2@ameredev.com


Hole Size	Formation Tops	Logs	Cement	Mud Weight
17.5"	Rustler 125' below Rustler 13.375" 54.5# J-55 BTC	TOC 0'	100% Excess	8.4-8.6 ppg WBM
12.25"	Salado DV Tool with ACP At Tansill Tansill Capitan Reef Lamar 50' below Lamar 9.625" 40# L-80HC BTC	TOC 0'	50% Excess	8.3-10.2 Fresh Water
8.75"	Bell Canyon Brushy Canyon Bone Spring Lime First Bone Spring Second Bone Spring Third Bone Spring Upper 125' below TBSG Upper 7.625" 29.7# L-80HC FJM	TOC 0'	25% Excess	8.5-9.4 Diesel Brine Emulsion
6.75" 12° Build @ KOP	Third Bone Spring Wolfcamp Wolfcamp B (If Applicable) 5.5" 20# P-110CYHP TMK UP SF TORQ (MD) Target Wolfcamp B TVD // MD	TOC 0'	25% Excess	10.5-14 ppg OBM

****EXAMPLE ONLY - NOT FOR CONSTRUCTION****

Contingency Casing Design and Safety Factor Check

Casing Specifications						
Segment	Hole ID	Depth	OD	Weight	Grade	Coupling
Surface	17.5	1,888'	13.375	54.5	J-55	BTC
Int #1	12.25	5,013'	9.625	40	HCL-80	BTC
Int #2	8.75	11,147'	7.625	29.7	HCL-80	FJM
Prod Segment A	6.75	11,147'	5.5	20	CYHP-110	TMK UPSF
Prod Segment B	6.75	22,496'	5.5	20	CYHP-110	TMK UPSF

Check Surface Casing				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
14.38	853	909	1,130	2,730
Safety Factors				
1.56	8.29	8.83	1.15	0.91
Check Int #1 Casing				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
10.625	916	1042	4230	5750
Safety Factors				
0.81	4.57	5.20	1.41	0.95
Check Int #2 Casing				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
7.625	940	558	6700	9460
Safety Factors				
0.56	2.84	1.96	1.10	1.24
Check Prod Casing, Segment A				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
5.777	728	655	12780	14360
Safety Factors				
0.49	3.11	2.79	1.77	1.89
Check Prod Casing, Segment B				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
5.777	728	655	12780	14360
Safety Factors				
0.49	63.53	57.16	1.68	1.89



Quotation

Downing Wellhead Equipment

Oklahoma City,
Oklahoma - USA

Reference Data:

16925 AMEREDEV

Proprietary and Confidential

The information contained in this drawing is the sole property of Downing Wellhead Equipment, any reproduction in part or in whole without the written permission of Downing Wellhead Equipment is prohibited.

TITLE:

AMEREDEV

DRAWN

CHECKED

APPROVED

SIZE

A

Scale:

DWG. NO.

Weight:

REV.

Sheet:


13 5/8" 5M BOP
Configuration

CO-FLEX LINE TO
CHOKE MANIFOLD

2" KILL LINE

4" 10M VALVES &

10M Check Valve




Pressure Control Plan

Pressure Control Equipment

- Following setting of 13-3/8" Surface Casing Ameredev will install 13-5/8 MB4 Multi Bowl Casing Head by welding on a 13-5/8 SOW x 13-5/8" 5M in combination with 13-5/8 5M x 13-5/8 10M B-Sec to Land Intm #1 and a 13-5/8 10M x 13-5/8 10M shouldered to land C-Sec to Land Intm #2 (Installation procedure witnessed and verified by a manufacturer's representative).
- Casing will be tested to 1500 psi or .22 psi/ft whichever is greater for 30 minutes with <10% leak off, but will not exceed 70% of the burst rating per Onshore Order No. 2.
- Ameredev will install a 5M System Blowout Preventer (BOPE) with a 5M Annular Preventer and related equipment (BOPE). Full testing will be performed utilizing a full isolation test plug and limited to 5,000 psi MOP of MB4 Multi Bowl Casing Head. Pressure will be held for 10 min or until provisions of test are met on all valves and rams. The 5M Annular Preventer will be tested to 50% of approved working pressure (2,500 psi). Casing will be tested to 1500 psi or .22 psi/ft whichever is greater for 30 minutes with <10% leak off, but will not exceed 70% of the burst rating per Onshore Order No. 2.
- Setting of 9-5/8" Intermediate will be done by landing a wellhead hanger in the 13-5/8" 5M Bowl, Cementing and setting Well Head Packing seals and testing same. (Installation procedure witnessed and verified by a manufacturer's representative) Casing will be tested to 1500 psi or .22 psi/ft whichever is greater for 30 minutes with <10% leak off, but will not exceed 70% of the burst rating per Onshore Order No. 2.
- Full testing will be performed utilizing a full isolation test plug to 10,000 psi MOP of MB4 Multi Bowl B-Section. Pressure will be held for 10 min or until provisions of test are met on all valves and rams. The 5M Annular Preventer will be tested to 100% of approved working pressure (5,000 psi).
- Before drilling >20ft of new formation under the 9-5/8" Casing Shoe a pressure integrity test of the Casing Shoe will be performed to minimum of the MWE anticipated to control formation pressure to the next casing depth.
- Following setting of 5-1/2" Production Casing and adequate WOC time Ameredev will break 10M System Blowout Preventer (BOP) from 10M DOL-2 Casing Head, install annulus casing slips and test same (Installation procedure witnessed and verified by a manufacturer's representative) and install 11" 10M x 5-1/8" 15M Tubing Head (Installation procedure witnessed and verified by a manufacturer's representative). Ameredev will test head to 70% casing design and install Dry Hole cap with needle valve and pressure gauge to monitor well awaiting completion.

Pressure Control Plan

- Slow pump speeds will be taken daily by each crew and recorded on Daily Drilling Report after mudding up.
- A choke manifold and accumulator with floor and remote operating stations will be functional and in place after installation of BOPE, as well as full functioning mud gas separator.
- Weekly BOPE pit level drills will be conducted by each crew and recorded on Daily Drilling Report.
- BOP will be fully operated when out of hole and will be documented on the daily drilling log.
- All B.O.P.s and associated equipment will be tested in accordance with Onshore Order #2
- All B.O.P. testing will be done by an independent service company.
- The B.O.P. will be tested within 21 days of the original test if drilling takes more time than planned.
- Ameredev requests a variance to connect the B.O.P. choke outlet to the choke manifold using a co-flex hose with a 10,000 psi working pressure that has been tested to 15,000psi and is built to API Spec 16C. Once the flex line is installed it will be tied down with safety clamps. (certifications will be sent to Carlsbad BLM Office prior to install)
- Ameredev requests a variance to install a 5M Annular Preventer on the 10M System to drill the Production Hole below the 9-5/8" Intermediate Section. 5M Annular will be tested to 100% working pressure (5,000 psi). A full well control procedure will be included to isolate well bore.



Quotation

Downing Wellhead Equipment

Oklahoma City,
Oklahoma - USA

Reference Data:

16925 AMEREDEV

Proprietary and Confidential

The information contained in this drawing is the sole property of Downing Wellhead Equipment, any reproduction in part or in whole without the written permission of Downing Wellhead Equipment is prohibited.

TITLE:

AMEREDEV

DRAWN

CHECKED

APPROVED

SIZE

A

DWG. NO.

Scale:

Weight:

Sheet:

REV.

Wellbore Schematic

Well: Camellia Fed Com 26-36-21 121H
SHL: Sec. 21 26S-36E 283' FSL & 270' FWL
BHL: Sec. 16 26S-36E 50' FNL 200' FWL
 Lea, NM

Wellhead: A - 13-5/8" 10M x 13-5/8" SOW
 B - 13-5/8" 10M x 13-5/8" 10M
 C - 13-5/8" 10M x 13-5/8" 10M
 Tubing Spool - 5-1/8" 15M x 13-3/8" 10M

Xmas Tree: 2-9/16" 10M

Tubing: 2-7/8" L-80 6.5# 8rd EUE

Co. Well ID: 40921
AFE No.: 2017-066
API No.: xxxxxxxxxxxx
GL: 2,924'
Field: Delaware
Objective: Wolfcamp B
TVD: 12,560'
MD: 23,283'
Rig: TBD **KB:** 27'
E-Mail: Wellsite2@ameredev.com

Hole Size	Formation Tops	Logs Cement	Mud Weight
17.5"	Rustler 1,876'	1,231 Sacks TOC 0'	8.4-8.6 ppg WBM
	13.375" 68# J-55 BTC 2,001'		
12.25"	Salado 2,224'		
	Tansill 3,206'		
	Capitan Reef 3,621'		
	Lamar 4,952'	884 Sacks TOC 0'	50% Excess
	DV Tool 5,002'		
	Bell Canyon 5,086'		
	Brushy Canyon 7,105'		
	Bone Spring Lime 8,129'		
	First Bone Spring 9,631'		
	Second Bone Spring 10,275'		
	Third Bone Spring Upper 10,806'		
	9.625" 40# L-80HC BTC 10,931'	1,723 Sacks TOC 0'	50% Excess
8.5"	Third Bone Spring 11,522'		
	Wolfcamp A 11,755'		
	Wolfcamp B 12,210'		
12° Build @ 12,034' MD thru 12,872' MD	5.5" 20# P-110CYHP BTC 23,283'		
	Target Wolfcamp B 12560 TVD // 23283 MD	4,971 Sacks TOC 0'	25% Excess
			10.5 - 12.5 ppg OBM

Casing Design and Safety Factor Check

Casing Specifications						
Segment	Hole ID	Depth	OD	Weight	Grade	Coupling
Surface	17.5	2,001'	13.375	68	J-55	BTC
Intermediate	12.25	10,931'	9.625	40	HCL-80	BTC
Prod Segment A	8.5	12,034'	5.5	20	CYHP-110	BTC
Prod Segment B	8.5	23,283'	5.5	20	CYHP-110	BTC

Check Surface Casing				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
14.375	1,069	915	4,100	3,450
Safety Factors				
1.56	7.86	6.72	4.59	0.65
Check Intermediate Casing				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
7.625	940	558	6700	9460
Safety Factors				
2.31	2.15	2.19	1.26	1.16
Check Prod Casing, Segment A				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
5.777	728	655	12780	14360
Safety Factors				
1.36	2.90	2.61	1.64	1.76
Check Prod Casing, Segment B				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
5.777	728	655	12780	14360
Safety Factors				
1.36	69.20	62.26	1.57	1.76

Wellbore Schematic

Well: Camellia Fed Com 26-36-21 121H
SHL: Sec. 21 26S-36E 283' FSL & 270' FWL
BHL: Sec. 16 26S-36E 50' FNL 200' FWL
 Lea, NM

Wellhead: A - 13-5/8" 10M x 13-5/8" SOW
 B - 13-5/8" 10M x 13-5/8" 10M
 C - 13-5/8" 10M x 13-5/8" 10M
 Tubing Spool - 5-1/8" 15M x 13-3/8" 10M

Xmas Tree: 2-9/16" 10M

Tubing: 2-7/8" L-80 6.5# 8rd EUE

Co. Well ID: 40921
AFE No.: 2017-066
API No.: xxxxxxxxxxxx
GL: 2,924'
Field: Delaware
Objective: Wolfcamp B
TVD: 12,560'
MD: 23,283'
Rig: TBD **KB:** 27'
E-Mail: Wellsite2@ameredev.com

Hole Size	Formation Tops	Logs Cement	Mud Weight
17.5"	Rustler 1,876'	1,231 Sacks TOC 0'	8.4-8.6 ppg WBM
	13.375" 68# J-55 BTC 2,001'		
12.25"	Salado 2,224'	884 Sacks TOC 0'	8.5 - 9.4 ppg Diesel Brine Emulsion
	Tansill 3,206'		
	Capitan Reef 3,621'		
	Lamar 4,952'		
	DV Tool 5,002'		
	Bell Canyon 5,086'	1,723 Sacks TOC 0'	8.5 - 9.4 ppg Diesel Brine Emulsion
	Brushy Canyon 7,105'		
	Bone Spring Lime 8,129'		
	First Bone Spring 9,631'		
	Second Bone Spring 10,275'		
	Third Bone Spring Upper 10,806'		
	9.625" 40# L-80HC BTC 10,931'		
8.5"	Third Bone Spring 11,522'	4,971 Sacks TOC 0'	10.5 - 12.5 ppg OBM
	Wolfcamp A 11,755'		
	Wolfcamp B 12,210'		
	5.5" 20# P-110CYHP BTC 23,283'		
12° Build @ 12,034' MD thru 12,872' MD	Target Wolfcamp B 12560 TVD // 23283 MD		

Casing Design and Safety Factor Check

Casing Specifications						
Segment	Hole ID	Depth	OD	Weight	Grade	Coupling
Surface	17.5	2,001'	13.375	68	J-55	BTC
Intermediate	12.25	10,931'	9.625	40	HCL-80	BTC
Prod Segment A	8.5	12,034'	5.5	20	CYHP-110	BTC
Prod Segment B	8.5	23,283'	5.5	20	CYHP-110	BTC

Check Surface Casing				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
14.375	1,069	915	4,100	3,450
Safety Factors				
1.56	7.86	6.72	4.59	0.65
Check Intermediate Casing				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
7.625	940	558	6700	9460
Safety Factors				
2.31	2.15	2.19	1.26	1.16
Check Prod Casing, Segment A				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
5.777	728	655	12780	14360
Safety Factors				
1.36	2.90	2.61	1.64	1.76
Check Prod Casing, Segment B				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
5.777	728	655	12780	14360
Safety Factors				
1.36	69.20	62.26	1.57	1.76

Wellbore Schematic

Well: Camellia Fed Com 26-36-21 121H
SHL: Sec. 21 26S-36E 283' FSL & 270' FWL
BHL: Sec. 16 26S-36E 50' FNL 200' FWL
 Lea, NM
Wellhead: A - 13-5/8" 10M x 13-5/8" SOW
 B - 13-5/8" 10M x 13-5/8" 10M
 C - 13-5/8" 10M x 13-5/8" 10M
 Tubing Spool - 5-1/8" 15M x 13-3/8" 10M
Xmas Tree: 2-9/16" 10M
Tubing: 2-7/8" L-80 6.5# 8rd EUE

Co. Well ID: 40921
AFE No.: 2017-066
API No.: xxxxxxxxxx
GL: 2,924'
Field: Delaware
Objective: Wolfcamp B
TVD: 12,560'
MD: 23,283'
Rig: TBD **KB:** 27'
E-Mail: Wellsite2@ameredev.com

Hole Size	Formation Tops	Logs Cement	Mud Weight
17.5"	Rustler 1,876' 13.375" 68# J-55 BTC 2,001'	1,231 Sacks TOC 0' 100% Excess	8.4-8.6 ppg WBM
12.25"	Salado 2,224' Tansill 3,206' Capitan Reef 3,621' Lamar 4,952' DV Tool 5,002' Bell Canyon 5,086' Brushy Canyon 7,105' Bone Spring Lime 8,129' First Bone Spring 9,631' Second Bone Spring 10,275' Third Bone Spring Upper 10,806' 9.625" 40# L-80HC BTC 10,931'	884 Sacks TOC 0' 50% Excess 1,723 Sacks TOC 0' 50% Excess	8.5 - 9.4 ppg Diesel Brine Emulsion
8.5"	Third Bone Spring 11,522' Wolfcamp A 11,755' Wolfcamp B 12,210' 5.5" 20# P-110CYHP BTC 23,283' Target Wolfcamp B 12560 TVD // 23283 MD	4,971 Sacks TOC 0' 25% Excess	10.5 - 12.5 ppg OBM

Casing Design and Safety Factor Check

Casing Specifications						
Segment	Hole ID	Depth	OD	Weight	Grade	Coupling
Surface	17.5	2,001'	13.375	68	J-55	BTC
Intermediate	12.25	10,931'	9.625	40	HCL-80	BTC
Prod Segment A	8.5	12,034'	5.5	20	CYHP-110	BTC
Prod Segment B	8.5	23,283'	5.5	20	CYHP-110	BTC

Check Surface Casing				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
14.375	1,069	915	4,100	3,450
Safety Factors				
1.56	7.86	6.72	4.59	0.65
Check Intermediate Casing				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
7.625	940	558	6700	9460
Safety Factors				
2.31	2.15	2.19	1.26	1.16
Check Prod Casing, Segment A				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
5.777	728	655	12780	14360
Safety Factors				
1.36	2.90	2.61	1.64	1.76
Check Prod Casing, Segment B				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
5.777	728	655	12780	14360
Safety Factors				
1.36	69.20	62.26	1.57	1.76

H₂S Drilling Operation Plan

1. **All Company and Contract personnel admitted on location must be trained by a qualified H₂S safety instructor to the following:**
 - a. Characteristics of H₂S
 - b. Physical effects and hazards
 - c. Principal and operation of H₂S detectors, warning system and briefing areas
 - d. Evacuation procedure, routes and first aid
 - e. Proper use of safety equipment and life support systems
 - f. Essential personnel meeting Medical Evaluation criteria will receive additional training on the proper use of 30 minute pressure demand air packs.
2. **Briefing Area:**
 - a. Two perpendicular areas will be designated by signs and readily accessible.
 - b. Upon location entry there will be a designated area to establish all safety compliance criteria (1.) has been met.
3. **H₂S Detection and Alarm Systems:**
 - a. H₂S sensors/detectors shall be located on the drilling rig floor, in the base of the sub structure/cellar area, and on the mud pits in the shale shaker area. Additional H₂S detectors may be placed as deemed necessary. All detectors will be set to initiate visual alarm at 10 ppm and visual with audible at 14 ppm and all equipment will be calibrated every 30 days or as needed.
 - b. An audio alarm will be installed on the derrick floor and in the top doghouse.
4. **Protective Equipment for Essential Personnel:**
 - a. **Breathing Apparatus:**
 - i. Rescue Packs (SCBA) - 1 Unit shall be placed at each briefing area.
 - ii. Two (SCBA) Units will be stored in safety trailer on location.
 - iii. Work/Escapes packs - 1 Unit will be available on rig floor in doghouse for emergency evacuation for driller.
 - b. **Auxiliary Rescue Equipment:**
 - i. Stretcher
 - ii. 2 - OSHA full body harnesses
 - iii. 100 ft. 5/8" OSHA approved rope
 - iv. 1 - 20# class ABC fire extinguisher
5. **Windsock and/or Wind Streamers:**
 - a. Windsock at mud pit area should be high enough to be visible.
 - b. Windsock on the rig floor should be high enough to be visible.
6. **Communication:**
 - a. While working under mask scripting boards will be used for communication where applicable.
 - b. Hand signals will be used when script boards are not applicable.

H₂S Drilling Operation Plan

- c. Two way radios will be used to communicate off location in case of emergency help is required. In most cases cellular telephones will be available at Drilling Foreman's Office.

7. **Drill Stem Testing:** - No Planned DST at this time.

8. **Mud program:**

- a. If H₂S is encountered, mud system will be altered if necessary to maintain control of formation. A mud gas separator will be brought into service along with H₂S scavengers if necessary.

9. **Metallurgy:**

- a. All drill strings, casing, tubing, wellhead, blowout preventer, drilling spool, kill lines, choke manifold and lines, and valves shall be suitable for H₂S service.
- b. Drilling Contractor supervisor will be required to be familiar with the effect H₂S has on tubular goods and other mechanical equipment provided through contractor.

H₂S Contingency Plan

Emergency Procedures

In the event of a release of H₂S, the first responder(s) must:

- Isolate the area and prevent entry by other persons into the 100 ppm ROE.
- Evacuate any public places encompassed by the 100 ppm ROE.
- Be equipped with H₂S monitors and air packs in order to control the release.
- Use the "buddy system" to ensure no injuries occur during the response.
- Take precautions to avoid personal injury during this operation.
- Contact Operator and/or local officials the aid in operation. See list of phone numbers attached.
- Have received training in the:
 - Detection of H₂S and
 - Measures for protection against the gas,
 - Equipment used for protection and emergency response.

Ignition of Gas Source

Should control of the well be considered lost and ignition considered, take care to protect against exposure to Sulfur Dioxide (SO₂). Intentional ignition must be coordinated with the NMOCD and local officials. Additionally, the NM State Police may become involved. NM State Police shall be the Incident Command on scene of any major release. Take care to protect downwind whenever there is an ignition of the gas.

Characteristics of H₂S and SO₂

Common Name	Chemical Formula	Specific Gravity	Threshold Limit	Hazardous Limit	Lethal Concentration
Hydrogen Sulfide	H ₂ S	1.189 Air=1	10 ppm	100 ppm/hr	600 ppm
Sulfur Dioxide	SO ₂	2.21 Air=1	2 ppm	N/A	1000 ppm

Contacting Authorities

Ameredev Operating LLC personnel must liaise with local and state agencies to ensure a proper response to a major release. Additionally, the OCD must be notified of the release as soon as possible but no later than 4 hours. Agencies will ask for information such as type and volume of release, wind direction, location of release, etc. Be prepared with all information available including direction to site. The following call list of essential and potential responders has been prepared for use during a release. Ameredev Operating LLC's response must be in coordination with the State of New Mexico's "Hazardous Materials Emergency Response Plan" (HMER)

H₂S Contingency Plan

Ameredev Operating LLC – Emergency Phone 737-300-4799			
Key Personnel:			
Name	Title	Office	Mobile
Floyd Hammond	Chief Operating officer	737-300-4724	512-783-6810
Zachary Boyd	Operations Superintendent	737-300-4725	432-385-6996
Blake Estrada	Construction Foreman		432-385-5831

<u>Artesia</u>			
Ambulance			911
State Police			575-746-2703
City Police			575-746-2703
Sheriff's Office			575-746-9888
Fire Department			575-746-2701
Local Emergency Planning Committee			575-746-2122
New Mexico Oil Conservation Division			575-748-1283
<u>Carlsbad</u>			
Ambulance			911
State Police			575-885-3137
City Police			575-885-2111
Sheriff's Office			575-887-7551
Fire Department			575-887-3798
Local Emergency Planning Committee			575-887-6544
US Bureau of Land Management			575-887-6544
<u>Santa Fe</u>			
New Mexico Emergency Response Commission (Santa Fe)			505-476-9600
New Mexico Emergency Response Commission (Santa Fe) 24 Hrs			505-827-9126
New Mexico State Emergency Operations Center			505-476-9635
<u>National</u>			
National Emergency Response Center (Washington, D.C.)			800-424-8802
<u>Medical</u>			
Flight for Life - 4000 24th St.; Lubbock, TX			806-743-9911
Aerocare - R3, Box 49F; Lubbock, TX			806-747-8923
Med Flight Air Amb - 2301 Yale Blvd S.E., #D3; Albuquerque, NM			505-842-4433
.SB Air Med Service - 2505 Clark Carr Loop S.E.; Albuquerque, NM			505-842-4949



Ameredev Operating, LLC.

CAM/AZ

CAM/AZ #1N

Camellia 121H

Wellbore #1

Plan: Design #1

Standard Planning Report

16 January, 2019

Database: EDM5000
Company: Ameredev Operating, LLC.
Project: CAM/AZ
Site: CAM/AZ #1N
Well: Camellia 121H
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well Camellia 121H
TVD Reference: KB @ 2951.0usft
MD Reference: KB @ 2951.0usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature

Project	CAM/AZ		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	New Mexico Eastern Zone		

Site	CAM/AZ #1N		
Site Position:		Northing:	373,448.30 usft
From:	Lat/Long	Easting:	868,493.74 usft
Position Uncertainty:	0.0 usft	Slot Radius:	13-3/16 "
		Latitude:	32° 1' 20.266 N
		Longitude:	103° 16' 39.795 W
		Grid Convergence:	0.56 °

Well	Camellia 121H		
Well Position	+N-S	0.0 usft	Northing:
	+E-W	0.0 usft	Easting:
Position Uncertainty	0.0 usft	Wellhead Elevation:	
		Latitude:	32° 1' 20.266 N
		Longitude:	103° 16' 39.795 W
		Ground Level:	2,924.0 usft

Wellbore	Wellbore #1		
Magnetics	Model Name	Sample Date	Declination
			(°)
	IGRF2015	1/11/2019	6.63
			Dip Angle
			(°)
			59.90
			Field Strength
			(nT)
			47,691.06803742

Design	Design #1		
Audit Notes:			
Version:	Phase:	PROTOTYPE	Tie On Depth:
			0.0
Vertical Section:	Depth From (TVD)	+N-S	+E-W
	(usft)	(usft)	(usft)
	0.0	0.0	0.0
			Direction
			(°)
			359.02

Plan Survey Tool Program	Date 1/16/2019		
Depth From	Depth To	Survey (Wellbore)	Tool Name
(usft)	(usft)		
1	0.0	23,283.4 Design #1 (Wellbore #1)	MWD
			OWSG MWD - Standard
			Remarks

Database: EDM5000
Company: Ameredev Operating, LLC.
Project: CAM/AZ
Site: CAM/AZ #1N
Well: Camellia 121H
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well Camellia 121H
TVD Reference: KB @ 2951.0usft
MD Reference: KB @ 2951.0usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature

Plan Sections

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
2,000.0	0.00	0.00	2,000.0	0.0	0.0	0.00	0.00	0.00	0.00	
2,300.0	6.00	180.00	2,299.5	-15.7	0.0	2.00	2.00	0.00	180.00	
6,724.8	6.00	180.00	6,700.0	-478.2	0.0	0.00	0.00	0.00	0.00	
7,024.8	0.00	0.00	6,999.5	-493.9	0.0	2.00	-2.00	0.00	180.00	
8,525.3	0.00	0.00	8,500.0	-493.9	0.0	0.00	0.00	0.00	0.00	
8,825.3	6.00	180.00	8,799.5	-509.6	0.0	2.00	2.00	0.00	180.00	
10,133.0	6.00	180.00	10,100.0	-646.3	0.0	0.00	0.00	0.00	0.00	
10,433.0	0.00	0.00	10,399.5	-662.0	0.0	2.00	-2.00	0.00	180.00	
12,033.6	0.00	0.00	12,000.0	-662.0	0.0	0.00	0.00	0.00	0.00	
12,094.7	7.29	248.11	12,061.0	-663.4	-3.6	11.93	11.93	0.00	248.11	
12,871.5	90.00	359.42	12,560.0	-184.1	-68.0	11.93	10.65	14.33	111.14	Cam121 FTP
23,283.4	90.00	359.42	12,560.0	10,227.1	-174.3	0.00	0.00	0.00	0.00	Cam121 BHL

Database: EDM5000
Company: Ameredev Operating, LLC.
Project: CAM/AZ
Site: CAM/AZ #1N
Well: Camellia 121H
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well Camellia 121H
TVD Reference: KB @ 2951.0usft
MD Reference: KB @ 2951.0usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00
300.0	0.00	0.00	300.0	0.0	0.0	0.0	0.00	0.00	0.00
400.0	0.00	0.00	400.0	0.0	0.0	0.0	0.00	0.00	0.00
500.0	0.00	0.00	500.0	0.0	0.0	0.0	0.00	0.00	0.00
600.0	0.00	0.00	600.0	0.0	0.0	0.0	0.00	0.00	0.00
700.0	0.00	0.00	700.0	0.0	0.0	0.0	0.00	0.00	0.00
800.0	0.00	0.00	800.0	0.0	0.0	0.0	0.00	0.00	0.00
900.0	0.00	0.00	900.0	0.0	0.0	0.0	0.00	0.00	0.00
1,000.0	0.00	0.00	1,000.0	0.0	0.0	0.0	0.00	0.00	0.00
1,100.0	0.00	0.00	1,100.0	0.0	0.0	0.0	0.00	0.00	0.00
1,200.0	0.00	0.00	1,200.0	0.0	0.0	0.0	0.00	0.00	0.00
1,300.0	0.00	0.00	1,300.0	0.0	0.0	0.0	0.00	0.00	0.00
1,400.0	0.00	0.00	1,400.0	0.0	0.0	0.0	0.00	0.00	0.00
1,500.0	0.00	0.00	1,500.0	0.0	0.0	0.0	0.00	0.00	0.00
1,600.0	0.00	0.00	1,600.0	0.0	0.0	0.0	0.00	0.00	0.00
1,700.0	0.00	0.00	1,700.0	0.0	0.0	0.0	0.00	0.00	0.00
1,800.0	0.00	0.00	1,800.0	0.0	0.0	0.0	0.00	0.00	0.00
1,900.0	0.00	0.00	1,900.0	0.0	0.0	0.0	0.00	0.00	0.00
2,000.0	0.00	0.00	2,000.0	0.0	0.0	0.0	0.00	0.00	0.00
2,100.0	2.00	180.00	2,100.0	-1.7	0.0	-1.7	2.00	2.00	0.00
2,200.0	4.00	180.00	2,199.8	-7.0	0.0	-7.0	2.00	2.00	0.00
2,300.0	6.00	180.00	2,299.5	-15.7	0.0	-15.7	2.00	2.00	0.00
2,400.0	6.00	180.00	2,398.9	-26.1	0.0	-26.1	0.00	0.00	0.00
2,500.0	6.00	180.00	2,498.4	-36.6	0.0	-36.6	0.00	0.00	0.00
2,600.0	6.00	180.00	2,597.8	-47.1	0.0	-47.0	0.00	0.00	0.00
2,700.0	6.00	180.00	2,697.3	-57.5	0.0	-57.5	0.00	0.00	0.00
2,800.0	6.00	180.00	2,796.7	-68.0	0.0	-67.9	0.00	0.00	0.00
2,900.0	6.00	180.00	2,896.2	-78.4	0.0	-78.4	0.00	0.00	0.00
3,000.0	6.00	180.00	2,995.6	-88.9	0.0	-88.9	0.00	0.00	0.00
3,100.0	6.00	180.00	3,095.1	-99.3	0.0	-99.3	0.00	0.00	0.00
3,200.0	6.00	180.00	3,194.5	-109.8	0.0	-109.8	0.00	0.00	0.00
3,300.0	6.00	180.00	3,294.0	-120.2	0.0	-120.2	0.00	0.00	0.00
3,400.0	6.00	180.00	3,393.4	-130.7	0.0	-130.7	0.00	0.00	0.00
3,500.0	6.00	180.00	3,492.9	-141.1	0.0	-141.1	0.00	0.00	0.00
3,600.0	6.00	180.00	3,592.3	-151.6	0.0	-151.6	0.00	0.00	0.00
3,700.0	6.00	180.00	3,691.8	-162.0	0.0	-162.0	0.00	0.00	0.00
3,800.0	6.00	180.00	3,791.2	-172.5	0.0	-172.5	0.00	0.00	0.00
3,900.0	6.00	180.00	3,890.7	-182.9	0.0	-182.9	0.00	0.00	0.00
4,000.0	6.00	180.00	3,990.1	-193.4	0.0	-193.4	0.00	0.00	0.00
4,100.0	6.00	180.00	4,089.6	-203.8	0.0	-203.8	0.00	0.00	0.00
4,200.0	6.00	180.00	4,189.0	-214.3	0.0	-214.3	0.00	0.00	0.00
4,300.0	6.00	180.00	4,288.5	-224.8	0.0	-224.7	0.00	0.00	0.00
4,400.0	6.00	180.00	4,387.9	-235.2	0.0	-235.2	0.00	0.00	0.00
4,500.0	6.00	180.00	4,487.4	-245.7	0.0	-245.6	0.00	0.00	0.00
4,600.0	6.00	180.00	4,586.9	-256.1	0.0	-256.1	0.00	0.00	0.00
4,700.0	6.00	180.00	4,686.3	-266.6	0.0	-266.5	0.00	0.00	0.00
4,800.0	6.00	180.00	4,785.8	-277.0	0.0	-277.0	0.00	0.00	0.00
4,900.0	6.00	180.00	4,885.2	-287.5	0.0	-287.4	0.00	0.00	0.00
5,000.0	6.00	180.00	4,984.7	-297.9	0.0	-297.9	0.00	0.00	0.00
5,100.0	6.00	180.00	5,084.1	-308.4	0.0	-308.3	0.00	0.00	0.00
5,200.0	6.00	180.00	5,183.6	-318.8	0.0	-318.8	0.00	0.00	0.00
5,300.0	6.00	180.00	5,283.0	-329.3	0.0	-329.2	0.00	0.00	0.00

Database: EDM5000
 Company: Ameredev Operating, LLC.
 Project: CAM/AZ
 Site: CAM/AZ #1N
 Well: Camellia 121H
 Wellbore: Wellbore #1
 Design: Design #1

Local Co-ordinate Reference: Well Camellia 121H
 TVD Reference: KB @ 2951.0usft
 MD Reference: KB @ 2951.0usft
 North Reference: Grid
 Survey Calculation Method: Minimum Curvature

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
5,400.0	6.00	180.00	5,382.5	-339.7	0.0	-339.7	0.00	0.00	0.00
5,500.0	6.00	180.00	5,481.9	-350.2	0.0	-350.1	0.00	0.00	0.00
5,600.0	6.00	180.00	5,581.4	-360.6	0.0	-360.6	0.00	0.00	0.00
5,700.0	6.00	180.00	5,680.8	-371.1	0.0	-371.0	0.00	0.00	0.00
5,800.0	6.00	180.00	5,780.3	-381.5	0.0	-381.5	0.00	0.00	0.00
5,900.0	6.00	180.00	5,879.7	-392.0	0.0	-391.9	0.00	0.00	0.00
6,000.0	6.00	180.00	5,979.2	-402.4	0.0	-402.4	0.00	0.00	0.00
6,100.0	6.00	180.00	6,078.6	-412.9	0.0	-412.8	0.00	0.00	0.00
6,200.0	6.00	180.00	6,178.1	-423.4	0.0	-423.3	0.00	0.00	0.00
6,300.0	6.00	180.00	6,277.5	-433.8	0.0	-433.7	0.00	0.00	0.00
6,400.0	6.00	180.00	6,377.0	-444.3	0.0	-444.2	0.00	0.00	0.00
6,500.0	6.00	180.00	6,476.4	-454.7	0.0	-454.6	0.00	0.00	0.00
6,600.0	6.00	180.00	6,575.9	-465.2	0.0	-465.1	0.00	0.00	0.00
6,700.0	6.00	180.00	6,675.3	-475.6	0.0	-475.5	0.00	0.00	0.00
6,724.8	6.00	180.00	6,700.0	-478.2	0.0	-478.1	0.00	0.00	0.00
6,800.0	4.50	180.00	6,774.9	-485.1	0.0	-485.0	2.00	-2.00	0.00
6,900.0	2.50	180.00	6,874.7	-491.2	0.0	-491.1	2.00	-2.00	0.00
7,000.0	0.50	180.00	6,974.7	-493.8	0.0	-493.7	2.00	-2.00	0.00
7,024.8	0.00	0.00	6,999.5	-493.9	0.0	-493.8	2.00	-2.00	0.00
7,100.0	0.00	0.00	7,074.7	-493.9	0.0	-493.8	0.00	0.00	0.00
7,200.0	0.00	0.00	7,174.7	-493.9	0.0	-493.8	0.00	0.00	0.00
7,300.0	0.00	0.00	7,274.7	-493.9	0.0	-493.8	0.00	0.00	0.00
7,400.0	0.00	0.00	7,374.7	-493.9	0.0	-493.8	0.00	0.00	0.00
7,500.0	0.00	0.00	7,474.7	-493.9	0.0	-493.8	0.00	0.00	0.00
7,600.0	0.00	0.00	7,574.7	-493.9	0.0	-493.8	0.00	0.00	0.00
7,700.0	0.00	0.00	7,674.7	-493.9	0.0	-493.8	0.00	0.00	0.00
7,800.0	0.00	0.00	7,774.7	-493.9	0.0	-493.8	0.00	0.00	0.00
7,900.0	0.00	0.00	7,874.7	-493.9	0.0	-493.8	0.00	0.00	0.00
8,000.0	0.00	0.00	7,974.7	-493.9	0.0	-493.8	0.00	0.00	0.00
8,100.0	0.00	0.00	8,074.7	-493.9	0.0	-493.8	0.00	0.00	0.00
8,200.0	0.00	0.00	8,174.7	-493.9	0.0	-493.8	0.00	0.00	0.00
8,300.0	0.00	0.00	8,274.7	-493.9	0.0	-493.8	0.00	0.00	0.00
8,400.0	0.00	0.00	8,374.7	-493.9	0.0	-493.8	0.00	0.00	0.00
8,500.0	0.00	0.00	8,474.7	-493.9	0.0	-493.8	0.00	0.00	0.00
8,525.3	0.00	0.00	8,500.0	-493.9	0.0	-493.8	0.00	0.00	0.00
8,600.0	1.49	180.00	8,574.7	-494.9	0.0	-494.8	2.00	2.00	0.00
8,700.0	3.49	180.00	8,674.6	-499.2	0.0	-499.2	2.00	2.00	0.00
8,800.0	5.49	180.00	8,774.2	-507.1	0.0	-507.0	2.00	2.00	0.00
8,825.3	6.00	180.00	8,799.5	-509.6	0.0	-509.5	2.00	2.00	0.00
8,900.0	6.00	180.00	8,873.7	-517.4	0.0	-517.3	0.00	0.00	0.00
9,000.0	6.00	180.00	8,973.2	-527.9	0.0	-527.8	0.00	0.00	0.00
9,100.0	6.00	180.00	9,072.6	-538.3	0.0	-538.2	0.00	0.00	0.00
9,200.0	6.00	180.00	9,172.1	-548.8	0.0	-548.7	0.00	0.00	0.00
9,300.0	6.00	180.00	9,271.5	-559.2	0.0	-559.1	0.00	0.00	0.00
9,400.0	6.00	180.00	9,371.0	-569.7	0.0	-569.6	0.00	0.00	0.00
9,500.0	6.00	180.00	9,470.4	-580.1	0.0	-580.0	0.00	0.00	0.00
9,600.0	6.00	180.00	9,569.9	-590.6	0.0	-590.5	0.00	0.00	0.00
9,700.0	6.00	180.00	9,669.3	-601.0	0.0	-600.9	0.00	0.00	0.00
9,800.0	6.00	180.00	9,768.8	-611.5	0.0	-611.4	0.00	0.00	0.00
9,900.0	6.00	180.00	9,868.2	-621.9	0.0	-621.8	0.00	0.00	0.00
10,000.0	6.00	180.00	9,967.7	-632.4	0.0	-632.3	0.00	0.00	0.00
10,100.0	6.00	180.00	10,067.1	-642.8	0.0	-642.7	0.00	0.00	0.00
10,133.0	6.00	180.00	10,100.0	-646.3	0.0	-646.2	0.00	0.00	0.00
10,200.0	4.66	180.00	10,166.7	-652.5	0.0	-652.4	2.00	-2.00	0.00

Database: EDM5000
Company: Ameredev Operating, LLC.
Project: CAM/AZ
Site: CAM/AZ #1N
Well: Camellia 121H
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well Camellia 121H
TVD Reference: KB @ 2951.0usft
MD Reference: KB @ 2951.0usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
10,300.0	2.66	180.00	10,266.5	-658.9	0.0	-658.8	2.00	-2.00	0.00
10,400.0	0.66	180.00	10,366.4	-661.8	0.0	-661.7	2.00	-2.00	0.00
Sec 28									
10,433.0	0.00	0.00	10,399.5	-662.0	0.0	-661.9	2.00	-2.00	0.00
10,500.0	0.00	0.00	10,466.4	-662.0	0.0	-661.9	0.00	0.00	0.00
10,600.0	0.00	0.00	10,566.4	-662.0	0.0	-661.9	0.00	0.00	0.00
10,700.0	0.00	0.00	10,666.4	-662.0	0.0	-661.9	0.00	0.00	0.00
10,800.0	0.00	0.00	10,766.4	-662.0	0.0	-661.9	0.00	0.00	0.00
10,900.0	0.00	0.00	10,866.4	-662.0	0.0	-661.9	0.00	0.00	0.00
11,000.0	0.00	0.00	10,966.4	-662.0	0.0	-661.9	0.00	0.00	0.00
11,100.0	0.00	0.00	11,066.4	-662.0	0.0	-661.9	0.00	0.00	0.00
11,200.0	0.00	0.00	11,166.4	-662.0	0.0	-661.9	0.00	0.00	0.00
11,300.0	0.00	0.00	11,266.4	-662.0	0.0	-661.9	0.00	0.00	0.00
11,400.0	0.00	0.00	11,366.4	-662.0	0.0	-661.9	0.00	0.00	0.00
11,500.0	0.00	0.00	11,466.4	-662.0	0.0	-661.9	0.00	0.00	0.00
11,600.0	0.00	0.00	11,566.4	-662.0	0.0	-661.9	0.00	0.00	0.00
11,700.0	0.00	0.00	11,666.4	-662.0	0.0	-661.9	0.00	0.00	0.00
11,800.0	0.00	0.00	11,766.4	-662.0	0.0	-661.9	0.00	0.00	0.00
11,800.6	0.00	0.00	11,767.0	-662.0	0.0	-661.9	0.00	0.00	0.00
Sec 21									
11,900.0	0.00	0.00	11,866.4	-662.0	0.0	-661.9	0.00	0.00	0.00
12,000.0	0.00	0.00	11,966.4	-662.0	0.0	-661.9	0.00	0.00	0.00
12,033.6	0.00	0.00	12,000.0	-662.0	0.0	-661.9	0.00	0.00	0.00
12,094.7	7.29	248.11	12,061.0	-663.4	-3.6	-663.3	11.93	11.93	0.00
12,100.0	7.09	252.88	12,066.2	-663.7	-4.2	-663.5	11.93	-3.84	90.26
12,200.0	12.00	325.31	12,165.1	-656.9	-16.1	-656.5	11.93	4.91	72.43
12,300.0	22.82	342.96	12,260.4	-629.7	-27.7	-629.1	11.93	10.82	17.65
12,400.0	34.36	349.38	12,348.1	-583.3	-38.6	-582.5	11.93	11.54	6.41
12,500.0	46.08	352.83	12,424.3	-519.5	-48.4	-518.7	11.93	11.72	3.45
12,600.0	57.87	355.12	12,485.8	-441.3	-56.5	-440.3	11.93	11.79	2.30
12,700.0	69.69	356.89	12,529.9	-352.0	-62.7	-350.9	11.93	11.82	1.76
12,800.0	81.53	358.40	12,554.7	-255.4	-66.6	-254.2	11.93	11.84	1.51
12,871.5	90.00	359.42	12,560.0	-184.1	-68.0	-183.0	11.93	11.84	1.42
Cam121 FTP									
12,900.0	90.00	359.42	12,560.0	-155.7	-68.3	-154.5	0.00	0.00	0.00
13,000.0	90.00	359.42	12,560.0	-55.7	-69.3	-54.5	0.00	0.00	0.00
13,100.0	90.00	359.42	12,560.0	44.3	-70.3	45.5	0.00	0.00	0.00
13,200.0	90.00	359.42	12,560.0	144.3	-71.3	145.5	0.00	0.00	0.00
13,300.0	90.00	359.42	12,560.0	244.3	-72.3	245.5	0.00	0.00	0.00
13,400.0	90.00	359.42	12,560.0	344.3	-73.4	345.5	0.00	0.00	0.00
13,500.0	90.00	359.42	12,560.0	444.3	-74.4	445.5	0.00	0.00	0.00
13,600.0	90.00	359.42	12,560.0	544.3	-75.4	545.5	0.00	0.00	0.00
13,700.0	90.00	359.42	12,560.0	644.3	-76.4	645.5	0.00	0.00	0.00
13,800.0	90.00	359.42	12,560.0	744.3	-77.5	745.5	0.00	0.00	0.00
13,900.0	90.00	359.42	12,560.0	844.3	-78.5	845.5	0.00	0.00	0.00
14,000.0	90.00	359.42	12,560.0	944.3	-79.5	945.5	0.00	0.00	0.00
14,100.0	90.00	359.42	12,560.0	1,044.3	-80.5	1,045.5	0.00	0.00	0.00
14,200.0	90.00	359.42	12,560.0	1,144.3	-81.5	1,145.5	0.00	0.00	0.00
14,300.0	90.00	359.42	12,560.0	1,244.3	-82.6	1,245.5	0.00	0.00	0.00
14,400.0	90.00	359.42	12,560.0	1,344.2	-83.6	1,345.5	0.00	0.00	0.00
14,500.0	90.00	359.42	12,560.0	1,444.2	-84.6	1,445.5	0.00	0.00	0.00
14,600.0	90.00	359.42	12,560.0	1,544.2	-85.6	1,545.5	0.00	0.00	0.00
14,700.0	90.00	359.42	12,560.0	1,644.2	-86.6	1,645.5	0.00	0.00	0.00

Database: EDM5000
Company: Ameredev Operating, LLC.
Project: CAM/AZ
Site: CAM/AZ #1N
Well: Camellia 121H
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well Camellia 121H
TVD Reference: KB @ 2951.0usft
MD Reference: KB @ 2951.0usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
14,800.0	90.00	359.42	12,560.0	1,744.2	-87.7	1,745.5	0.00	0.00	0.00
14,900.0	90.00	359.42	12,560.0	1,844.2	-88.7	1,845.5	0.00	0.00	0.00
15,000.0	90.00	359.42	12,560.0	1,944.2	-89.7	1,945.5	0.00	0.00	0.00
15,100.0	90.00	359.42	12,560.0	2,044.2	-90.7	2,045.5	0.00	0.00	0.00
15,200.0	90.00	359.42	12,560.0	2,144.2	-91.7	2,145.5	0.00	0.00	0.00
15,300.0	90.00	359.42	12,560.0	2,244.2	-92.8	2,245.5	0.00	0.00	0.00
15,400.0	90.00	359.42	12,560.0	2,344.2	-93.8	2,345.5	0.00	0.00	0.00
15,500.0	90.00	359.42	12,560.0	2,444.2	-94.8	2,445.5	0.00	0.00	0.00
15,600.0	90.00	359.42	12,560.0	2,544.2	-95.8	2,545.5	0.00	0.00	0.00
15,700.0	90.00	359.42	12,560.0	2,644.2	-96.9	2,645.4	0.00	0.00	0.00
15,800.0	90.00	359.42	12,560.0	2,744.2	-97.9	2,745.4	0.00	0.00	0.00
15,900.0	90.00	359.42	12,560.0	2,844.2	-98.9	2,845.4	0.00	0.00	0.00
16,000.0	90.00	359.42	12,560.0	2,944.2	-99.9	2,945.4	0.00	0.00	0.00
16,100.0	90.00	359.42	12,560.0	3,044.2	-100.9	3,045.4	0.00	0.00	0.00
16,200.0	90.00	359.42	12,560.0	3,144.2	-102.0	3,145.4	0.00	0.00	0.00
16,300.0	90.00	359.42	12,560.0	3,244.2	-103.0	3,245.4	0.00	0.00	0.00
16,400.0	90.00	359.42	12,560.0	3,344.1	-104.0	3,345.4	0.00	0.00	0.00
16,500.0	90.00	359.42	12,560.0	3,444.1	-105.0	3,445.4	0.00	0.00	0.00
16,600.0	90.00	359.42	12,560.0	3,544.1	-106.0	3,545.4	0.00	0.00	0.00
16,700.0	90.00	359.42	12,560.0	3,644.1	-107.1	3,645.4	0.00	0.00	0.00
16,800.0	90.00	359.42	12,560.0	3,744.1	-108.1	3,745.4	0.00	0.00	0.00
16,900.0	90.00	359.42	12,560.0	3,844.1	-109.1	3,845.4	0.00	0.00	0.00
17,000.0	90.00	359.42	12,560.0	3,944.1	-110.1	3,945.4	0.00	0.00	0.00
17,100.0	90.00	359.42	12,560.0	4,044.1	-111.1	4,045.4	0.00	0.00	0.00
17,200.0	90.00	359.42	12,560.0	4,144.1	-112.2	4,145.4	0.00	0.00	0.00
17,300.0	90.00	359.42	12,560.0	4,244.1	-113.2	4,245.4	0.00	0.00	0.00
17,400.0	90.00	359.42	12,560.0	4,344.1	-114.2	4,345.4	0.00	0.00	0.00
17,500.0	90.00	359.42	12,560.0	4,444.1	-115.2	4,445.4	0.00	0.00	0.00
17,600.0	90.00	359.42	12,560.0	4,544.1	-116.2	4,545.4	0.00	0.00	0.00
17,700.0	90.00	359.42	12,560.0	4,644.1	-117.3	4,645.4	0.00	0.00	0.00
17,800.0	90.00	359.42	12,560.0	4,744.1	-118.3	4,745.4	0.00	0.00	0.00
17,900.0	90.00	359.42	12,560.0	4,844.1	-119.3	4,845.4	0.00	0.00	0.00
18,000.0	90.00	359.42	12,560.0	4,944.1	-120.3	4,945.4	0.00	0.00	0.00
18,053.2	90.00	359.42	12,560.0	4,997.2	-120.9	4,998.5	0.00	0.00	0.00
Sec 16									
18,100.0	90.00	359.42	12,560.0	5,044.1	-121.4	5,045.4	0.00	0.00	0.00
18,200.0	90.00	359.42	12,560.0	5,144.1	-122.4	5,145.4	0.00	0.00	0.00
18,300.0	90.00	359.42	12,560.0	5,244.0	-123.4	5,245.4	0.00	0.00	0.00
18,400.0	90.00	359.42	12,560.0	5,344.0	-124.4	5,345.4	0.00	0.00	0.00
18,500.0	90.00	359.42	12,560.0	5,444.0	-125.4	5,445.4	0.00	0.00	0.00
18,600.0	90.00	359.42	12,560.0	5,544.0	-126.5	5,545.4	0.00	0.00	0.00
18,700.0	90.00	359.42	12,560.0	5,644.0	-127.5	5,645.4	0.00	0.00	0.00
18,800.0	90.00	359.42	12,560.0	5,744.0	-128.5	5,745.4	0.00	0.00	0.00
18,900.0	90.00	359.42	12,560.0	5,844.0	-129.5	5,845.4	0.00	0.00	0.00
19,000.0	90.00	359.42	12,560.0	5,944.0	-130.5	5,945.4	0.00	0.00	0.00
19,100.0	90.00	359.42	12,560.0	6,044.0	-131.6	6,045.4	0.00	0.00	0.00
19,200.0	90.00	359.42	12,560.0	6,144.0	-132.6	6,145.4	0.00	0.00	0.00
19,300.0	90.00	359.42	12,560.0	6,244.0	-133.6	6,245.4	0.00	0.00	0.00
19,400.0	90.00	359.42	12,560.0	6,344.0	-134.6	6,345.4	0.00	0.00	0.00
19,500.0	90.00	359.42	12,560.0	6,444.0	-135.6	6,445.4	0.00	0.00	0.00
19,600.0	90.00	359.42	12,560.0	6,544.0	-136.7	6,545.4	0.00	0.00	0.00
19,700.0	90.00	359.42	12,560.0	6,644.0	-137.7	6,645.4	0.00	0.00	0.00
19,800.0	90.00	359.42	12,560.0	6,744.0	-138.7	6,745.4	0.00	0.00	0.00

Database: EDM5000
Company: Ameredev Operating, LLC.
Project: CAM/AZ
Site: CAM/AZ #1N
Well: Camellia 121H
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well Camellia 121H
TVD Reference: KB @ 2951.0usft
MD Reference: KB @ 2951.0usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
19,900.0	90.00	359.42	12,560.0	6,844.0	-139.7	6,845.3	0.00	0.00	0.00
20,000.0	90.00	359.42	12,560.0	6,944.0	-140.7	6,945.3	0.00	0.00	0.00
20,100.0	90.00	359.42	12,560.0	7,044.0	-141.8	7,045.3	0.00	0.00	0.00
20,200.0	90.00	359.42	12,560.0	7,143.9	-142.8	7,145.3	0.00	0.00	0.00
20,300.0	90.00	359.42	12,560.0	7,243.9	-143.8	7,245.3	0.00	0.00	0.00
20,400.0	90.00	359.42	12,560.0	7,343.9	-144.8	7,345.3	0.00	0.00	0.00
20,500.0	90.00	359.42	12,560.0	7,443.9	-145.9	7,445.3	0.00	0.00	0.00
20,600.0	90.00	359.42	12,560.0	7,543.9	-146.9	7,545.3	0.00	0.00	0.00
20,700.0	90.00	359.42	12,560.0	7,643.9	-147.9	7,645.3	0.00	0.00	0.00
20,800.0	90.00	359.42	12,560.0	7,743.9	-148.9	7,745.3	0.00	0.00	0.00
20,900.0	90.00	359.42	12,560.0	7,843.9	-149.9	7,845.3	0.00	0.00	0.00
21,000.0	90.00	359.42	12,560.0	7,943.9	-151.0	7,945.3	0.00	0.00	0.00
21,100.0	90.00	359.42	12,560.0	8,043.9	-152.0	8,045.3	0.00	0.00	0.00
21,200.0	90.00	359.42	12,560.0	8,143.9	-153.0	8,145.3	0.00	0.00	0.00
21,300.0	90.00	359.42	12,560.0	8,243.9	-154.0	8,245.3	0.00	0.00	0.00
21,400.0	90.00	359.42	12,560.0	8,343.9	-155.0	8,345.3	0.00	0.00	0.00
21,500.0	90.00	359.42	12,560.0	8,443.9	-156.1	8,445.3	0.00	0.00	0.00
21,600.0	90.00	359.42	12,560.0	8,543.9	-157.1	8,545.3	0.00	0.00	0.00
21,700.0	90.00	359.42	12,560.0	8,643.9	-158.1	8,645.3	0.00	0.00	0.00
21,800.0	90.00	359.42	12,560.0	8,743.9	-159.1	8,745.3	0.00	0.00	0.00
21,900.0	90.00	359.42	12,560.0	8,843.9	-160.1	8,845.3	0.00	0.00	0.00
22,000.0	90.00	359.42	12,560.0	8,943.9	-161.2	8,945.3	0.00	0.00	0.00
22,100.0	90.00	359.42	12,560.0	9,043.8	-162.2	9,045.3	0.00	0.00	0.00
22,200.0	90.00	359.42	12,560.0	9,143.8	-163.2	9,145.3	0.00	0.00	0.00
22,300.0	90.00	359.42	12,560.0	9,243.8	-164.2	9,245.3	0.00	0.00	0.00
22,400.0	90.00	359.42	12,560.0	9,343.8	-165.3	9,345.3	0.00	0.00	0.00
22,500.0	90.00	359.42	12,560.0	9,443.8	-166.3	9,445.3	0.00	0.00	0.00
22,600.0	90.00	359.42	12,560.0	9,543.8	-167.3	9,545.3	0.00	0.00	0.00
22,700.0	90.00	359.42	12,560.0	9,643.8	-168.3	9,645.3	0.00	0.00	0.00
22,800.0	90.00	359.42	12,560.0	9,743.8	-169.3	9,745.3	0.00	0.00	0.00
22,900.0	90.00	359.42	12,560.0	9,843.8	-170.4	9,845.3	0.00	0.00	0.00
23,000.0	90.00	359.42	12,560.0	9,943.8	-171.4	9,945.3	0.00	0.00	0.00
23,100.0	90.00	359.42	12,560.0	10,043.8	-172.4	10,045.3	0.00	0.00	0.00
23,200.0	90.00	359.42	12,560.0	10,143.8	-173.4	10,145.3	0.00	0.00	0.00
Cam121 LTP									
23,283.4	90.00	359.42	12,560.0	10,227.1	-174.3	10,228.6	0.00	0.00	0.00
Cam121 BHL									

Database: EDM5000
 Company: Ameredev Operating, LLC.
 Project: CAM/AZ
 Site: CAM/AZ #1N
 Well: Camellia 121H
 Wellbore: Wellbore #1
 Design: Design #1

Local Co-ordinate Reference: Well Camellia 121H
 TVD Reference: KB @ 2951.0usft
 MD Reference: KB @ 2951.0usft
 North Reference: Grid
 Survey Calculation Method: Minimum Curvature

Design Targets

Target Name - hit/miss target - Shape	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
Sec 28	0.00	0.00	10,236.0	-5,570.2	-214.7	367,878.13	868,279.00	32° 0' 25.171 N	103° 16' 42.920 W
- plan misses target center by 4914.8usft at 10400.0usft MD (10366.4 TVD, -661.8 N, 0.0 E)									
- Polygon									
Point 1			10,236.0	0.0	0.0	367,878.13	868,279.00		
Point 2			10,236.0	5,283.8	-52.1	373,161.93	868,226.90		
Point 3			10,236.0	5,342.2	5,232.0	373,220.33	873,511.00		
Point 4			10,236.0	60.2	5,286.0	367,938.33	873,565.00		
Sec 21	0.00	0.00	11,767.0	-286.4	-266.9	373,161.95	868,226.87	32° 1' 17.458 N	103° 16' 42.927 W
- plan misses target center by 460.8usft at 11800.6usft MD (11767.0 TVD, -662.0 N, 0.0 E)									
- Polygon									
Point 1			11,767.0	0.0	0.0	373,161.95	868,226.87		
Point 2			11,767.0	5,281.5	-54.5	378,443.45	868,172.37		
Point 3			11,767.0	5,336.0	5,230.6	378,497.95	873,457.47		
Point 4			11,767.0	58.4	5,284.2	373,220.35	873,511.07		
Sec 16	0.00	0.00	11,767.0	4,995.2	-321.4	378,443.47	868,172.36	32° 2' 9.723 N	103° 16' 42.961 W
- plan misses target center by 818.0usft at 18053.2usft MD (12560.0 TVD, 4997.2 N, -120.9 E)									
- Polygon									
Point 1			11,767.0	0.0	0.0	378,443.47	868,172.36		
Point 2			11,767.0	5,280.0	-53.4	383,723.47	868,118.96		
Point 3			11,767.0	5,332.5	5,230.8	383,775.97	873,403.16		
Point 4			11,767.0	54.4	5,285.1	378,497.87	873,457.46		
Cam121 LTP	0.00	0.00	12,560.0	10,177.2	-173.8	383,625.46	868,319.96	32° 3' 0.982 N	103° 16' 40.658 W
- plan misses target center by 33.4usft at 23200.0usft MD (12560.0 TVD, 10143.8 N, -173.4 E)									
- Point									
Cam121 BHL	0.00	0.00	12,560.0	10,227.1	-174.3	383,675.45	868,319.47	32° 3' 1.477 N	103° 16' 40.658 W
- plan hits target center									
- Point									
Cam121 FTP	0.00	0.00	12,560.0	-184.1	-68.0	373,264.16	868,425.77	32° 1' 18.450 N	103° 16' 40.605 W
- plan hits target center									
- Point									

AMEREDEV

Ameredev Operating, LLC.

CAM/AZ

CAM/AZ #1N

Camellia 121H

Wellbore #1

Plan: Design #1

Lease Penetration Section Line Footages

16 January, 2019

Company: Ameredev Operating, LLC.
Project: CAM/AZ
Site: CAM/AZ #1N
Well: Camellia 121H
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well Camellia 121H
TVD Reference: KB @ 2951.0usft
MD Reference: KB @ 2951.0usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: EDM5000

Project CAM/AZ

Map System: US State Plane 1983
Geo Datum: North American Datum 1983
Map Zone: New Mexico Eastern Zone

System Datum: Mean Sea Level

Site CAM/AZ #1N

Site Position:		Northing:	373,448.30 usft	Latitude:	32° 1' 20.266 N
From:	Lat/Long	Easting:	868,493.74 usft	Longitude:	103° 16' 39.795 W
Position Uncertainty:	0.0 usft	Slot Radius:	13-3/16 "	Grid Convergence:	0.56 °

Well Camellia 121H

Well Position	+N-S	0.0 usft	Northing:	373,448.30 usft	Latitude:	32° 1' 20.266 N
	+E-W	0.0 usft	Easting:	868,493.74 usft	Longitude:	103° 16' 39.795 W
Position Uncertainty		0.0 usft	Wellhead Elevation:	usft	Ground Level:	2,924.0 usft

Wellbore Wellbore #1

Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2015	1/11/2019	6.63	59.90	47,691.06803742

Design Design #1

Audit Notes:

Version:	Phase:	PROTOTYPE	Tie On Depth:	0.0
Vertical Section:	Depth From (TVD) (usft)	+N-S (usft)	+E-W (usft)	Direction (°)
	0.0	0.0	0.0	359.02

Survey Tool Program Date 1/16/2019

From (usft)	To (usft)	Survey (Wellbore)	Tool Name	Description
0.0	23,283.4	Design #1 (Wellbore #1)	MWD	OWSG MWD - Standard



Ameredev Operating, LLC
Lease Penetration Section Line Footages

Company: Ameredev Operating, LLC.
Project: CAM/AZ
Site: CAM/AZ #1N
Well: Camellia 121H
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well Camellia 121H
TVD Reference: KB @ 2951.0usft
MD Reference: KB @ 2951.0usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: EDM5000

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	+FSL/-FNL (usft)	+FWL/-FEL (usft)	V. Sec (usft)	DLeg (°/100usft)	Build (°/100usft)	Turn (°/100usft)
0.0	0.00	0.00	0.0	283.0	270.0	0.0	0.00	0.00	0.00
100.0	0.00	0.00	100.0	283.0	270.0	0.0	0.00	0.00	0.00
200.0	0.00	0.00	200.0	283.0	270.0	0.0	0.00	0.00	0.00
300.0	0.00	0.00	300.0	283.0	270.0	0.0	0.00	0.00	0.00
400.0	0.00	0.00	400.0	283.0	270.0	0.0	0.00	0.00	0.00
500.0	0.00	0.00	500.0	283.0	270.0	0.0	0.00	0.00	0.00
600.0	0.00	0.00	600.0	283.0	270.0	0.0	0.00	0.00	0.00
700.0	0.00	0.00	700.0	283.0	270.0	0.0	0.00	0.00	0.00
800.0	0.00	0.00	800.0	283.0	270.0	0.0	0.00	0.00	0.00
900.0	0.00	0.00	900.0	283.0	270.0	0.0	0.00	0.00	0.00
1,000.0	0.00	0.00	1,000.0	283.0	270.0	0.0	0.00	0.00	0.00
1,100.0	0.00	0.00	1,100.0	283.0	270.0	0.0	0.00	0.00	0.00
1,200.0	0.00	0.00	1,200.0	283.0	270.0	0.0	0.00	0.00	0.00
1,300.0	0.00	0.00	1,300.0	283.0	270.0	0.0	0.00	0.00	0.00
1,400.0	0.00	0.00	1,400.0	283.0	270.0	0.0	0.00	0.00	0.00
1,500.0	0.00	0.00	1,500.0	283.0	270.0	0.0	0.00	0.00	0.00
1,600.0	0.00	0.00	1,600.0	283.0	270.0	0.0	0.00	0.00	0.00
1,700.0	0.00	0.00	1,700.0	283.0	270.0	0.0	0.00	0.00	0.00
1,800.0	0.00	0.00	1,800.0	283.0	270.0	0.0	0.00	0.00	0.00
1,900.0	0.00	0.00	1,900.0	283.0	270.0	0.0	0.00	0.00	0.00
2,000.0	0.00	0.00	2,000.0	283.0	270.0	0.0	0.00	0.00	0.00
2,100.0	2.00	180.00	2,100.0	281.3	270.0	-1.7	2.00	2.00	0.00
2,200.0	4.00	180.00	2,199.8	276.0	270.0	-7.0	2.00	2.00	0.00
2,300.0	6.00	180.00	2,299.5	267.3	270.0	-15.7	2.00	2.00	0.00
2,400.0	6.00	180.00	2,398.9	256.9	270.0	-26.1	0.00	0.00	0.00
2,500.0	6.00	180.00	2,498.4	246.4	270.0	-36.6	0.00	0.00	0.00
2,600.0	6.00	180.00	2,597.8	235.9	270.0	-47.0	0.00	0.00	0.00



Ameredev Operating, LLC
Lease Penetration Section Line Footages

Company: Ameredev Operating, LLC.
Project: CAM/AZ
Site: CAM/AZ #1N
Well: Camellia 121H
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well Camellia 121H
TVD Reference: KB @ 2951.0usft
MD Reference: KB @ 2951.0usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: EDM5000

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	+FSL/-FNL (usft)	+FWL/-FEL (usft)	V. Sec (usft)	DLeg (°/100usft)	Build (°/100usft)	Turn (°/100usft)
2,700.0	6.00	180.00	2,697.3	225.5	270.0	-57.5	0.00	0.00	0.00
2,800.0	6.00	180.00	2,796.7	215.0	270.0	-67.9	0.00	0.00	0.00
2,900.0	6.00	180.00	2,896.2	204.6	270.0	-78.4	0.00	0.00	0.00
3,000.0	6.00	180.00	2,995.6	194.1	270.0	-88.9	0.00	0.00	0.00
3,100.0	6.00	180.00	3,095.1	183.7	270.0	-99.3	0.00	0.00	0.00
3,200.0	6.00	180.00	3,194.5	173.2	270.0	-109.8	0.00	0.00	0.00
3,300.0	6.00	180.00	3,294.0	162.8	270.0	-120.2	0.00	0.00	0.00
3,400.0	6.00	180.00	3,393.4	152.3	270.0	-130.7	0.00	0.00	0.00
3,500.0	6.00	180.00	3,492.9	141.9	270.0	-141.1	0.00	0.00	0.00
3,600.0	6.00	180.00	3,592.3	131.4	270.0	-151.6	0.00	0.00	0.00
3,700.0	6.00	180.00	3,691.8	121.0	270.0	-162.0	0.00	0.00	0.00
3,800.0	6.00	180.00	3,791.2	110.5	270.0	-172.5	0.00	0.00	0.00
3,900.0	6.00	180.00	3,890.7	100.1	270.0	-182.9	0.00	0.00	0.00
4,000.0	6.00	180.00	3,990.1	89.6	270.0	-193.4	0.00	0.00	0.00
4,100.0	6.00	180.00	4,089.6	79.2	270.0	-203.8	0.00	0.00	0.00
4,200.0	6.00	180.00	4,189.0	68.7	270.0	-214.3	0.00	0.00	0.00
4,300.0	6.00	180.00	4,288.5	58.2	270.0	-224.7	0.00	0.00	0.00
4,400.0	6.00	180.00	4,387.9	47.8	270.0	-235.2	0.00	0.00	0.00
4,500.0	6.00	180.00	4,487.4	37.3	270.0	-245.6	0.00	0.00	0.00
4,600.0	6.00	180.00	4,586.9	26.9	270.0	-256.1	0.00	0.00	0.00
4,700.0	6.00	180.00	4,686.3	16.4	270.0	-266.5	0.00	0.00	0.00
4,800.0	6.00	180.00	4,785.8	6.0	270.0	-277.0	0.00	0.00	0.00
4,900.0	6.00	180.00	4,885.2	-4.5	270.0	-287.4	0.00	0.00	0.00
5,000.0	6.00	180.00	4,984.7	-14.9	270.0	-297.9	0.00	0.00	0.00
5,100.0	6.00	180.00	5,084.1	-25.4	270.0	-308.3	0.00	0.00	0.00
5,200.0	6.00	180.00	5,183.6	-35.8	270.0	-318.8	0.00	0.00	0.00
5,300.0	6.00	180.00	5,283.0	-46.3	270.0	-329.2	0.00	0.00	0.00

****EXAMPLE ONLY - NOT FOR CONSTRUCTION****

Stage 1 Lead	<table border="1"> <tr> <th>Hole Size</th> <th>Casing Size</th> <th>Depth</th> <th>Sacks</th> <th>Yield</th> <th>Density</th> </tr> <tr> <td align="center">17.5</td> <td align="center">13.375</td> <td align="center">1888</td> <td></td> <td align="center">1.76</td> <td align="center">13.5</td> </tr> </table>	Hole Size	Casing Size	Depth	Sacks	Yield	Density	17.5	13.375	1888		1.76	13.5	
	Hole Size	Casing Size	Depth	Sacks	Yield	Density								
	17.5	13.375	1888		1.76	13.5								
	Bbl/Sk	0.31372549												
	bbls	419.402246												
	Stage Tool Depth	N/A												
	Top MD of Segment	0												
	Bottom MD of Segment	1502												
	Cement Type	C												
	Additives	Bentonite, Accelerator, Kolseal, Defoamer, Celloflake												
	Quantity (sks)	1,337												
	Yield (cu ft/sk)	1.76												
	Density (lbs/gal)	13.5												
	Volume (cu ft)	2,352.85												
Percent Excess	100%	Target % 100%												
Column Height	3,389.88													
	Target TOC	0												
	Calc TOC	-1888	bbl	25% Excess	100%									
	calc vol	0.12372195	233.587041	291.9838012	467.174082									
Stage 1 Tail	<table border="1"> <tr> <th>Hole Size</th> <th>Casing Size</th> <th>Depth</th> <th>Sacks</th> <th>Yield</th> <th>Density</th> </tr> <tr> <td align="center">17.5</td> <td align="center">13.375</td> <td align="center">1888</td> <td></td> <td align="center">1.34</td> <td align="center">14.8</td> </tr> </table>	Hole Size	Casing Size	Depth	Sacks	Yield	Density	17.5	13.375	1888		1.34	14.8	
	Hole Size	Casing Size	Depth	Sacks	Yield	Density								
	17.5	13.375	1888		1.34	14.8								
	Bbl/Sk	0.23885918												
	bbls	47.77183601												
	Top MD of Segment	1502												
	Bottom MD of Segment	1888												
	Cement Type	C												
	Additives													
	Quantity (sks)	200												
	Yield (cu ft/sk)	1.34												
	Density (lbs/gal)	14.8												
	Volume (cu ft)	268												
	Percent Excess	100%												
Column Height	386.1225606													

SURFACE CEMENT

****EXAMPLE ONLY - NOT FOR CONSTRUCTION****

Stage 1	Lead	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th style="width:15%;">Hole Size</th> <th style="width:15%;">Casing Size</th> <th style="width:15%;">Depth</th> <th style="width:15%;">Sacks</th> <th style="width:15%;">Yield</th> <th style="width:15%;">Density</th> </tr> <tr> <td align="center">12.25</td> <td align="center">9.625</td> <td align="center">5013</td> <td></td> <td align="center">3.5</td> <td align="center">9</td> </tr> </table>						Hole Size	Casing Size	Depth	Sacks	Yield	Density	12.25	9.625	5013		3.5	9	
		Hole Size	Casing Size	Depth	Sacks	Yield	Density													
		12.25	9.625	5013		3.5	9													
		Bbl/Sk 0.623885918																		
		bbls 372.0365733																		
		Stage Tool Depth N/A																		
		Top MD of Segment 0																		
		Bottom MD of Segment 4163																		
		Cement Type C																		
		Additives Bentonite,Salt,Kolseal,Defoamer,Celloclake																		
		Quantity (sks) 596																		
		Yield (cu ft/sk) 3.5																		
		Density (lbs/gal) 9																		
		Volume (cu ft) 2,087.13																		
		Percent Excess 50%						Target %												
		Column Height 6,669.49						50%												
		<p align="center">Target TOC 0</p> <table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>Calc TOC</td> <td align="right">-2506.5</td> <td>bbl</td> <td>25% Excess</td> <td align="right">50%</td> </tr> <tr> <td>calc vol</td> <td align="right">0.055781888</td> <td>279.6346021</td> <td>349.5432526</td> <td align="right">419.4519031</td> </tr> </table>						Calc TOC	-2506.5	bbl	25% Excess	50%	calc vol	0.055781888	279.6346021	349.5432526	419.4519031			
		Calc TOC	-2506.5	bbl	25% Excess	50%														
calc vol	0.055781888	279.6346021	349.5432526	419.4519031																
Stage 1	Tail	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th style="width:15%;">Hole Size</th> <th style="width:15%;">Casing Size</th> <th style="width:15%;">Depth</th> <th style="width:15%;">Sacks</th> <th style="width:15%;">Yield</th> <th style="width:15%;">Density</th> </tr> <tr> <td align="center">12.25</td> <td align="center">9.625</td> <td align="center">5013</td> <td></td> <td align="center">1.33</td> <td align="center">14.8</td> </tr> </table>						Hole Size	Casing Size	Depth	Sacks	Yield	Density	12.25	9.625	5013		1.33	14.8	
		Hole Size	Casing Size	Depth	Sacks	Yield	Density													
		12.25	9.625	5013		1.33	14.8													
		Bbl/Sk 0.237076649																		
		bbls 47.41532977																		
		Top MD of Segment 4163																		
		Bottom MD of Segment 5013																		
		Cement Type C																		
		Additives																		
		Quantity (sks) 200																		
		Yield (cu ft/sk) 1.33																		
		Density (lbs/gal) 14.8																		
		Volume (cu ft) 266																		
		Percent Excess 25%																		
		Column Height 850.013004																		

INTERMEDIATE 1 CEMENT - STAGE 1

****EXAMPLE ONLY - NOT FOR CONSTRUCTION****

Stage 2	Lead	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th style="width:15%;">Hole Size</th> <th style="width:15%;">Casing Size</th> <th style="width:15%;">Depth</th> <th style="width:15%;">Sacks</th> <th style="width:15%;">Yield</th> <th style="width:15%;">Density</th> </tr> <tr> <td align="center">12.25</td> <td align="center">9.625</td> <td align="center">3262</td> <td></td> <td align="center">3.5</td> <td align="center">9</td> </tr> </table>						Hole Size	Casing Size	Depth	Sacks	Yield	Density	12.25	9.625	3262		3.5	9
		Hole Size	Casing Size	Depth	Sacks	Yield	Density												
		12.25	9.625	3262		3.5	9												
		Bbl/Sk 0.623885918																	
		bbls 225.5254458																	
		Stage Tool Depth N/A																	
		Top MD of Segment 0																	
		Bottom MD of Segment 2412																	
		Cement Type C																	
		Additives Bentonite, Salt, Kolseal, Defoamer, Cellocake																	
		Quantity (sks) 361																	
		Yield (cu ft/sk) 3.5																	
		Density (lbs/gal) 9																	
		Volume (cu ft) 1,265.20																	
		Percent Excess 50%																	
		Column Height 4,042.99																	
				Target TOC				0											
				Calc TOC		-1631	bbl	25% Excess											
				calc vol		0.055781888	181.960517	227.4506463											
								50%											
								272.9407756											
Stage 2	Tail	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th style="width:15%;">Hole Size</th> <th style="width:15%;">Casing Size</th> <th style="width:15%;">Depth</th> <th style="width:15%;">Sacks</th> <th style="width:15%;">Yield</th> <th style="width:15%;">Density</th> </tr> <tr> <td align="center">12.25</td> <td align="center">9.625</td> <td align="center">3262</td> <td></td> <td align="center">1.33</td> <td align="center">14.8</td> </tr> </table>						Hole Size	Casing Size	Depth	Sacks	Yield	Density	12.25	9.625	3262		1.33	14.8
		Hole Size	Casing Size	Depth	Sacks	Yield	Density												
		12.25	9.625	3262		1.33	14.8												
		Bbl/Sk 0.237076649																	
		bbls 47.41532977																	
		Top MD of Segment 2412																	
		Bottom MD of Segment 3262																	
		Cement Type C																	
		Additives																	
		Quantity (sks) 200																	
		Yield (cu ft/sk) 1.33																	
		Density (lbs/gal) 14.8																	
		Volume (cu ft) 266																	
		Percent Excess 25%																	
		Column Height 850.013004																	

INTERMEDIATE 1 CEMENT - STAGE 2

****EXAMPLE ONLY - NOT FOR CONSTRUCTION****

Stage 1 Lead	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th style="width:15%;">Hole Size</th> <th style="width:15%;">Casing Size</th> <th style="width:15%;">Depth</th> <th style="width:15%;">Sacks</th> <th style="width:15%;">Yield</th> <th style="width:15%;">Density</th> </tr> <tr> <td align="center">8.75</td> <td align="center">7.625</td> <td align="center">10670</td> <td align="center">[REDACTED]</td> <td align="center">2.47</td> <td align="center">9</td> </tr> </table>						Hole Size	Casing Size	Depth	Sacks	Yield	Density	8.75	7.625	10670	[REDACTED]	2.47	9
	Hole Size	Casing Size	Depth	Sacks	Yield	Density												
	8.75	7.625	10670	[REDACTED]	2.47	9												
	Bbl/Sk 0.440285205																	
	bbls 168.6309595																	
	Stage Tool Depth N/A																	
	Top MD of Segment 0																	
	Bottom MD of Segment 6755																	
	Cement Type H																	
	Additives Bentonite, Retarder, Kolseal, Defoamer, Celloflake, Anti-Settling																	
	Expansion Additive																	
	Quantity (sks) 383																	
	Yield (cu ft/sk) 2.47																	
	Density (lbs/gal) 9																	
	Volume (cu ft) 946.02																	
	Percent Excess 25%																	
	Column Height 9,422.97																	
	<div style="display: flex; justify-content: space-between;"> <div> Target TOC Calc TOC -2667.5 calc vol 0.01789574 </div> <div> 0 bbl 190.9475483 25% Excess 238.6844354 </div> <div> 25% 238.6844354 </div> </div>																	
	Stage 1 Tail	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th style="width:15%;">Hole Size</th> <th style="width:15%;">Casing Size</th> <th style="width:15%;">Depth</th> <th style="width:15%;">Sacks</th> <th style="width:15%;">Yield</th> <th style="width:15%;">Density</th> </tr> <tr> <td align="center">8.75</td> <td align="center">7.625</td> <td align="center">10670</td> <td align="center">[REDACTED]</td> <td align="center">1.31</td> <td align="center">14.2</td> </tr> </table>						Hole Size	Casing Size	Depth	Sacks	Yield	Density	8.75	7.625	10670	[REDACTED]	1.31
Hole Size		Casing Size	Depth	Sacks	Yield	Density												
8.75		7.625	10670	[REDACTED]	1.31	14.2												
Bbl/Sk 0.233511586																		
bbls 70.05347594																		
Top MD of Segment 6755																		
Bottom MD of Segment 10670																		
Cement Type H																		
Additives Salt, Bentonite, Retarder, Dispersant, Fluid Loss																		
Quantity (sks) 300																		
Yield (cu ft/sk) 1.31																		
Density (lbs/gal) 14.2																		
Volume (cu ft) 393																		
Percent Excess 25%																		
Column Height 3914.533571																		

INTERMEDIATE 2 CEMENT

****EXAMPLE ONLY - NOT FOR CONSTRUCTION****

Stage 1	Lead	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th style="width:15%;">Hole Size</th> <th style="width:15%;">Casing Size</th> <th style="width:15%;">Depth</th> <th style="width:15%;">Sacks</th> <th style="width:15%;">Yield</th> <th style="width:15%;">Density</th> </tr> <tr> <td align="center">6.75</td> <td align="center">5.5</td> <td align="center">22496</td> <td></td> <td align="center">1.34</td> <td align="center">14.2</td> </tr> </table>						Hole Size	Casing Size	Depth	Sacks	Yield	Density	6.75	5.5	22496		1.34	14.2	
		Hole Size	Casing Size	Depth	Sacks	Yield	Density													
		6.75	5.5	22496		1.34	14.2													
		Bbl/Sk 0.23885918																		
		bbls 418.2897805																		
		Stage Tool Depth N/A																		
		Top MD of Segment 0																		
		Bottom MD of Segment 22496																		
		Cement Type H																		
		Additives Salt, Bentonite, Fluid Loss, Dispersant, Retarder, Defoamer																		
		Quantity (sks) 1,751																		
		Yield (cu ft/sk) 1.34																		
		Density (lbs/gal) 14.2																		
		Volume (cu ft) 2,346.61																		
Percent Excess 25%						Target %														
Column Height 28,120.00						25%														
<p align="center">Target TOC 0</p> <table style="width:100%;"> <tr> <td>Calc TOC</td> <td align="right">-5624</td> <td>bbl</td> <td align="right">25% Excess</td> <td align="right">25%</td> </tr> <tr> <td>calc vol</td> <td align="right">0.01487517</td> <td>334.6318244</td> <td align="right">418.2897805</td> <td align="right">418.2897805</td> </tr> </table>						Calc TOC	-5624	bbl	25% Excess	25%	calc vol	0.01487517	334.6318244	418.2897805	418.2897805					
Calc TOC	-5624	bbl	25% Excess	25%																
calc vol	0.01487517	334.6318244	418.2897805	418.2897805																
Stage 1	Tail	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th style="width:15%;">Hole Size</th> <th style="width:15%;">Casing Size</th> <th style="width:15%;">Depth</th> <th style="width:15%;">Sacks</th> <th style="width:15%;">Yield</th> <th style="width:15%;">Density</th> </tr> <tr> <td align="center">6.75</td> <td align="center">5.5</td> <td align="center">22496</td> <td align="center">0</td> <td align="center">0</td> <td align="center">0</td> </tr> </table>						Hole Size	Casing Size	Depth	Sacks	Yield	Density	6.75	5.5	22496	0	0	0	
		Hole Size	Casing Size	Depth	Sacks	Yield	Density													
		6.75	5.5	22496	0	0	0													
		Bbl/Sk 0																		
		bbls 0																		
		Top MD of Segment 22496																		
		Bottom MD of Segment 22496																		
		Cement Type H																		
		Additives																		
		Quantity (sks) 0																		
		Yield (cu ft/sk) 0																		
		Density (lbs/gal) 0																		
		Volume (cu ft) 0																		
		Percent Excess																		
Column Height 0																				

PRODUCTION CEMENT

HALLIBURTON

Permian Basin, Ft Stockton

Lab Results- Lead

Job Information

Request/Slurry	2488456/2	Rig Name		Date	18/DEC/2018
Submitted By	Dillon Briers	Job Type	Intermediate Casing	Bulk Plant	
Customer	Ameredev	Location	Lea	Well	

Well Information

Casing/Liner Size	7.625 in	Depth MD	5013 ft	BHST	165°F
Hole Size	8.75 in	Depth TVD	5013 ft	BHCT	130°F

Cement Information - Lead Design

Conc	UOM	Cement/Additive	Cement Properties		
100	% BWOC	NeoCem	Slurry Density	9	lbm/gal
14.68	gal/sack	Heated Fresh Water	Slurry Yield	3.5	ft ³ /sack
			Water Requirement	14.68	gal/sack

Pilot Test Results Request ID 2488456/1

API Rheology, Request Test ID:35665340

Temp (degF)	300	200	100	60	30	6	3	Cond Time (min)
80 (up)	82	67	49	42	39	36	28	0
80 (down)	82	59	35	26	18	10	9	0
80 (avg.)	82	63	42	34	29	23	19	0

PV (cP) & YP (lbs/100ft²): 61.73 22.32 (Least-squares method)

PV (cP) & YP (lbs/100ft²): 60 22 (Traditional method (300 & 100 rpm based))

Generalized Herschel-Bulkley 4: YP(lb/100ft²)=20.33 MuInf(cP)=52.39 m=0.81 n=0.81

API Rheology, Request Test ID:35665341

Temp (degF)	300	200	100	60	30	6	3	Cond Time (min)	Cond Temp (degF)
134 (up)	63	47	29	21	15	7	6	30	134
134 (down)	63	46	29	21	14	7	4	30	134
134 (avg.)	63	47	29	21	15	7	5	30	134

PV (cP) & YP (lbs/100ft²): 57.12 7.98 (Least-squares method)

PV (cP) & YP (lbs/100ft²): 51 12 (Traditional method (300 & 100 rpm based))

Generalized Herschel-Bulkley 4: YP(lb/100ft²)=2.26 MuInf(cP)=30.64 m=0.41 n=0.41

API Fluid Loss, Request Test ID:35665342

Test Temp (degF)	Test Pressure (psi)	Test Time (min)	Meas. Vol.	Calculated FL (<30 min)	Conditioning time (min)	Conditioning Temp (degF)
134	1000	9.12	52	189	30	134

This report is the property of Halliburton Energy Services and neither it nor any part thereof, nor a copy thereof, is to be published or disclosed without first securing the expressed written approval of Halliburton. It may however be used in the course of regular business operations by any person or concern receiving such report from Halliburton. This report is for information purposes only and the content is limited to the sample described. Halliburton makes no warranties, expressed or implied, as to the accuracy of the contents or results. Any user of this report agrees Halliburton shall not be liable for any loss or damage regardless of cause, including any act or omission of Halliburton, resulting from the use hereof.

Free Fluid API 10B-2, Request Test ID:35665343

Con. Temp (degF)	Cond. Time (min)	Static T. (F)	Static time (min)	Incl. (deg)	% Fluid
134	30	80	120	0	0

Pilot Test Results Request ID 2504116/5

Thickening Time - ON-OFF-ON, Request Test ID:35852392

Test Temp (degF)	Pressure (psi)	Reached in (min)	70 Bc (hh:mm)	Start Bc
126	5800	40	6:18	16

UCA Comp. Strength, Request Test ID:35852394

End Temp (degF)	Pressure (psi)	50 psi (hh:mm)	500 psi (hh:mm)	12 hr CS (psi)	24 hr CS (psi)	48 hr CS (psi)
159	4000	8:55	12:23	456	749	681


This report is the property of Halliburton Energy Services and neither it nor any part thereof, nor a copy thereof, is to be published or disclosed without first securing the expressed written approval of Halliburton. It may however be used in the course of regular business operations by any person or concern receiving such report from Halliburton. This report is for information purposes only and the content is limited to the sample described. Halliburton makes no warranties, expressed or implied, as to the accuracy of the contents or results. Any user of this report agrees Halliburton shall not be liable for any loss or damage regardless of cause, including any act or omission of Halliburton, resulting from the use hereof.



U. S. Steel Tubular Products

6/6/2017 6:18:53 PM

7.625" 29.70lbs/ft (0.375" Wall) HCL80 USS-LIBERTY FJM®



MECHANICAL PROPERTIES	Pipe	USS-LIBERTY FJM®	
Minimum Yield Strength	110,000	--	psi
Maximum Yield Strength	140,000	--	psi
Minimum Tensile Strength	125,000	--	psi

DIMENSIONS	Pipe	USS-LIBERTY FJM®	
Outside Diameter	7.625	7.625	in.
Wall Thickness	0.375	--	in.
Inside Diameter	6.875	6.789	in.
Standard Drift	6.750	6.750	in.
Alternate Drift	--	--	in.
Nominal Linear Weight, T&C	29.70	--	lbs/ft
Plain End Weight	29.06	--	lbs/ft

SECTION AREA	Pipe	USS-LIBERTY FJM®	
Critical Area	8.541	5.074	sq. in.
Joint Efficiency	--	59.4	%

PERFORMANCE	Pipe	USS-LIBERTY FJM®	
Minimum Collapse Pressure	6,700	6,700	psi
Minimum Internal Yield Pressure	9,460	9,460	psi
Minimum Pipe Body Yield Strength	940,000	--	lbs
Joint Strength	--	558,000	lbs
Compression Rating	--	558,000	lbs
Reference Length	--	12,810	ft
Maximum Uniaxial Bend Rating	--	39.3	deg/100 ft

Make-Up Loss	--	3.92	in.
Minimum Make-Up Torque	--	10,800	ft-lbs
Maximum Make-Up Torque	--	15,250	ft-lbs

1. Other than proprietary collapse and connection values, performance properties have been calculated using standard equations defined by API 5C3 and do not incorporate any additional design or safety factors. Calculations assume nominal pipe OD, nominal wall thickness and Specified Minimum Yield Strength (SMYS).
2. Compressive & Tensile Connection Efficiencies are calculated by dividing the connection critical area by the pipe body area.
3. Uniaxial bending rating shown is structural only, and equal to compression efficiency.
4. USS-LIBERTY FJM™ connections are optimized for each combination of OD and wall thickness and cannot be interchanged.
5. Torques have been calculated assuming a thread compound friction factor of 1.0 and are recommended only. Field make-up torques may require adjustment based on actual field conditions (e.g. make-up speed, temperature, thread compound, etc.).
6. Reference length is calculated by joint strength divided by nominal plain end weight with 1.5 safety factor.
7. Connection external pressure leak resistance has been verified to 100% API pipe body collapse pressure following the guidelines of API 5C5 Cal III.

Legal Notice

USS-LIBERTY FJM® is a trademark of U. S. Steel Corporation. All material contained in this publication is for general information only. This material should not therefore be used or relied upon for any specific application without independent competent professional examination and verification of accuracy, suitability and applicability. Anyone making use of this material does so at their own risk and assumes any and all liability resulting from such use. U.S. Steel disclaims any and all expressed or implied warranties of fitness for any general or particular application.

U. S. Steel Tubular Products
10343 Sam Houston Park Dr., #120
Houston, TX 77064

1-877-893-9461
connections@uss.com
www.usstubular.com


U. S. Steel Tubular Products
5 1/2 20.00 lb (0.361) P110 HP
USS-EAGLE SFH™

	PIPE	CONNECTION	
MECHANICAL PROPERTIES			
Minimum Yield Strength	125,000	125,000	psi
Maximum Yield Strength	140,000	140,000	psi
Minimum Tensile Strength	130,000	130,000	psi
DIMENSIONS			
Outside Diameter	5.500	5.830	in.
Wall Thickness	0.361		in.
Inside Diameter	4.778	4.693	in.
Drift - API	4.653	4.653	in.
Nominal Linear Weight, T&C	19.83		lbs/ft
Plain End Weight	19.83	19.83	lbs/ft
SECTION AREA			
Cross Sectional Area Critical Area	5.828	5.054	sq. in.
Joint Efficiency		86.25	%
PERFORMANCE			
Minimum Collapse Pressure	13,150	13,150	psi
External Pressure Leak Resistance		10,000	psi
Minimum Internal Yield Pressure	14,360	14,360	psi
Minimum Pipe Body Yield Strength	729,000		lbs
Joint Strength		631,750	lbs
Compression Rating		631,750	lbs
Reference Length		21,240	ft
Maximum Uniaxial Bend Rating		89.9	deg/100 ft
Minimum Make-Up Torque		14,000	ft-lbs
Maximum Make-Up Torque		16,900	ft-lbs
Maximum Operating Torque		25,000	ft-lbs
Make-Up Loss		5.92	in.

Notes:

- Other than proprietary collapse and connection values, performance properties have been calculated using standard equations defined by API 5C3 and do not incorporate any additional design or safety factors. Calculations assume nominal pipe OD, nominal wall thickness, and Specified Minimum Yield Strength (SMYS).
- Compressive & Tensile Connection Efficiencies are calculated by dividing the connection critical area by the pipe body area.
- Uniaxial bending rating shown is structural only, and equal to compression efficiency.
- Torques have been calculated assuming a thread compound friction factor of 1.0 and are recommended only. Field make-up torques may require adjustment based on actual field conditions (e.g. make-up speed, temperature, thread compound, etc.).
- Reference length is calculated by joint strength divided by plain end weight with 1.5 safety factor.
- Connection external pressure resistance has been verified to 10,000 psi (Application specific testing).

Legal Notice: All material contained in this publication is for general information only. This material should not therefore be used or relied upon for any specific application without independent competent professional examination and verification of accuracy, suitability, and applicability. Anyone making use of this material does so at their own risk and assumes any and all liability resulting from such use. U. S. Steel disclaims any and all expressed or implied warranties of fitness for any general or particular application.
Manuel USS Product Data Sheet 2017 rev25 (April)

QUALITY CONTROL	No.: QC-DB- 651 / 2013
	Page : 1 / 44
Hose No.: 66551, 66552, 66553, 66554	Revision : 0
	Date: 14. November 2013.
	Prepared by : <i>Sebastian Lander</i>
	Appr. by: <i>Sebastian Lander</i>

CHOKE AND KILL HOSES

id.: 3" 69 MPa x 35 ft (10,67 m)

DATA BOOK

Purchaser: H&P STOCK

Purchaser Order No.:

ContiTech Rubber Order No.: 537587

ContiTech Oil & Marine Corp. Order No.:
4500370505

NOT DESIGNED FOR WELL TESTING

CONTENT

		<u>Page</u>
1.	API QMS Certificate (No.: 0760)	3.
2.	American Petroleum Institute Certificate of Authority To Use the Official API Monogram (No.: 16C-0004)	4.
3.	Quality Control Inspection and Test Certificates (No.: 1905, 1906, 1907, 1908)	5-8.
4.	Hose Data Sheet	9.
5.	Metal Parts	
5.1.	Raw Material Quality Certificates (No.: TR070687, EUR-265844, 86989/13-0)	10-13.
5.2.	Hardness Test Reports (No.: 561/13, 562/13)	14-15.
5.3.	Ultrasonic Test Reports (No.: 513/13, 514/13, 515/13)	16-18.
5.4.	NDT Examiner Certificate (Name: Tóth Ákos József)	19-20.
5.5.	Welding Procedure Specification (No.: 140-71)	21-24.
5.6.	Welding Procedure Qualification Record (No.: BUD 0700002/1)	25-26.
5.7.	Welder's Approval Test Certificate (No.: RK1825997.R1)	27-28.
5.8.	Welding Log Sheet (No.: 2013/2898)	29.
5.9.	Visual Examination Record (No.: 813/13)	30.
5.10.	NDT Examiner Certificate (Name: Kis Gábor Balázs)	31-32.
5.11.	Radiographic Test Certificates (No.: 2431/13, 2430/13)	33-34.
5.12.	NDT Examiner Certificate (Name: Ménesi István)	35-36.
5.13.	MP Examination Record (No.: 1222/13)	37.
5.14.	NDT Examiner Certificate (Name: Oravec Gábor)	38-39.
6.	Steel Cord	
6.1.	Inspection Certificate (No.: 4046181212)	40.
7.	Outside Stripwound Tube	
7.1.	Inspection Certificate (No.: 63892/2012)	41.
8.	Certificate of Calibration (Manometer Serial No.: 1518086)	42-44.



ContiTech Rubber
Industrial Kft.
Quality Control Dept.
(1)



Certificate of Registration

APIQR REGISTRATION NUMBER

0760

This certifies that the quality management system of

CONTITECH RUBBER INDUSTRIAL LTD.

Budapesti ut 10

Szeged

Hungary

*has been assessed by the American Petroleum Institute Quality Registrar (APIQR®) and
found it to be in conformance with the following standard:*

ISO 9001:2008

The scope of this registration and the approved quality management system applies to the
Design and Manufacture of High Pressure Hoses

APIQR® approves the organization's justification for excluding:

No Exclusions Identified as Applicable

Effective Date: October 15, 2013

Expiration Date: October 15, 2016

Registered Since: October 15, 2007

W. Dan Whittaker
Manager of Operations, APIQR

Accredited by Member of
the International
Accreditation Forum
Multilateral Recognition
Arrangement for Quality
Management Systems



This certificate is valid for the period specified herein. The registered organization must continuously meet all requirements of APIQR's Registration Program and the requirements of the Registration Agreement. Registration is maintained and regularly monitored through annual full system audits. Further clarifications regarding the scope of this certificate and the applicability of ISO 9001 standard requirements may be obtained by consulting the registered organization. This certificate has been issued from APIQR offices located at 1220 I Street, N.W., Washington, D.C. 20005-4030, U.S.A. It is the property of APIQR, and must be returned upon request. To verify the authenticity of this certificate, go to www.apiqr.com/verification.



Certificate of Authority to use the Official API Monogram

License Number: 16C-0004

ORIGINAL

The American Petroleum Institute hereby grants to

CONTITECH RUBBER INDUSTRIAL LTD.

Budapesti ut 10

Szeged

Hungary

the right to use the Official API Monogram® on manufactured products under the conditions in the official publications of the American Petroleum Institute entitled API Spec Q1® and API Spec 16C and in accordance with the provisions of the License Agreement.

In all cases where the Official API Monogram is applied, the API Monogram should be used in conjunction with this certificate number: 16C-0004

The American Petroleum Institute reserves the right to revoke this authorization to use the Official API Monogram for any reason satisfactory to the Board of Directors of the American Petroleum Institute.

The scope of this license includes the following product: Flexible Cocks and Kill Lines


QMS Exclusions: No Exclusions Identified as Applicable

Effective Date: OCTOBER 15, 2013

Expiration Date: OCTOBER 15, 2016

To verify the authenticity of this license, go to www.api.org/compositelist.


American Petroleum Institute



Director of Global Industry Services



American
Petroleum
Institute





2011113


CONTITECH RUBBER
Industrial Kft.


No:QC-DB- 651 /2013

Page: 4 / 44

QUALITY CONTROL INSPECTION AND TEST CERTIFICATE		CERT. N°: 1905	
PURCHASER: ContiTech Oil & Marine Corp.		P.O. N°: 4500370505	
CONTITECH RUBBER order N°: 537587	HOSE TYPE: 3" ID Choke and Kill Hose		
HOSE SERIAL N°: 66551	NOMINAL / ACTUAL LENGTH: 10,67 m / 10,75 m		
W.P. 68,9 MPa 10000 psi	T.P. 103,4 MPa 15000 psi	Duration: 60 min.	
<p>Pressure test with water at ambient temperature</p> <p style="text-align: center;">See attachment. (1 page)</p> <p>↑ 10 mm = 10 Min. → 10 mm = 25 MPa</p>			
COUPLINGS Type	Serial N°	Quality	Heat N°
3" coupling with	8084 8083	AISI 4130	24613
4 1/16" 10K API Flange end		AISI 4130	034939
NOT DESIGNED FOR WELL TESTING		API Spec 16 C	
		Temperature rate:"B"	
All metal parts are flawless			
WE CERTIFY THAT THE ABOVE HOSE HAS BEEN MANUFACTURED IN ACCORDANCE WITH THE TERMS OF THE ORDER INSPECTED AND PRESSURE TESTED AS ABOVE WITH SATISFACTORY RESULT.			
STATEMENT OF CONFORMITY: We hereby certify that the above items/equipment supplied by us are in conformity with the terms, conditions and specifications of the above Purchaser Order and that these items/equipment were fabricated inspected and tested in accordance with the referenced standards, codes and specifications and meet the relevant acceptance criteria and design requirements.			
COUNTRY OF ORIGIN HUNGARY/EU			
Date:	Inspector	Quality Control	
13. November 2013.		ContiTech Rubber Industrial Kft. Quality Control Dept.  	

Yacine
 Contitech Rubber
 Industrial Kft.
 Quality Control Dept.



QUALITY CONTROL INSPECTION AND TEST CERTIFICATE		CERT. N°: 1906	
PURCHASER: ContiTech Oil & Marine Corp.		P.O. N°: 4500370505	
CONTITECH RUBBER order N°: 537587	HOSE TYPE: 3" ID Choke and Kill Hose		
HOSE SERIAL N°: 66552	NOMINAL / ACTUAL LENGTH: 10,67 m / 10,73 m		
W.P. 68,9 MPa 10000 psi	T.P. 103,4 MPa 15000 psi	Duration: 60	min.
<p>Pressure test with water at ambient temperature</p> <p style="text-align: center;">See attachment. (1 page)</p> <p>↑ 10 mm = 10 Min. → 10 mm = 25 MPa</p>			
COUPLINGS Type	Serial N°	Quality	Heat N°
3" coupling with	8088 8085	AISI 4130	24613
4 1/16" 10K API Flange end		AISI 4130	034939
NOT DESIGNED FOR WELL TESTING		API Spec 16 C	
		Temperature rate:"B"	
All metal parts are flawless			
WE CERTIFY THAT THE ABOVE HOSE HAS BEEN MANUFACTURED IN ACCORDANCE WITH THE TERMS OF THE ORDER INSPECTED AND PRESSURE TESTED AS ABOVE WITH SATISFACTORY RESULT.			
STATEMENT OF CONFORMITY: We hereby certify that the above items/equipment supplied by us are in conformity with the terms, conditions and specifications of the above Purchaser Order and that these items/equipment were fabricated inspected and tested in accordance with the referenced standards, codes and specifications and meet the relevant acceptance criteria and design requirements.			
COUNTRY OF ORIGIN HUNGARY/EU			
Date:	Inspector	Quality Control	
13. November 2013.		ContiTech Rubber Industrial Kft. Quality Control Dept. 	

QUALITY CONTROL INSPECTION AND TEST CERTIFICATE				CERT. N°: 1907	
PURCHASER: ContiTech Oil & Marine Corp.			P.O. N°: 4500370505		
CONTITECH RUBBER order N°: 537587		HOSE TYPE: 3" ID Choke and Kill Hose			
HOSE SERIAL N°: 66553		NOMINAL / ACTUAL LENGTH: 10,67 m / 10,745 m			
W.P. 68,9 MPa 10000 psi		T.P. 103,4 MPa 15000 psi		Duration: 60 min.	
<p>Pressure test with water at ambient temperature</p> <p style="text-align: center;">See attachment. (1 page)</p> <p>↑ 10 mm = 10 Min. → 10 mm = 25 MPa</p>					
COUPLINGS Type		Serial N°		Quality	
3" coupling with		8089 8087		AISI 4130	
4 1/16" 10K API Flange end				AISI 4130	
				Heat N°	
				23171 24613	
				034939	
NOT DESIGNED FOR WELL TESTING				API Spec 16 C	
				Temperature rate:"B"	
All metal parts are flawless					
WE CERTIFY THAT THE ABOVE HOSE HAS BEEN MANUFACTURED IN ACCORDANCE WITH THE TERMS OF THE ORDER INSPECTED AND PRESSURE TESTED AS ABOVE WITH SATISFACTORY RESULT.					
STATEMENT OF CONFORMITY: We hereby certify that the above items/equipment supplied by us are in conformity with the terms, conditions and specifications of the above Purchaser Order and that these items/equipment were fabricated inspected and tested in accordance with the referenced standards, codes and specifications and meet the relevant acceptance criteria and design requirements.					
COUNTRY OF ORIGIN HUNGARY/EU					
Date:		Inspector		Quality Control	
13. November 2013.				<p>ContiTech Rubber Industrial Kft. Quality Control Dept.</p> <p><i>[Signature]</i> <i>[Signature]</i> <i>[Signature]</i></p>	

QUALITY CONTROL INSPECTION AND TEST CERTIFICATE		CERT. N°: 1908	
PURCHASER: ContiTech Oil & Marine Corp.		P.O. N°: 4500370505	
CONTITECH RUBBER order N°: 537587	HOSE TYPE: 3" ID Choke and Kill Hose		
HOSE SERIAL N°: 66554	NOMINAL / ACTUAL LENGTH: 10,67 m / 10,71 m		
W.P. 68,9 MPa 10000 psi	T.P. 103,4 MPa 15000 psi	Duration: 60	min.
<p>Pressure test with water at ambient temperature</p> <p style="text-align: center;">See attachment. (1 page)</p> <p>↑ 10 mm = 10 Min. → 10 mm = 25 MPa</p>			
COUPLINGS Type	Serial N°	Quality	Heat N°
3" coupling with	8090 8086	AISI 4130	23171 24613
4 1/16" 10K API Flange end		AISI 4130	034939
NOT DESIGNED FOR WELL TESTING		API Spec 16 C	
		Temperature rate:"B"	
All metal parts are flawless			
WE CERTIFY THAT THE ABOVE HOSE HAS BEEN MANUFACTURED IN ACCORDANCE WITH THE TERMS OF THE ORDER INSPECTED AND PRESSURE TESTED AS ABOVE WITH SATISFACTORY RESULT.			
STATEMENT OF CONFORMITY: We hereby certify that the above items/equipment supplied by us are in conformity with the terms, conditions and specifications of the above Purchaser Order and that these items/equipment were fabricated inspected and tested in accordance with the referenced standards, codes and specifications and meet the relevant acceptance criteria and design requirements.			
COUNTRY OF ORIGIN HUNGARY/EU			
Date:	Inspector	Quality Control	
13. November 2013.		<p>ContiTech Rubber Industrial Kft. Quality Control Dept.</p> <p><i>[Signature]</i> <i>[Signature]</i></p>	



Hose Data Sheet

CRI Order No.	537587
Customer	ContiTech Oil & Marine Corp.
Customer Order No	4500370505
Item No.	1
Hose Type	Flexible Hose
Standard	API SPEC 16 C
Inside dia in inches	3
Length	35 ft
Type of coupling one end	FLANGE 4.1/16" 10KPSI API SPEC 6A TYPE 6BX FLANGE C/W BX155STANDARD RING GROOVE
Type of coupling other end	FLANGE 4.1/16" 10KPSI API SPEC 6A TYPE 6BX FLANGE C/W BX155 STANDARD RING GROOVE
H2S service NACE MR0175	Yes
Working Pressure	10 000 psi
Design Pressure	10 000 psi
Test Pressure	15 000 psi
Safety Factor	2,25
Marking	USUAL PHOENIX
Cover	NOT FIRE RESISTANT
Outside protection	St. steel outer wrap
Internal stripwound tube	No
Lining	OIL RESISTANT
Safety clamp	No
Lifting collar	No
Element C	No
Safety chain	No
Safety wire rope	No
Max.design temperature [°C]	100
Min.design temperature [°C]	-20
Min. Bend Radius operating [m]	0,90
Min. Bend Radius storage [m]	0,90
Electrical continuity	The Hose is electrically continuous
Type of packing	WOODEN CRATE ISPM-15

Body

8083-8088

TM
steels

3451-3466

42 0516 0045

Customer: ContiTech Rubber Industrial Kft
Order Number: 32258500
Part Number: 4205160045
Our Ref: SO64201
Date: 11th February 2013
Certificate Number: TR070687 (Rev. 18/06/2013)
Approved Signatories: R M Greaves A Cocking J Jarvis A Pears S Selman

Description CERTIFICATE OF CONFORMITY Heat Treatment

AISI 4130 BLACK ROLLED BAR, HEAT TREATED & TESTED TO 197-238 BHN, 655MPA MIN TENSILE, 517MPA MIN YIELD, 18% MIN ELONGATION, CHARPY IMPACT TESTING 27J MIN @ -30C (OR COLDER) LATERAL EXPANSION 0.38 MIN. ROLLING REDUCTION 3:1 MIN. NI 1% MAX & CE 0.82 MAX. TESTS MAY BE TAKEN FROM A 4" SQR QTC AS PER API 6A/PSL 3 QTC SIZE. MECHANICAL TEST SPECIMEN TO ASTM A370 NACE MR0175/ISO15156 APPLIES

APPROX 20 TONNES 210 MM DIA

CERTS TO EN10204 3.1

HARDENED FROM 860°C FOR 5.30 HOURS (WATER QUENCH) TEMPERED AT 670°C FOR 10 HOURS (AIR COOL) WATER TEMPERATURE BEFORE QUENCH, 28°C. AFTER, 35°C. TEMP. MEASUREMENT, FURNACE ATMOSPHERE THERMOCOUPLE COMPONENT HARDNESS E10 - 211 HBW10/3000 TEST COUPON - 4" SQ X 8" LONG, TESTED AT 1/4 T LOCATION REDUCTION RATIO - 6.2 REDUCTION RATIO & HT APPLY TO BOTH JOB & TEST PIECE FURNACE CALIBRATION: API8A 20th ed, annex M C/E = 0.693

CAST 24613

C	Si	Mn	S	P	Ni	Cr	Mo	Al	Cu	Sn	Nb
0.3200	0.2590	0.5680	0.0090	0.0100	0.1660	1.0580	0.2350	0.0200	0.1420	0.0070	0.0010
V	Ta	Ti	Nb+Ta	Co	N	B	W	Ce	Fa	As	Sb
0.0010		0.0010			0.0078	0.0001					
Pb	Ca	H (ppm)	CEV								
		1.20	0.69								

TEST SPECIFICATION 517 N/mm2 MIN YIELD

Temperature	Re	Rp 0.2	Rm	A %	Z %	Impact	Temp.	Hardness
RT		517.000						
	N/mm2	N/mm2	N/mm2	%				

TEST RESULTS

Test Number	Dir./Temp.	Re	Rp	Rm	A %	Z %	Joules	Charpy Direction
ST22561N	20.0°C		524.000	698.000	27.80	87.70	KCV 48°C 60 50 78 KCV -80°C 50 50 46	LONG
Specimen Ø 12.500mm							% Shear Surface 62.0% 52.0% 60.0%	
							Lateral Expansion (mm) 0.840 0.740 1.020	LONG

For and on Behalf of TM Steels Ltd.

A Cocking

ContiTech Rubber
Industrial Kft.
CERTIFICATE
ACCEPTABLE
QC INSPECTOR
DATE: 14.06.21.



ok Street
ld S9 2JN
one: +44 114 244 8711
nile: +44 114 244 7469



Body

8089-8090

Test Certificate

To: CONTITECH RUBBER INDUSTRIAL KFT H-8728, SZEGED, BUDAPESTI UT 10, K.1562-K.1575 HUNGARY 420516 0045	Customer Order Number 32252193 - 01 Customer Order Date 27Feb12 Sales Order Number EUR-352067-1 Report Date 25Sep12 Quantity 14 Pcs 17402 Kgs 210 mm Dia	Test Number 402483 Part Number 4205160045 Cast Number 23171 Cert Number EUR-265844 Steel Type ALLOY 4130
Description AISI 4130 76KSI .2% PS API QTC		

quoted only refer to the items tested.

Material Specification	AISI4130										
Heat Treatment Spec	197-237BHN				Test Spec 517N/MM2MIN.YLD				Test Spec		
Production Practice	EFVD		Production Method		FORGED						
Heat Treatment	Temp(°C)	Soak	Coolant	Charge Ref.	Init	Max(°C)	Batch	Temp recorded using CONTACT THERMOCOUPLE			
IN	860	3 HRS	WATER QUENCH	SHF-158284	20	30	0912091308	Nature of T/P Separate			
R	650	4 HRS	TABLE COOL	SHF-158284			1012091319	Qtc size 4inch SQ X 6inch LONG			
								Req. Min/Max		Achieved	
								Hardness on T/P		197 237 HBW	229 229 HBW
								Hardness on Material		197 237 HBW	218 235 HBW

Impacts -										
Location	Direction	Rp 0.20%	Rm	A%	Z%	Location	Direction	CVN	Lat. Exp. (mm)	% Shear
1/4T	LONGITUDINAL	517 Min	655 to 800	18 Min (4d)	0 Min	1/4T	LONGITUDINAL	27 Min Ave	0.380 Min	0
(N/mm2)		580	785	25 (50.0mm)	84.0 (12.56mm)	Results (Joules)	-30 Centigrade	106 104 102	1.44 1.42 1.4	40 40 40
						Results				

in										
Resistance		Ferrite				Microstructure				
Equivalent		.871				Grain Size		Min 6	Max 6	
Si	Mn	P	S	Cr	Mo	Ni	Cu			
0.2820	0.5370	0.0110	0.0050	1.0620	0.2290	0.1860	0.2430			

BSEN10204.2004 3.1
R-01-75
TON RATIO 6.5:1

Contitech Rubber
Industrial Kft.
CERTIFICATE
ACCEPTABLE
QC INSPECTOR
DATE: 12.10.01

All furnace Calibration conforms to API6A 20th Edition ANNEX M.
Hardness load/penetration depth - HBW 10 diameter (mm)/3000 kgf test force per ASTM E10.

Third party inspection :

Approved Signatories : S.Maxted G.Smith S.Suter P.Rogers M.Brown
It is not to be reproduced without written approval.

Signature

Page 1 of 1

CONTITECH RUBBER
Industrial Kft.

No:QC-DB- 651 /2013
Page: 11 / 44

HAMOR zRt.

FORGING, MACHINING, HEAT-TREATING

Flange

8083-8030

3386

4205140284

EMI-TÜV
ISO9001

H-3531 Miskolc, Kiss Ernő u. 17. Phone: 36/46/401-033 Fax: 36/46/379-199

INSPECTION CERTIFICATE

ACCEPTANCE ACCORDING EN 10204-05/3.1

Certificate No.: **86989/13-0**

Date of issue: 2013.03.27 | Hámor No.: 98-39B5263 | Order No.: 32259784/13/2

Customer: Contitech Rubber Industrial Kft.
6728 Szeged Budapesti út 10

Quality: AISI 4130/CONTI Spec.No.: API 6A PSL3 325/133 x 182

Dimension: MSO-100597-002/A/H mm

Final dim.:MSO-100597-002/A(4 1/16") Heat-treatment:Quenched & tempered

Quantity: 30 pcs | Weight: 73.0 kg/pc | Total weight: 2190.00 kg

nomination of product: Forged,machined disc

Chemical analysis %


Heat No.: **034939**

Steelmaker: CELSA Hutaostrowiec POLA

Test No.	Spec. value	C	MN	SI	P	S	CR	MO	V	Ce
	Min.									
	Max.	0.45	1.80	1.00	0.025	0.025	2.75	1.500	0.300	0.82
	Result	0.28	0.56	0.20	0.006	0.003	0.99	0.170	0.003	0.62

Mechanical properties:

Test No.	Spec. value	HB	Rp0.2 MPa	Rm MPa	A5 %	KV-J -30°C
	Min.	197	517	655	18	27
	Max.	238				
	Result	235				
L13314	Result	238	525	662	19.50	35
						52
						82



Test bar from product.

Dimensional and visual control: passed

Ultrasonic test acc. to SEP 1921-84 spec. is satisfactory C/c

Steel making (melting) process: UHP-ASEA vacuum-treated.

NACE MR 0175/ISO 15156+API 17K + API 6A PSL3.

HB-E10, Mechanika: ASTM A370 acc.

Grade Of forging: 9.81

30 pc/series.

Executive

Hámor Zoltán
Ellenőrző

Expert



MISKOLC Kiss Ernő u. 17. sz. H-3531

tel:36/46/401-033


fax:36/46/379-199

e-mail: hamor@t-online.hu

PROTOCOL NUMMER: 98-39B5263

HEAT-TREATMENT PROTOCOL		
BUYER: CONTITECH RUBBER INDUSTRIAL Kft. Szeged Budapesti út 10. sz.	Order No. of Buyer: 32259784/13/2	
	Work No. of Buyer:	
PRODUCT: forged	QUANTITY: PIECE 30	No. of drawing: MSO-100597-002/A/H
MATERIAL QUALITY: AISI 4130 CONTI API 6A PSL3	Charge No.: 34939	Test No.:
HEAT-TREATMENT: quenching and tempering Typ of furnace: electric furnace Hardening medium: water		

PROCESS OF HEAT-TREATMENT



Miskolc, Hámor ZRt. 2013-03-26.



Hám-

Kandó
head of heat-treatment

Felado : 61344

gamma controll kft



19/10/13 12:54 Lap: 2


 <p>www.gamma-controll.hu 6750 Algyó, Kálterület 0189 474. hrsz. Tel./Fax.: +36 82 617 400 / 01844</p>		HARDNESS TEST REPORT		Report No: 561/13.
CLIENT: JE-ZO KFT. SZEGED, KÜLTERÜLET, 01408/22.				
TEST EQUIPMENT: TH 160-D Hardness tester				
PROCEDURE: QCP-45-R1				
DESCRIPTION OF COUPLING: coupling(s) after PWHT				
DRAWING NUMBER: MT-3121-3000				
SERIAL NUMBER: 8083; 8084; 8085; 8086				
BRINELL HARDNESS REQUIREMENT	SERIAL NO OF COUPLING	PART OF THE COUPLING	ACTUAL HARDNESS RESULT (HB)	
Min HB 197 Max HB 238	✓ 8083	body	224	
		weld	222	
		flange	236	
		connection face	238	
	✓ 8084	body	213	
		weld	208	
		flange	220	
		connection face	238	
	✓ 8085	body	214	
		weld	214	
		flange	219	
		connection face	222	
	✓ 8086	body	232	
		weld	237	
		flange	238	
		connection face	197	
The coupling(s) conform to API Spec 6A requirements.				
DATE: 2013. október 30.	PREPARED:  Ménési István		APPROVED: GAMMA-CONTROLL KFT. 6750 Algyó, Kálterület 0189 474. hrsz. Addószám: 1109457-2-02 www.gamma-controll.hu Ménési István	


Felado : 61344


gamma controll kft


19/10/13 12:54 Lap: 3

 <p>HARDNESS TEST REPORT</p> <p><small>www.gamma-controll.hu 6750 Algyó, Költérület 01408/14. hrsz. Tel./Fax: +36 52217-00 / 01844</small></p>		<p>Report No: 562/13.</p>	
<p>CLIENT: JE-ZO KFT. SZEGED, KÜLTÉRÜLET, 01408/22.</p>			
<p>TEST EQUIPMENT: TH 160-D Hardness tester</p>			
<p>PROCEDURE: QCP-45-R1</p>			
<p>DESCRIPTION OF COUPLING: coupling(s) after PWHT</p>			
<p>DRAWING NUMBER: MT-3121-3000</p>			
<p>SERIAL NUMBER: 8087; 8088; 8089; 8090</p>			
BRINELL HARDNESS REQUIREMENT	SERIAL NO OF COUPLING	PART OF THE COUPLING	ACTUAL HARDNESS RESULT (HB)
<p>Min HB 197 Max HB 238</p>	✓ 8087	body	213
		weld	216
		flange	220
		connection face	225
	✓ 8088	body	229
		weld	212
		flange	223
		connection face	213
	✓ 8089	body	219
		weld	229
		flange	231
		connection face	238
	✓ 8090	body	207
		weld	210
		flange	226
		connection face	234
<p>The coupling(s) conform to API Spec 6A requirements.</p>			
<p>DATE:</p> <p>2013. október 30.</p>		<p>PREPARED:</p> <p> Ménési István</p>	
		<p>APPROVED: CONTROLL KFT.</p> <p><small>6750 Algyó, Költérület 01408/14. hrsz. Adószám: 11094014-B-06 www.gamma-controll.hu</small></p> <p>Varga Miklós</p>	

 <p>GAMMA-CONTROLL www.gamma-controll.hu 6750 Algyő, külterület 01884/14. hrsz. Tel./Fax.: +36 62/517-400 / 61344 A NAT által MAT-1-1148/2010 sz.úttal akkreditált vizsgálólaboratórium</p>	<p>ULTRAHANG VIZSGÁLATI JEGYZŐKÖNYV</p> <p>ULTRASONIC EXAMINATION REPORT</p>	<p>Vizsgálati szám: Report No.: 513/13</p>
---	--	--

Vizsgálat tárgya / Object of test				Coupling (Body)	
Gyártó Manufacturer		Megrendelő Customer JE-ZO Kft. Szeged			
Gyártási szám Serial-No.		Rendelési szám Order-No. —			
Azonosító jel Identification 8083-8088		Követelmény Requirement ASTM A388			
Geometria kialakítás / Rajzsám Geometric configuration / Drawing-No. MT-3121-3000 $\phi 200 \times \phi 70 \times 491$		Vizsgálati hőkezelés Test heat treatment előtt prior			
Anyagminőség Material AISI 4130 /		Letapogatási irányok Direction of scanning axiális és radiális			
Adagszám Heat-No. 24613 /					
Vizsgálati felület állapota Surface condition forgácsolt machined		Vizsgálati terjedelem Extent of Test 100%			
Vizsgált darabszám Testing pieces 6 db					
Vizsgálati adatok / Examination data					
Készülék típusa Type of US-equipment USM25		Készülék gyári száma Serial-No. Of US-equipment 7875f			
Vizsgálófej(ek) Search unit(s) SEB-2, SEB4H		Frekvencia(k) Frequency(ies) 2 MHz 4 MHz MHz MHz			
Kalibrációs blokk Calibration standard identification ET1,ET2		Erősítés(ek) Gain axiálisan 18 dB dB dB radiálisan 6 dB			
Csatoló közeg Couplant olaj oil		Hanggyengülés Attenuation dB/m			
Értékelés / észlelt kijelzések / Evaluation / recordable indications					
Értékelés Evaluation	X	megfelelő satisfactory		nem megfelelő / not acceptable	
Megjegyzés(ek) Remark(s)					
Hely / kelt Place / date Gamma-Controll Kft. Algyő, 2013.10.17		 Vizsgálatot végezte Tested by Tóth Ákos UT20103090307		GAMMA-CONTROLL KFT. 6750 Algyő, külterület 01884/14. hrsz. Adószám: 11094614-2-06 www.gamma-controll.hu Tel.: 06-30-218-2640 Approved by Benkő Péter - Felelős vezetőh.	

 <p>GAMMA-CONTROLL</p> <p>www.gamma-controll.hu 6750 Algyő, Kőbányai út 01894/14. hrsz. Tel./Fax.: +36 62/517-400 / 61344 A NAT 661 NAT-1-1140/2010 sz. szerinti akkreditált vizsgálólaboratórium</p>	<p>ULTRAHANG VIZSGÁLATI JEGYZŐKÖNYV</p> <p>ULTRASONIC EXAMINATION REPORT</p>	<p>Vizsgálati szám: Report No.: 514/13</p>

Vizsgálat tárgya / Object of test		Coupling (Body)	
Gyártó Manufacturer	Megrendelő Customer	JE-ZO Kft. Szeged	
Gyáriszám Serial-No.	Rendelési szám Order-No.	---	
Azonosító jel Identification	Követelmény Requirement	8089-8090 ASTM A388	
Geometria kialakítás / Rajzszám Geometric configuration / Drawing-No.	Vizsgálati hőkezelés Test heat treatment	előtt prior	
MT-3121-3000 ø200xø70x491	Letapogatási irányok Direction of scanning	axiális és radiális	
Anyagminőség Material	Adagszám Heat-No.	AISI 4130 / 23171 /	
Vizsgálati felület állapota Surface condition	Vizsgálati terjedelem Exted of Test	forgácsolt machined 100%	
Vizsgált darabszám Testing pieces		2 db	
Vizsgálati adatok / Examination data			
Készülék típusa Type of US-equipment	Készülék gyári száma Serial-No. Of US-equipment	USM25 7875f	
Vizsgálófeje(ek) Searc unit(s)	Frekvencia(k) Frequency(ies)	SEB-2, SEB4H 2 MHz 4 MHz MHz MHz	
Kalibrációs blokk Calibration standard identification	Erősítés(ek) Gain	ET1,ET2 axiálisan 18 dB dB dB radiálisan 6 dB	
Csatoló közeg Couplant	Hanggyengülés Attenuation	olaj oil dB/m	
Értékelés / észlelt kijelzések / Evaluation / recordable indications			
Értékelés Evaluation	X	megfelelő satisfactory	nem megfelelő / not acceptable
Megjegyzés(ek) Remark(s)			
Hely / kelt Place / date	 Vizsgálatot végezte Tested by Tóth Ákos UT20103090307		GAMMA - CONTROLL KFT. 6750 Algyő, Kőbányai út 01894/14. hrsz. Adatszám: 21094614-2-06 www.gamma-controll.hu Tel.: 06 30 2178-2640 Approved by Benkő Péter - Felelős vezető

Ex a nyomtatvány részleteiben nem másolható! / Copying details is prohibited!



MAGYAR HEGESZTÉSTECHNIKAI ÉS ANYAGVIZSGÁLATI EGYESÜLÉS
(HUNGARIAN ASSOCIATION OF WELDING TECHNOLOGY AND MATERIAL TESTING)
(Certification Body)

RONCSOLÁSMENTES ANYAGVIZSGÁLÓ TANÚSÍTVÁNY
(Certificate of NDT personnel)

Azonosító szám: **UT20103090307**
(Identification No.):

A tanúsított neve:
(The name and forename of
the certificated individual):
Születési hely/ideje:
(Place and date of birth):

Tóth Ákos József

**Hódmezővásárhely, 1987. 09.
19.**

A tanúsított személy aláírása
(The signature of the certificated individual)

Vizsgálati eljárás(ok):
(The NDT method(s)):

Ultraszónikus anyagvizsgálat
(**Ultrasonic testing**)

Ipari terület:
(Industrial sector):

Készülékek, berendezések, létesítmények vizsgálata EM
(**Pre and in-service testing of equipment, plant and structure**)

Termék terület(ek):
(Product sector(s)):

(c)+Fv, (w)+Fv, (wp)+Fv, (f)+Fv

A minősítés fokozata:
(The level of certification):

UT2

A tanúsítás és kiadásának időpontja:
(The date of certification and its issue):

Budapest, 2009. 12. 07.

A tanúsítás érvényes:
(The date upon which certification expires):

2014. 12. 06.

Tanúsító Testület nevében
(On behalf of certifying body)

Az ipari és/vagy termék terület érvényesség kiterjesztve:
(The industrial and/or product sector has been expanded to):

9/2001 GM, 97/23 EC

Dátum (Date): **2009. 12. 07.**

A tanúsítás érvényessége
(Renewed the validity of the certification until (MSZ EN 473 9.):)

-ig megújítva (MSZ EN 473 9.):

Dátum (Date):

Tanúsító Testület nevében
(On behalf of certification body)



AKKREDITÁLT TANÚSÍTÓ
MACE-5-0013/2006

A Magyar Hegesztéstechnikai és Anyagvizsgálati Egyesülés, mint a Nemzeti Akkreditáló Testület által a NAT-5-0013/2006 számon akkreditált tanúsító testület az MSZ EN 473 számú szabvány szerint eredményes vizsgálata alapján a nevezett személyt tanúsítja a fentiek szerint:
(The Hungarian Association of Welding Technology and Material Testing as an accredited by the National Accreditation Board (under No. NAT-5-0013/2006) certification body, on the basis of his/her successful examination under the standard MSZ EN 473, hereby certifies the named individual according to the above.)

UT20103090307



MAGYAR HEGESZTÉSTECHNIKAI ÉS ANYAGVIZSGÁLATI EGYESÜLÉS
(HUNGARIAN ASSOCIATION OF WELDING TECHNOLOGY AND MATERIAL TESTING)
(Certification Body)

Meghatalmazzuk a tanúsítvány tulajdonosát, hogy vizsgálatokat végezzen és azok eredményéért felelősséget vállaljon.
(MSZ EN 473 3.21)

(The holder of this certificate has been authorised to perform tests and take responsibility for the test results. (MSZ EN 473 3.21))

GAMMA - CONTROLL KFT

6722 Szeged, Gyertyános u. 14-16/A

Adószám: 11024514-006

OTP Bank: 1173806920406154

www.gamma-controll.hu

Tel.: 06 30 216-2640




Munkáltató aláírása:
(Signature of the employer:)

Dátum: 2009.12.07.
(Date:)

Folyamatos munkavégzés igazolása (MSZ EN 473 9.) (Evidence of continued work activity (MSZ EN 473 9.))			
Sorsz.: (No.)	Munkáltató aláírása (Signature of the employer)	GAMMA-CONTROLL (Stamp) Anyagvizsgáló és Minőségellenőrző Kft.	Dátum (Date)
1.		GAMMA-CONTROLL	2010.01.04.
2.		GAMMA-CONTROLL	2011.01.06.
3.		GAMMA-CONTROLL	2012.01.09.
4.		GAMMA-CONTROLL	2013.01.09.
5.		Anyagvizsgáló és Minőségellenőrző Kft.	
6.			
7.			
8.			
9.			
10.			










Kiegészítések:

(Additional remarks:)

 PHOENIX PHOENIX RUBBER INDUSTRIAL LTD.		TECHNICAL DATA SHEET		TDS	Page
		WELDING PROCEDURE SPECIFICATION		WPS	Nº 1 of 2
CLIENT IDENTITY CODE		THIS SPECIFICATION IS BASED ON ASME CODE SECTION IX		WPS Nº 140-71 REV 4 SUPPORTING PQR Nº BUD 0700002/1	
ITEM Qty DATA FOR ACCEPTANCE		WELDING PROCESS: GTAW-SMAW TYPES: MANUAL		PERFORMED BY: WELDER'S STAMP	
JOINTS (QW-402)			  <p>Sequences of weld see on addendum</p>		
JOINT DESIGN		BACKING: YES/NO		WELD SEQUENCE	
BASE METALS (QW-403)		PART „A”		PART „B”	
DRW Nº					
GRADE:		WNo.:1.7220		ASTM A 322-91: AISI 4130 / 34CrMo4 (MSZ EN 10083-1) *	
CARBON EQUIVALENT		max. C _e =		0.82	
MECHANICAL PROPERTIES:					
TENSILE STRENGTH		N/mm ² min.		655	
DUCTILITY		% min.		18	
HARDNESS		HB max.		238	
IMPACT TEST -30°C		J Average		27	
THICKNESS:		t = 5-38 mm		OUTSIDE DIAMETER : ØD = 60-280 mm	
FILLER METALS (QW-404)					
WELD MATERIAL	DIAMETER	BRAND	STANDARD	SUPPLIER	
Rod	2.4 mm	EML 5	AWS A5.18-01: ER70S-3	Böhler	
Electrode	3.2; 4.0	T-PUT NiMo 100**	AWS A 5.5-96: E 10018-D2 (mod.)	Böhler	
LAPSE BETWEEN OF PASSES		MIN./min			
POSITIONS (QW-405)			PREHEAT (QW-406)		
POSITIONS: 1G Rotated (horizontal)			PREHEAT TEMP.: 300-330 °C		
WELDING PROGRESSION: Weld flat at or near to the top			INTERPASS TEMP.: max. 350 °C		
POSITION OF FILLET			PREHEAT MAINTENANCE: Till the begining of postweld heat treating		
OTHER			METHOD OF PREHEATING: Furnace		

CONTINUATION OF WPS N° 140-71 Rev.4						Page N° 2 of 2	
POSTWELD HEAT TREATMENT (QW-407)				GAS (QW-408)			
HOLDING TEMP. RANG 620 +20 / -0 C°				SHIELDING GAS Argon for root			
HOLDING TEMP. TIME 4 HR				PERCENTAGE COMPOSITION (MIXTURE)			
HEATING RATE MAX.:				99.995 %			
COOLING RATE MAX.: 80 °C/HR				FLOW RATE 10-12 LITRES/min.			
LOCATION OF THERMOCOUPLE				GAS BACKING: Argon (for 1st and 2nd passes)			
FURNACE ATMOSPHERE Air				FLOW RATE 7-9 Litres/min			
TYPE:				TRAILING SHIELDING GAS COMP.			
ELECTRICAL CHARACTERISTICS (QW-409)						1st	pass: -
CURRENT DC						ELECTRODE POLARITY : 2nd-28th	passes: +
TUNGSTEN ELEKTRODE SIZE/TYPE: Ø3.2 mm thoriated tungsten							
MODE OF TRANSFER FOR GMAW							
ELECTRODE / WIRE FEED SPEED RANGE							
WELD LAYERS	PROCESS	FILLER METAL CLASS	DIAMETER	CURRENT TYPE POLAR.	AMP. RANGE	VOLT RANGE	HEAT INPUT (KJ/cm)
1	GTAW	EML 5	2.4 mm	-	110-130	11-12	5-8.4
2-3	SMAW	T-PUT NiMo 100	3.2 mm	+	120-140	24-26	12-19.6
4-28	SMAW	T-PUT NiMo 100	4.0 mm	+	150-170	26-30	16.2-27.5
TRAVEL SPEED RANGE 100-130 mm/min							
TECHNIQUE (QW-410)							
STRING OR WEAWE BEAD				ORIFACE OR GAS CUP SIZE Ø9mm			
INITIAL/INTERPASS CLEANING: Brushing, Grinding							
EQUIPMENTS FOR WELDING:							
OTHER:							
EXAMINATION - Acc. to the acceptance instruction N° MIO-FB 2 Based on ASME IX.				REMARKS - * Formerly CMo3 (MSZ 61) - ** Ni content less than 1 % - Before welding bake electrodes for 2 hours at 350 °C			
BY		DATE		TECHNICAL DATA SHEET			
Desig.	Bazlo	14.06.2007	WELDING PROCEDURE SPECIFICATION				HOSE TECHNICAL DEPARTMENT WPS N° 140-71 Rev.4
Appr.	Zetiv	14.06.2007	SUBJECT: Butt weld of hose coupling for H2S service;				
Chek'd			Strenght 75K				

PHOENIX RUBBER Industrial Ltd. Hose Division	N°:	WPS 140-71 Addendum
	Revision:	4
ADDENDUM for the approved wall thickness range 5-38 mm Based on WPS 140-71 Rev.4, PQR No.: BUD 0700002/1	Page N°:	1/2
	Date:	2007-06-12
	Designed:	<i>Bauer</i>
	Checked:	
	Approval:	<i>Seifert</i>





No.	Wall thickness [mm]	Weld layers	Electrode Ø [mm]
1.	5-7	 1 2	3,2 3,2
2.	7-9	 1 2-3	3,2 3,2
3.	9-11	 1 2-3 4-5	3,2 3,2 4,0
4.	11-13	 1 2-3 4-6	3,2 3,2 4,0
5.	13-15	 1 2-3 4-8	3,2 3,2 4,0
6.	15-18	 1 2-3 4-10	3,2 3,2 4,0
7.	18-20	 1 2-3 4-11	3,2 3,2 4,0
8.	20-22,22	 1 2-3 4-15	3,2 3,2 4,0
9.	22,2-26	 1 2-3 4-19	3,2 3,2 4,0

PHOENIX RUBBER Industrial Ltd.

ADDENDUM

for the approved wall thickness range 5-38 mm
Based on WPS 140-71Rev.4, PQR No.: BUD 0700002/1

Nº:	WPS 140-71 Addendum
Revision:	4
Page Nº:	2/2

No.	Wall thickness [mm]	Weld layers	Electrode Ø [mm]
10.	26-29		1 2-3 4-19 3,2 3,2 4,0
11.	29-32		1 2-3 4-23 3,2 3,2 4,0
12.	32-35		1 2-3 4-24 3,2 3,2 4,0
13.	35-38		1 2-3 4-28 3,2 3,2 4,0

Certificate no: 8UD 0700002/1
Page 1 of 2



Welding Procedure Qualification Record (PQR) ASME IX Energy and Transportation

Company Name: Phoenix Rubber Gumilpart Kft. SZEGED

Procedure Qualification Record No. BUD 0700002/1



Date: 28 February 2007

WPS No. 140-71

Welding Process(es) GTAW/SAW

Types (Manual, Automatic, Semi-Auto.) Manual

Joint: (QW-402)



Groove Design for Test Coupon

(For combination qualifications, the deposited weld metal thickness shall be recorded for each filler metal or process used.)

Base Metals (QW-403)

Material Spec. ASTM A 322-91, AISI 4130

Type or Grade AISI 4130

P.No. AISI 4130 to P.No. AISI 4130

Thickness of Test Coupon 19 mm

Diameter of Test Coupon 72 mm

Other

Postweld Heat Treatment (QW-407)

Temperature 620 +20-0 °C

Time 4 hours

Other

Gas (QW-408)

Percent Composition

	Gas(es)	(Mixture)	Flow Rate
Shielding	Ar 99.95%		10-12 l/min
Trailing			
Backing	Ar 99.95%		7-9 l/min

Filler Metals (QW-404)

SFA Specification ER 70S-3

AWS Classification A5.18

Filler Metal F-No. 6

Weld Metal Analysis A-No. 1

Size of Filler Metal 2.4 mm

Other

GTAW SMAW

E 10018-G

A5.5

4

2

3.2, 4.0 mm

Electrical Characteristics (QW-409)

Current DC

Polarity GTAW DCEN, SMAW DCEP

Amps. Layer 1 120, Layer 2-3 127, Layer 4-12 136

Tungsten Electrode Size 3.2 mm

Other

Technique (QW-410)

Travel Speed Layer 1-11 100-130 Layer 12 120 mm/min

String or Weave Bead Layer 1-11 String Layer 12 Weave

Weld Metal Thickness 3 mm 16 mm

Position (QW-405)

Position of Groove 1G rotated

Weld Progression (Uphill, Downhill)

Other

	GTAW	SMAW
Multipass or Single Pass (per side)	S	M
Single or Multiple Electrodes	S	M

Heat input Layer 1 6.0-8.6 KJ/cm Layer 2-3 14.1-19.8 KJ/cm Layer 4-12 18.7-28.1 KJ/cm

Preheat (QW-406)

Preheat Temp. 300-330 °C

Interpass Temp. max 350 °C

Other

Lloyd's Register, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as the 'Lloyd's Register Group'. The Lloyd's Register Group assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register Group entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.

Certificate no: BUD 0700002/1
Page 2 of 2

PQR No. BUD 0700002/1

Tensile Test (QW-150)						
Specimen No.	Width mm	Thickness mm	Area mm ²	Ultimate Total Load kN	Ultimate Unit Stress MPa	Type of Failure & Location
39/1	18.9	15.8		657		Base material
39/2	18.9	15.7		664		Base material

Guided Bend Test (QW-160)

Type and Figure No.
180° Bend roller dia. 36 mm 2+2 pcs

Results
Satisfactory

Toughness Tests (QW-170)

Specimen No.	Notch Location	Specimen Size mm	Test Temp. °C	Impact Value J	% Shear	Mils	Drop Weight Break (Y/N)
39	S	10x10x55	-30	33			
39	S	10x10x55	-30	49			
39	S	10x10x55	-30	41			
39	HAZ	10x10x55	-30	38			
39	HAZ	10x10x55	-30	97			
39	HAZ	10x10x55	-30	62			

Comments:

Ball Penetration (QW-180)

Result- Satisfactory: Yes ☐ No ☐ Penetration into Parent Metal: Yes ☐ No ☐

Macro - Results

Other Tests

Type of Test Hardness test

Deposit Analysis

Other

Macro - Satisfactory
X-ray - Satisfactory

Welder's Name Tivadar Szabo DC-IL 378258

Clock No. (BC 15)

Stamp No.


Test Conducted By: DKG EAST Anyagvizsgalati Labor.

Laboratory Test No: TMO 007-7/07 VJK 1207/2007


We certify that the statements in this record are correct and that the test welds were prepared, welded, and tested in accordance with the requirements of Section IX of the ASME Code.

Date issued: 28 February 2007

Manufacturer's Representative Laszlo Bajusz
Manufacturer Phoenix Rubber Gumipari Kft, SZEGED



A member of the Lloyd's Register Group



Fluid Technology

WELDER'S APPROVAL TEST CERTIFICATE - ASME CODE IX

Examiner or test body: ABS

Registration No.: RK1825997.R1

Designation ASME IX: GTAW / SMAW Pipe BW s19 1G

Welder's name: Tivadar Szabó (BC15)

Identification card No: 517278EA

Date and place of birth: 19. August 1949; SZEGED

		Weld test details	Range of approval	Photo (if required)
Welding process		GTAW/SMAW		
Filler metal	Type	Rod / Electrode		
	Designation	AWS 5.18: ER70S-3 AWS 5.5: E9018		
Parent metal group(s)		ASTM A 322-91; AISI 4130		
Plate or pipe		Pipe	Pipe/Plate	
Welding position		1G	1G/Flat	
Outside diameter (mm)		72 mm	> 25 mm	Identification of test pieces:
Test piece thickness (mm)		19	Max to be welded	
Single/ both side welding		Single		WPS No.: 140-60 Rev.4
Gouging/ backing				
Joint type		Groove	Groove / Fillet	Testing standard: ASME IX
Shielding/ backing gas(es)		Argon (99,95%)		
Welding carried out, place: Szeged			Date: 29 April 2010 Welding Engineer: László Bajusz <i>Bajusz</i>	
Type of test	Performed and accepted	Not required	Place and date:	
Visual	Accepted (Vjk-1739/10)		Szeged, 18-Jun-2010	
Radiography	Accepted (Vjk-1739/10)		Surveyor:	
Ultrasonic		+	Péter Szabó	
Magnetic particle		+	Stamp and signature:	
Penetrant		+		
Macro		+		
Fracture		+		
Bend		+		
Additional tests		+		
See attached page(s) for prolongation by employer every 6 months				



Registration No.: RK1825997.R1

Date and place of birth: 19. August 1949; SZEGED

[illegible]

6728 Szege, Külterület 01408/22 hrsz.
Adószám: 13341039-2-06
Bankszámlaszám:
12067001-00127077-00160001

JE-ZO KFT.

**WELDING LOG SHEET
HEGESZTÉSI MUNKALAP**


WLS N^o.
Szám: 2013. / 2898.
PAGE /oldal 1/1

CLIENT Megrendelő		CONTITECH RUBBER Industrial Kft.		PURCH.ORDER N ^o . Rendelészám		32261598	
CONTRACT N ^o . Kötésszám		SPOOL/JOB N ^o . Özemi m.szám		WPS N ^o . Heg.ut.szám		140-71. Rev. 4. / 7	
NAME OF WEDED PARTS Heg. alkatrész megnevezése		Body + Flange		DRWG N ^o . Rajzszám		WT 3121-3000	
NAME/ N ^o . OF WELDER Hegesztő neve és száma		Szabó Tivador László. D.C. 15.		LOCATION/SHOP Munkavégzés helye		Szege. Töpe széle 6.	
DATE Dátum		2013. 10. 25		QUANTITY Darabszám		8	
SERIAL NUMBERS Sorszámok		8083 - 8090					
1. MATERIAL CONTROL Anyag megfelelés azonosítása	SUBJECT 1 Tárgy 1	body	MATERIAL Anyag	ASTI. 4130.	CAST N ^o . Adagszám	24615, 8093-8094	
	SUBJECT 2 Tárgy 2	Flange	MATERIAL Anyag	ASTI. 4130.	CAST N ^o . Adagszám	034939.	
2. FILLER METAL Elektroda minőség és méret	WELD LAYERS Varratszám		1.	2-3.	4-11.		
	TYPE Típus		FW. 5.	NIMD. 100.	NIMD. 100.		
	DIAMETER Átmérő		2.4.	3.2.	4.		
	FILLER CAST N ^o . Elekt. adagszám		800303.	1124075	1127750.		
3. ELECTRICAL CHARACTERISTICS Elektromos adatok	TYPE POLAR Polaritás		-	+	+		
	VOLT (V)		12.	24.	26.		
	AMPERE (A)		180.	140.	180.		
4. PRE HEAT TREATMENT OF ELECTRODES Elektroda felhasználást megelőző hőkezelése			300. °C		8. Hours		
5. APPLIED SHILDING GAS Alkalmazott védőgáz		TYPE Típus	Argon.		Percentage Composition Tisztaság.	99.95. %	
					Flow Rate Áramlási seb l/min	8.	
6. HEAT TREATMENT (pre-weld) Előmelegítés		300. °C		7. POSITION Helyzet			
				Forgatott.			
8. SPEED OF TRAVELS Hegesztési sebesség		100 ÷ 130. mm/min		9. LAPSE BETWEEN OF PASSES Varratfelrakási szünetek			
				8. min			
10. POSTWELD HEAT TREATMENT Utóhőkezelési adatok		Time Idő	240. min		Temperature Hőmérséklet	Furnace atmosph. Hűtőközeg	Cooling rate Hűlési sebesség
				620. °C		Levegő.	80. °C/H
11. RADIOGRAPHIC TEST CERT. N ^o . Radiográfiai vizsg. biz. száma							
2450/15, 2451/15							
REPAIR Javítás	YES/ Igen			X NO/ Nem			
	PLACE OF DEFECT Hiba helye			TYPE OF DEFECT Hiba típusa			
	METHOD OF REPAIR Javítási módszer						
VISUAL INSPECTION Szemrevételezés							
Megfelelő / Satisfactory.							
REMARKS Megjegyzés							
Fronius. Magic. Wave. 2600.							
Date, end of cooling down time Dátum, kihűlés vége		2013. 10. 26. - 13. óra		WELDING LOG SHEET HEGESZTÉSI MUNKALAP		INSPECTOR Ellenőrző	
				BC 15		6728 Szege, Külterület 01408/22 hrsz. Adószám: 13341039-2-06 Bankszámlaszám: 12067001-00127077-00160001	
						DATE Dátum	
						2013 NOV 04	

Felado : 61344

gamma controll kft

19/10/13 12:50 Lap: 1

 <p>GAMMA-CONTROL</p> <p>www.gamma-controll.hu</p> <p>5760 Albert, Kölcsey út 01594/14. sz. sz. Tel./Fax.: +36 82/517-499 / 51544</p> <p>A NYIT ÉS ZÁRÓ ÉRTÉKELÉS SZÁMA: 813/13</p>	<p>SZEMREVÉTELEZÉSES VIZSGÁLATI JEGYZŐKÖNYV</p> <p>VISUAL EXAMINATION REPORT</p>	<p>Record No. Jegyzőkönyv száma:</p> <p>813/13</p>
---	--	---

Object Tárgy	Coupling welding Csatlakozó hegesztés	Serial No. Gyári szám	8083-8090
Customer Megrendel	JE-ZO Kft. Szeged	Drawing No. Rajzsám	MT-3121-3000
Job Nr. Munkaszám	002/13	Material / Dimension Anyagminőség/méret	AISI 4130 118/77
Quantity Mennyiség	8 db	Extent of examination Vizsgálat terjedelme	100%
Requirements Követelmények	ASME code VIII/1	Heat treatment Hőkezelés	after PWHT
Written Procedure No. Vizsgálati eljárás száma	QCP-09-1	Welder Hegesztő	BC15

Visual examination / Szemrevételezéses vizsgálat

Technique Módszer	Direct visual	-
Instrument Készülék	-	-
Visual aids Segédesszközök	3x magnifying lens	-

Measurement / Mérés

Equipment Készülék		
Instrument Készülék		
Surface temperature A felület hőmérséklete	20 °C	Surface condition Felület állapota
		Lighting intensity Megvilágítás
		1000lx
Test results Eredmények :		
SATISFACTORY		
megfelelő.....8 pc(a)/db		
not accepted		
nem megfelelő.....0 pc(s)/db		
Vizsgálat helye és ideje: Place and date of test:	Vizsgálatot végezte: Tested by:	Áttekintette és jóváhagyta: Reviewed and approved by:
Gamma-Controll Kft. Algyő, 2013.10.30. (10h)	Kis Gábor VT20103130102	GAMMA - CONTROLL KFT. 6750 Algyő, Kollár u. 0154/44-44 Adaszorgó 11044612-2-06 www.gamma-controll.hu Tel: 06-22-622965



MAGYAR HEGESZTÉSTECHNIKAI ÉS ANYAGVIZSGÁLATI EGYESÜLÉS
(HUNGARIAN ASSOCIATION OF WELDING TECHNOLOGY AND MATERIAL TESTING)
(Certification Body)

RONCSOLÁSMENTES ANYAGVIZSGÁLÓ TANÚSÍTVÁNY
(Certificate of NDT personnel)

A tanúsított neve:
(The name and forename of
the certificated individual):
Születési hely/Idő:
(Place and date of birth):

Kis Gábor Balázs
Szeged, 1980. 02. 29.

Azonosító szám:
(Identification No.): **VT20103130102**

A tanúsított személy aláírása
(The signature of the certificated individual)

Vizsgálati eljárás(ok):
(The NDT method(s)):

Szemrevételezéses anyagvizsgáló
(Visual testing)

Ipari terület:
(Industrial sector):

Készülékek, berendezések, létesítmények vizsgálata EM
(Pre and in-service testing of equipment, plant and structure)
(c), (w), (wp), (f)

Termék terület(ek):
(Product sector(s)):

A minősítés fokozata:
(The level of certification):

VT2

A tanúsítás és kiadásának időpontja:
(The date of certification and its issue):

Budapest, 2013. 02. 19.

A tanúsítás érvényes:
(The date upon which certification expires):

2018. 02. 18.

Tanúsító Testület nevében
(On behalf of certifying body)

Vizsgáló
(Examiner)

Az ipari és/vagy termék terület
érvényesség kiterjesztve:
(The industrial and/or product sector has
been expanded to):

Dátum (Date):

Tanúsító Testület nevében
(On behalf of certifying body)

A tanúsítás érvényessége

(Renewed the validity of the certification until (MSZ EN ISO 9712 10.):

-ig megújítva (MSZ EN ISO 9712 10.):

Dátum
(Date):

Tanúsító Testület nevében
(On behalf of certification body)

VT20103130102




MAGYAR HEGESZTÉSTECHNIKAI ÉS ANYAGVIZSGÁLATI EGYESÜLÉS
(HUNGARIAN ASSOCIATION OF WELDING TECHNOLOGY AND MATERIAL TESTING)
(Certification Body)

Meghatalmazzuk a tanúsítvány tulajdonosát, hogy vizsgálatokat végezzen és azok eredményéért felelősséget vállaljon.
(MSZ EN ISO 9712 3.21)

(The holder of this certificate has been authorised to perform tests and take responsibility for the test results. (MSZ EN ISO 9712 3.21))

6726 Szeged, Tűzok u. 8/A
Munkáltató aláírása: Adószám: 11094414-2-067
(Signature of the employer) P Bank: 11735005-20606134
www.gamma-control.hu
Tel.: 06-30-116-3500

Dátum: 2013.02.06.
(Date)


Folyamatos munkavégzés igazolása (MSZ EN ISO 9712 10.) (Evidence of continued work activity (MSZ EN ISO 9712 10.))			
Sorsz.:	Munkáltató aláírása (Signature of the employer)	Ph "GAMMA-CONTROL" Anyagvizsgáló és Minőségellenőrző Kft.	Dátum (Date)
1.			2013.02.06.
2.			
3.			
4.			
5.			
6.			
7.			
8.			
9.			
10.			

Kiegészítések:
(Additional remarks:)

Feladó : 61344

gamma controll kft

19/10/13 12:54 Lap: 1

 GAMMA-CONTROLL <small>www.gamma-controll.hu 6700 Algyő, Kálvária út 01004/H, I. em. Tel/Fax: +36 62/917-400 / 91844 A HAT 0101 HAT-1-11022010 számú elvárások vizsgálati követelménye</small>	RADIOGRÁFIAI VIZSGÁLATI JEGYZŐKÖNYV	Jegyzőkönyv szám: Report No.: 2431/13
	RADIOGRAPHIC EXAMINATION REPORT	Készítés dátuma: Date of report: 2013.10.30

Vizsgálat tárgya: Object:		Coupling		Megrendelő: Client:		JE-ZO Kft. Szeged									
Munkaszám:		—		Rendelési szám:		—									
Job No.:		—		Order No.:		—									
Rajzsám:		MT-3121-3000		Anyagminőség:		AISI 4130									
Drawing No.:		—		Material:		—									
Vizsgálati szabvány:		QCP-13-1		Vizsgálat terjedelme:		100%									
Testing standard:		—		Extent of testing:		—									
Arvóti követelmény:		ASTM E94		Hőkezelés:		After PWHT									
Acceptance criteria:		—		Heat treatment condition:		—									
Kód:		MSZ EN ISO 6520-1		Hegesztési jel:		BC15									
Code:		—		Welder stamp:		—									
Berendezés típusa:		GAMMAT		Képmínőségjelző típusa:		ASTM set B type									
Type of equipment:		—		Type of IQI:		—									
Sugárforrás:		Ir192		Képmínőség jelző helye:		F									
Source:		—		Placement of IQI:		—									
Sugárforrás mérete:		3x1,5mm		Előírt képmínőség:		2% (2-2T)									
Source size:		—		Required IQI:		—									
Aktivitás:		0,4 TBq		Film típusa:		FOMA RS									
Activity:		—		Film Type:		—									
Filmfeldolgozás módja:		Kézi: Automata: X		Fóliafajta és vastagság:		Pb 0,027									
Film processing:		Manual: Automatic: X		Screen type and thick:		—									
Megnevezés Designation	Méret Size	Fényerősség Number of radiograph	Átlagított expozíciós idő Exposure time	Sugárforrás film távolság Source-to-film distance	Film táv. a tárgy sugárforrás felől Distance from source side of object to film	Féltelenség Density	Még vizsgálási idő Expos. Time	Működési Állapot Result	Vizsgálati időpontja Date of test	Hibák/Defects					
										Gáz Porosity A	Salak Slag B	Kötés Lack of fusion C	Gyök Lack of penetration D	Repedés Crack E	Felület Surface F
8083	115/77	4	19	96	19	2,4	0,5	A	10.30.10b						
8084	115/77	4	19	96	19	2,4	0,5	A	10.30.10b						
8085	115/77	4	19	96	19	2,4	0,5	A	10.30.10b						
8086	115/77	4	19	96	19	2,4	0,5	A	10.30.10b						
8087	115/77	4	19	96	19	2,4	0,5	A	10.30.10b						
8088	115/77	4	19	96	19	2,4	0,5	A	10.30.10b						
A filmszámok és varratszámok azonosak, beazonosításuk a megrendelőt terheli. The numbers of the films and welds are identical, their identification is the task of the customer.															
Vizsgálatot végezte: Performed by: Ménesi I. - Szabó T.															
Vizsgálat helye: Place of test: 6750 Algyő, Gamma-Controll Kft. Telephely										Értékelte: Evaluated by: Ménesi István RT20101120107			Jóváhagyta: Gamma-Controll Kft. Algyő, Kálvária út 01004/H, I. em. Tel/Fax: +36 62/917-400 / 91844 www.gamma-controll.hu Üzleti Osztály		


Ez a jegyzőkönyv másolatban nem használható / Copying details is prohibited!

8. változat.2013.07.16

Feladó : 61344

gamma controll kft

19/10/13 12:48 Lap: 1

 GAMMA-CONTROLL www.gamma-controll.hu 6750 Algyő, Kálváriaút 01804/14. hrsz. Tel./Fax: +36 02817-400 / 01804 A RÖK 61344 MÉR: 1 / 19402010 számú algyői vizsgálati jegyzőkönyv	RADIOGRÁFIAI VIZSGÁLATI JEGYZŐKÖNYV RADIOGRAPHIC EXAMINATION REPORT	Jegyzőkönyv szám: Report No.: 2430/13 Kiállítás dátuma: Date of report: 2013.10.30
--	--	---

Vizsgálat tárgya: Object:		Coupling		Megrendelő: Client:		JE-ZO Kft. Szeged	
Munkaszám:		—		Rendelési szám:		—	
Joh No.:		—		Order No.:		—	
Rajzszerző:		MT-3121-3000		Anyagminőség:		AISI 4130	
Drawing No.:		—		Material:		—	
Vizsgálati szabvány:		QCP-13-1		Vizsgálat terjedelme:		100%	
Testing standard:		—		Extent of testing:		—	
Átvételi követelmény:		ASTM E94		Hőkezelés:		After PWHT	
Acceptance criteria:		—		Heat treatment condition:		—	
Kód:		MSZ EN ISO 6520-1		Hegesztési jel:		BC15	
Code:		—		Welder stamp:		—	
Berendezés típusa:		GAMMAMAT		Képmínőségjelző típusa:		ASTM set B type	
Type of equipment:		—		Type of IQI:		—	
Sugárforrás:		Ir192		Képmínőség jelző helye:		F	
Source:		—		Placement of IQI:		—	
Sugárforrás mérete:		3x1,5mm		Képmínőség:		2% (2-2T)	
Source size:		—		Required IQI:		—	
Aktivitás:		0,4 TBq		Film típusa:		FOMA R5	
Activity:		—		Film Type:		—	
Filmfeldolgozás módja:		Kézi: Automatizál: X		Röntgen típusa és vastagság:		Pb 0,027	
Film processing:		Manual: Automatic: X		Screen type and thick:		—	

Megnevezés Designation	Méret Size	Féldetek szám Number of radiographs	Átvételi követelmény Presented thickness	Sugárforrás film vastagság Source-to-film distance	Féldetek a tárgy mag. távolságától Distance from source side of object to film	Féldetek Density	Mérési idő Expos. Time	Mérési mód Exposure mode	Vizsgálati időpontja, dátuma Date of test	Hibák/Defects					
										Porosítás A	Salak B	Kötés C	Gyök D	Repedés E	Felület F
8089	115/77	4	19	96	19	2,4	0,5	A	10.30.10h						
8090	115/77	4	19	96	19	2,4	0,5	A	10.30.10h						
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

A filmszámok és varratszámok azonosak, beazonosításuk a megrendelőt terheli.
The numbers of the films and welds are identical, their identification is the task of the customer.

Vizsgálatot végezte: Performed by:		Ménesi I. - Szabó T.	
Vizsgálat helye: Place of test:		Értékelte: Evaluated by:	
6750 Algyő, Gamma-Controll Kft. Telephely		Ménesi István RT20101120107	
		Jóváhagyta: Approved by: 6750 Algyő, Kálváriaút 01804/14. hrsz. Add: 01804/14-2-96 www.gamma-controll.hu Tel: 02817-400	

Ez a jegyzőkönyv részleteiben nem másolható! / Copying details is prohibited!



MAGYAR HEGESZTÉSTECHNIKAI ÉS ANYAGVIZSGÁLATI EGYESÜLÉS
(HUNGARIAN ASSOCIATION OF WELDING TECHNOLOGY AND MATERIAL TESTING)
(Certification Body)

RONCSOLÁSMENTES ANYAGVIZSGÁLÓ TANÚSÍTVÁNY
(Certificate of NDT personnel)

Azonosító szám: **RT20101120107**
(Identification No.):

A tanúsított neve:
(The name and forename of
the certificated individual):

Ménesi István

Születési hely/ideje:
(Place and date of birth):

Szentes, 1988. 09. 06.

A tanúsított személy aláírása
(The signature of the certificated individual)

Vizsgálati eljárás(ok):
(The NDT method(s)):

Radiográfiai anyagvizsgálat
(Radiographic testing)

Ipari terület:
(Industrial sector):

Készülékek, berendezések, létesítmények vizsgálata EM
(Pre and in-service testing of equipment, plant and structure)

Termék terület(ek):
(Product sector(s)):

(c), (w)

A minősítés fokozata:
(The level of certification):

RT2

A tanúsítás és kiadásának időpontja:
(The date of certification and its issue):

Budapest, 2012. 03. 28.

A tanúsítás érvényes:
(The date upon which certification expires):

2017. 03. 27.

Tanúsító Testület nevében
(On behalf of certifying body)

Vizsgáló
(Examiner)

Az ipari és/vagy termék terület érvényesség kiterjesztve:
(The industrial and/or product sector has been expanded to):

Dátum (Date):

A tanúsítás érvényessége
(Renewed the validity of the certification until (MSZ EN 473 9.):)

ig megújítva (MSZ EN 473 9.):

Dátum (Date):

Tanúsító Testület nevében
(On behalf of certification body)

A Magyar Hegesztéstechnikai és Anyagvizsgáló Egyesülés, mint „a Nemzeti Akkreditáló Testület által a NAT-S-0013/2010 számon akkreditált személytanúsító szervezet” a nevezett személyt tanúsítja az MSZ EN 473 szerint eredményes vizsgálata alapján a fentiek szerint:
(The Hungarian Association of Welding Technology and Material Testing as an “accredited certification body for person an by National Accreditation Board (under No. NAT-S-013/2010”, on the basis of his/her successful examination under the standard MSZ EN 473, hereby certifies the named individual according to the above:)

* c - öntvények (castings); f - kovacsolt termékek (forgings); w - hegesztett kötések-termékek (welded products); t - csövek (tubes); wp - alakított termékek (wrought products); p - műanyag termékek (plastics products); k - kompozitok (composites products).



MAGYAR HEGESZTÉSTECHNIKAI ÉS ANYAGVIZSGÁLATI EGYESÜLÉS
(HUNGARIAN ASSOCIATION OF WELDING TECHNOLOGY AND MATERIAL TESTING)
(Certification Body)

Meghatalmazzuk a tanúsítvány tulajdonosát, hogy vizsgálatokat végezzen és azok eredményéért felelősséget vállaljon.
(MSZ EN 473 3.21)

(The holder of this certificate has been authorised to perform tests and take responsibility for the test results. (MSZ EN 473 3.21))

Munkáltató aláírása:
(Signature of the employer:)

GAMMA-CONTROLL Kft.
6126 Szeged, 18. Belföldi út
Adószám: 11094614-2-06
OTP Bank: 11735005-20406154
www.gamma-control.hu
Tel: 06-30-218-2640

Dátum: 2012. 04. 19.
(Date:)

Folyamatos munkavégzés igazolása (MSZ EN 473 9.) (Evidence of continued work activity (MSZ EN 473 9.))			
Sorsz.: (No.)	Munkáltató aláírása (Signature of the employer)	Ph. "GAMMA-CONTROLL" Anyagvizsgáló és Minőségellenőrző Kft. "GAMMA-CONTROL" Anyagvizsgáló és Minőségellenőrző Kft.	Dátum (Date)
1.			2012. 04. 19.
2.			2013. 06. 09.
3.			
4.			
5.			
6.			
7.			
8.			
9.			
10.			

Kiegészítések:
(Additional remarks:)

ContiTech Rubber Industrial Kft. Szeged/Hungary		Examination record Vizsgálati jegyzőkönyv Liquid penetrant examination Festékdifúziós vizsgálat <input checked="" type="checkbox"/> Magnetic particle examination Mágneses repedésvizsgálat		Record No. Jegyzőkönyv száma : 1222/13	
Manufacturer Gyártó		JE-ZO Kft.		Serial No. Gyári szám	
Customer Megrendelő		ContiTech Rubber Industrial Kft.		8083-8090	
Object Tárgy		coupling(s)		Drawing No. Rajzszám	
Quantity Mennyiség		8 pc(s)		MT 3121-3000	
Requirements Követelmények		ASTM E 709		Material Anyagminőség	
Written Procedure No. Vizsgálati eljárás száma		QCP-11-1		AISI 4130	
				Extent of examination Vizsgálat terjedelme	
				100 % outside	
				Heat treatment Hőkezelés	
				yes	
				Welder: Hegesztő:	
				Szabó T.	
Liquid penetrant examination /Folyadékbehatolásos vizsgálat					
Penetrant Behatoló anyag		Remover Tisztító		Developer Előhívó	
Dwell time Behatolási idő		Drying Szárítás		Developing time Előhívási idő	
Surface temperature A felület hőmérséklete		Surface condition Felület állapota		Lighting intensity Megvilágítás	
Magnetic particle examination/Mágnesezhető poros vizsgálat					
Equipment type Készülék típusa		Testing material Vizsgáló anyag		Magnetizing current Mágnesező áram	
TSW 1000		MR 76F		1000 A	
Black light type UV-A lámpa típusa		Field strength checking Téroró mérő		Field strength Téroró	
Superlight C 10A-HE		Berthold disc		4,2 kA/m	
Surface temperature A felület hőmérséklete		Surface condition Felület állapota		Lighting intensity Megvilágítás	
23 °C		machined		1000 µW/cm²	
Test results Eredmények :					
satisfactory megfelelő.....8..... pc(s)/db					
not accepted nem megfelelő.....-..... pc(s)/db					
Performed by NDE Level II. Vizsgálatot végezte			Revised by Q.C. manager Ellenőrizte – MEO vezető		
Signature Aláírás			Signature Aláírás		
Oravec Gábor			Markó László		
Place/Date Kelt			Place/Date Kelt		
Szeged, 04.11.2013.			Szeged, 04.11.2013.		



MAGYAR HEGESZTÉSTECHNIKAI ÉS ANYAGVIZSGÁLATI EGYESÜLÉS
(HUNGARIAN ASSOCIATION OF WELDING TECHNOLOGY AND MATERIAL TESTING)
(Certification Body)

RONCSOLÁSMENTES ANYAGVIZSGÁLÓ TANÚSÍTVÁNY
(Certificate of NDT personnel)

Azonosító szám: **MT20103010506Ú**
(Identification No.):

A tanúsított neve:
(The name and forename of
the certificated individual):

Oravecz Gábor

Születési hely/idő:
(Place and date of birth):

Szeged, 1958. 07. 07.

A tanúsított személy aláírása
(The signature of the certificated individual)

Vizsgálati eljárás(ok):
(The NDT method(s)):

**Mágnesezhető poros anyagvizsgáló
(Magnetic particle testing)**

Ipari terület:
(Industrial sector):

**Fémfeldolgozás MM
(Metal manufacturing)**

Termék terület(ek):
Product sector(s):

(c), (f), (w), (wp)

A minősítés szintje:
(The level of certification):

MT2

A tanúsítás és kiadásának időpontja:
(The date of certification and its issue):

Budapest, 2012. 02. 21.

A tanúsítás érvényes:
(The date upon which certification expires):

2017. 02. 20.

Tanúsító Testület nevében
(On behalf of certifying body)

Vizsgáztató
(Examiner)

Az ipari és/vagy termék terület érvényesség kiterjesztve:
(The industrial and/or product sector has been expanded to):

Dátum (Date):

Tanúsító Testület nevében
(On behalf of certifying body)

A tanúsítás érvényessége
(Renewed the validity of the certification until (MSZ EN 473 9.):)

-ig megújítva (MSZ EN 473 9.):

Dátum (Date):

Tanúsító Testület nevében
(On behalf of certification body)

A Magyar Hegesztéstechnikai és Anyagvizsgáló Egyesülés, mint „a Nemzeti Akkreditáló Testület által a NAT-5-0013/2010 számon akkreditált személytanúsító szervezet” a nevezett személyt tanúsítja az MSZ EN 473 szerint eredményes vizsgálja alapján a fentiek szerint:
(The Hungarian Association of Welding Technology and Material Testing as an “accredited certification body for person an by National Accreditation Board (under No. NAT-5-013/2010”, on the basis of his/her successful examination under the standard MSZ EN 473, hereby certifies the named individual according to the above:)

* c - öntvények (castings); f - kovacsolt termékek (forgings); w - hegesztett kötések-termékek (welded products); t - csövek (tubes); wp - alakított termékek (wrought products); p - műanyag termékek (plastics products); k - kompozitok (composites products).

MT20103010506Ú



MAGYAR HEGESZTÉSTECHNIKAI ÉS ANYAGVIZSGÁLATI EGYESÜLÉS
(HUNGARIAN ASSOCIATION OF WELDING TECHNOLOGY AND MATERIAL TESTING)
(Certification Body)

* Meghatalmazzuk a tanúsítvány tulajdonosát, hogy vizsgálatokat végezzen és azok eredményéért felelősséget vállaljon.
(MSZ EN 473 3.21)

(The holder of this certificate has been authorised to perform tests and take responsibility for the test results. (MSZ EN 473 3.21))

Munkáltató aláírása:
(Signature of the employer:)

[Handwritten signature]

Dátum:
(Date:)

2012. 02. 21.

Folyamatos munkavégzés igazolása (MSZ EN 473 9.) (Evidence of continued work activity (MSZ EN 473 9.))			
Sorsz.:	Munkáltató aláírása (Signature of the employer)	Ph. Contitech Rubber Industrial Kft. Quality Control Dept. (1)	Dátum (Date)
1.	<i>[Handwritten signature]</i>		2013. 01. 24.
2.			
3.			
4.			
5.			
6.			
7.			
8.			
9.			
10.			

Kiegészítések:
(Additional remarks:)

Bekaert Hlohovec a.s.

Mierová 2317

92028 Hlohovec / Slovakia

Tel.: 00421337383111

Fax: 00421337422742

505760

STEELCORD
MANUFACTURER : BKHL

Page : 1 / 1

Certificate of Analysis

Delivery No. : 4046181212

Contitech Rubber Industrial Kft.
CONTITECH RUBBER IND SZEGED
Budapesti út 10
H-6728 SZEGED

Sales Order 3046059220/10
Purchase Order 32260330
Inspection lot 090000200665/000001
Batch 3500245379
Date produced 01.07.2013
Date COA 09.08.2013
Spools 32 delivered from a batch of 32 produced
Units 18 delivered from a batch of 18 produced
Delivery net Qty. 10517 KG
Material Description Zinc coated steelcord 1X24DW/3.6 NT 20/36 ZZ B650
5000 M
Lay direction ZZ
Lay length 20/36

Spec customer Contitech Rubber Industrial Kft.
Your code 14-18-07/1
Your spec REV.3 / 15.01.2002
Our Spec H207297 / 26.10.2012

Tests			Specs		Results		
Test	Procedure	Unit	Alm	Min. Max.	Avg. N	Min ind Max ind	
Cord diameter	RA12-100	mm	3,6000	3,4200 3,7800	3,6845 6	3,6840 3,6930	
Linear density	RA30-110	g/m	65,000	61,700 68,300	65,632 6	65,300 65,870	
Cord breaking strength	RA30-203	N		17900,0	19337,0 6	19087,0 18584,0	
Cord elongation at break	RA30-203	%		2,50	2,98 6	2,80 3,15	
Zinc D1	RA40-741	g/m2		32,000	40,057 6	37,870 44,630	
Zinc D2	RA40-741	g/m2		44,000	48,788 6	45,350 55,100	
Residual torsions	RA30-150	Nt	0,000	-3,000 3,000	-0,260 6	-0,500 0,000	

Comments :

D1: 0,54

D2: 0,73

Nominal Chemical composition of High Grade Oxysteel:

%Carbon : 0.70-0.90

%Manganese: 0.40-0.60

%Silicon: <0.230

%S: <0.011

%P: <0.012

Microstructure/Texture: Metallurgically the texture is known as a highly drawn, fine perlite structure.



Conforme a EN.10204/ 3.1

n° : **63892/2012**

pecifica/Specification:
 10088-2

Destinatario/Receiver:
 ACCIAI VENDER S.P.A.
 VIA A. NOBEL, 3/A
 43100 PARMA

Cliente/Customer: ACCIAI VENDER S.P.A.
 VIA A. NOBEL, 4/A Q.RE IND.LE S.P.I.P
 43100 PARMA
 Acciaio/Steel: 304PS

DEL. NOTE : 16753 DEL/OF: 24/05/2012 Ordine/order Terninox : P04249 Ord. Cliente/Customer :

ricola ial Number	Pos Item	Tipo Prodotto Product Type	Fin	Descrizione Description	Dimensioni(mm) Dimensions(mm)	Pezzi Pieces	Weight (Kg)	Rif. Cli. Cust. Ref.	Colata Heat	NIM
197 <i>T-13882</i>	22	COIL	2B		0.60 x 460.0	1	6040		0431359	310727
189 <i>T-13887</i>	27	NASTRI STRETTI	BA		0.79 x 284.7	1	1290		0431741	324612

TERIALE SOPRA ELENCATO E' STATO DIMENSIONALMENTE E/O SUPERFICIALMENTE TRASFORMATO DA TERNINOX SENZA ALTERARNE LE CARATTERISTICHE MECCANICHE E CHIMICHE
 MATERIAL DESCRIBED ABOVE HAS BEEN DIMENSIONALLY AND/OR SUPERFICIALLY TRANSFORMED BY TERNINOX WITHOUT CHANGING THE MECHANICAL AND CHEMICAL FEATURES

lisi di colata/Chemical Composition

Colata/Heat	C %	Si %	Mn %	P %	S %	Cr %	Ni %	Mo %	N %	Ti %	Cu %	Nb %	B %	Al %	Co %
0431359	0.045	0.300	1.290	0.027	0.001	18.000	9.040	0.260	0.024		0.310				
0431741	0.048	0.310	1.420	0.029	0.001	18.080	9.050	0.320	0.019		0.370				

dati delle prove/Test Result (1N/mm²=1 M Pa)

NIM	T	T	Caric. unit. snervamento Yield strenght		Caric. unit. Rottura Tensile strength		Allungamento a rottura Ultimate elongation (%)			Durezza Hardness	Piega a Bend To 180°	Trat. termico Ricott. di solub./ heat treatment of annealing for solubiliz.	Resistenza alla corrosione intergranulare secondo / Resistance to corrosion intergranulare	Grano Grain
			Rp02% N/mm²	Rp1% N/mm²	Rm N/mm²	Lo =2"	Lo =80	Lo =A5	HRB					
310727	T	T	245	271	607		80.7		70.5			1050	EN ISO 3651-2	
324612	C	T	230	261	604		62.8		66.0					
	T	T	235	262	588		62.4		70.5			1050	EN ISO 3651-2	
	C	T	237	267	605		62.1		72.0					

dati e fisici sopra riportati sono tratti dal certificato di qualità del nostro fornitore qualificato il cui originale è in nostro possesso e disponibile su richiesta.
 and physical data reported above are extracted from quality certificate emitted from our qualified supplier; the original document is in our posses and it is
 upon your request.

me che i prodotti sopra elencati sono conformi alle prescrizioni d'ordine/We certify that products listed above are compliant to order prescriptions

ITAL INOX
 HUNGARIA KFT.
 1184 Budapest, Laktany út 42/A
 Tel: 097-1690, 291-6239 Fax: 290-5067
 Addesim: 12141537-2-43
 BAE SA 18000080-00000005-01-2011/14

COMPLIES WITH ED 2000/53/EC

Certificato emesso automaticamente

Data/Date 24/05/2012

R. GOVONI

25 mm

OUTSIDE STRIP WOUND TUBE

CONTITECH RUBBER
 Industrial Kft.

No: QC-DB- 651 /2013
 Page: 41 / 44

500/124
 506320

Spring
 Top
 Bottom

(2) Seta
 T = Trasversale - Transverse
 L = Longitudinale - Longitudinal



MKEH

Metrológiai Hatóság/Metrology Authority
Mechanikai Mérések Osztály
Section of Mechanical Measurements
BUDAPEST XII., NEMETVÖLGYI ÚT 37-39.
1535 Budapest, Pf. 919
Telefon: 458-5800
Telefax: 458-5927

Ügyiratszám / File No.:

MKEH-MH/00287-003/2013/NY

Bizonyítványszám / Certificate No.:

NYO - 0008/2013

Hivatkozási szám / Reference No.:

32259470

Page 1/3 oldal

Kiadva / Issued

Budapest, 2013. 01. 28. / 28 01 2013

KALIBRÁLÁSI BIZONYÍTVÁNY
CALIBRATION CERTIFICATE

A kalibrálás tárgya:

villamos kimenőjelű nyomásmérő

Object of calibration:

electrical-output manometer

Gyártó / Manufacturer:

AFRISO-EURO-INDEX GmbH

Típus / Type:

DMU03 HD

Azonosító szám / Serial No.:

1518086

Műszaki adatok / Technical data:

(0...2500) bar méréstartomány / measuring range (0...2500) bar

(4...20) mA kimenőjel tartomány / output signal range (4...20) mA

Kalibrálásra bemutatta:

ContiTech Rubber Industrial Kft.

Customer:

6728 Szeged, Budapesti út 10.

A kalibrálás helye és ideje:

Magyar Kereskedelmi Engedélyezési Hivatal

Place and date of calibration:

Hungarian Trade Licensing Office

Metrológiai Hatóság, Mechanikai Mérések Osztály

Metrology Authority, Section of Mechanical Measurements

Budapest, 2013.01.24.

A kalibrálást végezte:

Calibrated by:

Szaulich Dénes

metrológus / metrologist

A kalibrálásnál alkalmazott etalonok:

Standards used for the calibration:

Megnevezés:	Gyártó:	Típus:	Gyártási szám:	Bizonyítvány szám:
Designation:	Manufacturer:	Type:	Serial No.:	Certificate No.:
túlnyomás etalon / pressure standard	Budenberg	283	20603	NYO-0001/2013
digitális multiméter / digital multimeter	Keithley	2000	0597910	ELD-0014/2012
normál ellenállás / resistance standard	ZIP	P 331	117530	ELD-0021/2012
hőmérő / temperature measuring instr.	GANZ MM	DTH1	33656	Hőm-0296/2012

A mérési eredmények a nemzeti (nemzetközi) etalonra visszavezetettek.

The measuring results are traceable to national standards.

A kalibrálás módja:

Calibration method:

A kalibrálást a KE NYO-3-2002 számú kalibrálás eljárás alapján végeztük.

The calibration was done according to the calibration procedure No.: KE NYO-3-2002.



This certificate is consistent with Calibration and Measurement Capabilities (CMCs) that are included in Appendix C of the Mutual Recognition Arrangement (MRA) drawn up by the International Committee for Weights and Measures (CIPM). Under the MRA, all participating institutes recognize the validity of each other's calibration and measurement certificates for the quantities, ranges and measurement uncertainties specified in Appendix C (for details see <http://www.bipm.org>).



MKEH
Metrológiai Hatóság/Metrology Authority
Mechanikai Mérések Osztály
Section of Mechanical Measurements

Ügyiratszám / File No.:

MKEH-MH/00287-003/2013/NY

Bizonyítványszám / Certificate No.:

NYO - 0008/2013

Page 2/3 oldal

A kalibrálás körülményei:**Calibration conditions:**

környezeti hőmérséklet / Ambient temperature

21,1 °C

a kalibrált eszköz helyzete / Position of the calibrated manometer

függőleges / vertical

a kalibrált eszköz tápfeszültsége / Supply voltage of the calibrated manometer

24V DC

nyomóközeg / Pressure transfer medium

olaj / oil

Mérési eredmények a (0...2500) bar nyomástartományban:**Results of the measurements in the pressure range of (0...2500) bar:**

Nyomás, névleges érték <i>Pressure, nominal value</i> bar	Áram-kimenőjel, névleges érték <i>Current-Output, nominal value</i> mA	Áram-kimenőjel, mért eltérés a helyes értéktől <i>Current-Output, measured deviation from the reference value</i> mA	Nyomás, mért eltérés a helyes értéktől <i>Pressure, measured deviation from the reference value</i> bar	Eredő mérési bizonytalanság <i>Expanded uncertainty of the measurement</i> bar
0	4,0	-0,0042	-0,7	2,6
250	5,6	-0,0002	0,0	
500	7,2	0,0029	0,5	
750	8,8	0,0050	0,8	
1000	10,4	0,0063	1,0	
1250	12,0	0,0053	0,8	
1500	13,6	0,0033	0,5	
1750	15,2	-0,0003	-0,1	
2000	16,8	-0,0052	-0,8	
2250	18,4	-0,0117	-1,8	
2500	20,0	-0,0192	-3,0	

Mérési bizonytalanság: A mérési eredmény(ek) mellett közölve.*Uncertainty of measurement:* See next to the results of the measurements.

A közölt kiterjesztett mérési bizonytalanság a standard bizonytalanságnak k kiterjesztési tényezővel szorzott értéke ($k = 2$), amely normális (Gauss) eloszlás feltételezésével közelítőleg 95%-os fedési valószínűségnek felel meg.

The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to coverage probability of approximately 95 %.

A mérési bizonytalanság tartalmazza az etalonból, a kalibrálás módszeréből, a környezeti feltételekből, a kalibrált mérőeszközből stb. eredő részbizonytalanságokat.

It contains the uncertainties of the standards, calibration method, environmental conditions, calibrated device etc.

A standard bizonytalanság meghatározása az EA-4/02 (Expression of the Uncertainty of Measurement in Calibration) kiadványnak megfelelően történt.

The standard uncertainty of measurement has been determined in accordance with the EA Publication EA 4/02 (Expression of the Uncertainty of Measurement in Calibration).



MKEH

Metrológiai Hatóság/Metrology Authority
Mechanikai Mérések Osztály
Section of Mechanical Measurements

Ügyiratszám / File No.:

MKEH-MH/00287-003/2013/NY

Bizonyítványszám / Certificate No.:

NYO - 0008/2013

Page 3/3 oldal

Bélyegzés:

Calibration mark:

A kalibrált mérőeszközön **K067662** azonosító számú kalibrálási bélyeget helyeztünk el.

We have placed a calibration stamp No.: K067662 on the calibrated instrument.

Megjegyzések:

Additional remarks:

Jelen bizonyítvány összhangban van a Nemzetközi Súly és Mértékügyi Bizottság (CIPM) Kölcsonös Elismerési Megegyezése (MRA) C függeléke által tartalmazott kalibrálási és mérési képességekkel (CMCs). Az MRA minden aláíró intézete elismeri egymás kalibrálási és mérési bizonyítványait a C függelék szerinti mennyiségfajtákra, azok értéktartományaival és mérési bizonytalanságaival (közelebbit lásd: <http://www.bipm.org>)

This certificate is consistent with Calibration and Measurement Capabilities (CMCs) that are included in Appendix C of the Mutual Recognition Arrangement (MRA) drawn up by the International Committee for Weights and Measures (CIPM). Under the MRA, all participating institutes recognize the validity of each other's calibration and measurement certificates for the quantities, ranges and measurement uncertainties specified in Appendix C (for details see <http://www.bipm.org>)

A kalibrálási bizonyítványban megadott értékek a mérőeszköznek a kalibrálás idejére és körülményeire jellemző adatai.

The measurement results show the metrological properties of the device during the time of the calibration under the environmental conditions listed above.

Az újrakalibrálás időpontját a felhasználó dönti el a mérőeszköz használatának és állapotának függvényében.

The date of the next calibration is decided by the user. It depends on the usage and the condition of the device.

A bizonyítvány kiadható / Approved by:



Kálóczi László

osztályvezető / Head of Section

Requested Exceptions

- Variance is requested to connect the BOP choke outlet to the choke manifold using a co-flex line (instead of using a 4" OD steel line) with a 10,000 psi working pressure that has been tested to 15,000 psi and is built to API Spec 16C. Once the flex line is installed it will be tied down with safety clamps.
- Variance is requested to allow Option of rig not capable of reaching TD presetting Surface, Drilling Plan will be same using Fresh Water fluid system.
- Variance is requested to wave any centralizer requirements on the 5-1/2" casing. Ameredev will utilize cement expansion additives in the cement slurry to maximize cement bond and zonal isolation.
- Variance is requested to wave any centralizer requirements on the 9-5/8" casing. Ameredev will utilize cement expansion additives in the cement slurry to maximize cement bond and zonal isolation.
- Variance is requested to allow Temporary Postponement of Operations on well to skid to adjacent well if multiple wells on drilling pad are drilled.
- Variance is requested to allow use of Multi-Bowl Well Head System.
- Variance is requested to allow adjustment of Casing Design Safety Factor on conditions that Ameredev keeps minimum of 1/3 casing capacity filled with OMW drilling fluids.
- Variance is requested to allow 5M Annular Preventer on 10M BOPE System to drill Production Interval. (Supporting Documentation Attached)



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

PWD Data Report

05/03/2019

Section 1 - General

Would you like to address long-term produced water disposal? NO

Section 2 - Lined Pits

Would you like to utilize Lined Pit PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Lined pit PWD on or off channel:

Lined pit PWD discharge volume (bbl/day):

Lined pit specifications:

Pit liner description:

Pit liner manufacturers information:

Precipitated solids disposal:

Describe precipitated solids disposal:

Precipitated solids disposal permit:

Lined pit precipitated solids disposal schedule:

Lined pit precipitated solids disposal schedule attachment:

Lined pit reclamation description:

Lined pit reclamation attachment:

Leak detection system description:

Leak detection system attachment:

Lined pit Monitor description:

Lined pit Monitor attachment:

Lined pit: do you have a reclamation bond for the pit?

Is the reclamation bond a rider under the BLM bond?

Lined pit bond number:

Section 3 - Unlined Pits

Would you like to utilize Unlined Pit PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Unlined pit PWD on or off channel:

Unlined pit PWD discharge volume (bbl/day):

Unlined pit specifications:

Precipitated solids disposal:

Describe precipitated solids disposal:

Precipitated solids disposal permit:

Unlined pit precipitated solids disposal schedule:

Unlined pit precipitated solids disposal schedule attachment:

Unlined pit reclamation description:

Unlined pit reclamation attachment:

Unlined pit Monitor description:

Unlined pit Monitor attachment:

Do you propose to put the produced water to beneficial use?

Beneficial use user confirmation:

Estimated depth of the shallowest aquifer (feet):

Does the produced water have an annual average Total Dissolved Solids (TDS) concentration equal to or less than that of the existing water to be protected?

TDS lab results:

Geologic and hydrologic evidence:

State authorization:

Unlined Produced Water Pit Estimated percolation:

Unlined pit: do you have a reclamation bond for the pit?

Is the reclamation bond a rider under the BLM bond?

Unlined pit bond number:

Unlined pit bond amount:

Additional bond information attachment:

Section 4 - Injection

Would you like to utilize Injection PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Injection PWD discharge volume (bbl/day):

Injection well type:

Injection well number:

Assigned injection well API number?

Injection well new surface disturbance (acres):

Minerals protection information:

Mineral protection attachment:

Underground Injection Control (UIC) Permit?

UIC Permit attachment:

Injection well name:

Injection well API number:

Section 5 - Surface Discharge

Would you like to utilize Surface Discharge PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Surface discharge PWD discharge volume (bbl/day):

Surface Discharge NPDES Permit?

Surface Discharge NPDES Permit attachment:

Surface Discharge site facilities information:

Surface discharge site facilities map:

Section 6 - Other

Would you like to utilize Other PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Other PWD discharge volume (bbl/day):

Other PWD type description:

Other PWD type attachment:

Have other regulatory requirements been met?

Other regulatory requirements attachment:



**U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT**

Bond Info Data Report

05/03/2019

Bond Information

Federal/Indian APD: FED

BLM Bond number: NMB001478

BIA Bond number:

Do you have a reclamation bond? NO

Is the reclamation bond a rider under the BLM bond?

Is the reclamation bond BLM or Forest Service?

BLM reclamation bond number:

Forest Service reclamation bond number:

Forest Service reclamation bond attachment:

Reclamation bond number:

Reclamation bond amount:

Reclamation bond rider amount:

Additional reclamation bond information attachment: