			Q.				
Form 3160-5 (June 2015) UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT SUNDRY NOTICES AND REPORTS ON VIELS Do not use this form for proposals to drill or thre-enter an abandoned well. Use form 3160-3 (APD) for such proposals. SUBMIT IN TRIPLICATE - Other instructions on page 2					FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018		
SUNDRY NOTICES AND REPORTS ON WELLS					5. Lease Serial No. NMNM97151		
BUREAU OF LAND MANAGEMENT SUNDRY NOTICES AND REPORTS ON VELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.					6. If Indian, Allottee or	Tribe Name	
SUBMIT IN TRIPLICATE - Other instructions on page 2					7. If Unit or CA/Agreement, Name and/or No.		
1. Type of Well Gas Well Other					8. Well Name and No. FLAGLER 8 FED 4H		
2. Name of Operator Contact: REBECCA DEAL DEVON ENERGY PRODUCTION CONTRACT: Rebecca.Deal@dvn.com				9. API Well No. 30-025-45258-00-X1			
3a. Address 3b. Phone No 333 WEST SHERIDAN AVENUE Ph: 405-22 OKLAHOMA CITY, OK 73102 Ph: 405-22			o. (include area code) 28-8429	,	10. Field and Pool or Exploratory Arca WC025G09S253309A-UPR WOLFCAM		
4. Location of Well (Footage, Sec., 7			11. County or Parish, S	State			
Sec 8 T25S R33E SWSE 180 32.138348 N Lat, 103.591370		LEA COUNTY, NM					
12. CHECK THE A	PPROPRIATE BOX(ES)	TO INDICA	TE NATURE O	F NOTICE,	REPORT, OR OTH	ER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION						
□ Notice of Intent	Acidize	ze 🗋 Deepen 🖸		Producti	on (Start/Resume)	UWater Shut-Off	
Subsequent Report	Alter Casing		raulic Fracturing D Reclar		tion	Well Integrity	
	Casing Repair			Recomplete		Drilling Operations	
Final Abandonment Notice			g and Abandon g Back	 Temporarily Abandon Water Disposal 		Drining Operations	
Attach the Bond under which the wo following completion of the involved usting has been completed. Final Al determined that the site is ready for f Drilling Operations Summary (10/29/2018 - 11/23/18) Spuc BTC csg, set @ 1175.6'. Tail cmt to surf. PT BOPE 250/50 OK. (11/23/18 - 12/4/18) TD 9-7/8 11,863.7'. Lead w/ 680 sx cm 540 bbls BW. Circ 345.88 sx pumps 250/7000, all for 10min	d operations. If the operation re- bandonment Notices must be fil inal inspection. d @ 15:30. TD 14-3/4" ho w/ 757 sx CIH, yld 1.33 c 00 psi, held each test for ble @ 11,876'. RIH w/ it, yld 4.71 cu ft/sk. Tail w cmt to surf. PT BOPE 25	sults in a multip cd only after all u ft/sk. Disp 10 min, OK. / 261 jts 7-5/8 // 501 sx cmt, 0/10000psi, f	le completion or reco requirements, includ RIH w/ 29 jts 10- w/ 109bbls BW. PT csg to 1500 p " 29.7# P-110 BT yld 1.33 cu ft/sk ower Kelly valve	mplction in a n ling reclamation 3/4" 45.50# Circ 177sx osi for 30 min TC csg, set (. Disp w/	cw interval, a Form 3160 , have been completed at J-55 ns,)-4 must be filed once	
	# Electronic Submission For DEVON ENERG nmitted to AFMSS for proce	SY PRODUCTI	ON COMPAN, sei	nt to the Hob n 01/07/2019	bs (19PP0704SE)		
Namc (Printed/Typed) REBECCA DEAL			Title REGUL	ATORY CO	MPLIANCE PROFES	SSI	
Signature (Electronic S	Submission)		Date 12/21/20	018			
<u> </u>	THIS SPACE FO	DR FEDERA		OFFICE US	SE		
ACCEPTED			JONATHON SHEPARD TitlePETROELUM ENGINEER			Date 01/29/2019	
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.			Office Hobbs				
Title 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent				willfully to ma	ke to any department or a	agency of the United	
(Instructions on page 2)							

*** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED **

Additional data for EC transaction #448773 that would not fit on the form

32. Additional remarks, continued

(12/4/18 - 12/15/18) TD 6-3/4" hole @ 17,237'. RIH w/ 368 jts 5-1/2" 20# P110EC csg & 3 jts 4-1/2" 13.5# P-110 csg, set @ 17,188'. Lead w/ 302sx cmt, yld 1.39 cu ft/sk. Tail w/ 180 sx CIPOZ MIX, yld 1.18 cu ft/sk. Disp w/ 381 bbls disp. TOC @ surf. Install packoff & tst seals to 10,000psi for 10min, ok. RR @ 12:30 MST.