District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410

State of New Mexico Energy, Minerals and Natural Resources Department

Submit Original to Appropriate District Office

Oil Conservation Division 1220 South St. Francis Dr.

HOBBS OCD

1220 S. St. Francis Dr., Sania Fe, N	IN 67303	1	Santa Fe, N.	M 87505		
**		GAS CAPTURE PLAN			MAY	282019
Date: 05/29/19					RE	CEIVED
☑ Original	Operator & OGRID No.: Mewbourne Oil Company - 14744					
☐ Amended - Reason for A	Amendment:	-				:
This Gas Capture Plan out new completion (new drill,				o reduce we	ell/production	facility flaring/venting
Note: Form C-129 must be sub	mitted and app	proved prior to excee	eding 60 days a	Illowed by Rui	le (Subsection)	4 of 19.15.18.12 NMAC).
Well(s)/Production Facility	tv – Name of	f facility				
The well(s) that will be located						
Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
Red Hills West 21 WOAP Fed Com #3H	30-025-42912	A, Sec 21-26S-32E	185 N & 650 W	0	NA	Online after frac
			<u> </u>		• · · · · · · · · · · · · · · · · · · ·	
Gathering System and Pi					1-4- 'C	
Well(s) will be connected to place. The gas produced	o a produciio	n racility after it	owback oper	ations are c	omplete, if g	gas transporter system is
Western low/h	ob pressure	gathering system	n located in	western (County New	Mexico It will requi
						ourne Oil Company provid
(periodically) to Western	а	drilling, completion	on and estima	ted first prod	luction date for	or wells that are scheduled
be drilled in the foreseeabl	e future. In	addition, Mewbo	ourne Oil Co	mpany and	Western	have period
conference calls to discuss	changes to	drilling and com	apletion sche	dules. Gas	from these	wells will be processed
						ounty, Texas. The actual flo
of the gas will be based on co	ompression of	perating parameters	s and gatherin	g system pre	ssures.	
Flowback Strategy						
After the fracture treatment	/completion	operations, well(s) will be pro-	duced to tem	porary produ	action tanks and gas will
			, 55 p. 6.		-F , P	TOTAL TOTAL STATE

flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on Gastaransporter system at that time. Based on current information, it is Operator's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - o Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines