

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised July 18, 2013

WELL API NO.
30-025-45761

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
320644

7. Lease Name or Unit Agreement Name
BANDIT 29 STATE COM

8. Well Number 601H

9. OGRID Number
7377

10. Pool name or Wildcat
96682] TRISTE DRAW; BONE SPRING, EAST

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
EOG Resources

3. Address of Operator
PO BOX 2267, MIDLAND, TX 79702

4. Well Location
Unit Letter A : 442 feet from the NORTH line and 347 feet from the EAST line
Section 29 Township 24S Range 33E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3530 GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐
OTHER: DRILLING CASING ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

05/12/19 8-3/4" HOLE

05/12/19 Intermediate Casing @ 11,636'

Ran 7-5/8", 29.7#, HCP-110 BTC SCC (0' - 1,010')

Ran 7-5/8", 29.7#, HCP-110 MO-FXL (1,010' - 11,636')

Stage 1: Lead Cement w/ 460 sx Class C (1.04 yld, 14.0 ppg)

Test casing to 2,500 psi for 30 min - Good Did not circ cement to surface, TOC @ 10,134' by Calc

Stage 2: Bradenhead squeeze w/ 1,000 sx Class C (1.5 yld, 14.8 ppg)

Stage 3: Top out w/ 60 sx Class C (1.37 yld, 14.8 ppg) TOC @ surface Resume Drilling 6-3/4" hole

✓ p.m.

Spud Date:

04/30/19

04/22/19

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Emily Follis

TITLE

Sr. Regulatory Administrator

DATE 05/28/19

Type or print name

Emily Follis

E-mail address:

emily_follis@eog.com

PHONE:

432-848-9163

For State Use Only

APPROVED BY:

[Signature]

TITLE

Petroleum Engineer

DATE

06/06/19

Conditions of Approval (if any):