Form 3160-3 (June 2015)

(Continued on page 2)

UNITED STATES HOBBS OCD

FORM APPROVED OMB No. 1004-0137 Expires: January 31, 2018

*(Instructions on page 2)

P/F /H>

BUREAU OF LAND MANAGEMENT APPLICATION FOR PERMIT TO DRILL OR REENTER 1s. Type of work: DRILL REENTER 1s. Type of work: DRILL STATE OF Well: Other 1s. Type of Well: DRILL STATE OF Well: Other 2s. Name of Operator DEVON ENERGY PRODUCTION COMPANY LP 2s. Devator Operator DEVON ENERGY PRODUCTION COMPANY LP 2s. Devator Operator DEVON ENERGY PRODUCTION DEVON ENERGY PRODUCTIO	DEPARTMENT OF THE IN		-		5. Lease Serial No.	•		
1a. Type of work: DRILL			MAIDUL	019		m 11 - 3.1		
1a. Type of Well: Oil Well Gas Well Other	APPLICATION FOR PERMIT TO DI	RILL OR			6. If Indian, Allote	e or Tribe Name		
1a. Type of Wolf:			RECEI	/ED	7 1511-1 CA A	A Name of N		
Ic. Type of Completion: Hydraulic Fracturing Single Zone Multiple Zone GREN WAVE 20 32 FED STATE OF 16H 2. Name of Operator DEVON ENERGY PRODUCTION COMPANY LP 2. Name of Operator DEVON ENERGY PRODUCTION COMPANY LP 3. Address 3. Address 3. Address 4. Location of Well (Report location clearly and in accordance with any State requirements.*) 4. Location of Well (Report location clearly and in accordance with any State requirements.*) 4. Location of Well (Report location clearly and in accordance with any State requirements.*) 4. Location of Well (Report location clearly and in accordance with any State requirements.*) 4. Location of Well (Report location from clearly and in accordance with any State requirements.*) 4. Distance in miles and direction from nearest town or post office* 13. Distance from proposed clease line, ft. (Als to nearest drig, unit line, if any) (Als to nearest well, drilling, completed, 1451 feet applied fro, on this lease, ft. 12. Elevations (Show whether DF, KDB, RT, GL, etc.) 23. Application on this lease, ft. 12. A Drilling Plan. 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropried Portest Service Office) Name (Primed/Typed) (Cody Layout Plan (if the location) plants as may be requested by the Bulleton Organization of the Surhambers of Cody Layout Plants (Triped) (Cody Layout Plants) (Electropic Submission) Name (Primed/Typed) (Diffee CARLSBAD Application Application Approved by Gignature) (Electropic Submission) Name (Primed/Typed) (Cody Layout Plants) (Electropic Submission) Name (Primed/Typed) (Cody Layout Plants) (Electropic Submission) (Diffee CARLSBAD Application Approved by Gignature) (Cody Layout Plants) (Electropic Submission) (Carlicions) (CARLSBAD Application Approved by Gignature) (Cody Layout Plants) (Carli			1	y.4" '	7. If Unit or CA Ag	greement, Name and No.		
2. Name of Operator DEVON ENERGY PRODUCTION COMPANY LP 33. Address 33. West Shendan Avenue Oklahoma City OK 73102 [800)583-3866 [800)583-8966 [800)583-8966 [800)583-8966 [800)583-8966 [800)583-8966 [800)583-8966		_	_	1	8. Lease Name and	l Well No.		
DEVON ENERGY PRODUCTION COMPANY LP 3a. Address 3a. West Sheridan Avenue Oklahoma City OK 73102 (600)583-3866 (600)583-3866 (600)583-3866 (600)583-3866 (700)583-3866 (800)583-386	1c. Type of Completion: Hydraulic Fracturing Sir	ngle Zone	Multiple Zone		//	0-32 FEO STATE COM		
DEVON ENERGY PRODUCTION COMPANY LP 3a. Address 3b. Phone No. (include area code) (600)583-3866 (600)583-3866 (600)583-3866 (600)583-3866 (700)583-7834E / NMP (700)583								
33. West Sheridan Avenue Oklahoma City OK 73102 4. Location of Well (Report location clearly and in accordance with any State requirements.*) At surface NESW / 2199 FSL / 1911 FWL / LAT 32.0277218 / LONG - 103.4942537 At proposed prod. zone LOT 3 / 2490 FNL / 1660 FWL / LAT 32.000327 / LONG - 103.4942537 At proposed prod. zone LOT 3 / 2490 FNL / 1660 FWL / LAT 32.000327 / LONG - 103.4942537 At proposed prod. zone LOT 3 / 2490 FNL / 1660 FWL / LAT 32.000327 / LONG - 103.4942537 At proposed prod. zone LOT 3 / 2490 FNL / 1660 FWL / LAT 32.000327 / LONG - 103.4942537 At proposed prod. zone LOT 3 / 2490 FNL / 1660 FWL / LAT 32.000327 / LONG - 103.4942537 At proposed prod. zone LOT 3 / 2490 FNL / 1660 FWL / LAT 32.000327 / LONG - 103.4942537 At proposed prod. zone LOT 3 / 2490 FNL / 1660 FWL / LAT 32.000327 / LONG - 103.4942537 At proposed prod. zone LOT 3 / 2490 FNL / 1660 FWL / LAT 32.000327 / LONG - 103.4942537 At proposed prod. zone LOT 3 / 2490 FNL / 1660 FWL / LAT 32.000327 / LONG - 103.4942537 At proposed prod. zone LOT 3 / 2490 FNL / 1660 FWL / LAT 32.000327 / LONG - 103.4942537 At proposed prod. zone LOT 3 / 2490 FNL / 1660 FWL / LAT 32.000327 / LONG - 103.4942537 At proposed prod. zone LOT 3 / 2490 FNL / 1660 FWL / LAT 32.000327 / LONG - 103.4942537 At proposed prod. zone LOT 3 / 2490 FNL / 1660 FWL / LAT 32.000327 / LONG - 103.4942537 At proposed prod. zone LOT 3 / 2490 FNL / 1660 FWL / LAT 32.000327 / LONG - 103.4942537 At proposed prod. zone LOT 3 / 2490 FNL / 1660 FWL / LAT 32.000327 / LONG - 103.4942537 At proposed prod. zone LOT 3 / 2490 FNL / 1660 FWL / LAT 32.000327 / LONG - 103.4942537 At proposed prod. zone LOT 3 / 2490 FNL / 1660 FWL / LAT 32.000327 / LONG - 103.4942537 At provide proposed prod. zone LOT 3 / 2490 FNL / 1660 FWL / LAT 32.000327 / LONG - 103.4942537 At provide proposed prod. zone LOT 3 / 2490 FNL / 1660 FWL / LAT 32.000327 / LONG - 103.4942537 At provide proposed prod. zone LOT 3 / 2490 FNL / 1660 FWL / 16	/ / /	<i>3</i> 7)		_	/ \	-410056		
4. Location of Well (Report location clearly and in accordance with any State requirements.*) At surface NESW / 2199 FSL / 1911 FWL / LAT 32.0277218 / LONG - 103.4942537 At proposed prod. zone LOT 3 / 2490 FNL / 1660 FWL / LAT 32.000327 / LONG - 103.4950295 14. Distance in miles and direction from nearest town or post office* 15. Distance from proposed* location to nearest property or lease line, fl. (Also to nearest drig. unit line, if any) 16. Distance from proposed* location* to nearest legi. unit line, if any) 17. Specifing Unit dedicated to this well property or lease line, fl. (Also to nearest drig. unit line, if any) 18. Distance from proposed location* to nearest legi. unit line, if any) 18. Distance from proposed location* 19. Proposed Depth 19.	3a. Address	3b. Phone N	lo. (include area cod	ie)		or Exploratory 728		
At surface NESW / 2199 FSL / 1911 FWL / LAT 32.0277218 / LONG -103.4942537 At proposed prod. zone LOT 3 / 2490 FNL / 1660 FWL / LAT 32.000327 / LONG -103.4942537 14. Distance in miles and direction from nearest town or post office* 15. Distance from proposed* 15. Distance from proposed location to nearest property or lease line, fl. (Also to nearest drig, unit line, if any) 16. No of acres in lease property or lease line, fl. (Also to nearest drig, unit line, if any) 1880 1880 1911 feet property or lease line, fl. (Also to nearest drig, unit line, if any) 1880 1880 19 Proposed Depth 1880 19 Proposed Depth 19 Proposed Depth 10 Proposed Depth 1256 feet / 22395 feet FED: CO1104 21. Elevations (Show whether DF, KDB, RT, GL, etc.) 22 Approximate date work will start* 23. Estimated duration 45 days 24. Attachasents The following, completed in accordance with the requirements of Onshort, Oil and Gas Order No. 1, and the Hydraulic Fracturing rule per 43 CFR 3162. (as applicable) 1. Well plate critified by a registered surveyor. 2. A Drilling Plan. 3. A Surface Use Plan (if the location is on, National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office) 1. Well plate critified by a registered surveyor. 2. A Drilling Plan. 3. A Surface Use Plan (if the location is on, National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office) 1. Well plate critified by a registered surveyor. 2. A Drilling Plan. 3. A Surface Use Plan (if the location is on, National Forest System Lands, the Support of the	333 West Sheridan Avenue Oklahoma City OK 73102	(800)583-3	866		BRADLEY / BON	E SPRIING \		
At proposed prod. zone LOT 3 / 2490 FNL / 1660 FWL / LAT 32.000327 / LONG - 103.850295 14. Distance from proposed* 1911 feet property or lease line, ft. (Also to nearest drig. unit line, if any) 18. Distance from proposed location* 19. Proposed Depth 19. Proposed Depth 20. BLM/BIA Bond No. in file to nearest unit, drilling, completed, applied for, on this lease, ft. 12. Elevations (Show whether DF, KDB, RT, GL, etc.) 22. Approximate date work will start* 23. Estimated duration 24. Attachments The following, completed in accordance with the requirements of Onstone Oil and Gas Order No. 1, and the Hydraulic Fracturing rule per 43 CFR 3162. (as applicable) 1. Well plat certified by a registered surveyor. 2. A Drilling Plan. 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office) 14. Bond to cover the operations unless covered by an existing bond on file Item 20 above). 5. Operator certification. 5. Such other site specific information and/or plans as may be requested by the BLM. 25. Signature (Electronic Submission) Title Regulatory Compliance Professional Approved by (Gigneture) Name (Printed/Typed) Cody Layton / Ph: (575)234-5959 O3/22/2019 Date CARLISBAD Application happroval friefly, are attached. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or age of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.	4. Location of Well (Report location clearly and in accordance w	vith any State	requirements.*)					
14. Distance in miles and direction from nearest town or post office* 12. Country or Parish LEA 15. Distance from proposed* 1911 feet location to nearest property or lease line, ft. (Also to nearest drig, unit line, if any) 18. Distance from proposed location* 1911 feet lonearest well, drilling, completed, 1451 feet lonearest well, drilling, completed, post lonearest well, drilling, completed, post lonearest well applied for, on this lease, ft. 19. Proposed Depth 20/BLM/BIA Bond No. in file to nearest well, drilling, completed, post lonearest well start* 12. Elevations (Show whether DF, KDB, RT, GL, etc.) 22. A proximate date work will start* 23. Estimated duration described by a registered surveyor. 24. A Drilling Plan. 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Posts Service Office) 1. Well plat certified by a registered surveyor. 23. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Posts Service Office) 25. Signature (Electronic Submission) 16. Such other site specific information and/or plans as may be requested by the BLM. 25. Signature (Electronic Submission) 17. Specially Use dedicated to this well lands are proposed location in the subject lease which would entitle the applicant to conduct operations thereon. 18. Distance Frence Tipe and the special post location is on National Forest System Lands, the Submission) 19. Proposed Depth 20/BLM/BIA Bond No. in file to this well distance and the submission of the location is on National Forest System Lands, the Submission on the International Conditions of the Operation of the International Conditions of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.	At surface NESW / 2199 FSL / 1911 FWL / LAT 32.027	7218 / LON	G -103.4942537		SEC 201 T265/1	R34E / NMP		
15. Distance from proposed* location to nearest property or lease line, fl. (Also to nearest drig, unit line, if any) 18. Distance from proposed location* location to nearest well, drilling, completed, 1451 feet applied for, on this lease, fl. (Also to nearest well, drilling, completed, 1451 feet applied for, on this lease, fl. (Also to nearest well, drilling, completed, 1451 feet applied for, on this lease, fl. (Also to nearest well, drilling, completed, 1451 feet applied for, on this lease, fl. (Also to nearest well, drilling, completed, 1451 feet applied for, on this lease, fl. (Also to nearest well, drilling, completed, 1451 feet applied for, on this lease, fl. (Also to nearest well, drilling, completed, 1451 feet applied for, on this lease, fl. (Also to nearest well, drilling, completed in accordance with the requirements of Ohstora Oil and Gas Order No. 1, and the Hydraulic Fracturing rule per 43 CFR 3162. (as applicable) 1. Well plat certified by a registered surveyor. 2. A Drilling Plan. 3. A Surface Use Plan (if the location is on, National Forest System Lands, the SUPO must be filed with the appropriate Porest System Lands, the SUPO must be filed with the appropriate Porest Service Office) 1. Well plat certified by a registered surveyor. 2. A Drilling Plan. 3. A Surface Use Plan (if the location is on, National Forest System Lands, the SUPO must be filed with the appropriate Porest System Lands, the Support of the Suppor	At proposed prod. zone LOT 3 / 2490 FNL / 1660 FWL / L	LAT 32.0003	327 / LONG -103.4	95 0295				
1880 1880	14. Distance in miles and direction from nearest town or post office	ce*				•		
property or lease line, ft. (Also to nearest drig, unit line, if any) 18. Distance from proposed location* to nearest well, drilling, completed, 1451 feet applied for, on this lease, ft. 21. Elevations (Show whether DF, KDB, RT, GL, etc.) 3349 feet 22. Approximate date work will start* 23. Estimated duration 349 feet 24. Attachments The following, completed in accordance with the requirements of Orishort-Oil and Gas Order No. 1, and the Hydraulic Fracturing rule per 43 CFR 3162. (as applicable) 1. Well plat certified by a registered surveyor. 2. A Drilling Plan. 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office) 5. Operator certification. 5. Such other site specific information and/or plans as may be requested by the BLM. 25. Signature (Electronic Submission) Title Regulatory Compliance Professional Approved by (Signature) (Electronic Submission) Title Assistant Field Manager Lands & Minerals CARLSBAD Application approval does not variant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Conditions of approval, it for a stacked. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or age of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.		16. No of ac	cres in lease	<i>x</i>	Unit dedicated to	this well		
18. Distance from proposed location* to nearest well, drilling, completed, 1451 feet applied for, on this lease, ft. 21. Elevations (Show whether DF, KDB, RT, GL, etc.) 22. Approximate date work will start* 23. Estimated duration 3349 feet 24. Attachments The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, and the Hydraulic Fracturing rule per 43 CFR 3162.: (as applicable) 1. Well plat certified by a registered surveyor. 2. A Drilling Plan. 3. Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office) 25. Signature (Electronic Submission) Name (PrintedTyped) Rebecca Deal / Ph: (405)228-8429 Name (PrintedTyped) Rebecca Deal / Ph: (575)234-5959 Date (Clectrofity Submission) Name (PrintedTyped) Cody Layton / Ph: (575)234-5959 O3/22/2019 Title Assistant Field Manager Lands & Minerals Asplication approval does not variant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Conditions of approval, if fany, are attached. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or age of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.	• • •	1880		316 .2				
to nearest well, drilling, completed, applied for, on this lease, ft. 12565 Feat / 22395 feet FED: CO1104 21. Elevations (Show whether DF, KDB, RT, GL, etc.) 22. Approximate date work will start* 23. Estimated duration 24. Attachments 24. Attachments 25. Approximate date work will start* 25. Estimated duration 26. Approximate date work will start* 25. Estimated duration 26. Approximate date work will start* 25. Estimated duration 26. Approximate date work will start* 25. Estimated duration 26. Approximate date work will start* 26. Approximate date work will start* 27. Approximate date work will start* 28. Estimated duration 27. Approximate date work will start* 28. Estimated duration 27. Approximate date work will start* 28. Estimated duration 27. Approximate date work will start* 28. Estimated duration 27. Approximate date work will start* 28. Estimated duration 27. Approximate date work will start* 28. Estimated duration 28. Approximate date work will start* 28. Estimated duration 28. Approximate date work will start* 28. Estimated duration 28. Approximate date work will start* 28. Estimated duration 28. Approximate date work will start* 28. Estimated duration 28. Approximate date work will start* 28. Estimated duration 28. Approximate date work will start* 28. Estimated duration 28. Approximate date work will start* 28. Estimated duration 28. Estimated duration 28. Approximate 28. Approxima	18 Distance from proposed location*	10 Proposi	d Denth	20/BI M	/BIA Bond No. in file	<u>. </u>		
The following, completed in accordance with the requirements of Orishore Oil and Gas Order No. 1, and the Hydraulic Fracturing rule per 43 CFR 3162 (as applicable) 1. Well plat certified by a registered surveyor. 2. A Drilling Plan. 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office) 5. Operator certification. 6. Such other site specific information and/or plans as may be requested by the BLM. 25. Signature (Electronic Submission) Title Regulatory Compliance Professional Approved by (Signature) (Electronic Submission) Title Assistant Field Manager Lands & Minerals Application approval does not variant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Conditions of approval, if any, are attached. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or age of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.	to nearest well, drilling, completed,							
The following, completed in accordance with the requirements of Orishore Oil and Gas Order No. 1, and the Hydraulic Fracturing rule per 43 CFR 3162 (as applicable) 1. Well plat certified by a registered surveyor. 2. A Drilling Plan. 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office) 5. Operator certification. 6. Such other site specific information and/or plans as may be requested by the BLM. 25. Signature (Electronic Submission) Title Regulatory Compliance Professional Approved by (Signature) (Electronic Submission) Title Approved by (Signature) (Electronic Submission) Name (Printed/Typed) Cody Layton / Ph: (405)228-8429 Date Cody Layton / Ph: (575)234-5959 O3/22/2019 Title Application approval does not variant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Conditions of approval, if any, are attached. File 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or age of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.	21. Elevations (Show whether DF, KDB, RT, GL, etc.)	22. Approxi	mate date work will	start*	23. Estimated dura	tion		
The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, and the Hydraulic Fracturing rule per 43 CFR 3162 (as applicable) 1. Well plat certified by a registered surveyor. 2. A Drilling Plan. 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office) 5. Operator certification. 6. Such other site specific information and/or plans as may be requested by the BLM. 7. Signature (Electronic Submission) 7. Name (Printed/Typed) Rebecca Deal / Ph: (405)228-8429 8. Date Cody Layton / Ph: (575)234-5959 9. O3/22/2019 1. Well plat certified Manager Lands & Minerals Approved by (Signature) (Electronic Submission) 7. Title Regulatory Compliance Professional Application approval does not variant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Conditions of approval, if any, are attached. 7. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or age of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.		04/01/2020) 💛		45 days			
1. Well plat certified by a registered surveyor. 2. A Drilling Plan. 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office) 25. Signature (Electronic Submission) Title Regulatory Compliance Professional Approved by (Signature) (Electronic Submission) Title Responsibility (Signature) (Electronic Submission) Title Responsibility (Signature) (Electronic Submission) Title Assistant Field Manager Lands & Minerals Application approval does not variant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Conditions of approval, if any, are attached. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or ages of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.		24. Attac	hments					
2. A Drilling Plan. 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office) 25. Signature (Electronic Submission) Title Regulatory Compliance Professional Approved by (Signature) (Electronic Submission) Title Residuatory Compliance Professional Approved by (Signature) (Electronic Submission) Title Assistant Field Manager Lands & Minerals Application approval does not variant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Conditions of approval, if any are attached. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or ager of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.		Onshore Oil	and Gas Order No.	l, and the I	Hydraulic Fracturing	rule per 43 CFR 3162.3-3		
3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office). 25. Signature (Electronic Submission) Title Regulatory Compliance Professional Approved by (Signature) (Electronic Submission) Name (Printed/Typed) Regulatory Compliance Professional Approved by (Signature) (Electronic Submission) Name (Printed/Typed) Cody Layton / Ph: (575)234-5959 Date (Electronic Submission) Title Assistant Field Manager Lands & Minerals Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Conditions of approval, if any are attached. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or ager of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.		Š	1	-	ns unless covered by	an existing bond on file (see		
25. Signature (Electronic Submission) Title Regulatory Compliance Professional Approved by (Signature) (Electronic Submission) Name (Printed/Typed) Cody Layton / Ph: (575)234-5959 Date (Cody Layton / Ph: (575)234-5959 Title Assistant Field Manager Lands & Minerals Application approval does not variant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Conditions of approval, if any, are attached. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or ager of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.	3. A Surface Use Plan (if the location is on National Forest System	n Lands, the	6. Such other site s		rmation and/or plans a	as may be requested by the		
(Electronic Submission) Rebecca Deal / Ph: (405)228-8429 10/22/2018 Title Regulatory Compliance Professional Approved by (Signature) (Electronic Submission) Title Assistant Field Manager Lands & Minerals Application approval does not variant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Conditions of approval, if any, are attached. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or ager of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.	25. Signature	Name	<u> </u>		· · · · · · · · · · · · · · · · · · ·	Date		
Regulatory Compliance Professional Approved by (Signature) (Electronic Submission) Title Assistant Field Manager Lands & Minerals Application approval does not variant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Conditions of approval, if any, are attached. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or ager of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.	(Electronic Submission)	Rebed	cca Deal / Ph: (405	5)228-8429	9			
Cody Layton / Ph: (575)234-5959 O3/22/2019 Title Assistant Field Manager Lands & Minerals Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Conditions of approval, if any, are attached. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or ager of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.		•						
Assistant Field Manager Lands & Minerals Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Conditions of approval, if any, are attached. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or ager of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.		l l		234-5959				
Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Conditions of approval, if any, are attached. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or ages of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.	Title							
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or ages of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.	Application approval does not warrant or certify that the applicant applicant to conduct operations thereon.			hose rights	in the subject lease v	which would entitle the		
of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.		aka it o ories	for any namon line	wingh: and	willfully to make to	any department or access		
GC/ Rec 05/20/19	of the United States any false, fictitious or fraudulent statements o							
THIONS PE	GCP Kee 05/20/19				X4.103	, [] 7		
			- auni	IONS	96			

INSTRUCTIONS

GENERAL: This form is designed for submitting proposals to perform certain well operations, as indicated on Federal and Indian lands and leases for action by appropriate Federal agencies, pursuant to applicable Federal laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from local Federal offices.

ITEM I: If the proposal is to redrill to the same reservoir at a different subsurface location or to a new reservoir, use this form with appropriate notations. Consult applicable Federal regulations concerning subsequent work proposals or reports on the well.

ITEM 4: Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local Federal offices for specific instructions.

ITEM 14: Needed only when location of well cannot readily be found by road from the land or lease description. A plat, or plats, separate or on the reverse side, showing the roads to, and the surveyed location of, the wen, and any other required information, should be furnished when required by Federal agency offices.

ITEMS 15 AND 18: If well is to be, or has been directionany drilled, give distances for subsurface location of hole in any present or objective productive zone.

ITEM 22: Consult applicable Federal regulations, or appropriate officials, concerning approval of the proposal before operations are started.

ITEM 24: If the proposal will involve hydraulic fracturing operations, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state of tribal regulatory agencies and from local BLM offices.

NOTICES

The Privacy Act of 1974 and regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 25 U.S.C. 396; 43 CFR 3160

PRINCIPAL PURPOSES: The information will be used to: (1) process and evaluate your application for a permit to drill a new oil, gas, or service wen or to reenter a plugged and abandoned well; and (2) document, for administrative use, information for the management, disposal and use of National Resource Lands and resources including (a) analyzing your proposal to discover and extract the Federal or Indian resources encountered; (b) reviewing procedures and equipment and the projected impact on the land involved; and (c) evaluating the effects of the proposed operation on the surface and subsurface water and other environmental impacts.

ROUTINE USE: Information from the record and/or the record win be transferred to appropriate Federal, State, and local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecution, in connection with congressional inquiries and for regulatory responsibilities.

EFFECT OF NOT PROVIDING INFORMATION: Filing of this application and disclosure of the information is mandatory only if you elect to initiate a drilling or reentry operation on an oil and gas lease.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM conects this information to anow evaluation of the technical, safety, and environmental factors involved with drilling for oil and/or gas on Federal and Indian oil and gas leases. This information will be used to analyze and approve applications. Response to this request is mandatory only if the operator elects to initiate drilling or reentry operations on an oil and gas lease. The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Conection Clearance Officer (WO-630), 1849 C Street, N.W., Mail Stop 401 LS, Washington, D.C. 20240.

(Form 3160-3, page 2)

(Continued on page 3)

Additional Operator Remarks

Location of Well

1. SHL: NESW / 2199 FSL / 1911 FWL / TWSP: 26S / RANGE: 34E / SECTION: 20 / LAT: 32.0277218 / LONG: -103.4942537 (TVD: Offeet, MD: Offeet)

PPP: NESW / 2299 FSL / 1660 FWL / TWSP: 26S / RANGE: 34E / SECTION: 20 / LAT: 32.028002 / LONG: -103.495061 (TVD: 11992 Feet, MD: 11996 feet)


BHL: LOT 3 / 2490 FNL / 1660 FWL / TWSP: 26S / RANGE: 34E / SECTION: 32 / LAT: 32.000327 / LONG: -103.4950295 (TVD: 12565 feet, MD: 22395 feet)

BLM Point of Contact

Name: Tenille Ortiz

Title: Legal Instruments Examiner

Phone: 5752342224 Email: tortiz@blm.gov



Review and Appeal Rights

A person contesting a decision shall request a State Director review. This request must be filed within 20 working days of receipt of the Notice with the appropriate State Director (see 43 CFR 3165.3). The State Director review decision may be appealed to the Interior Board of Land Appeals, 801 North Quincy Street, Suite 300, Arlington, VA 22203 (see 43 CFR 3165.4). Contact the above listed Bureau of Land Management office for further information.



(Form 3160-3, page 4)

PECOS DISTRICT DRILLING CONDITIONS OF APPROVAL

OPERATOR'S NAME: DEVON ENERGY PRODUCTION COMPANY LP

LEASE NO.: | NMNM114991

WELL NAME & NO.: 16H – GREEN WAVE 20-32 FED STATE COM

SURFACE HOLE FOOTAGE: 2199'/S & 1911'/W **BOTTOM HOLE FOOTAGE** 2490'/N & 1660'/W

LOCATION: | SECTION 20, T26S, R34E, NMPM

COUNTY: LEA

COA

H2S	C Yes	© No	
Potash	© None	Secretary ■ Company Secretary ■ Company Secretary The secretary Secretary	C R-111-P
Cave/Karst Potential	© Low	○ Medium	○ High
Variance	None	Flex Hose	○ Other
Wellhead	C Conventional		© Both
Other	☐4 String Area	Capitan Reef	□ WIPP
Other	Fluid Filled	☑ Cement Squeeze	Pilot Hole
Special Requirements	Water Disposal	☑ COM	□ Unit

A. HYDROGEN SULFIDE

Hydrogen Sulfide (H2S) monitors shall be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the Hydrogen Sulfide area shall meet Onshore Order 6 requirements, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, provide measured values and formations to the BLM.

B. CASING

Primary Casing Design:

- 1. The 13-3/8 inch surface casing shall be set at approximately 820 feet (a minimum of 25 feet into the Rustler Anhydrite and above the salt) and cemented to the surface.
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
 - b. Wait on cement (WOC) time for a primary cement job will be a minimum of 8

- <u>hours</u> or 500 pounds compressive strength, whichever is greater. (This is to include the lead cement)
- c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
- d. If cement falls back, remedial cementing will be done prior to drilling out that string.

Intermediate casing must be kept fluid filled to meet BLM minimum collapse requirement.

2. The minimum required fill of cement behind the 9-5/8 inch intermediate casing shall be set at approximately 5200 feet is:

Option 1 (Single Stage):

• Cement to surface. If cement does not circulate see B.1.a, c-d above.

Option 2:

Operator has proposed a DV tool, the depth may be adjusted as long as the cement is changed proportionally. The DV tool may be cancelled if cement circulates to surface on the first stage.

- a. First stage to DV tool: Cement to circulate. If cement does not circulate off the DV tool, contact the appropriate BLM office before proceeding with second stage cement job.
- b. Second stage above DV tool:
 - Cement to surface. If cement does not circulate, contact the appropriate BLM office.

Operator has proposed to pump down 13-3/8" X 9-5/8" annulus. Operator must run a CBL from TD of the 9-5/8" casing to surface. Submit results to BLM.

- 3. The minimum required fill of cement behind the 5-1/2 inch production casing is:
 - Cement should tie-back at least **200 feet** into previous casing string. Operator shall provide method of verification.

Alternate Casing Design:

- 4. The 13-3/8 inch surface casing shall be set at approximately 820 feet (a minimum of 25 feet into the Rustler Anhydrite and above the salt) and cemented to the surface.
 - e. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
 - f. Wait on cement (WOC) time for a primary cement job will be a minimum of **8** hours or 500 pounds compressive strength, whichever is greater. (This is to include the lead cement)
 - g. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
 - h. If cement falls back, remedial cementing will be done prior to drilling out that string.

Intermediate casing must be kept fluid filled to meet BLM minimum collapse requirement.

5. The minimum required fill of cement behind the 8-5/8 inch intermediate casing is:

Option 1 (Single Stage):

• Cement to surface. If cement does not circulate see B.1.a, c-d above. Cement excess is less than 25%, more cement might be required.

Option 2:

Operator has proposed a DV tool, the depth may be adjusted as long as the cement is changed proportionally. The DV tool may be cancelled if cement circulates to surface on the first stage.

- c. First stage to DV tool: Cement to circulate. If cement does not circulate off the DV tool, contact the appropriate BLM office before proceeding with second stage cement job.
- d. Second stage above DV tool:
 - Cement to surface. If cement does not circulate, contact the appropriate BLM office.

Cement excess is less than 25%, more cement might be required.

Operator has proposed to pump down 13-3/8" X 8-5/8" annulus. Operator must run a CBL from TD of the 8-5/8" casing to surface. Submit results to BLM.

- 6. The minimum required fill of cement behind the 5-1/2 inch production casing is:
 - Cement should tie-back at least **200 feet** into previous casing string. Operator shall provide method of verification.

Alternate Casing Design 2:

- 7. The 13-3/8 inch surface casing shall be set at approximately 820 feet (a minimum of 25 feet into the Rustler Anhydrite and above the salt) and cemented to the surface.
 - i. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
 - j. Wait on cement (WOC) time for a primary cement job will be a minimum of **8** hours or 500 pounds compressive strength, whichever is greater. (This is to include the lead cement)
 - k. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
 - 1. If cement falls back, remedial cementing will be done prior to drilling out that string.

Intermediate casing must be kept fluid filled to meet BLM minimum collapse requirement.

8. The minimum required fill of cement behind the 9-5/8 inch intermediate casing is:

Option 1 (Single Stage):

• Cement to surface. If cement does not circulate see B.1.a, c-d above.

Option 2:

Operator has proposed a DV tool, the depth may be adjusted as long as the cement is changed proportionally. The DV tool may be cancelled if cement circulates to surface on the first stage.

e. First stage to DV tool: Cement to circulate. If cement does not circulate off the DV tool, contact the appropriate BLM office before proceeding with second stage cement job.

- f. Second stage above DV tool:
 - Cement to surface. If cement does not circulate, contact the appropriate BLM office.

Operator has proposed to pump down 13-3/8" X 9-5/8" annulus. Operator must run a CBL from TD of the 9-5/8" casing to surface. Submit results to BLM.

- 9. The minimum required fill of cement behind the 5-1/2 inch production casing is:
 - Cement should tie-back at least **200 feet** into previous casing string. Operator shall provide method of verification.

C. PRESSURE CONTROL

1. Variance approved to use flex line from BOP to choke manifold. Manufacturer's specification to be readily available. No external damage to flex line. Flex line to be installed as straight as possible (no hard bends).'

2.

Option 1:

- a. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be 5000 (5M) psi.
- b. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the intermediate casing shoe shall be 10,000 (10M) psi. Variance is approved to use a 5000 (5M) Annular which shall be tested to 5000 (5M) psi.

Option 2:

- 1. Operator has proposed a multi-bowl wellhead assembly. This assembly will only be tested when installed on the surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be 10,000 (10M) psi. Variance is approved to use a 5000 (5M) Annular which shall be tested to 5000 (5M) psi.
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.

- b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
- c. Manufacturer representative shall install the test plug for the initial BOP test.
- d. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
- e. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.

D. SPECIAL REQUIREMENT (S)

Communitization Agreement

- The operator will submit a Communitization Agreement to the Carlsbad Field Office, 620 E Greene St. Carlsbad, New Mexico 88220, at least 90 days before the anticipated date of first production from a well subject to a spacing order issued by the New Mexico Oil Conservation Division. The Communitization Agreement will include the signatures of all working interest owners in all Federal and Indian leases subject to the Communitization Agreement (i.e., operating rights owners and lessees of record), or certification that the operator has obtained the written signatures of all such owners and will make those signatures available to the BLM immediately upon request.
- If the operator does not comply with this condition of approval, the BLM may take enforcement actions that include, but are not limited to, those specified in 43 CFR 3163.1.
- In addition, the well sign shall include the surface and bottom hole lease numbers. When the Communitization Agreement number is known, it shall also be on the sign.

Page 6 of 11

GENERAL REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)
 - \(\sum_{\text{ounties}} \)
 \(\text{Call the Roswell Field Office, 2909 West Second St., Roswell NM 88201. \)
 \(\text{During office hours call (575) 627-0272. } \)
 \(\text{After office hours call (575)} \)
 - ☑ Eddy CountyCall the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220, (575) 361-2822
 - ✓ Lea CountyCall the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240, (575)393-3612
- 1. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
 - a. In the event the operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).
 - b. When the operator proposes to set surface casing with Spudder Rig
 - Notify the BLM when moving in and removing the Spudder Rig.
 - Notify the BLM when moving in the 2nd Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
 - BOP/BOPE test to be conducted per Onshore Oil and Gas Order No. 2 as soon as 2nd Rig is rigged up on well.
- 2. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.

3. The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well – vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.

A. CASING

- 1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.
- 2. Wait on cement (WOC) for Potash Areas: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends, 2) until cement has been in place at least 24 hours. WOC time will be recorded in the driller's log.
- 3. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements.
- 4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
- 5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.
- 6. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.
- 7. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.

Page 8 of 11

8. Whenever a casing string is cemented in the R-111-P potash area, the NMOCD requirements shall be followed.

B. PRESSURE CONTROL

- 1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.
- 2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.
- 3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
- 4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test
 - d. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.
 - e. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
- 5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
 - a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the

plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead when specified), whichever is greater. However, if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).

- b. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the plug. However, **no tests** shall commence until the cement has had a minimum of 24 hours setup time.
- c. The tests shall be done by an independent service company utilizing a test plug not a cup or J-packer. The operator also has the option of utilizing an independent tester to test without a plug (i.e. against the casing) pursuant to Onshore Order 2 with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for water basin (8 hours) or potash (24 hours) or 500 pounds compressive strength, whichever is greater, prior to initiating the test (see casing segment as lead cement may be critical item).
- d. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
- e. The results of the test shall be reported to the appropriate BLM office.
- f. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
- g. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.
- h. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per Onshore Order No. 2.

C. DRILLING MUD

Page 10 of 11

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

D. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

Page 11 of 11

PECOS DISTRICT SURFACE USE CONDITIONS OF APPROVAL

OPERATOR'S NAME:
LEASE NO.:
NMNM
WELL NAME & NO.:
SURFACE HOLE FOOTAGE:
BOTTOM HOLE FOOTAGE
LOCATION:
COUNTY:
DEVON ENERGY PRODUCTION COMPANY LP
NMNM
16H – GREEN WAVE 20-32 FED STATE COM
2199'/S & 1911'/W
2490'/N & 1660'/W
SECTION 20, T26S, R34E, NMPM
LEA

TABLE OF CONTENTS

Standard Conditions of Approval (COA) apply to this APD. If any deviations to these standards exist or special COAs are required, the section with the deviation or requirement will be checked below.

General Provisions
Permit Expiration
Archaeology, Paleontology, and Historical Sites
☐ Noxious Weeds
Special Requirements
Ground-level Abandoned Well Marker
Range
☐ Construction
Notification
Topsoil
Closed Loop System
Federal Mineral Material Pits
Well Pads
Roads
Road Section Diagram
Production (Post Drilling)
Well Structures & Facilities
Pipelines
Electric Lines
☐ Interim Reclamation
Final Abandonment & Reclamation

Page 1 of 18

I. GENERAL PROVISIONS

The approval of the Application For Permit To Drill (APD) is in compliance with all applicable laws and regulations: 43 Code of Federal Regulations 3160, the lease terms, Onshore Oil and Gas Orders, Notices To Lessees, New Mexico Oil Conservation Division (NMOCD) Rules, National Historical Preservation Act As Amended, and instructions and orders of the Authorized Officer. Any request for a variance shall be submitted to the Authorized Officer on Form 3160-5, Sundry Notices and Report on Wells.

II. PERMIT EXPIRATION

If the permit terminates prior to drilling and drilling cannot be commenced within 60 days after expiration, an operator is required to submit Form 3160-5, Sundry Notices and Reports on Wells, requesting surface reclamation requirements for any surface disturbance. However, if the operator will be able to initiate drilling within 60 days after the expiration of the permit, the operator must have set the conductor pipe in order to allow for an extension of 60 days beyond the expiration date of the APD. (Filing of a Sundry Notice is required for this 60 day extension.)

III. ARCHAEOLOGICAL, PALEONTOLOGY & HISTORICAL SITES

Any cultural and/or paleontological resource discovered by the operator or by any person working on the operator's behalf shall immediately report such findings to the Authorized Officer. The operator is fully accountable for the actions of their contractors and subcontractors. The operator shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery shall be made by the Authorized Officer to determine the appropriate actions that shall be required to prevent the loss of significant cultural or scientific values of the discovery. The operator shall be held responsible for the cost of the proper mitigation measures that the Authorized Officer assesses after consultation with the operator on the evaluation and decisions of the discovery. Any unauthorized collection or disturbance of cultural or paleontological resources may result in a shutdown order by the Authorized Officer.

IV. NOXIOUS WEEDS

The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

Page 2 of 18

Approval Date: 03/22/2019 .

V. SPECIAL REQUIREMENT(S)

Build as you go pads No grading outside of the subpad.

Temporary Fence Crossing Requirement

Where entry is granted across a fence line, the fence must be braced and tied off on both sides of the passageway with H-braces prior to cutting. Once the work is completed, the fence will be restored to its prior condition, or better. Devon shall notify the private surface landowner or the grazing allotment holder prior to crossing any fences.

Cattle Guard Requirement

Where entry is granted across a fence line for an access road, the fence must be braced and tied off on both sides of the passageway with H-braces prior to cutting. Once the work is completed, the fence will be restored to its prior condition with an appropriately sized cattle guard sufficient to carry out the project. Any new or existing cattle guards on the access route shall be repaired or replaced if they are damaged or have deteriorated beyond practical use. Devon shall be responsible for the condition of the existing cattle guards that are in place and are utilized during lease operations. Once the road is abandoned, the fence would be restored to its prior condition, or better. Devon shall notify the private surface landowner or the grazing allotment holder prior to crossing any fences.

During construction, Devon shall minimize disturbance to existing fences, water lines, troughs, windmills, and other improvements on public lands. Devon is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the grazing permittee/allottee prior to disturbing any range improvement projects. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting of the fence. No permanent gates will be allowed unless approved by the Authorized Officer.

Devon would adhere to the following stipulations:

- Upon abandonment, a low profile abandoned well marker will be installed to prevent raptor perching.
- Devon would need to construct and maintain escape ramps according to the following criteria:
 - Earthen escape ramps would be required to be constructed to sufficiently support livestock at no more than a 30-degree slope and spaced no more than 500 feet apart.
 - o If trench is left open under an 8-hour time period, it would not be required to have an escape ramp; however, before the trench is backfilled, Lucid would inspect the trench for wildlife and remove any species that are trapped at a distance of at least 100 yards away from the trench.
- Power lines shall be constructed and designed in accordance to standards outlined in "Suggested Practices for Avian Protection on Power lines: The State of the Art in 2006" Edison Electric Institute, APLIC, and the California Energy Commission 2006. The holder shall assume the burden and expense of proving that pole designs not shown in the above publication deter raptor perching, roosting, and nesting. Such proof shall be provided by a raptor expert approved by the Authorized Officer. The BLM reserves the right to require modification or additions to all power line structures placed on this right-of-way, should they be necessary to ensure the safety of large perching birds. The holder without liability or expense shall make such modifications and/or additions to the United States.

A BLM Wildlife Biologist must be contacted by Devon prior to construction activities to
determine if the raptor nest is active. Raptors nest on special, natural habitat features,
such as trees, large brush, cliff faces and escarpments, will be protected by not allowing
surface disturbance within up to 200 meters of nests or by delaying activity for up to 90
days, or a combination of both. Exceptions to this requirement for raptor nests will be
considered if the nests expected to be disturbed are inactive, the proposed activity is of
short duration (e.g. habitat enhancement projects, fences, pipelines), and will not result in
continuing activity in proximity to the nest.

VI. CONSTRUCTION

A. NOTIFICATION

The BLM shall administer compliance and monitor construction of the access road and well pad. Notify the Carlsbad Field Office at (575) 234-5909 at least 3 working days prior to commencing construction of the access road and/or well pad.

When construction operations are being conducted on this well, the operator shall have the approved APD and Conditions of Approval (COA) on the well site and they shall be made available upon request by the Authorized Officer.

B. TOPSOIL

The operator shall strip the top portion of the soil (root zone) from the entire well pad area and stockpile the topsoil along the edge of the well pad as depicted in the APD. The root zone is typically six (6) inches in depth. All the stockpiled topsoil will be redistributed over the interim reclamation areas. Topsoil shall not be used for berming the pad or facilities. For final reclamation, the topsoil shall be spread over the entire pad area for seeding preparation.

Other subsoil (below six inches) stockpiles must be completely segregated from the topsoil stockpile. Large rocks or subsoil clods (not evident in the surrounding terrain) must be buried within the approved area for interim and final reclamation.

C. CLOSED LOOP SYSTEM

Tanks are required for drilling operations: No Pits.

The operator shall properly dispose of drilling contents at an authorized disposal site.

D. FEDERAL MINERAL MATERIALS PIT

Payment shall be made to the BLM prior to removal of any federal mineral materials. Call the Carlsbad Field Office at (575) 234-5972.

E. WELL PAD SURFACING

Surfacing of the well pad is not required.

If the operator elects to surface the well pad, the surfacing material may be required to be removed at the time of reclamation. The well pad shall be constructed in a manner which creates the smallest possible surface disturbance, consistent with safety and operational needs.

F. EXCLOSURE FENCING (CELLARS & PITS)

Page 5 of 18

Exclosure Fencing

The operator will install and maintain exclosure fencing for all open well cellars to prevent access to public, livestock, and large forms of wildlife before and after drilling operations until the pit is free of fluids and the operator initiates backfilling. (For examples of exclosure fencing design, refer to BLM's Oil and Gas Gold Book, Exclosure Fence Illustrations, Figure 1, Page 18.)

G. ON LEASE ACCESS ROADS

Road Width

The access road shall have a driving surface that creates the smallest possible surface disturbance and does not exceed fourteen (14) feet in width. The maximum width of surface disturbance, when constructing the access road, shall not exceed twenty-five (25) feet.

Surfacing

Surfacing material is not required on the new access road driving surface. If the operator elects to surface the new access road or pad, the surfacing material may be required to be removed at the time of reclamation.

Where possible, no improvements should be made on the unsurfaced access road other than to remove vegetation as necessary, road irregularities, safety issues, or to fill low areas that may sustain standing water.

The Authorized Officer reserves the right to require surfacing of any portion of the access road at any time deemed necessary. Surfacing may be required in the event the road deteriorates, erodes, road traffic increases, or it is determined to be beneficial for future field development. The surfacing depth and type of material will be determined at the time of notification.

Crowning

Crowning shall be done on the access road driving surface. The road crown shall have a grade of approximately 2% (i.e., a 1" crown on a 14' wide road). The road shall conform to Figure 1; cross section and plans for typical road construction.

Ditching

Ditching shall be required on both sides of the road.

Turnouts


Vehicle turnouts shall be constructed on the road. Turnouts shall be intervisible with interval spacing distance less than 1000 feet. Turnouts shall conform to Figure 1; cross section and plans for typical road construction.

Drainage

Drainage control systems shall be constructed on the entire length of road (e.g. ditches, sidehill outsloping and insloping, lead-off ditches, culvert installation, and low water crossings).

A typical lead-off ditch has a minimum depth of 1 foot below and a berm of 6 inches above natural ground level. The berm shall be on the down-slope side of the lead-off ditch.

Cross Section of a Typical Lead-off Ditch



All lead-off ditches shall be graded to drain water with a 1 percent minimum to 3 percent maximum ditch slope. The spacing interval are variable for lead-off ditches and shall be determined according to the formula for spacing intervals of lead-off ditches, but may be amended depending upon existing soil types and centerline road slope (in %);

Formula for Spacing Interval of Lead-off Ditches

Example - On a 4% road slope that is 400 feet long, the water flow shall drain water into a lead-off ditch. Spacing interval shall be determined by the following formula:

400 foot road with 4% road slope:
$$\frac{400'}{4\%}$$
 + 100' = 200' lead-off ditch interval

Cattle guards

An appropriately sized cattle guard sufficient to carry out the project shall be installed and maintained at fence/road crossings. Any existing cattle guards on the access road route shall be repaired or replaced if they are damaged or have deteriorated beyond practical use. The operator shall be responsible for the condition of the existing cattle guards that are in place and are utilized during lease operations.

Fence Requirement

Where entry is granted across a fence line, the fence shall be braced and tied off on both sides of the passageway prior to cutting. The operator shall notify the private surface landowner or the grazing allotment holder prior to crossing any fences.

Public Access

Public access on this road shall not be restricted by the operator without specific written approval granted by the Authorized Officer.

Construction Steps

- 1. Salvage topsoil 2. Construct road
- 3. Redistribute topsoil4. Revegetate slopes
- center line of roadway shoulder turnout 10' transition full turnout width Intervisible tumouts shall be constructed on all single lane roads on all blind curves with additional tunouts as needed to keep spacing below 1000 feet. **Typical Turnout Plan** natural ground **Level Ground Section** road CLOWU type £0. − £0. earth surface aggregate surface .D2 - .D4 ft/ft .02 - .03 ft/ft paved surface Depth measured from the bottom of the ditch **Side Hill Section** center line center travel surface → travel surface 🗢 (stope 2 - 4%) (slope 2 - 4%) **Typical Outsloped Section Typical Inslope Section**

Figure 1. Cross-sections and plans for typical road sections representative of BLM resource or FS local and higher-class roads.

VII. PRODUCTION (POST DRILLING)

A. WELL STRUCTURES & FACILITIES

Placement of Production Facilities

Production facilities should be placed on the well pad to allow for maximum interim recontouring and revegetation of the well location.

Exclosure Netting (Open-top Tanks)

Immediately following active drilling or completion operations, the operator will take actions necessary to prevent wildlife and livestock access, including avian wildlife, to all open-topped tanks that contain or have the potential to contain salinity sufficient to cause harm to wildlife or livestock, hydrocarbons, or Resource Conservation and Recovery Act of 1976-exempt hazardous substances. At a minimum, the operator will net, screen, or cover open-topped tanks to exclude wildlife and livestock and prevent mortality. If the operator uses netting, the operator will cover and secure the open portion of the tank to prevent wildlife entry. The operator will net, screen, or cover the tanks until the operator removes the tanks from the location or the tanks no longer contain substances that could be harmful to wildlife or livestock. Use a maximum netting mesh size of 1 ½ inches. The netting must not be in contact with fluids and must not have holes or gaps.

Chemical and Fuel Secondary Containment and Exclosure Screening

The operator will prevent all hazardous, poisonous, flammable, and toxic substances from coming into contact with soil and water. At a minimum, the operator will install and maintain an impervious secondary containment system for any tank or barrel containing hazardous, poisonous, flammable, or toxic substances sufficient to contain the contents of the tank or barrel and any drips, leaks, and anticipated precipitation. The operator will dispose of fluids within the containment system that do not meet applicable state or U. S. Environmental Protection Agency livestock water standards in accordance with state law; the operator must not drain the fluids to the soil or ground. The operator will design, construct, and maintain all secondary containment systems to prevent wildlife and livestock exposure to harmful substances. At a minimum, the operator will install effective wildlife and livestock exclosure systems such as fencing, netting, expanded metal mesh, lids, and grate covers. Use a maximum netting mesh size of 1 ½ inches.

Open-Vent Exhaust Stack Exclosures

The operator will construct, modify, equip, and maintain all open-vent exhaust stacks on production equipment to prevent birds and bats from entering, and to discourage perching, roosting, and nesting. (Recommended exclosure structures on open-vent exhaust stacks are in the shape of a cone.) Production equipment includes, but may not be limited to, tanks, heater-treaters, separators, dehydrators, flare stacks, in-line units, and compressor mufflers.

Containment Structures

Page 9 of 18

Proposed production facilities such as storage tanks and other vessels will have a secondary containment structure that is constructed to hold the capacity of 1.5 times the largest tank, plus freeboard to account for precipitation, unless more stringent protective requirements are deemed necessary.

Painting Requirement

All above-ground structures including meter housing that are not subject to safety requirements shall be painted a flat non-reflective paint color, **Shale Green** from the BLM Standard Environmental Color Chart (CC-001: June 2008).

B. PIPELINES

BURIED PIPELINE STIPULATIONS

A copy of the application (Grant, APD, or Sundry Notice) and attachments, including conditions of approval, survey plat and/or map, will be on location during construction. BLM personnel may request to you a copy of your permit during construction to ensure compliance with all stipulations.

Holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer:

- 1. The Holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant.
- 2. The Holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976 as amended, 15 USC 2601 et seq. (1982) with regards to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized under this right-of-way grant. (See 40 CFR Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation, and Liability Act, section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the authorized officer concurrent with the filing of the reports to the involved Federal agency or State government.
- 3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, et seq. or the Resource Conservation and Recovery Act, 42 U.S.C.6901, et seq.) on the Right-of-Way (unless the release or threatened release is wholly unrelated to the Right-of-Way holder's activity on the Right-of-Way), or resulting from the activity of the Right-of-Way holder on the Right-of-Way. This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

Page 10 of 18

4. If, during any phase of the construction, operation, maintenance, or termination of the pipeline, any oil or other pollutant should be discharged from the pipeline system, impacting Federal lands, the control and total removal, disposal, and cleaning up of such oil or other pollutant, wherever found, shall be the responsibility of holder, regardless of fault. Upon failure of holder to control, dispose of, or clean up such discharge on or affecting Federal lands, or to repair all damages resulting therefrom, on the Federal lands, the Authorized Officer may take such measures as he deems necessary to control and clean up the discharge and restore the area, including where appropriate, the aquatic environment and fish and wildlife habitats, at the full expense of the holder. Such action by the Authorized Officer shall not relieve holder of any responsibility as provided herein.

5. All const	struction and ma	intenance activit	y will be con	fined to th	e authorized righ	nt-of-way.
6. The pipe pipe and gro		ied with a minin	num cover of	<u>36</u>	inches between	the top of the
7. The max	kimum allowable	e disturbance for	construction	in this rig	ht-of-way will b	e <u>30</u> feet:
blac	ding operations	7	20 feet. The	trench is i	wed: maximum included in this a getation.)	
clea this <i>(gra</i>	aring operations area. (Clearing	will not exceed ng is defined as c.) intact. Cleari	30 feet. The	e trench and for trush wh	llowed: maximund bladed area are hile leaving groud by holding the l	e included in nd vegetation
	vegetation. (Co	_	• . • .	•	be disturbed by c es, placement of	•
topsoil to be from other s	e stripped is app	proximately(trench construct	5 inches in	n depth. Tl	blading is allow the topsoil will be e evenly distribut	segregated
lands. The Functional wowner of an line, the fen	holder is require use of these imp ny improvement nce shall be brace	ed to promptly reprovements will some some some some some some some some	epair improve be maintained oing them. We of the passag	ements to a d at all tim hen necess geway price	her improvement at least their form es. The holder we sary to pass throus or to cutting of the d Officer.	ner state. vill contact the ugh a fence
randomly so otherwise ap match the si	cattered on this approved by the surrounding land	right-of-way and Authorized Offic	i will not be le cer. The entire cfilled soil sha	eft in rows re right-of- all be com	aintenance activi s, piles, or berms -way shall be rec pacted and a 6 ir	, unless contoured to
holder will	install such stru		table for the s	pecific so	stabilize soil con il conditions beir ctices.	

Page 12 of 18

	eseed all disturbed areas. So, using the following seed r		eding will be done according to the attached x.
()s	seed mixture 1	() seed mixture 3
(X) s	seed mixture 2	() seed mixture 4
() s	seed mixture 2/LPC	() Aplomado Falcon Mixture
to blend with the natu	aral color of the landscape.	Tl	ety requirements shall be painted by the holder he paint used shall be color which simulates Munsell Soil Color No. 5Y 4/2.
way and at all road cr number, and the prod	rossings. At a minimum, si uct being transported. All	gn sig	point of origin and completion of the right-of- s will state the holder's name, BLM serial gns and information thereon will be posted in a tained in a legible condition for the life of the
maintenance as determined before maintenance be pipeline route is not use	mined necessary by the Aut begins. The holder will take used as a roadway. As deter	the w	road for purposes other than routine orized Officer in consultation with the holder whatever steps are necessary to ensure that the nined necessary during the life of the pipeline, ruct temporary deterrence structures.
discovered by the hol immediately reported immediate area of suc Authorized Officer. A determine appropriate holder will be response	der, or any person working to the Authorized Officer. It of the discovery until written at An evaluation of the discover actions to prevent the loss sible for the cost of evaluat	or H uth er; of	(historic or prehistoric site or object) In his behalf, on public or Federal land shall be colder shall suspend all operations in the corization to proceed is issued by the y will be made by the Authorized Officer to f significant cultural or scientific values. The mand any decision as to proper mitigation after consulting with the holder.
of operations. Weed of which includes associated of weeds due to this a	control shall be required on iated roads, pipeline corridontion. The operator shall continue to the control of	th or a	ous weeds become established within the areas be disturbed land where noxious weeds exist, and adjacent land affected by the establishment sult with the Authorized Officer for acceptable PA and BLM requirements and policies.
18. Escape Ramps -	The operator will construct	an	nd maintain pipeline/utility trenches that are not

Page 13 of 18

otherwise fenced, screened, or netted to prevent livestock, wildlife, and humans from becoming entrapped. At a minimum, the operator will construct and maintain escape ramps, ladders, or

other methods of avian and terrestrial wildlife escape in the trenches according to the following criteria:

- a. Any trench left open for eight (8) hours or less is not required to have escape ramps; however, before the trench is backfilled, the contractor/operator shall inspect the trench for wildlife, remove all trapped wildlife, and release them at least 100 yards from the trench.
- b. For trenches left open for eight (8) hours or more, earthen escape ramps (built at no more than a 30 degree slope and spaced no more than 500 feet apart) shall be placed in the trench.

C. ELECTRIC LINES

STANDARD STIPULATIONS FOR OVERHEAD ELECTRIC DISTRIBUTION LINES

A copy of the grant and attachments, including stipulations, survey plat and/or map, will be on location during construction. BLM personnel may request to you a copy of your permit during construction to ensure compliance with all stipulations.

Holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer:

- 1. The holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant.
- 2. The holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976 as amended, 15 USC 2601 et seq. (1982) with regards to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized under this right-of-way grant. (See 40 CFR, Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR, Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation, and Liability Act, section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the authorized officer concurrent with the filing of the reports to the involved Federal agency or State government.
- 3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, et seq. or the Resource Conservation and Recovery Act, 42 U.S.C. 6901, et seq.) on the Right-of-Way (unless the release or threatened release is wholly unrelated to the Right-of-Way holder's activity on the Right-of-Way), or resulting from the activity of the Right-of-Way holder on the Right-of-Way. This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

Page 14 of 18

- 4. There will be no clearing or blading of the right-of-way unless otherwise agreed to in writing by the Authorized Officer.
- 5. Power lines shall be constructed and designed in accordance to standards outlined in "Suggested Practices for Avian Protection on Power lines: The State of the Art in 2006" Edison Electric Institute, APLIC, and the California Energy Commission 2006. The holder shall assume the burden and expense of proving that pole designs not shown in the above publication deter raptor perching, roosting, and nesting. Such proof shall be provided by a raptor expert approved by the Authorized Officer. The BLM reserves the right to require modification or additions to all powerline structures placed on this right-of-way, should they be necessary to ensure the safety of large perching birds. Such modifications and/or additions shall be made by the holder without liability or expense to the United States.

Raptor deterrence will consist of but not limited to the following: triangle perch discouragers shall be placed on each side of the cross arms and a nonconductive perching deterrence shall be placed on all vertical poles that extend past the cross arms.

- 6. The holder shall minimize disturbance to existing fences and other improvements on public lands. The holder is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the owner of any improvements prior to disturbing them. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting the fence. No permanent gates will be allowed unless approved by the Authorized Officer.
- 7. The BLM serial number assigned to this authorization shall be posted in a permanent, conspicuous manner where the power line crosses roads and at all serviced facilities. Numbers will be at least two inches high and will be affixed to the pole nearest the road crossing and at the facilities served.
- 8. Upon cancellation, relinquishment, or expiration of this grant, the holder shall comply with those abandonment procedures as prescribed by the Authorized Officer.
- 9. All surface structures (poles, lines, transformers, etc.) shall be removed within 180 days of abandonment, relinquishment, or termination of use of the serviced facility or facilities or within 180 days of abandonment, relinquishment, cancellation, or expiration of this grant, whichever comes first. This will not apply where the power line extends service to an active, adjoining facility or facilities.
- 10. Any cultural and/or paleontological resource (historic or prehistoric site or object) discovered by the holder, or any person working on his behalf, on public or Federal land shall be immediately reported to the Authorized Officer. Holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery will be made by the

Page 15 of 18

Authorized Officer to determine appropriate actions to prevent the loss of significant cultural or scientific values. The holder will be responsible for the cost of evaluation and any decision as to proper mitigation measures will be made by the Authorized Officer after consulting with the holder.

11. Special Stipulations:

- For reclamation remove poles, lines, transformer, etc. and dispose of properly.
- Fill in any holes from the poles removed.

VIII. INTERIM RECLAMATION

During the life of the development, all disturbed areas not needed for active support of production operations should undergo interim reclamation in order to minimize the environmental impacts of development on other resources and uses.

Within six (6) months of well completion, operators should work with BLM surface management specialists (Jim Amos: 575-234-5909) to devise the best strategies to reduce the size of the location. Interim reclamation should allow for remedial well operations, as well as safe and efficient removal of oil and gas.

During reclamation, the removal of caliche is important to increasing the success of revegetating the site. Removed caliche that is free of contaminants may be used for road repairs, fire walls or for building other roads and locations. In order to operate the well or complete workover operations, it may be necessary to drive, park and operate on restored interim vegetation within the previously disturbed area. Disturbing revegetated areas for production or workover operations will be allowed. If there is significant disturbance and loss of vegetation, the area will need to be revegetated. Communicate with the appropriate BLM office for any exceptions/exemptions if needed.

All disturbed areas after they have been satisfactorily prepared need to be reseeded with the seed mixture provided below.

Upon completion of interim reclamation, the operator shall submit a Sundry Notices and Reports on Wells, Subsequent Report of Reclamation (Form 3160-5).

IX. FINAL ABANDONMENT & RECLAMATION

At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land are restored.

Earthwork for final reclamation must be completed within six (6) months of well plugging. All pads, pits, facility locations and roads must be reclaimed to a satisfactory revegetated, safe, and stable condition, unless an agreement is made with the landowner or BLM to keep the road and/or pad intact.

Page 16 of 18

After all disturbed areas have been satisfactorily prepared, these areas need to be revegetated with the seed mixture provided below. Seeding should be accomplished by drilling on the contour whenever practical or by other approved methods. Seeding may need to be repeated until revegetation is successful, as determined by the BLM.

Operators shall contact a BLM surface protection specialist prior to surface abandonment operations for site specific objectives (Jim Amos: 575-234-5909).

Ground-level Abandoned Well Marker to avoid raptor perching: Upon the plugging and subsequent abandonment of the well, the well marker will be installed at ground level on a plate containing the pertinent information for the plugged well.

Seed Mixture 2, for Sandy Sites

The holder shall seed all disturbed areas with the seed mixture listed below. The seed mixture shall be planted in the amounts specified in pounds of pure live seed (PLS)* per acre. There shall be <u>no</u> primary or secondary noxious weeds in the seed mixture. Seed will be tested and the viability testing of seed will be done in accordance with State law (s) and within nine (9) months prior to purchase. Commercial seed will be either certified or registered seed. The seed container will be tagged in accordance with State law(s) and available for inspection by the authorized officer.

Seed will be planted using a drill equipped with a depth regulator to ensure proper depth of planting where drilling is possible. The seed mixture will be evenly and uniformly planted over the disturbed area (smaller/heavier seeds have a tendency to drop the bottom of the drill and are planted first). The holder shall take appropriate measures to ensure this does not occur. Where drilling is not possible, seed will be broadcast and the area shall be raked or chained to cover the seed. When broadcasting the seed, the pounds per acre are to be doubled. The seeding will be repeated until a satisfactory stand is established as determined by the authorized officer. Evaluation of growth will not be made before completion of at least one full growing season after seeding.

Species to be planted in pounds of pure live seed* per acre:

Species	l <u>b/acre</u>
Sand dropseed (Sporobolus cryptandrus)	1.0
Sand love grass (Eragrostis trichodes)	1.0
Plains bristlegrass (Setaria macrostachya)	2.0

*Pounds of pure live seed:

Pounds of seed x percent purity x percent germination = pounds pure live seed

Page 18 of 18



U.S. Department of the Interior BUREAU OF LAND MANAGEMENT



Operator Certification

I hereby certify that I, or someone under my direct supervision, have inspected the drill site and access route proposed herein; that I am familiar with the conditions which currently exist; that I have full knowledge of state and Federal laws applicable to this operation; that the statements made in this APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for the operations conducted under this application. These statements are subject to the provisions of 18 U.S.C. 1001 for the filing of false statements.

NAME: Rebecca Deal Signed on: 10/22/2018

Title: Regulatory Compliance Professional

Street Address: 333 West Sheridan Avenue

City: Oklahoma City State: OK Zip: 73102

Phone: (405)228-8429

Email address: Rebecca.Deal@dvn.com

Field Representative

Representative Name: Travis Phibbs

Street Address: 333 W SHERIDAN AVE


City: OKC State: OK Zip: 73102

Phone: (575)748-9929

Email address: travis.phibbs@dvn.com



U.S. Department of the Interior BUREAU OF LAND MANAGEMENT



APD ID: 10400035366 **Submission Date:** 10/22/2018

Operator Name: DEVON ENERGY PRODUCTION COMPANY LP

Well Name: GREEN WAVE 20-32 FED STATE COM

Well Number: 16H

Well Type: OIL WELL Well Work Type: Drill

Show Final Text

Section 1 - General

APD ID: 10400035366

Tie to previous NOS?

Submission Date: 10/22/2018

BLM Office: CARLSBAD

Federal/Indian APD: FED

Lease number: NMNM114991

User: Rebecca Deal

Title: Regulatory Compliance

Professional Is the first lease penetrated for production Federal or Indian? FED

Lease Acres: 1880

Surface access agreement in place?

Allotted?

Reservation:

Agreement in place? NO

Federal or Indian agreement:

Agreement number:

Agreement name:

Keep application confidential? YES

Permitting Agent? NO

APD Operator: DEVON ENERGY PRODUCTION COMPANY LP

Operator letter of designation:

Operator Info

Operator Organization Name: DEVON ENERGY PRODUCTION COMPANY LP

Operator Address: 333 West Sheridan Avenue

Zip: 73102

Operator PO Box:

Operator City: Oklahoma City

State: OK

Operator Phone: (800)583-3866

Operator Internet Address:

Section 2 - Well Information

Well in Master Development Plan? EXISTING

Mater Development Plan name: RATTLESNAKE 2 MDP

Well in Master SUPO? NO

Master SUPO name:

Well in Master Drilling Plan? NO

Master Drilling Plan name:

Well Name: GREEN WAVE 20-32 FED STATE COM

Well Number: 16H

Well API Number:

Field/Pool or Exploratory? Field and Pool

Field Name: BRADLEY

Pool Name: BONE SPRIING

Is the proposed well in an area containing other mineral resources? NATURAL GAS,OIL

Operator Name: DEVON ENERGY PRODUCTION COMPANY LP

Well Name: GREEN WAVE 20-32 FED STATE COM

Well Number: 16H

Describe other minerals:

Is the proposed well in a Helium production area? N Use Existing Well Pad? NO New surface disturbance?

Type of Well Pad: MULTIPLE WELL

Multiple Well Pad Name: Number: 20-08
RATTLESNAKE MDP 1 PAD

Well Class: HORIZONTAL

Number of Legs: 1

Well Work Type: Drill

Well Type: OIL WELL

Describe Well Type:

Well sub-Type: INFILL

Describe sub-type:
Distance to town:

Distance to nearest well: 1451 FT Distance to lease line: 1911 FT

Reservoir well spacing assigned acres Measurement: 316.2 Acres

Well plat: Green_Wave_20_32_Fed_State_Com_16H_C_102_20181022071805.pdf

Well work start Date: 04/01/2020 Duration: 45 DAYS

Section 3 - Well Location Table

Survey Type: RECTANGULAR

Describe Survey Type:

Datum: NAD83 Vertical Datum: NAVD88

Survey number:

	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	MD	TVD
SHL Leg #1	219 9	FSL	191 - 1	FWL	26\$	34E	20	Aliquot NESW	32.02772 18	- 103.4942 537	LEA	1	NEW MEXI CO	F		334 9	0	0
KOP Leg #1	229 9	FSL	166 0	FWL	26S	34E	20	Aliquot NESW	32.02800 2	- 103.4950 61	LEA	1	NEW MEXI CO	F	NMNM 114991	- 864 3	119 96	119 92
PPP Leg #1	229 9	FSL	166 0	FWL	26S	34E	20	Aliquot NESW	32.02800 2	- 103.4950 61	LEA	NEW MEXI CO	NEW MEXI CO	F	NMNM 114991	- 864 3	119 96	119 92

Well Name: GREEN WAVE 20-32 FED STATE COM Well Number: 16H

	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	MD	ΩΛΙ
EXIT	100	FNL	166	FWL	26S	34E	32	Lot	32.00053	-	LEA	NEW	NEW	S	STATE	-	223	125
Leg			0					3	7	103.4950		MEXI	l .			921	14	65
#1										41		co	co			6		
BHL	249	FNL	166	FWL	26S	34E	32	Lot	32.00032	-	LEA	NEW	NEW	s	STATE	-	223	125
Leg	0		0					3	7	103.4950		MEXI	MEXI		,	921	95	65



Well Type: OIL WELL

U.S. Department of the Interior BUREAU OF LAND MANAGEMENT.

Drilling Plan Data Report

03/25/2019

APD ID: 10400035366 **Submission Date:** 10/22/2018

Operator Name: DEVON ENERGY PRODUCTION COMPANY LP

Well Name: GREEN WAVE 20-32 FED STATE COM

Well Number: 16H

Well Work Type: Drill



Show Final Text

Section 1 - Geologic Formations

Formation			True Vertical	Measured			Producing
ID	Formation Name	Elevation	Depth	Depth	Lithologies	Mineral Resources	Formation
1		3348	0	0	SANDSTONE,OTHER: SURFACE	NONE	No
2	RUSTLER	2653	695	695	SANDSTONE	NONE	No
3	TOP SALT	2283	1065	1065	SALT	NONE	No
4	BASE OF SALT	-1738	5085	5085	OTHER	NONE	·No
5	BELL CANYON	-2002	5350	5350	SANDSTONE	NATURAL GAS,OIL	No
6	CHERRY CANYON	-3083	6430	6430	SANDSTONE	NATURAL GAS,OIL	No
7	BRUSHY CANYON	-4712	8060	8060	SANDSTONE	NATURAL GAS,OIL	No
8	BONE SPRINGS	-6267	9615	9615	SANDSTONE	NATURAL GAS,OIL	No
9	BONE SPRING 1ST	-7232	10580	10580	SANDSTONE	NATURAL GAS,OIL	No
10	BONE SPRING 2ND	-7792	11140	11140	SANDSTONE	NATURAL GAS,OIL	No
11	BONE SPRING 3RD	-8862	12210	12210	SANDSTONE	NATURAL GAS,OIL	Yes
12	WOLFCAMP	-9282	12630	12630	SHALE	NATURAL GAS,OIL	No

Section 2 - Blowout Prevention

Rating Depth: 12565

Requesting Variance? YES

Well Name: GREEN WAVE 20-32 FED STATE COM

Well Number: 16H

Choke Diagram Attachment:

10M_BOPE_CHK_DR_CLS_RKL_20190306133658.pdf

BOP Diagram Attachment:

10M_BOPE_CHK_DR_CLS_RKL_20190306133706.pdf

Rating Depth: 5200

Requesting Variance? YES

Choke Diagram Attachment:

5M_BOPE__CK_20190306133429.pdf

BOP Diagram Attachment:

5M_BOPE__CK_20190306133446.pdf

Section 3 - Casing

Casing ID	String Type	Hole Size	Csg Size	Condition	Standard	Tapered String	Top Set MD	Bottom Set MD	Top Set TVD	Bottom Set TVD	Top Set MSL	Bottom Set MSL	Calculated casing length MD	Grade	Weight	Joint Type	Collapse SF	Burst SF	Joint SF Type	Joint SF	Body SF Type	Body SF
1	SURFACE	17.5	13.375	NEW	API	N	0	725	0	725			725	H-40		OTHER - BTC	1.12 5	1.25	BUOY	1.6	BUOY	1.6
2		12.2 5	9.625	NEW	API	N	0	5200	0	5200			5200	J-55	l .	OTHER - BTC	1.12 5	1.25	BUOY	1.6	BUOY	1.6
3	PRODUCTI ON	8.75	5.5	NEW	API	N	0	22394	0	12565			22394	P- 110		OTHER - BTC	1.12 5	1.25	BUOY	1.6	BUOY	1.6

Casing Attachments
Casing ID: 1 String Type:SURFACE
Inspection Document:
Spec Document:
Tapered String Spec:
Casing Design Assumptions and Worksheet(s):
Surf_Csg_Ass_20181022072335.pdf
Casing ID: 2 String Type:INTERMEDIATE
Inspection Document:
Spec Document:
Tapered String Spec:
Casing Design Assumptions and Worksheet(s):
Int_Csg_Ass_20181009072743.pdf
Casing ID: 3 String Type: PRODUCTION
Inspection Document:
Spec Document:
Tapered String Spec:
Casing Design Assumptions and Worksheet(s):
Prod_Csg_Ass_20181022072440.pdf

Well Number: 16H

Operator Name: DEVON ENERGY PRODUCTION COMPANY LP

Well Name: GREEN WAVE 20-32 FED STATE COM

Section 4 - Cement

Well Name: GREEN WAVE 20-32 FED STATE COM Well Number: 16H

String Type	Lead/Tail	Stage Tool Depth	Тор МD	Bottom MD	Quantity(sx)	Yield	Density	Cu Ft	Excess%	Cement type	Additives
SURFACE	Lead		0	725	563	1.34	14.8	755	50	С	1% Calcium Chloride

INTERMEDIATE	Lead	0	4700	1034	1.85	12.9	1914	30	С	(65:35) Class C Cement: Poz (Fly Ash): 6% BWOC Bentonite + 5% BWOW Sodium Chloride + 0.125 lbs/sks Poly-E-Flake
INTERMEDIATE	Tail	4700	5200	153	1.33	14.8	204	30	С	0.125 lbs/sack Poly-F- Flake
PRODUCTION	Lead	5000	1188 4	665	3.27	9	2174	25	TUNED	TUNED LITE
PRODUCTION	Tail	1188	2239 4	2766	1.2	14.5	3319	25	H	(50:50) Clas H Cement: Poz (Fly Ash) + 0.5% bwoc HALAD-344 + 0.4% bwoc CFR-3 + 0.2% BWOC HR-601 + 2% bwoc Bentonite

Section 5 - Circulating Medium

Mud System Type: Closed

Will an air or gas system be Used? NO

Description of the equipment for the circulating system in accordance with Onshore Order #2:

Diagram of the equipment for the circulating system in accordance with Onshore Order #2:

Describe what will be on location to control well or mitigate other conditions: Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

Describe the mud monitoring system utilized: PVT/Pason/Visual Monitoring

Circulating Medium Table

Well Name: GREEN WAVE 20-32 FED STATE COM

Well Number: 16H

Top Depth	Bottom Depth	Mud Type	Min Weight (lbs/gal)	Max Weight (lbs/gal)	Density (lbs/cu ft)	Gel Strength (lbs/100 sqft)	ЬН	Viscosity (CP)	Salinity (ppm)	Filtration (cc)	Additional Characteristics
5200	2239 4	WATER-BASED MUD	8.4	10				12			
0	725	SPUD MUD	8.34	8.6		<u> </u>		2		i. •	
725	5200	SALT SATURATED	9	10				2			

Section 6 - Test, Logging, Coring

List of production tests including testing procedures, equipment and safety measures:

Will run GRMWD from TD to from KOP. Cement bond logs will be run in vertical to determine top of cement. Stated logs run will be in the Completion Report and submitted to the BLM.

List of open and cased hole logs run in the well:

CALIPER, CBL, DS, GR, MUDLOG

Coring operation description for the well:

N/A

Section 7 - Pressure

Anticipated Bottom Hole Pressure: 6850

Anticipated Surface Pressure: 4085.7

Anticipated Bottom Hole Temperature(F): 175

Anticipated abnormal pressures, temperatures, or potential geologic hazards? NO

Describe:

Contingency Plans geoharzards description:

Contingency Plans geohazards attachment:

Hydrogen Sulfide drilling operations plan required? YES

Hydrogen sulfide drilling operations plan:

Green_Wave_20_32_Fed_State_Com_16H_H2S_PLAN_20181022072618.pdf

Well Name: GREEN WAVE 20-32 FED STATE COM Well Number: 16H

Section 8 - Other Information

Proposed horizontal/directional/multi-lateral plan submission:

Green_Wave_20_32_Fed_State_Com_16H_Dir_Svy_20181022072718.pdf

Green_Wave_20_32_Fed_State_Com_16H_Plot_20181022072718.pdf

Other proposed operations facets description:



Other proposed operations facets attachment:

Spudder_Rig_Info_20180823120206.pdf

Clsd_Loop_20180823120203.pdf

Green_Wave_20_32_Fed_WP_20_8_GCP_Form_20181022072808.pdf

5.5_x_17__P_110_BTC_20190306134836.pdf

8.625_32.00_L80HC_20190306134837.pdf

9.625_40__J_55_20190306134837.pdf

13.375_48__H40_20190306134838.pdf

9.625_40__P110EC_BTC_V_M_4230_Collapse_20190306134838.pdf

MB_Wellhd_10M___SDT_1815_20190306135340.pdf

MB_Wellhd_10M_2_20190306135426.pdf

MB_Verb_10M_20190306135447.pdf


Green_Wave_20_32_Fed_State_Com_16H_Drilling_Document_R1_20190306135612.pdf


Other Variance attachment:


Co_flex_20180823120220.pdf


10M_BOPE_CHK_DR_CLS_RKL_20190306134745.pdf


Annular_Variance___Preventer_Summary_20190306134745.pdf


















































Casing Assumptions and Load Cases

Intermediate

Intermediate Casing Burst Design							
Load Case	External Pressure	Internal Pressure					
Pressure Test	Formation Pore Pressure	Max mud weight of next hole- section plus Test psi					
Drill Ahead	Formation Pore Pressure	Max mud weight of next hole section					
Fracture @ Shoe	Formation Pore Pressure	Dry gas					

	Intermediate Casing Collapse Design							
Load Case External Pressure Internal Pressure								
Full Evacuation	Water gradient in cement, mud above TOC	None						
Cementing Wet cement weight Water (8.33ppg)								

Intermediate Casing Tension Design							
Load Case Assumptions							
Overpull	100kips						
Runing in hole	2 ft/s						
Service Loads	N/A						

Casing Assumptions and Load Cases

Intermediate

Intermediate Casing Burst Design						
Load Case	External Pressure	Internal Pressure				
Pressure Test	Formation Pore Pressure	Max mud weight of next hole- section plus Test psi				
Drill Ahead	Formation Pore Pressure	Max mud weight of next hole section				
Fracture @ Shoe	Formation Pore Pressure	Dry gas				

Intermediate Casing Collapse Design									
Load Case External Pressure Internal Pressure									
Full Evacuation	Water gradient in cement, mud above TOC	None							
Cementing Wet cement weight Water (8.33ppg)									

Intermediate Casing Tension Design		
Load Case Assumptions		
Overpull 100kips		
Runing in hole 2 ft/s		
Service Loads N/A		

Production Casing Burst Design		
Load Case	External Pressure	Internal Pressure
Pressure Test	Formation Pore Pressure	Fluid in hole (water or produced water) + test psi
Tubing Leak	Formation Pore Pressure	Packer @ KOP, leak below surface 8.6 ppg packer fluid
Stimulation	Formation Pore Pressure	Max frac pressure with heaviest frac fluid

Production Casing Collapse Design		
Load Case External Pressure Internal Pressure		
Full Evacuation	Water gradient in cement, mud above TOC.	None
Cementing	Wet cement weight	Water (8.33ppg)

Production Casing Tension Design		
Load Case Assumptions		
Overpull 100kips		
Runing in hole 2 ft/s		
Service Loads N/A		

Surface

Surface Casing Burst Design		
Load Case External Pressure Internal Pressure		
Pressure Test	Formation Pore Pressure	Max mud weight of next hole- section plus Test psi
Drill Ahead	Formation Pore Pressure	Max mud weight of next hole section
Displace to Gas	Formation Pore Pressure	Dry gas from next casing point

Surface Casing Collapse Design		
Load Case External Pressure Internal Pressure		
Full Evacuation	Water gradient in cement, mud above TOC	None -
Cementing	Wet cement weight	Water (8.33ppg)

Surface Casing Tension Design		
Load Case Assumptions		
Overpull 100kips		
Runing in hole 3 ft/s		
Service Loads N/A		

Casing Assumptions and Load Cases

Intermediate

Intermediate Casing Burst Design		
Load Case	Internal Pressure	
Pressure Test	Formation Pore Pressure	Max mud weight of next hole- section plus Test psi
Drill Ahead	Formation Pore Pressure	Max mud weight of next hole section
Fracture @ Shoe	Formation Pore Pressure	Dry gas

Intermediate Casing Collapse Design		
Load Case External Pressure Internal Pressure		
Full Evacuation	Water gradient in cement, mud above TOC	None ·
Cementing	Wet cement weight	Water (8.33ppg)

Intermediate Casing Tension Design		
Load Case Assumptions		
Overpull 100kips		
Runing in hole 2 ft/s		
Service Loads N/A		

Production Casing Burst Design		
Load Case	Internal Pressure	
Pressure Test	Formation Pore Pressure	Fluid in hole (water or produced water) + test psi
Tubing Leak	Formation Pore Pressure	Packer @ KOP, leak below surface 8.6 ppg packer fluid
Stimulation	Formation Pore Pressure	Max frac pressure with heaviest frac fluid

Production Casing Collapse Design		
Load Case External Pressure Internal Pressure		
Full Evacuation	Water gradient in cement, mud above TOC.	None
Cementing	Wet cement weight	Water (8.33ppg)

Production Casing Tension Design			
Load Case Assumptions			
Overpull	100kips		
Runing in hole 2 ft/s			
Service Loads	N/A		

Production Casing Burst Design			
Load Case	External Pressure	Internal Pressure	
Pressure Test	Formation Pore Pressure	Fluid in hole (water or produced water) + test psi	
Tubing Leak	Formation Pore Pressure	Packer @ KOP, leak below surface 8.6 ppg packer fluid	
Stimulation	Formation Pore Pressure	Max frac pressure with heaviest frac fluid	

Production Casing Collapse Design					
Load Case External Pressure Internal Pressure					
Full Evacuation	Water gradient in cement, mud above TOC.	None			
Cementing	Wet cement weight	Water (8.33ppg)			

Production Casing Tension Design			
Load Case Assumptions			
Overpull	100kips		
Runing in hole	n hole 2 ft/s		
Service Loads N/A			

Surface

Surface Casing Burst Design			
Load Case	External Pressure	Internal Pressure Max mud weight of next holesection plus Test psi	
Pressure Test	Formation Pore Pressure		
I		Max mud weight of next hole section	
Displace to Gas	Formation Pore Pressure	Dry gas from next casing point	

Surface Casing Collapse Design				
Load Case External Pressure Internal Pressure				
Full Evacuation	Water gradient in cement, mud above TOC	None ·		
Cementing	Wet cement weight	Water (8.33ppg)		

Surface Casing Tension Design			
Load Case Assumptions			
Overpull	100kips		
Runing in hole 3 ft/s			
Service Loads N/A			



Devon Energy Center 333 West Sheridan Avenue Oklahoma City, Oklahoma 73102-5015


Hydrogen Sulfide (H₂S) Contingency Plan

For

Green Wave 20-32 Fed State Com 16H

Sec-20 T-26S R-34E 2199' FSL & 1911' FWL LAT. = 32.0277218' N (NAD83) LONG = 103.4942537' W

Lea County NM



Escape

Crews shall escape upwind of escaping gas in the event of an emergency release of gas. Escape can be facilitated from the location entrance road. Crews should then block the entrance to the location from the lease road so as not to allow anyone traversing into a hazardous area. The blockade should be at a safe distance outside of the ROE. There are no homes or buildings in or near the ROE.

Assumed 100 ppm ROE = 3000'

100 ppm H₂S concentration shall trigger activation of this plan.

Emergency Procedures

In the event of a release of gas containing H₂S, the first responder(s) must

- Isolate the area and prevent entry by other persons into the 100 ppm ROE.
- Evacuate any public places encompassed by the 100 ppm ROE.
- Be equipped with H₂S monitors and air packs in order to control the release.
- Use the "buddy system" to ensure no injuries occur during the response
- Take precautions to avoid personal injury during this operation.
- Contact operator and/or local officials to aid in operation. See list of phone numbers attached.
- · Have received training in the
 - o Detection of H₂S, and
 - o Measures for protection against the gas,
 - o Equipment used for protection and emergency response.

Ignition of Gas Source

Should control of the well be considered lost and ignition considered, take care to protect against exposure to Sulfur Dioxide (SO₂). Intentional ignition must be coordinated with the NMOCD and local officials. Additionally the NM State Police may become involved. NM State Police shall be the Incident Command on scene of any major release. Take care to protect downwind whenever there is an ignition of the gas

Characteristics of H₂S and SO₂

Common Name	Chemical Formula	Specific Gravity	Threshold Limit	Hazardous Limit	Lethal Concentration
Hydrogen Sulfide	H ₂ S	1.189 Air = 1	10 ppm	100 ppm/hr	600 ppm
Sulfur Dioxide	SO ₂	2.21 Air = 1	2 ppm	N/A	1000 ppm

Contacting Authorities

Devon Energy Corp. personnel must liaison with local and state agencies to ensure a proper response to a major release. Additionally, the OCD must be notified of the release as soon as possible but no later than 4 hours. Agencies will ask for information such as type and volume of release, wind direction, location of release, etc. Be prepared with all information available. The following call list of essential and potential responders has been prepared for use during a release. Devon Energy Corp. Company response must be in coordination with the State of New Mexico's 'Hazardous Materials Emergency Response Plan' (HMER)

Hydrogen Sulfide Drilling Operation Plan

I. HYDROGEN SULFIDE (H₂S) TRAINING

All personnel, whether regularly assigned, contracted, or employed on an unscheduled basis, will receive training from a qualified instructor in the following areas prior to commencing drilling operations on this well:

- 1. The hazards and characteristics of hydrogen sulfide (H₂S)
- 2. The proper use and maintenance of personal protective equipment and life support systems.
- 3. The proper use of H₂S detectors, alarms, warning systems, briefing areas, evacuation procedures, and prevailing winds.
- 4. The proper techniques for first aid and rescue procedures.

In addition, supervisory personnel will be trained in the following areas:

- 1. The effects of H₂S metal components. If high tensile tubulars are to be used, personnel will be trained in their special maintenance requirements.
- 2. Corrective action and shut-in procedures when drilling or reworking a well and blowout prevention and well control procedures.
- 3. The contents and requirements of the H₂S Drilling Operations Plan and Public Protection Plan.

There will be an initial training session just prior to encountering a known or probable H₂S zone (within 3 days or 500 feet) and weekly H₂S and well control drills for all personnel in each crew. The initial training session shall include a review of the site specific H₂S Drilling Operations Plan and the Public Protection Plan.

II. HYDROGEN SULFIDE TRAINING

Note: All H₂S safety equipment and systems will be installed, tested, and operational when drilling reaches a depth of 500 feet above, or three days prior to penetrating the first zone containing or reasonably expected to contain H₂S.

1. Well Control Equipment

- A. Flare line
- B. Choke manifold Remotely Operated
- C. Blind rams and pipe rams to accommodate all pipe sizes with properly sized closing unit
- D. Auxiliary equipment may include if applicable: annular preventer and rotating head.
- E. Mud/Gas Separator

2. Protective equipment for essential personnel:

30-minute SCBA units located at briefing areas, as indicated on well site diagram, with escape units available in the top doghouse. As it may be difficult to communicate audibly while wearing these units, hand signals shall be utilized.

3. H₂S detection and monitoring equipment:

Portable H₂S monitors positioned on location for best coverage and response. These units have warning lights which activate when H₂S levels reach 10 ppm and audible sirens which activate at 15 ppm. Sensor locations:

- Bell nipple
- Possum Belly/Shale shaker
- Rig floor
- Choke manifold
- Cellar

Visual warning systems:

- A. Wind direction indicators as shown on well site diagram
- B. Caution/ Danger signs shall be posted on roads providing direct access to locations. Signs will be painted a high visibility yellow with black lettering of sufficient size to be reasonable distance from the immediate location. Bilingual signs will be used when appropriate.

4. Mud program:

The mud program has been designed to minimize the volume of H₂S circulated to surface. Proper mud weight, safe drilling practices and the use of H₂S scavengers will minimize hazards when penetrating H₂S bearing zones.

5. Metallurgy:

- A. All drill strings, casings, tubing, wellhead, blowout preventer, drilling spool, kill lines, choke manifold lines, and valves shall be H₂S trim.
- B. All elastomers used for packing and seals shall be H₂S trim.

6. Communication:

- A. Company personnel have/use cellular telephones in the field.
- B. Land line (telephone) communications at Office

7. Well testing:


- A. Drill stem testing will be performed with a minimum number of personnel in the immediate vicinity, which are necessary to safety and adequately conduct the test. The drill stem testing will be conducted during daylight hours and formation fluids will not be flowed to the surface. All drill-stem-testing operations conducted in an H₂S environment will use the closed chamber method of testing.
- B. There will be no drill stem testing.

Drilling Su	pervisor – Basin – Mark Kramer		405-823-479
EHS Profe	essional – Laura Wright		405-439-812
<u>Agency</u>	Call List		
<u>Lea</u>	Hobbs		
County	Lea County Communication Authority	<u>'</u>	393-398
<u>(575)</u>	State Police		392-558
	City Police		397-926
	Sheriff's Office		393-251
	Ambulance		91
	Fire Department	397-930	
	LEPC (Local Emergency Planning Co	393-287	
	NMOCD		393-616
	US Bureau of Land Management		393-361
Eddy	Carlsbad		
County	State Police	•	885-313
(575)	City Police		885-211
	Sheriff's Office		887-755
	Ambulance		91
	Fire Department		885-312
	LEPC (Local Emergency Planning Co	ommittee)	887-379
	US Bureau of Land Management		887-654
	NM Emergency Response Commission	on (Santa Fe)	(505) 476-960
	24 HR	on (ountain o)	(505) 827-912
	National Emergency Response Center		(800) 424-880
	National Pollution Control Center: Dir		(703) 872-600
	For Oil Spills		(800) 280-711
	Emergency Services		(000) 200-711
			(201) 704 470
	Wild Well Control	(045) 000	(281) 784-470
	Cudd Pressure Control	(915) 699- 0139	(915) 563-335
	Halliburton		(575) 746-275
	B. J. Services		(575) 746-356
Give	Native Air – Emergency Helicopter –	Hobbs	(575) 392-642
GPS	Flight For Life - Lubbock, TX		(806) 743-991
position:	Aerocare - Lubbock, TX	14	(806) 747-892
	Med Flight Air Amb - Albuquerque, N		(575) 842-443
	Lifeguard Air Med Svc. Albuquerque,	NM	(800) 222-122
	Poison Control (24/7)		(575) 272-311
	Oil & Gas Pipeline 24 Hour Service		(800) 364-436
	NOAA – Website - www.nhc.noaa.go	OV	





Devon Energy - Well Pad Rig Location Layout Safety Equipment Location



WCDSC Permian NM

Lea County (NAD83 New Mexico East) Sec 20-T26S-R34E Green Wave 20-32 Fed State Com 16H

Wellbore #1

Plan: Permit Plan 1

Standard Planning Report - Geographic

26 September, 2018

Database: Company: Project:

EDM r5000.141_Prod US

WCDSC Permian NM Lea County (NAD83 New Mexico East)

Site:

Sec 20-T26S-R34E

Well:

Wellbore: Design:

Green Wave 20-32 Fed State Com 16H

Wellbore #1 Permit Plan 1 Local Co-ordinate Reference:

TVD Reference: MD Reference:

North Reference:

Survey Calculation Method:

Well Green Wave 20-32 Fed State Com 16H

RKB @ 3374.00ft

RKB @ 3374.00ft Grid

Minimum Curvature

Project

Lea County (NAD83 New Mexico East)

Map System: Geo Datum: Map Zone:

US State Plane 1983 North American Datum 1983 New Mexico Eastern Zone

System Datum:

Mean Sea Level

Site

Sec 20-T26S-R34E

Site Position: From:

Position Uncertainty:

Мар

Northing: Easting:

Slot Radius:

375,305.15 usft 804,412.02 usft

Latitude: Longitude:

32.028952 -103,484420 0.45° **Grid Convergence:**

Well

Green Wave 20-32 Fed State Com 16H

Well Position

Position Uncertainty

+N/-S +E/-W

0.00 ft 0.00 ft 0.50 ft

0.00 ft

Northing: Easting: Wellhead Elevation:

9/26/2018

374,833.68 usft 801,367.98 usft

13-3/16"

Latitude: Longitude:

32.027722 -103.494254

3,349.00 ft

Ground Level:

Wellbore

Wellbore #1

Magnetics

Model Name IGRF2015

Sample Date

Declination (°) 6.76 Dip Angle (°)

Field Strength (nT)

47,699.02545985

Design

Permit Plan 1

Audit Notes:

Version:

Phase:

PROTOTYPE

Tie On Depth:

0.00

59.88

Vertical Section:

Depth From (TVD) (ft) 0.00

9/26/2018

+N/-S (ft) 0.00

+E/-W (ft) 0.00

Direction (°) 180.96

Plan Survey Tool Program Depth From

(ft)

Depth To

Date

Survey (Wellbore)

Tool Name

Remarks

(ft) 0.00

22,394.83 Permit Plan 1 (Wellbore #1)

MWD+HDGM OWSG MWD + HDGM

Plan Sections Vertical Dogleg Measured Build Turn Depth Inclination Azimuth Depth +N/-S +E/-W Rate Rate Rate TFO (°/100usft) (°/100usft) (°/100usft) (ft) (ft) (ft) (ft) (°) (°) (°) Target 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 2,500.00 0.00 0.00 2,500.00 0.00 0.00 0.00 0.00 0.00 0.00 2,671.98 1.72 291.72 2,671.95 0.96 -2.40 1.00 1.00 0.00 291.72 11,531.38 1.72 291.72 11,527.36 99.36 -249.40 0.00 0.00 0.00 0.00 11,646.03 0.00 0.00 11,642.00 100.00 -251.00 1.50 -1.50 0.00 180.00 11,996.07 11,992.04 100.00 -251.00 0.00 0.00 0.00 0.00 0.00 0.00 12,896.08 90.00 179.52 12,565.00 -472.94 -246.20 10.00 10.00 0.00 179.52 PBHL - Green Wave 2 22,394.83 90.00 179.52 12,565.00 -9,971.36 -166.56 0.00 0.00 0.00 0.00 PBHL - Green Wave 2

Database: Company: EDM r5000.141_Prod US

WCDSC Permian NM

Project: Lea County (NAD83 New Mexico East)

Site: Sec 20-T26S-R34E

Well:

Green Wave 20-32 Fed State Com 16H

Wellbore #1 Wellbore: Permit Plan 1 Design:

TVD Reference:

MD Reference: North Reference:

Survey Calculation Method:

Local Co-ordinate Reference:

Well Green Wave 20-32 Fed State Com 16H

RKB @ 3374.00ft RKB @ 3374.00ft

Grid

Minimum Curvature

Planned Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Map Northing (usft)	Map Easting . (usft)	Latitude	Longitude
0.00		0.00	0.00	0.00	0.00	374,833.68	801,367.98	32.027722	-103.4942
100.00		0.00	100.00	0.00	0.00	374,833.68	801,367.98	32.027722	-103.4942
200.00		0.00	200.00	0.00	0.00	374,833.68	801,367.98	32.027722	-103.4942
300.00		0.00	300.00	0.00	0.00	374,833.68	801,367.98	32.027722	-103.4942
400.00		0.00	400.00	0.00	0.00	374,833.68	801,367.98	32.027722	-103.4942
500.00		0.00	500.00	0.00	0.00	374,833.68	801,367.98	32.027722	-103.4942
600.00		0.00	600.00	0.00	0.00	374,833.68	801,367.98	32.027722	-103.4942
700.00		0.00	700.00	0.00	0.00	374,833.68	801,367.98	32.027722	-103.4942
800.00		0.00	800.00	0.00	0.00	374,833.68	801,367.98	32.027722	-103.4942
900.00	0.00	0.00	900.00	0.00	0.00	374,833.68	801,367.98	32.027722	-103.4942
1,000.00	0.00	0.00	1,000.00	0.00	0.00	374,833.68	801,367.98	32.027722	-103.4942
1,100.00	0.00	0.00	1,100.00	0.00	0.00	374,833.68	801,367.98	32.027722	-103.4942
1,200.00	0.00	0.00	1,200.00	0.00	0.00	374,833.68	801,367.98	32.027722	-103.4942
1,300.00		0.00	1,300.00	0.00	0.00	374,833.68	801,367.98	32.027722	-103.4942
1,400.00		0.00	1,400.00	0.00	0.00	374,833.68	801,367.98	32.027722	-103.494
1,500.00		0.00	1,500.00	0.00	0.00	374,833.68	801,367.98	32.027722	-103.494
1,600.00	0.00	0.00	1,600.00	0.00	0.00	374,833.68	801,367.98	32.027722	-103.494
1,700.00	0.00	0.00	1,700.00	0.00	0.00	374,833.68	801,367.98	32.027722	-103.494
1,800.00	0.00	0.00	1,800.00	0.00	0.00	374,833.68	801,367.98	32.027722	-103.494
1,900.00	0.00	0.00	1,900.00	0.00	0.00	374,833.68	801,367.98	32.027722	-103.494
2,000.00	0.00	0.00	2,000.00	0.00	0.00	374,833.68	801,367.98	32.027722	-103.494
2,100.00	0.00	0.00	2,100.00	0.00	0.00	374,833.68	801,367.98	32.027722	-103.494
2,200.00	0.00	0.00	2,200.00	0.00	0.00	374,833.68	801,367.98	32.027722	-103.494
2,300.00	0.00	0.00	2,300.00	0.00	0.00	374,833.68	801,367.98	32.027722	-103.494
2,400.00	0.00	0.00	2,400.00	0.00	0.00	374,833.68	801,367.98	32.027722	-103.494
2,500.00	0.00	0.00	2,500.00	0.00	0.00	374,833.68	801,367.98	32.027722	-103.494
2,600.00	1.00	291.72	2,599.99	0.32	-0.81	374,834.00	801,367.17	32.027723	-103.494
2,671.98	1.72	291.72	2,671.95	0.96	-2.40	374,834.63	801,365.58	32.027725	-103.494
2,700.00	1.72	291.72	2,699.96	1.27	-3.18	374,834.94	801,364.80	32.027725	-103.494
2,800.00	1.72	291.72	2,799.92	2.38	-5.97	374,836.06	801,362.01	32.027729	-103.494
2,900.00	1.72	291.72	2,899.87	3.49	-8.75	374,837.17	801,359.22	32.027732	-103.494
3,000.00	1.72	291.72	2,999.83	4.60	-11.54	374,838.28	801,356.43	32.027735	-103.494
3,100.00	1.72	291.72	3,099.78	5.71	-14.33	374,839.39	801,353.65	32.027738	-103.494
3,200.00	1.72	291.72	3,199.74	6.82	-17.12	374,840.50	801,350.86	32.027741	-103.494
3,300.00	1.72	291.72	3,299.69	7.93	-19.91	374,841.61	801,348.07	32.027744	-103.494
3,400.00	1.72	291.72	3,399.65	9.04	-22.70	374,842.72	801,345.28	32.027747	-103.494
3,500.00		291.72	3,499.60	10.15	-25.48	374,843.83	801,342.49	32.027750	-103.494
3,600.00	1.72	291.72	3,599.56	11.26	-28.27	374,844.94	801,339.71	32.027753	-103.494
3,700.00		291.72	3,699.51	12.37	-31.06	374,846.05	801,336.92	32.027757	-103.494
3,800.00	1.72	291.72	3,799.47	13.48	-33.85	374,847.16	801,334.13	32.027760	-103.494
3,900.00		291.72	3,899.42	14.60	-36.64	374,848.27	801,331.34	32.027763	-103.494
4,000.00		291.72	3,999.38	15.71	-39.42	374,849.38	801,328.55	32.027766	-103.494
4,100.00		291.72	4,099.33	16.82	-42.21	374,850.50	801,325.77	32.027769	-103.494
4,200.00		291.72	4,199.29	17.93	-45.00	374,851.61	801,322.98	32.027772	-103.494
4,300.00	1.72	291.72	4,299.24	19.04	-47.79	374,852.72	801,320.19	32.027775	-103.494
4,400.00		291.72	4,399.20	20.15	-50.58	374,853.83	801,317.40	32.027778	-103.494
4,500.00		291.72	4,499.15	21.26	-53.36	374,854.94	801,314.61	32.027781	-103.494
4,600.00	1.72	291.72	4,599.11	22.37	-56.15	374,856.05	801,311.83	32.027785	-103.494
4,700.00	1.72	291.72	4,699.06	23.48	-58.94	374,857.16	801,309.04	32.027788	-103.494
4,800.00	1.72	291.72	4,799.02	24.59	-61.73	374,858.27	801,306.25	32.027791	-103.494
4,900.00	1.72	291.72	4,898.97	25.70	-64.52	374,859.38	801,303.46	32.027794	-103.494
5,000.00	1.72	291.72	4,998.93	26.81	-67.30	374,860.49	801,300.67	32.027797	-103.494
5,100.00	1.72	291.72	5,098.88	27.93	-70.09	374,861.60	801,297.89	32.027800	-103.494
5,200.00	1.72	291.72	5,198.84	29.04	-72.88	374,862.71	801,295.10	32.027803	-103.494
5,300.00		291.72	5,298.79	30.15	-75.67	374,863.82	801,292.31	32,027806	-103.494

Database: Company: Project: EDM r5000.141_Prod US

WCDSC Permian NM

Lea County (NAD83 New Mexico East)

Site: Sec 20-T26S-R34E

Well: Green Wave 20-32 Fed State Com 16H
Wellbore: Wellbore #1

Weilbore: Weilbore #1

Design: Permit Plan 1

Local Co-ordinate Reference:

TVD Reference:

MD Reference: North Reference:

Survey Calculation Method:

Well Green Wave 20-32 Fed State Com 16H

RKB @ 3374.00ft RKB @ 3374.00ft

Grid

Minimum Curvature

Planned Survey

Planned Survey	,	-		· · · ·					
Measured Depth	Inclination	Azimuth	Vertical Depth	+N/-S	+E/-W	Map Northing	Map Easting		
(ft)	(°)	(°)	(ft)	(ft)	(ft)	(usft)	(usft)	Latitude	Longitude
5,400.00	1.72	291.72	5,398.75	31.26	-78.46	374,864.94	801,289.52	32.027810	-103.494506
5,500.00	1.72	291.72	5,498.70	32.37	-81.24	374,866.05	801,286.73	32.027813	-103.494515
5,600.00	1.72	291.72	5,598.66	33.48	-84.03	374,867.16	801,283.95	32.027816	-103.494524
5,700.00	1.72	291.72	5,698.61	34.59	-86.82	374,868.27	801,281.16	32.027819	-103.494533
5,800.00	1.72	291.72	5,798.57	35.70	-89.61	374,869.38	801,278.37	32.027822	-103.494542
5,900.00	1.72	291.72	5,898.52	36.81	-92.40	374,870.49	801,275.58	32.027825	-103.494551
6,000.00	1.72	291.72	5,998.48	37.92	-95.18	374,871.60	801,272.79	32.027828	-103.494560
6,100.00	1.72	291.72	6,098.43	39.03	-97.97	374,872.71	801,270.01	32.027831	-103.494569
6,200.00	1.72	291.72	6,198.39	40.14	-100.76	374,873.82	801,267.22	32.027834	-103.494578
6,300.00	1.72	291.72	6,298.34	41.25	-103.55	374,874.93	801,264.43	32.027838	-103.494587
6,400.00	1.72	291.72	6,398.30	42.37	-106.34	374,876.04	801,261.64	32.027841	-103.494596
6,500.00	1.72	291.72	6,498.25	43.48	-109.12	374,877.15	801,258.85	32.027844	-103.494605
6,600.00	- 1.72	291.72	6,598.20	44.59	-111.91	374,878.26	801,256.07	32.027847	-103.494614
6,700.00	1.72	291.72	6,698.16	45.70	-114.70	374,879.38	801,253.28	32.027850	-103.494623
6,800.00	1.72	291.72	6,798.11	46.81	-117.49	374,880.49	801,250.49	32.027853	-103.494632
6,900.00		291.72	6,898.07	47.92	-120.28	374,881.60	801,247.70	32.027856	-103.494641
7,000.00		291.72	6,998.02	49.03	-123.06	374,882.71	801,244.91	32.027859	-103.494650
7,100.00		291.72	7,097.98	50.14	-125.85	374,883.82	801,242.13	32.027862	-103.494659
7,200.00		291.72	7,197.93	51.25	-128.64	374,884.93	801,239.34	32.027866	-103.494668
7,300.00		291.72	7,297.89	52.36	-131.43	374,886.04	801,236.55	32.027869	-103.494677
7,400.00		291.72	7,397.84	53.47	-134.22	374,887.15	801,233.76	32.027872	-103.494686
7,500.00		291.72	7,497.80	54.58	-137.00	374,888.26	801,230.97	32.027875	-103.494695
7,600.00		291.72	7,597.75	55.69	-139.79	374,889.37	801,228.19	32.027878	-103.494704
7,700.00		291.72	7,697.71	56.81	-142.58	374,890.48	801,225.40	32.027881	-103.494713
7,800.00		291.72	7,797.66	57.92	-145.37	374,891.59	801,222.61	32.027884	-103.494722
7,900.00		291.72	7,897.62	59.03	-148.16	374,892.70	801,219.82	32.027887	-103.494722
8,000.00		291.72	7,097.52	60.14	-150.95	374,893.82	801,217.03	32.027890	-103.494739
8,100.00		291.72	8,097.53	61.25	-150. 3 3	374,894.93	801,214.25	32.027894	-103.494748
8,200.00		291.72	8,197.48	62.36	-156.52	374,896.04	801,211.46	32.027897	-103.494746
8,300.00		291.72	8,297.44	63.47	-159.31	374,897.15	801,208.67	32.027990	
8,400.00		291.72	8,397.39	64.58	-162.10	374,898.26	801,205.88	32.027900	-103.494766 -103.494775
8,500.00		291.72	8,497.35	65.69	-164.89				
8,600.00		291.72	8,597.30	66.80	-164.69 -167.67	374,899.37	801,203.09	32.027906	-103.494784
8,700.00		291.72 291.72		67.91		374,900.48	801,200.30	32.027909	-103.494793
8,800.00			8,697.26		-170.46	374,901.59	801,197.52	32.027912	-103.494802
8,900.00		291.72	8,797.21	69.02	-173.25	374,902.70	801,194.73	32.027915	-103.494811
9,000.00		291.72 291.72	8,897.17 8,997.12	70.13 71.25	-176.04 -178.83	374,903.81	801,191.94	32.027918	-103.494820
9,100.00						374,904.92	801,189.15	32.027922	-103.494829
		291.72	9,097.08	72.36	-181.61	374,906.03	801,186.36	32.027925	-103.494838
9,200.00 9,300.00		291.72	9,197.03	73.47	-184.40 -407.40	374,907.15	801,183.58	32.027928	-103.494847
9,300.00		291.72	9,296.99	74.58	-187.19	374,908.26	801,180.79	32.027931	-103.494856
-,		291.72	9,396.94	75.69	-189.98	374,909.37	801,178.00	32.027934	-103.494865
9,500.00		291.72	9,496.90	76.80	-192.77	374,910.48	801,175.21	32.027937	-103.494874
9,600.00		291.72	9,596.85	77.91	-195.55	374,911.59	801,172.42	32.027940	-103.494883
9,700.00		291.72	9,696.81	79.02	-198.34	374,912.70	801,169.64	32.027943	-103.494892
9,800.00		291.72	9,796.76	80.13	-201.13	374,913.81	801,166.85	32.027946	-103.494901
9,900.00		291.72	9,896.72	81.24	-203.92	374,914.92	801,164.06	32.027950	-103.494910
10,000.00		291.72	9,996.67	82.35	-206.71	374,916.03	801,161.27	32.027953	-103.494919
10,100.00		291.72	10,096.63	83.46	-209.49	374,917.14	801,158.48	32.027956	-103.494928
10,200.00		291.72	10,196.58	84.57	-212.28	374,918.25	801,155.70	32.027959	-103.494937
10,300.00		291.72	10,296.54	85.69	-215.07	374,919.36	801,152.91	32.027962	-103.494946
10,400.00	1.72	291.72	10,396.49	86.80	-217.86	374,920.47	801,150.12	32.027965	-103.494955
10,500.00		291.72	10,496.45	87.91	-220.65	374,921.59	801,147.33	32.027968	-103.494964
10,600.00	1.72	291.72	10,596.40	89.02	-223.43	374,922.70	801,144.54	32.027971	-103.494973
10,700.00	1.72	291.72	10,696.36	90.13	-226.22	374,923.81	801,141.76	32.027974	-103.494982
10,800.00	1.72	291.72	10,796.31	91.24	-229.01	374,924.92	801,138.97	32.027978	-103.494991

Database: Company: EDM r5000.141_Prod US

WCDSC Permian NM

Project: Lea County (NAD83 New Mexico East)

Sec 20-T26S-R34E

Well:

Site:

Green Wave 20-32 Fed State Com 16H

Wellbore: Wellbore #1
Design: Permit Plan 1

Local Co-ordinate Reference:

TVD Reference:

MD Reference:

Survey Calculation Method:

Well Green Wave 20-32 Fed State Com 16H

RKB @ 3374.00ft

RKB @ 3374.00ft

Grid

Minimum Curvature

Planned Survey Measured Vertical Map Map Depth Depth +E/-W Northing Easting Azimuth +N/-S Inclination (ft) (ft) (usft) (usft) Latitude (°) (ft) (ft) Longitude (°) 10.900.00 1.72 291.72 10,896.27 92.35 -231.80 374,926.03 801,136.18 32.027981 -103.495000 11,000.00 291.72 10,996.22 93.46 -234.59 374,927.14 801,133.39 32.027984 -103.495009 1.72 291 72 11 096 18 94 57 -237 37 374 928 25 32 027987 -103 495017 11.100.00 1 72 801,130,60 -103.495026 11,200.00 1.72 291.72 11 196 13 95 68 -240 16 374,929.36 801,127.82 32 027990 374,930.47 11,300.00 1.72 291.72 11,296,09 96.79 -242.95801,125.03 32.027993 -103 495035 11.400.00 1.72 291.72 11.396.04 97.90 -245.74 374,931.58 801,122.24 32.027996 -103.495044 11,500.00 1.72 291.72 11,496.00 99.01 -248.53 374,932.69 801,119.45 32.027999 -103.495053 11.531.38 1.72 291.72 11.527.36 99.36 -249.40 374.933.04 801.118.58 32.028000 -103.495056 11,595.97 -250.74 374,933.58 801,117.24 32.028002 -103.495060 11.600.00 0.69 291.72 99.90 801,116.98 11.642.00 100.00 -251 00 374,933,68 32 028002 -103 495061 11,646.03 0.00 0.00 11,700.00 0.00 0.00 11 695 97 100 00 -251 00 374 933 68 801,116.98 32 028002 -103 495061 11,800.00 0.00 0.00 11.795.97 100.00 -251.00 374,933,68 801,116,98 32.028002 -103.495061 11,900.00 0.00 0.00 11,895.97 100.00 -251.00 374,933.68 801,116.98 32.028002 -103.495061 11,996.07 0.00 0.00 11,992.04 100.00 -251.00 374,933.68 801,116.98 32.028002 -103.495061 KOP & FTP @ 11996' MD, 2299' FSL, 1660' FWL 99.99 -251.00 374,933.66 32.028002 -103.495061 12 000 00 0.39 179.52 11.995.97 801.116.98 12,100.00 10.39 179.52 12,095.40 90.60 -250.92 374,924.28 801,117.06 32.027976 -103.495061 12 200 00 20.39 179 52 12 191 69 64 09 -250 70 374 897 77 801 117 28 32 027903 -103.495061 12,300.00 179.52 12,281.91 -250.34 374,854.94 801,117.64 32.027786 -103.495061 30.39 21.27 12,400.00 12.363.33 -249 85 374.797.10 32.027627 -103 495061 40.39 179 52 -36 58 801.118.12 -103.495061 12,500.00 50.39 179.52 12.433.47 -107.68-249.26 374.726.00 801,118.72 32.027431 -103,495061 12.600.00 60.39 179 52 12 490 19 -189 88 -248 57 374,643,80 801.119.41 32 027205 12,700.00 70.39 179.52 12,531.78 -280.67 -247.81 374,553.00 801,120.17 32.026956 -103.495061 12,800.00 80 39 179.52 12,556.96 -377.32 -247.00 374,456.36 801,120.98 32.026690 -103.495060 12,565.00 374,360.74 32.026427 -103.495060 12 896 08 90.00 179.52 -472.94 -246.20 801.121.78 12,900.00 90.00 179.52 12,565.00 -476.86 -246.16 374,356.82 801,121.81 32.026416 -103.495060 13.000.00 90.00 179 52 12 565 00 -576.86 -245 33 374 256 82 801 122 65 32 026142 -103 495060 32.025867 -103.495060 13,100.00 90.00 179.52 12.565.00 -676.86 -244.49 374,156.82 801,123.49 13,200.00 90.00 179.52 12.565.00 -776 85 -243 65 374,056,83 801.124.33 32 025592 -103 495060 13,300.00 90.00 179.52 12,565.00 -876.85 -242.81 373,956.83 801,125.17 32.025317 -103.495059 13,400.00 90.00 179.52 12 565.00 -976.85 -241.97 373,856.83 801,126.01 32.025042 -103.495059 90.00 179.52 12,565.00 -241.13 373,756.84 32.024767 -103.495059 13.500.00 -1.076.84 801.126.85 13,600.00 90.00 179.52 12,565.00 -1.176.84 -240.29 373,656.84 801.127.68 32.024492 -103.495059 -239.46 373,556.85 32.024217 -103.495059 13,700.00 90.00 179.52 12.565.00 -1.276.83801.128.52 13,800.00 90.00 179.52 12,565.00 -1,376.83 -238.62 373,456.85 801,129.36 32.023943 -103.495058 179.52 -237.78 373,356.85 32.023668 -103.495058 13 900 00 90.00 12.565.00 -1.476.83 801.130.20 14,000.00 90.00 179.52 12,565.00 -1,576.82 -236.94 373,256.86 801,131.04 32.023393 -103.495058 -103,495058 14.100.00 90.00 179 52 12 565 00 -1 676 82 -236 10 373 156 86 801 131 88 32 023118 179.52 12,565.00 -1,776.82 -235.26 373,056.86 801,132.71 32.022843 -103.495058 14,200,00 90.00 90.00 179.52 12 565 00 -1.876.81 -234.43 372.956.87 801.133.55 32.022568 -103.495057 14,300.00 372,856.87 -233.59 32.022293 -103.495057 14,400.00 90.00 179.52 12.565.00 -1,976.81 801,134.39 372,756.88 -232 75 32 022018 -103.495057 14,500.00 90.00 179.52 12.565.00 -2.076.81801.135.23 14,600.00 90.00 179.52 12,565.00 -2,176.80 -231 91 372 656 88 801,136.07 32 021743 -103.495057 14,622.00 90.00 179.52 12,565.00 -2,198.80 -231.73372,634.88 801,136.25 32.021683 -103.495057 Cross Section @ 14622' MD, 0' FNL, 1660' FWL 32.021469 -103.495057 14,700.00 90 00 179 52 12 565 00 -2,276.80 -231.07 372.556.88 801.136.91 801,137.74 32.021194 -103.495056 14,800.00 90.00 179.52 12.565.00 -2,376.80 -230.23 372.456.89 -103.495056 14,900.00 90.00 179.52 12,565.00 -2,476,79 -229.40372,356.89 801,138.58 32.020919 12.565.00 -228.56 372,256.89 801,139.42 32.020644 -103.495056 15 000 00 90 00 179 52 -2 576 79 90.00 179.52 12,565.00 -2,676.79 -227.72 372,156.90 801,140.26 32.020369 -103.495056 15,100,00 15.200.00 90.00 179.52 12 565 00 -2,776,78 -226 88 372.056.90 801.141.10 32.020094 -103.495056 15,300.00 90.00 179.52 12,565.00 -2,876.78 -226.04 371,956.91 801,141.94 32.019819 -103.495055 15,400.00 90.00 179.52 12,565.00 -2,976.78 -225.20 371,856.91 801,142.77 32.019544 -103.495055 32.019270 -103.495055 179.52 12,565.00 -3,076.77 -224.37 371,756.91 801,143.61 15,500.00 90.00

Database: Company: EDM r5000.141_Prod US

WCDSC Permian NM

Project:

Lea County (NAD83 New Mexico East)

Site: Sec 20-T26S-R34E

Well:

Green Wave 20-32 Fed State Com 16H

Wellbore: Wellbore #1 Design:

Permit Plan 1

Local Co-ordinate Reference:

TVD Reference:

MD Reference:

North Reference: Survey Calculation Method: Well Green Wave 20-32 Fed State Com 16H

RKB @ 3374.00ft

RKB @ 3374.00ft

Grid

Minimum Curvature

ned Survey								-	
Measured Depth	Inclination	Azimuth	Vertical Depth	+N/-S	+E/-W	Map Northing	Map Easting		
(ft)	(°)	(°)	(ft)	(ft)	(ft)	(usft)	(usft)	Latitude	Longitude
15,600.00	90.00	179.52	12,565.00	-3,176.77	-223.53	371,656.92	801,144.45	32.018995	-103.49
15,700.00	90.00	179.52	12,565.00	-3,276.76	-222.69	371,556.92	801,145.29	32.018720	-103.49
15,800.00	90.00	179.52	12,565.00	-3,376.76	-221.85	371,456.92	801,146.13	32.018445	-103.4
15,900.00	90.00	179.52	12,565.00	-3,476.76	-221.01	371,356.93	801,146.97	32.018170	-103.4
16,000.00	90.00	179.52	12,565.00	-3,576.75	-220.17	371,256.93	801,147.80	32.017895	-103.4
16,100.00	90.00	179.52	12,565.00	-3,676.75	-219.34	371,156.94	801,148.64	32.017620	-103.4
16,200.00	90.00	179.52	12,565.00	-3,776.75	-218.50	371,056.94	801,149.48	32.017345	-103.4
16,300.00	90.00	179.52	12,565.00	-3,876.74	-217.66	370,956.94	801,150.32	32.017071	-103.4
16,400.00	90.00	179.52	12,565.00	-3,976.74	-216.82	370,856.95	801,151.16	32.016796	-103.4
16,500.00	90.00	179.52	12,565.00	-4,076.74	-215.98	370,756.95	801,152.00	32.016521	-103.4
16,600.00	90.00	179.52	12,565.00	-4,176.73	-215.14	370,656.95	801,152.84	32.016246	-103.4
16,700.00	90.00	179.52	12,565.00	-4,276.73	-214.30	370,556.96	801,153.67	32.015971	-103.4
16,800.00	90.90	179.52	12,565.00	-4,376.73	-213.47	370,456.96	801,154.51	32.015696	-103.4
16,900.00	90.00	179.52	12,565.00	-4,476.72	-212.63	370,356.96	801,155.35	32.015421	-103.4
17,000.00	90.00	179.52	12,565.00	-4,576.72	-211.79	370,256.97	801,156.19	32.015146	-103.4
17,100.00	90.00	179.52	12,565.00	-4,676.72	-210.95	370,156.97	801,157.03	32.014872	-103.4
17,200.00	90.00	179.52	12,565.00	-4,776.71	-210.11	370,056.98	801,157.87	32.014597	-103.4
17,300.00	90.00	179.52	12,565.00	-4,876.71	-209.27	369,956.98	801,158.70	32.014322	-103.4
17,400.00	90.00	179.52	12,565.00	-4,976.71	-208.44	369,856.98	801,159.54	32.014047	-103.4
	90.00	179.52	12,565.00	-5,076.70	-200. 44 -207.60	369,756.99		32.013772	
17,500.00			•	•	-207. 80 -206.76	·	801,160.38		-103.4
17,600.00	90.00	179.52	12,565.00	-5,176.70		369,656.99	801,161.22	32.013497	-103.4
17,700.00	90.00	179.52	12,565.00	-5,276.69	-205.92	369,556.99	801,162.06	32.013222	-103.4
17,800.00	90.00	179.52	12,565.00	-5,376.69	-205.08	369,457.00	801,162.90	32.012947	-103.4
17,900.00	90.00	179.52	12,565.00	-5,476.69	-204.24	369,357.00	801,163.73	32.012673	-103.4
18,000.00	90.00	179.52	12,565.00	-5,576.68	-203.41	369,257.01	801,164.57	32.012398	-103.4
18,100.00	90.00	179.52	12,565.00	-5,676.68	-202.57	369,157.01	801,165.41	32.012123	-103.4
18,200.00	90.00	179.52	12,565.00	-5,776.68	-201.73	369,057.01	801,166.25	32.011848	-103.4
18,300.00	90.00	179.52	12,565.00	-5,876.67	-200.89	368,957.02	801,167.09	32.011573	-103.4
18,400.00	90.00	179.52	12,565.00	-5,976.67	-200.05	368,857.02	801,167.93	32.011298	-103.4
18,500.00	90.00	179.52	12,565.00	-6,076.67	-199.21	368,757.02	801,168.76	32.011023	-103.4
18,600.00	90.00	179.52	12,565.00	-6,176.66	-198.38	368,657.03	801,169.60	32.010748	-103.4
18,700.00	90.00	179.52	12,565.00	-6,276.66	-197.54	368,557.03	801,170.44	32.010474	-103.4
18,800.00	90.00	179.52	12,565.00	-6,376.66	-196.70	368,457.04	801,171.28	32.010199	-103.4
18,900.00	90.00	179.52	12,565.00	-6,476.65	-195.86	368,357.04	801,172.12	32.009924	-103.4
19,000.00	90.00	179.52	12,565.00	-6,576.65	-195.02	368,257.04	801,172.96	32.009649	-103.4
19,100.00	90.00	179.52	12,565.00	-6,676.65	-194.18	368,157.05	801,173.79	32.009374	-103.4
19,200.00	90.00	179.52	12,565.00	-6,776.64	-193.35	368,057.05	801,174.63	32.009099	-103.4
19,300.00	90.00	179.52	12,565.00	-6,876.64	-192.51	367,957.05	801,175.47	32.008824	-103.4
19,400.00	90.00	179.52	12,565.00	-6,976.63	-191.67	367,857.06	801,176.31	32.008549	-103.4
19,500.00	90.00	179.52	12,565.00	-7,076.63	-190.83	367,757.06	801,177.15	32.008274	-103.4
19,600.00	90.00	179.52	12,565.00	-7,176.63	-189.99	367,657.06	801,177.99	32.008000	-103.4
19,700.00	90.00	179.52	12,565.00	-7,276.62	-189.15	367,557.07	801,178.82	32.007725	-103.4
19,800.00	90.00	179.52	12,565.00	-7,376.62	-188.31	367,457.07	801,179.66	32.007450	-103.4
19,900.00	90.00	179.52	12,565.00	-7,476.62	-187.48	367,357.08	801,180.50	32.007175	-103.4
19,904.00	90.00	179.52	12,565.00	-7,480.62	-187.44	367,353.08	801,180.54	32.007164	-103.4
-				7,-100.02	107.44	001,000.00	001,100.01	02.007104	100.4
	ection @ 1990			7 576 64	100 64	267 257 00	001 101 34	22 000000	400.4
20,000.00	90.00	179.52	12,565.00	-7,576.61	-186.64	367,257.08	801,181.34	32.006900	-103.4
20,100.00	90.00	179.52	12,565.00	-7,676.61	-185.80	367,157.08	801,182.18	32.006625	-103.4
20,200.00	90.00	179.52	12,565.00	-7,776.61	-184.96	367,057.09	801,183.02	32.006350	-103.4
20,300.00	90.00	179.52	12,565.00	-7,876.60	-184.12	366,957.09	801,183.86	32.006075	-103.4
20,400.00	90.00	179.52	12,565.00	-7,976.60	-183.28	366,857.09	801,184.69	32.005801	-103.4
20,500.00	90.00	179.52	12,565.00	-8,076.60	-182.45	366,757.10	801,185.53	32.005526	-103.4
20,600.00	90.00	179.52	12,565.00	-8,176.59	-181.61	366,657.10	801,186.37	32.005251	-103.4
20,700.00	90.00	179.52	12,565.00	-8,276.59	-180.77	366,557.11	801,187.21	32.004976	-103.49

Database: Company: EDM r5000.141_Prod US

WCDSC Permian NM

Project:

Site:

Design:

Lea County (NAD83 New Mexico East)

Sec 20-T26S-R34E

Well: Green Wave 20-32 Fed State Com 16H Wellbore: Wellbore #1 Permit Plan 1

Local Co-ordinate Reference:

TVD Reference:

MD Reference: North Reference:

Survey Calculation Method:

Well Green Wave 20-32 Fed State Com 16H

RKB @ 3374.00ft RKB @ 3374.00ft

Grid

Minimum Curvature

Planned	Survey

iailileu Sulvey			= -					*	•
Measured			Vertical			Мар	Map		
Depth	Inclination	Azimuth	Depth	+N/-S	+E/-W	Northing	Easting		
(ft)	(°)	(°)	(ft)	(ft)	(ft)	(usft)	(usft)	Latitude	Longitude
20,800.00	90.00	179.52	12,565.00	-8,376.59	-179.93	366,457.11	801,188.05	32.004701	-103.495044
20,900.00	90.00	179.52	12,565.00	-8,476.58	-179.09	366,357.11	801,188.89	32.004426	-103.495044
21,000.00	90.00	179.52	12,565.00	-8,576.58	-178.25	366,257.12	801,189.72	32.004151	-103.495044
21,100.00	90.00	179.52	12,565.00	-8,676.58	-177.42	366,157.12	801,190.56	32.003876	-103.495044
21,200.00	90.00	179.52	12,565.00	-8,776.57	-176.58	366,057.12	801,191.40	32.003602	-103.495043
21,300.00	90.00	179.52	12,565.00	-8,876.57	-175.74	365,957.13	801,192.24	32.003327	-103.495043
21,400.00	90.00	179.52	12,565.00	-8,976.56	-174.90	365,857.13	801,193.08	32.003052	-103.495043
21,500.00	90.00	179.52	12,565.00	-9,076.56	-174.06	365,757.14	801,193.92	32.002777	-103.495043
21,600.00	90.00	179.52	12,565.00	-9,176.56	-173.22	365,657.14	801,194.75	32.002502	-103.495043
21,700.00	90.00	179.52	12,565.00	-9,276.55	-172.39	365,557.14	801,195.59	32.002227	-103.495042
21,800.00	90.00	179.52	12,565.00	-9,376.55	-171.55	365,457.15	801,196.43	32.001952	-103.495042
21,900.00	90.00	179.52	12,565.00	-9,476.55	-170.71	365,357.15	801,197.27	32.001677	-103.495042
22,000.00	90.00-	179.52	12,565.00	-9,576.54	-169.87	365,257.15	801,198.11	- 32.001403	-103.495042
22,100.00	90.00	179.52	12,565.00	-9,676.54	-169.03	365,157.16	801,198.95	32.001128	-103.495042
22,200.00	90.00	179.52	12,565.00	-9,776.54	-168.19	365,057.16	801,199.78	32.000853	-103.495041
22,300.00	90.00	179.52	12,565.00	-9,876.53	-167.36	364,957.17	801,200.62	32.000578	-103.495041
22,314.83	90.00	179.52	12,565.00	-9,891.36	-167.23	364,942.34	801,200.75	32.000537	-103.495041
LTP@2	2315' MD, 241	0' FNL, 1660'	FWL	-					
22,394.83	90.00	179.52	12,565.00	-9,971.36	-166.56	364,862.34	801,201.42	32.000317	-103.495041
PBHL; 2	490' FNL, 166	0' FWL					-	•	

Design	Targets
--------	---------

Target	Name
--------	------

- hit/miss target	Dip Angle	Dip Dir.	TVD	+N/-\$	+E/-W	Northing	Easting		
- Shape	(°)	(°)	(ft)	(ft)	(ft)	(usft)	(usft)	Latitude	Longitude
									

PBHL - Green Wave 20-

0.00

0.00

0.00 - plan misses target center by 9972.75ft at 0.00ft MD (0.00 TVD, 0.00 N, 0.00 E)
- Point

-9,971.36 -166.56 364,862.34


801,201.42

32.000317

-103.495041

	_
Plan	Annotations

Measured	Vertical	Local Coor	dinates	
Depth	Depth	+N/-S	+E/-W	
(ft)	(ft)	(ft)	(ft)	Comment
11,996.07	11,992.04	100.00	-251.00	KOP & FTP @ 11996' MD, 2299' FSL, 1660' FWL
14,622.00	12,565.00	-2,198.80	-231.73	Cross Section @ 14622' MD, 0' FNL, 1660' FWL
19,904.00	12,565.00	-7,480.62	-187.44	Cross Section @ 19904' MD, 0' FNL, 1660' FWL
22,314.83	12,565.00	-9,891.36	-167.23	LTP @ 22315' MD, 2410' FNL, 1660' FWL
22,394,83	12,565.00	-9,971.36	-166.56	PBHL: 2490' FNL, 1660' FWL



Devon Energy APD VARIANCE DATA

OPERATOR NAME: Devon Energy

1. SUMMARY OF Variance:

Devon Energy respectfully requests approval for the following additions to the drilling plan:


1. Potential utilization of a spudder rig to pre-set surface casing.

2. Description of Operations

- 1. A spudder rig contractor may move in their rig to drill the surface hole section and pre-set surface casing on this well.
 - **a.** After drilling the surface hole section, the rig will run casing and cement following all of the applicable rules and regulations (OnShore Order 2, all COAs and NMOCD regulations).
 - **b.** Rig will utilize fresh water based mud to drill surface hole to TD.
- 2. The wellhead will be installed and tested once the surface casing is cut off and the WOC time has been reached.
- 3. A blind flange with the same pressure rating as the wellhead will be installed to seal the wellbore. Pressure will be monitored with needle valves installed on two wingvalves.
 - a. A means for intervention will be maintained while the drilling rig is not over the well.
- 4. The BLM will be contacted and notified 24 hours prior to commencing spudder rig operations.
- 5. Drilling operation will be performed with the big rig. At that time an approved BOP stack will be nippled up and tested on the wellhead before drilling operations commences on each well.
 - **a.** The BLM will be contacted / notified 24 hours before the big rig moves back on to the pad with the pre-set surface casing.
- **6.** Devon Energy will have supervision on the rig to ensure compliance with all BLM and NMOCD regulations and to oversee operations.
- 7. Once the rig is removed, Devon Energy will secure the wellhead area by placing a guard rail around the cellar area.



Commitment Runs Deep



Design Plan
Operation and Maintenance Plan
Closure Plan

SENM - Closed Loop Systems June 2010

I. Design Plan

Devon uses MI SWACO closed loop system (CLS). The MI SWACO CLS is designed to maintain drill solids at or below 5%. The equipment is arranged to progressively remove solids from the largest to the smallest size. Drilling fluids can thus be reused and savings is realized on mud and disposal costs. Dewatering may be required with the centrifuges to insure removal of ultra fine solids.

The drilling location is constructed to allow storm water to flow to a central sump normally the cellar. This insures no contamination leaves the drilling pad in the event of a spill. Storm water is reused in the mud system or stored in a reserve fluid tank farm until it can be reused. All lubricants, oils, or chemicals are removed immediately from the ground to prevent the contamination of storm water. An oil trap is normally installed on the sump if an oil spill occurs during a storm.

A tank farm is utilized to store drilling fluids including fresh water and brine fluids. The tank farm is constructed on a 20 ml plastic lined, bermed pad to prevent the contamination of the drilling site during a spill. Fluids from other sites may be stored in these tanks for processing by the solids control equipment and reused in the mud system. At the end of the well the fluids are transported from the tank farm to an adjoining well or to the next well for the rig.


Prior to installing a closed-loop system on site, the topsoil, if present, will be stripped and stockpiled for use as the final cover or fill at the time of closure.

Signs will be posted on the fence surrounding the closed-loop system unless the closed-loop system is located on a site where there is an existing well, that is operated by Devon.

II. Operations and Maintenance Plan

Primary Shakers: The primary shakers make the first removal of drill solids from the drilling mud as it leaves the well bore. The shakers are sized to handle maximum drilling rate at optimal screen size. The shakers normally remove solids down to 74 microns.

Mud Cleaner: The Mud Cleaner cleans the fluid after it leaves the shakers. A set of hydrocyclones are sized to handle 1.25 to 1.5 times the maximum circulating rate. This ensures all the fluid is being processed to an average cut point of 25 microns. The wet discharged is dewatered on a shaker equipped with ultra fine mesh screens and generally cut at 40 microns.



Centrifuges: The centrifuges can be one or two in number depending on the well geometry or depth of well. The centrifuges are sized to maintain low gravity solids at 5% or below. They may or may not need a dewatering system to enhance the removal rates. The centrifuges can make a cut point of 8-10 microns depending on bowl speed, feed rate, solids loading and other factors.

The centrifuge system is designed to work on the active system and be flexible to process incoming fluids from other locations. This set-up is also dependant on well factors.

Dewatering System: The dewatering system is a chemical mixing and dosing system designed to enhance the solids removal of the centrifuge. Not commonly used in shallow wells. It may contain pH adjustment, coagulant mixing and dosing, and polymer mixing and dosing. Chemical flocculation binds ultra fine solids into a mass that is within the centrifuge operating design. The

dewatering system improves the centrifuge cut point to infinity or allows for the return of clear water or brine fluid. This ability allows for the ultimate control of low gravity solids.

Cuttings Boxes: Cuttings boxes are utilized to capture drill solids that are discarded from the solids control equipment. These boxes are set upon a rail system that allows for the removal and replacement of a full box of cuttings with an empty one. They are equipped with a cover that insures no product is spilled into the environment during the transportation phase.

Process Tank: (Optional) The process tank allows for the holding and process of fluids that are being transferred into the mud system. Additionally, during times of lost circulation the process tank may hold active fluids that are removed for additional treatment. It can further be used as a mixing tank during well control conditions.

Sump and Sump Pump: The sump is used to collect storm water and the pump is used to transfer this fluid to the active system or to the tank for to hold in reserve. It can also be used to collect fluids that may escape during spills. The location contains drainage ditches that allow the location fluids to drain to the sump.

Reserve Fluids (Tank Farm): A series of frac tanks are used to replace the reserve pit. These are steel tanks that are equipped with a manifold system and a transfer pump. These tanks can contain any number of fluids used during the drilling process. These can include fresh water, cut brine, and saturated salt fluid. The fluid can be from the active well or reclaimed fluid from other locations. A 20 ml liner and berm system is employed to ensure the fluids do not migrate to the environment during a spill.

If a leak develops, the appropriate division district office will be notified within 48 hours of the discovery and the leak will be addressed. Spill prevention is accomplished by maintaining pump packing, hoses, and pipe fittings to insure no leaks are occurring. During an upset condition the source of the spill is isolated and repaired as soon as it is discovered. Free liquid is removed by a diaphragm pump and returned to the mud system. Loose topsoil may be used to stabilize the spill and the contaminated soil is excavated and placed in the cuttings boxes. After the well is finished and the rig has moved, the entire location is scrapped and testing will be performed to determine if a release has occurred.

All trash is kept in a wire mesh enclosure and removed to an approved landfill when full. All spent motor oils are kept in separate containers and they are removed and sent to an approved recycling center. Any spilled lubricants, pipe

dope, or regulated chemicals are removed from soil and sent to landfills approved for these products.

These operations are monitored by Mi Swaco service technicians. Daily logs are maintained to ensure optimal equipment operation and maintenance. Screen and chemical use is logged to maintain inventory control. Fluid properties are monitored and recorded and drilling mud volumes are accounted for in the mud storage farm. This data is kept for end of well review to insure performance goals are met. Lessons learned are logged and used to help with continuous improvement.

A MI SWACO field supervisor manages from 3-5 wells. They are responsible for training personnel, supervising installations, and inspecting sites for compliance of MI SWACO safety and operational policy.

III. Closure Plan

A maximum 340' X 340' caliche pad is built per well. All of the trucks and steel tanks fit on this pad. All fluid cuttings go to the steel tanks to be hauled by various trucking companies to an agency approved disposal.



U. S. Steel Tubular Products 5.500" 17.00lbs/ft (0.304" Wall) P110

MECHANICAL PROPERTIES	Pipe	втс	LTC	STC	
Minimum Yield Strength	110,000				psi
Maximum Yield Strength	140,000				psi
Minimum Tensile Strength	125,000				psi
DIMENSIONS	Pipe	втс	LTC	STC	
Outside Diameter	5.500	6.050	6.050		in.
Wall Thickness	0.304				in.
Inside Diameter	4.892	4.892	4.892		in.
Standard Drift	4.767	4.767	4.767		in.
Alternate Drift					in.
Nominal Linear Weight, T&C	17.00				lbs/ft
Plain End Weight	16.89				lbs/ft
PERFORMANCE	Pipe	ВТС	LTC	STC	
Minimum Collapse Pressure	7,480	7,480	7,480		psi
Minimum Internal Yield Pressure	10,640	10,640	10,640		psi
Minimum Pipe Body Yield Strength	546				1,000 lbs
Joint Strength		568	445		1,000 lbs
Reference Length		22,271	17,449	· 	ft
MAKE-UP DATA	Pipe	втс	LTC	STC	
Make-Up Loss		4.13	3.50		in.
Minimum Make-Up Torque			3,470		ft-lbs
Maximum Make-Up Torque			5,780		ft-lbs

Legal Notice

All material contained in this publication is for general information only. This material should not therefore be used or relied upon for any specific application without independent competent professional examination and verification of accuracy, suitability and applicability. Anyone making use of this material does so at their own risk and assumes any and all liability resulting from such use. U. S. Steel disclaims any and all expressed or implied warranties of fitness for any general or particular application.

U. S. Steel Tubular Products 1-877-893-9461
460 Wildwood Forest Drive, Suite 300S connections@uss.com
Spring, Texas 77380 www.usstubular.com



U. S. Steel Tubular Products 8.625" 32.00lbs/ft (0.352" Wall) L80 HC

<u>-</u>					
CENTRETOTAL LASINATEE	Pipo	etc.	LTG	Sig	
Minimum Yield Strength	80,000				psi
Maximum Yield Strength	95,000				psi
Minimum Tensile Strength	95,000				psi
IMENSIONS	Apo	ETC	LIG	SīC	
Outside Diameter	8.625				in.
Wall Thickness	0.352				in.
Inside Diameter	7.921				in.
Standard Drift	7.796	7.796			in.
Alternate Drift	7.875	7.875			in.
Nominal Linear Weight, T&C	32.00				lbs/ft
Plain End Weight	31.13				lbs/ft
ERFORMANGE	Apo	ETC	LTC	SīC	
Minimum Collapse Pressure	3,820	3,820			psi
Minimum Internal Yield Pressure	5,710	5,710			psi
Minimum Pipe Body Yield Strength	732				1,000 lbs
Joint Strength					1,000 lbs
Reference Length				<u></u>	ft
	Apo	ETC	T <u>ic</u>	SīC	
Make-Up Loss	_				in.
Minimum Make-Up Torque					ft-lbs
Maximum Make-Up Torque					ft-lbs

Legal Notice

'All material contained in this publication is for general information only. This material should not therefore be used or relied upon for any specific application without independent competent professional examination and verification of accuracy, suitability and applicability. Anyone making use of this material does so at their own risk and assumes any and all liability resulting from such use. U. S. Steel disclaims any and all expressed or implied warranties of fitness for any general or particular application.

U. S. Steel Tubular Products 1-877-893-9461
460 Wildwood Forest Drive, Suite 300S connections@uss.com
Spring, Texas 77380 www.usstubular.com



U. S. Steel Tubular Products 9.625" 40.00lbs/ft (0.395" Wall)

CEUTEROTH LASITATEEM	Pipo	e To	LIG	S16	
Minimum Yield Strength	55,000				psi
Maximum Yield Strength	80,000				psi
Minimum Tensile Strength	75,000				psi
DIMENSIONS	Pipo	eic	T1G	STC	
Outside Diameter	9.625	10.625	10.625	10.625	in.
Wall Thickness	0.395				in.
Inside Diameter	8.835	8.835	8.835	8.835	in.
Standard Drift	8.679	8.679	8.679	8.679	in.
Alternate Drift	8.750	8.750	8.750	8.750	in.
Nominal Linear Weight, T&C	40.00				lbs/ft
Plain End Weight	38.97				lbs/ft
PERFORMANCE	Apo	eic	LIG	SIG	
Minimum Collapse Pressure	2,570	2,570	2,570	2,570	psi
Minimum Internal Yield Pressure	3,950	3,950	3,950	3,950	psi
Minimum Pipe Body Yield Strength	630				1,000 lbs
Joint Strength		714	520	452	1,000 lbs
Reference Length	·	11,898	8,665	7,529	ft .
MAKEUPDATA	Fipo	ETC	LIG	SīC	
Make-Up Loss	-	4.81	4.75	3.38	in.
Minimum Make-Up Torque	-		3,900	3,390	ft-lbs
Maximum Make-Up Torque			6,500	5,650	ft-lbs

Legal Notice

All material contained in this publication is for general information only. This material should not therefore be used or relied upon for any specific application without independent competent professional examination and verification of accuracy, suitability and applicability. Anyone making use of this material does so at their own risk and assumes any and all liability resulting from such use. U. S. Steel disclaims any and all expressed or implied warranties of fitness for any general or particular application.

> U. S. Steel Tubular Products 1-877-893-9461 460 Wildwood Forest Drive, Suite 300S connections@uss.com
> Spring, Texas 77380 www.usstubular.com



U. S. Steel Tubular Products 13.375" 48.00lbs/ft (0.330" Wall) H40

CENTEROTALIA SINGHEEM	Pipo	eic	P1G	STC	
Minimum Yield Strength	40,000				psi
Maximum Yield Strength	80,000				psi
Minimum Tensile Strength	60,000				psi
DIMENSIONS	Pipo	BIC	PLG.	STC	
Outside Diameter	13.375			14.375	in.
Wall Thickness	0.330				in.
Inside Diameter	12.715			12.715	in.
Standard Drift	12.559	12.559		12.559	in.
Alternate Drift					in.
Nominal Linear Weight, T&C	48.00				lbs/ft
Plain End Weight	46.02				lbs/ft
PERFORMANCE	Pipe	BTC	Līc	STC	
Minimum Collapse Pressure	740	740		740	psi
Minimum Internal Yield Pressure	1,730	1,730		1,730	psi
Minimum Pipe Body Yield Strength	541				1,000 lbs
Joint Strength	_			322	1,000 lbs
Reference Length	·		-	4,473	ft
MAKEUP DATA	Apo	eig.	LIG	STC	
Make-Up Loss				3.50	in.
Minimum Make-Up Torque				2,420	ft-lbs
Maximum Make-Up Torque				4.030	ft-lbs

All material contained in this publication is for general information only. This material should not therefore be used or relied upon for any specific application without independent competent professional examination and verification of accuracy, suitability and applicability. Anyone making use of this material does so at their own risk and assumes any and all liability resulting from such use. U. S. Steel disclaims any and all expressed or implied warranties of fitness for any general or particular application.

U. S. Steel Tubular Products 1-877-893-9461
460 Wildwood Forest Drive, Suite 300S connections@uss.com

Spring, Texas 77380 www.usstubular.com

OCTG Casing Data Sheet




VALLOUREC & MANNESMANN TUBES

			VALLOUREC & MANNESI	MANN TUBES
-				
O.D.	T&C LB/FT	PE LB/FT	GRADE	
9.625	40.00	38.97	P110 EC	
	Grade - Materia	al Properties		
Mini	mum Yield Strength:	125.0	ksi	
	mum Yield Strength:	140	ksi	
	um Tensile Strength:	135	ksi	
	Pipe Body			
	Geom	•		
	Nominal ID:	8.835	inch	
	Wall:	0.395	inch	
•	Nominal Area:	11.454	inch ²	•
	API Drift:	8.679	inch	
	Alternate Drift:	8.750	inch	
	Perforn	nance		
Pipe I	Body Yield Strength:	1,432	kips	
C	Collapse Resistance:	4,230	psi	
Internal Yield Press	ure (API Historical):	8,980	psi	
	Lamé - Internal	Yield Pressure		
	Lamé open:	8,950	psi	
1.4 Let	Lamé capped:	9,970	psi	
L L	amé ductile rupture:	9,700	psi	
	API Connec	tion Data		
ОТ				
51	C Internal Pressure:	8,980	psi	
	STC Joint Strength:	861	kips	
L	C Internal Pressure:	8,980	psi	
	LC Joint Strength:	988	kips	
В	C Internal Pressure:	8,980	psi	
	BC Joint Strength:	1,266	kips	
	LC Torque		•	
	LO TOTQUE			

minimum: 7,410 optimum: 9,880 maximum: 12,350

This data sheet is for informational purposes only. While every effort has been made to ensure the accuracy of all data and that the information contained herein is correct, this material is presented as a reference guide only. V & M Tubes assumes no responsibility for the results obtained through the use of this material.

API grades with enhanced performance are supplied with API couplings produced from standard API grades.



INFORMATION CONTAINED HEREIN IS THE PROPERTY OF CACTUS WELLHEAD, LLC. REPRODUCTION, DISCLOSURE, OR USE THEREOF IS PERMISSIBLE ONLY AS PROVIDED BY CONTRACT OR AS EXPRESSLY AUTHORIZED BY CACTUS WELLHEAD, LLC.

CACTUS WELLHEAD LLC


20" x 13-3/8" x 9-5/8" x 5-1/2" 15M MBU-3T-CFL-R-DBLO System With 13-3/8", 9-5/8" & 5-1/2" MBU-3T Mandrel Casing Hangers And 13-5/8" 10M x 7-1/16" 15M CTH-DBLHPS Tubing Head

ALL DIMENSIONS APPROXIMATE

DEVON ENERGY CORPORATION ANADARKO BASIN / STACK

DRAWN DLE 13DEC18
APPRV

DRAWING NO. SDT-1815



INFORMATION CONTAINED HEREIN IS THE PROPERTY OF CACTUS WELLHEAD, LLC. REPRODUCTION, DISCLOSURE, OR USE THEREOF IS PERMISSIBLE ONLY AS PROVIDED BY CONTRACT OR AS EXPRESSLY AUTHORIZED BY CACTUS WELLHEAD, LLC.

CACTUS WELLHEAD LLC

13-3/8" x 8-5/8" x 5-1/2" 5M MBU-3T Wellhead System With 8-5/8" & 5-1/2" Pin Down Rotating Mandrel Hangers And 13-5/8" 10M x 7-1/16" 15M CTH-P-DBLHPS Tubing Head

DEVON ENERGY CORPORATION

DRAWN DLE 10MAY18
APPRV

DRAWING NO. ODE0002309

A multibowl wellhead may be used. The BOP will be tested per Onshore Order #2 after installation on the surface casing which will cover testing requirements for a maximum of 30 days. If any seal subject to test pressure is broken the system must be tested.

Devon proposes using a multi-bowl wellhead assembly. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be 5000 (5M) psi.

- Wellhead will be installed by wellhead representatives.
- If the welding is performed by a third party, the wellhead representative will monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
- Wellhead representative will install the test plug for the initial BOP test.
- Wellhead company will install a solid steel body pack-off to completely isolate the lower head after cementing intermediate casing. After installation of the pack-off, the pack-off and the lower flange will be tested to 5M, as shown on the attached schematic.
 Everything above the pack-off will not have been altered whatsoever from the initial nipple up. Therefore the BOP components will not be retested at that time.
- If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head will be cut and top out operations will be conducted.
- Devon will pressure test all seals above and below the mandrel (but still above the casing) to full working pressure rating.
- Devon will test the casing to 0.22 psi/ft or 1500 psi, whichever is greater, as per Onshore Order #2.

After running the surface casing, a 13-5/8" BOP/BOPE system with a minimum rating of 5M will be installed on the wellhead system and will undergo a 250 psi low pressure test followed by a 5,000 psi high pressure test. The 5,000 psi high and 250 psi low test will cover testing requirements a maximum of 30 days, as per Onshore Order #2. If the well is not complete within 30 days of this BOP test, another full BOP test will be conducted, as per Onshore Order #2.

After running the intermediate casing with a mandrel hanger, the 13-5/8" BOP/BOPE system with a minimum rating of 10M will be installed and tested, with 5M annular being tested to 100% of rated working pressure.

The pipe rams will be operated and checked each 24 hour period and each time the drill pipe is out of the hole. These tests will be logged in the daily driller's log. A 2" kill line and 3" choke line will be incorporated into the drilling spool below the ram BOP. In addition to the rams and annular preventer, additional BOP accessories include a kelly cock, floor safety valve, choke lines, and choke manifold rated at 10,000 psi WP.

Devon's proposed wellhead manufactures will be FMC Technologies, Cactus Wellhead, or Cameron.

1. Geologic Formations

TVD of target	12,565	Pilot hole depth	N/A
MD at TD:	22,394	Deepest expected fresh water:	

Basin

Depth (TVD) from KB	Water/Mineral Bearing/ Target Zone?	Hazards*
675		
1050		
5330		
5330		
9414		
9620		<u> </u>
12500		
	(TVD) from KB 675 1050 5330 5330 9414 9620	(TVD) from KB 675 1050 5330 9414 9620

^{*}H2S, water flows, loss of circulation, abnormal pressures, etc.

2. Casing Program (3-String Primary Design)

Hole Size Casing Interv	Casing Inter	Casing Interval		Wt	Grade	
	To	Csg. Size	(PPF)	Grade	Conn	
17.5"	See AFMSS	See AFMSS	See AFMSS	See AFMSS	See AFMSS	See AFMSS
12.25"	See AFMSS	See AFMSS	See AFMSS	See AFMSS	See AFMSS	See AFMSS
8.75"	See AFMSS	See AFMSS	See AFMSS	See AFMSS	See AFMSS	See AFMSS
BLM Minimum Safety Factor				Collapse: 1.125	Burst: 1.00	Tension: 1.6 Dry 1.8 Wet

- All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h Must have table for contingency casing
- Rustler top will be validated via drilling parameters (i.e. reduction in ROP) and surface casing setting depth revised accordingly if needed.
- Int casing shoe will be selected based on drilling data / gamma, setting depth with be revised accordingly if needed.

Casing Program (3-String Alternate Design)

Hole Size	Casing In	Interval	terval Csg. Size	Wt (PPF)	Grade	Comm
noie size	From	To	CSg. Size		Grade	Conn
17.5"	0	725'	13.375"	48	H-40	ВТС
10.625"	0	10,000'	8.625"	32	L80HC	ВТС
7.875"	0	TD	5.5"	17	P-110	ВТС
BLM Minimum Safety Factor				Collapse: 1.125	Burst: 1.00	Tension: 1.6 Dry 1.8 Wet

- All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h Must have table for contingency casing
- Rustler top will be validated via drilling parameters (i.e. reduction in ROP) and surface casing setting depth revised accordingly if needed.
- Variance is requested for collapse rating on 8-5/8" casing. Operator will keep pipe full while running casing. No losses are expected in subsequent hole section.
- Int casing shoe will be selected based on drilling data / gamma, setting depth with be revised accordingly if needed.
- A variance is requested to wave the centralizer requirement for the 10-5/8" casing and 5-1/2" casing.

Casing Program (3-String Alternate Design)

Hole Size Casin	Casing	Interval	Csg. Size	Weight	Grade	Conn.
HOIE SIZE	From	To	Csg. Size	(PPF)	Grade	Conn.
17.5"	0	725'	13.375"	48	H-40	STC
12.25"	0	4,500'	9.625"	40	J-55	BTC
12.25" 4,500'	4,500'	10,000'	9.625"	40	P-110EC	ВТС
8.75"	.0	TD	5.5"	17	P-110	ВТС
		Colla	Collapse:	Burst:	Tension:	
BLM Minimum Safety Factor	tor	1.125	1.00	1.6 Dry		
				1.123	1.00	1.8 Wet

- All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h Must have table for contingency casing
- Rustler top will be validated via drilling parameters (i.e. reduction in ROP) and surface casing setting depth revised accordingly if needed.
- Int casing shoe will be selected based on drilling data / gamma, setting depth with be revised accordingly if needed.

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Υ
Does casing meet API specifications? If no, attach casing specification sheet.	Υ
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the intermediate pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
Is well located within Capitan Reef?	N
If yes, does production casing cement tie back a minimum of 50' above the Reef? Is well within the designated 4 string boundary.	
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3 rd string cement tied back 500' into previous casing?	
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	

Is 2 nd string set 100' to 600' below the base of salt?	
Is well located in high Cave/Karst?	N
If yes, are there two strings cemented to surface?	
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

Cementing Program (3-String Primary Design)

	TOC	Wt. (lb/gal)	H _z 0 (gal/sk)	Yld (ft3/sack)	Slurry Descriptio n
See AFMSS	See AFMSS	See AFMSS	See AFMSS	See AFMSS	See AFMSS
See AFMSS	See AFMSS	See AFMSS	See AFMSS	See AFMSS	See AFMSS
See AFMSS	See AFMSS	See AFMSS	See AFMSS	See AFMSS	See AFMSS
See AFMSS	See AFMSS	See AFMSS	See AFMSS	See AFMSS	See AFMSS
See AFMSS	See AFMSS	See AFMSS	See AFMSS	See AFMSS	See AFMSS
	See AFMSS See AFMSS	See AFMSS See AFMSS See AFMSS See AFMSS See AFMSS See AFMSS	See AFMSSSee AFMSSSee AFMSSSee AFMSSSee AFMSSSee AFMSSSee AFMSSSee AFMSSSee AFMSS	See AFMSSSee AFMSSSee AFMSSSee AFMSSSee AFMSSSee AFMSSSee AFMSSSee AFMSSSee AFMSS	See AFMSS See AFMSS See AFMSS See AFMSS See AFMSS See AFMSS See AFMSS See AFMSS See AFMSS See AFMSS See AFMSS See AFMSS

If a DV tool is ran the depth(s) will be adjusted based on hole conditions and cement volumes will be adjusted proportionally. Slurry weights will be adjusted based on estimated fracture gradient of the formation. DV tool will be set a minimum of 50 feet below previous casing and a minimum of 200 feet above current shoe. If cement is not returned to surface during the primary cement job on the surface casing string, a planned top job will be conducted immediately after completion of the primary job.

Cementing Program (3-String Alternate Design)

Casing	# Sks	тос	Wt. (lb/gal)	H₂0 (gal/s k)	Yld (ft3/sack)	Slurry Description		
Surface	560	Surf	14.8	6.33	1.33	Lead: Class C Cement + additive		
	660	Surf	9	20.6	3.31	Lead: Class C Cement + additives		
Int	411	2000' above shoe	14.8	6.42	1.33	Tail: Class H / C + additives		
Int	As needed	Surf	14.8	6.32	1.33	Squeeze Lead: Class C Cement + additives		
Squeeze	411	2000' above shoe	13.2	5.31	1.6	Tail: Class H / C + additives		

Production	2300	200' tieback	13.2	5.31	1.6	Lead: Class H / C + additives
------------	------	-----------------	------	------	-----	-------------------------------

If a DV tool is ran the depth(s) will be adjusted based on hole conditions and cement volumes will be adjusted proportionally. Slurry weights will be adjusted based on estimated fracture gradient of the formation. DV tool will be set a minimum of 50 feet below previous casing and a minimum of 200 feet above current shoe. If cement is not returned to surface during the primary cement job on the surface casing string, a planned top job will be conducted immediately after completion of the primary job.

Casing String	% Excess
Surface	50%
Intermediate	50%
Production	10%

Cementing Program (3-String Alternate Design)

Casing	# Sks	тос	Wt. (ib/gai)	H₂0 (gal/sk)	Yld (ft3/sack)	Slurry Description
Surface	560	Surf	14.8	6.33	1.33	Lead: Class C Cement + additives
Int	985	Surf	9	20.6	3.31	Lead: Class C Cement + additives
	612	2000' above shoe	14.8	6.42	1.33	Tail: Class H / C + additives
Int	As needed	Surf	14.8	6.32	1.33	Squeeze Lead: Class C Cement + additives
Squeeze	612	2000' above shoe	14.8	6.42	1.33	Tail: Class H / C + additives
Production	2800	200' tieback	13.2	5.31	1.6	Lead: Class H / C + additives

If a DV tool is ran the depth(s) will be adjusted based on hole conditions and cement volumes will be adjusted proportionally. Slurry weights will be adjusted based on estimated fracture gradient of the formation. DV tool will be set a minimum of 50 feet below previous casing and a minimum of 200 feet above current shoe. If cement is not returned to surface during the primary cement job on the surface casing string, a planned top job will be conducted immediately after completion of the primary job.

Casing String	% Excess
Surface	50%
Intermediate	50%
Production	10%

3. Pressure Control Equipment (Primary Design)

BOP installed and tested before drilling which hole?	Size?	Min. Required WP	Ty	/pe	8	Tested to:		
			Ann	nular	X	50% of rated working pressure		
1	42.5/0"	5M	Blind	Blind Ram				
Intermediate	13-5/8"		Pipe Ram		Х	5M		
			Double Ram		Х			
			Other*					
		10M	Annula	Annular (5M)		100% of rated working pressure		
Dan dan dian	12.5/0"		Blind	Blind Ram				
Production	13-5/8"		Pipe Ram		Pipe Ram		X	1014
			Doub	le Ram	Х	10M		
			Other*					
	•		Anr	nular				
			Blind Ram					

4. Mud Program (Primary Design)

5. (Depth	Time	Moight (nng)	Vis	Water Loss	
From	То	Туре	Weight (ppg)	VIS .		
0	725'	FW Gel	See AFMSS	See AFMSS	See AFMSS	
725'	5200'	Saturated Brine	See AFMSS	See AFMSS	See AFMSS	
5200'	TD	OBM / WBM	See AFMSS	See AFMSS	See AFMSS	

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

What will be used to monitor the loss or gain of fluid?	PVT/Pason/Visual Monitoring
---	-----------------------------

8. Other facets of operation

Is this a walking operation? Potentially

- 1. If operator elects, drilling rig will batch drill the surface holes and run/cement surface casing; walking the rig to next wells on the pad.
- 2. The drilling rig will then batch drill the intermediate sections and run/cement intermediate casing; the wellbore will be isolated with a blind flange and pressure gauge installed for monitoring the well before walking to the next well.
- 3. The drilling rig will then batch drill the production hole sections on the wells with OBM, run/cement production casing, and install TA caps or tubing heads for completions.

NOTE: During batch operations the drilling rig will be moved from well to well however, it will not be removed from the pad until all wells have production casing run/cemented.

Will be pre-setting casing? Potentially

- 1. Spudder rig will move in and drill surface hole.
 - a. Rig will utilize fresh water based mud to drill surface hole to TD. Solids control will be handled entirely on a closed loop basis.
- 2. After drilling the surface hole section, the spudder rig will run casing and cement following all of the applicable rules and regulations (OnShore Order 2, all COAs and NMOCD regulations).
- 3. The wellhead will be installed and tested once the 10 ¾" surface casing is cut off and the WOC time has been reached.
- 4. A blind flange with the same pressure rating as the wellhead will be installed to seal the wellbore. Pressure will be monitored with a pressure gauge installed on the wellhead.
- 5. Spudder rig operations is expected to take 4-5 days per well on a multi well pad.
- 6. The NMOCD will be contacted and notified 24 hours prior to commencing spudder rig operations.
- 7. Drilling operations will be performed with the drilling rig. At that time an approved BOP stack will be nippled up and tested on the wellhead before drilling operations commences on each well.
 - a. The NMOCD will be contacted / notified 24 hours before the drilling rig moves back on to the pad with the pre-set surface casing.

Att	achments
<u> x</u>	Directional Plan
	Other, describe



Fluid Technology

ContiTech Beattle Corp. Website: www.contitechbeattle.com

Monday, June 14, 2010

RE:

Drilling & Production Hoses Lifting & Safety Equipment

To Helmerich & Payne,

A Continental ContiTech hose assembly can perform as intended and suitable for the application regardless of whether the hose is secured or unsecured in its configuration. As a manufacturer of High Pressure Hose Assemblies for use in Drilling & Production, we do offer the corresponding lifting and safety equipment, this has the added benefit of easing the lifting and handling of each hose assembly whilst affording hose longevity by ensuring correct handling methods and procedures as well as securing the hose in the unlikely event of a failure; but in no way does the lifting and safety equipment affect the performance of the hoses providing the hoses have been handled and installed correctly it is good practice to use lifting & safety equipment but not mandatory

Should you have any questions or require any additional information/clarifications then please do not hesitate to contact us.

ContiTech Beattie is part of the Continental AG Corporation and can offer the full support resources associated with a global organization.

Best regards,

Robin Hodgson Sales Manager ContiTech Beattie Corp

ContiTech Beattle Corp, 11535 Brittmoore Park Drive, Houston, TX 77041 Phone: +1 (832) 327-0141 Fax: +1 (832) 327-0148 www.contitechbeattle.com



R16 212



QUALITY DOCUMENT


PHOENIX RUBBER INDUSTRIAL LTD.


6728 Szeged, Budapesti út 10. Narrgary • H-6701 Szeged, P. O. Box 152 none: (3962) 566-737 • Fau: (3662) 566-738 SALES & MARKETING: H-1092 Budspest, Rådsy u. 42-44. Hungary • H-1440 Budspest, P. O. Box 26
Phone: (361) 458-4200 • Fox: (361) 217-2972, 458-4273 • www.tourusemergu.hu

QUAI INSPECTION	ITY CONTR		ATE .	CERT. N	÷ 5	52	
PURCHASER:	Phoenix Beat	tie Co.		P.O. Nº	1519F	A-871	
PHOENIX RUBBER order No.	170466	HOSE TYPE:	3" ID	Cho	ke and Kill H	lose	
HOSE SERIAL Nº	34128	NOMINAL / AC	TUAL LENGTH:		11,43 m		
W.P. 68,96 MPa	0000 psi	T.P. 103,4	MPa 1500	() psi	Duration:	60	min.
Pressure test with water at ambient temperature					· • •		
•	e est ^e e e e e e e e e e e e e e e e e e e e					,	
:	: Coo ette	: - Abenaet /d		•		. •	
!	See au	achment (1	page)				# #
				· .			3
	• .		•				
	. :		•			•	
↑ 10 mm = 10 Min → 10 mm = 25 MPa	•						
→ 10 mm = 25 MP		COUPLIN	igs				. موريد . ت
Туре		Serial N°	1	Quality		Heat N°	
3" coupling with	72	20 719	A	ISI 4130		C7626	
4 1/16" Flange end			A	ISI 4130	1	47357	
				:			
						•	
			API Spec 16 Temperatur		}"		
All metal parts are flawless	P HOOF HAS DON						
WE CERTIFY THAT THE ABOV PRESSURE TESTED AS ABOVI			U IN ACCORDA	NCE WITH	THE TERMS OF	THE ORDE	K AND
Date:	Inspector		Quality Contr		NIX RUBB	ER	
29. April. 2002.			Daar (Hose	lustrial Ltd. Inspection ar	colorvi	<u>~</u>
				PHO	ENIK KUBBE	at Q.C.	

VERIFIED TRUE CO.
PHOENIX RUBBER & C.

•\$





Devon Energy Annular Preventer Summary

1. Component and Preventer Compatibility Table

The table below, which covers the drilling and casing of the 10M MASP portion of the well, outlines the tubulars and the compatible preventers in use. This table, combined with the mud program, documents that two barriers to flow can be maintained at all times, independent of the rating of the annular preventer.

6-3/4" Production hole section, 10M requirement

Component	OD	Preventer	RWP
Drillpipe	4.5"	Fixed lower 4.5"	10M
		Upper 4.5-7" VBR	
HWDP	4.5"	Fixed lower 4.5"	10M
		Upper 4.5-7" VBR	
Drill collars and MWD tools	4.75"	Upper 4.5-7" VBR	10M
Mud Motor	4.75"	Upper 4.5-7" VBR	10M
Production casing	5.5"	Upper 4.5-7" VBR	10M
ALL	0-13-5/8"	Annular	5M
Open-hole	_	Blind Rams	10M

VBR = Variable Bore Ram. Compatible range listed in chart.

2. Well Control Procedures

Well control procedures are specific to the rig equipment and the operation at the time the kick occurs. Below are the minimal high-level tasks prescribed to assure a proper shut-in while drilling, tripping, running casing, pipe out of the hole (open hole), and moving the BHA through the BOPs. The pressure at which control is swapped from the annular to another compatible ram is variable, but the operator will document in the submission their operating pressure limit. The operator may chose an operating pressure less than or equal to RWP, but in no case will it exceed the RWP of the annular preventer.

General Procedure While Drilling

- 1. Sound alarm (alert crew)
- 2. Space out drill string
- 3. Shut down pumps (stop pumps and rotary)
- 4. Shut-in Well (uppermost applicable BOP, typically annular preventer first. HCR and choke will already be in the closed position.)
- 5. Confirm shut-in
- 6. Notify toolpusher/company representative
- 7. Read and record the following:
 - a. SIDPP and SICP
 - b. Pit gain
 - c. Time
- 8. Regroup and identify forward plan
- 9. If pressure has built or is anticipated during the kill to reach the RWP of the annular preventer, confirm spacing and swap to the upper pipe ram.

Devon Energy Annular Preventer Summary

General Procedure While Tripping

- 1. Sound alarm (alert crew)
- 2. Stab full opening safety valve and close
- 3. Space out drill string
- 4. Shut-in (uppermost applicable BOP, typically annular preventer first. HCR and choke will already be in the closed position.)
- 5. Confirm shut-in
- 6. Notify toolpusher/company representative
- 7. Read and record the following:
 - a. SIDPP and SICP
 - b. Pit gain
 - c. Time
- 8. Regroup and identify forward plan
- 9. If pressure has built or is anticipated during the kill to reach the RWP of the annular preventer, confirm spacing and swap to the upper pipe ram.

General Procedure While Running Casing

- 1. Sound alarm (alert crew)
- 2. Stab crossover and full opening safety valve and close
- 3. Space out string
- 4. Shut-in (uppermost applicable BOP, typically annular preventer first. HCR and choke will already be in the closed position.)
- 5. Confirm shut-in
- 6. Notify toolpusher/company representative
- 7. Read and record the following:
 - a. SIDPP and SICP
 - b. Pit gain
 - c. Time
- 8. Regroup and identify forward plan
- 9. If pressure has built or is anticipated during the kill to reach the RWP of the annular preventer, confirm spacing and swap to compatible pipe ram.

General Procedure With No Pipe In Hole (Open Hole)

- 1. Sound alarm (alert crew)
- 2. Shut-in with blind rams or BSR. (HCR and choke will already be in the closed position.)
- 3. Confirm shut-in
- 4. Notify toolpusher/company representative
- 5. Read and record the following:
 - a. SICP
 - b. Pit gain
 - c. Time
- 6. Regroup and identify forward plan

Devon Energy Annular Preventer Summary

General Procedures While Pulling BHA thru Stack

- 1. PRIOR to pulling last joint of drillpipe thru the stack.
 - a. Perform flowcheck, if flowing:
 - b. Sound alarm (alert crew)
 - c. Stab full opening safety valve and close
 - d. Space out drill string with tool joint just beneath the upper pipe ram.
 - e. Shut-in using upper pipe ram. (HCR and choke will already be in the closed position.)
 - f. Confirm shut-in
 - g. Notify toolpusher/company representative
 - h. Read and record the following:
 - i. SIDPP and SICP
 - ii. Pit gain
 - iii. Time
 - i. Regroup and identify forward plan
- 2. With BHA in the stack and compatible ram preventer and pipe combo immediately available.
 - a. Sound alarm (alert crew)
 - b. Stab crossover and full opening safety valve and close
 - c. Space out drill string with upset just beneath the compatible pipe ram.
 - d. Shut-in using compatible pipe ram. (HCR and choke will already be in the closed position.)
 - e. Confirm shut-in
 - f. Notify toolpusher/company representative
 - g. Read and record the following:
 - i. SIDPP and SICP
 - ii. Pit gain
 - iii. Time
 - h. Regroup and identify forward plan
- 3. With BHA in the stack and NO compatible ram preventer and pipe combo immediately available.
 - a. Sound alarm (alert crew)
 - b. If possible to pick up high enough, pull string clear of the stack and follow "Open Hole" scenario.
 - c. If impossible to pick up high enough to pull the string clear of the stack:
 - d. Stab crossover, make up one joint/stand of drillpipe, and full opening safety valve and close
 - e. Space out drill string with tooljoint just beneath the upper pipe ram.
 - f. Shut-in using upper pipe ram. (HCR and choke will already be in the closed position.)
 - g. Confirm shut-in
 - h. Notify toolpusher/company representative
 - i. Read and record the following:
 - i. SIDPP and SICP
 - ii. Pit gain
 - iii. Time
 - i. Regroup and identify forward plan



U.S. Department of the Interior BUREAU OF LAND MANAGEMENT



APD ID: 10400035366

Submission Date: 10/22/2018

Operator Name: DEVON ENERGY PRODUCTION COMPANY LP

Well Name: GREEN WAVE 20-32 FED STATE COM

Well Number: 16H

Well Type: OIL WELL Well Work Type: Drill



Show Final Text

Section 1 - Existing Roads

Will existing roads be used? YES

Existing Road Map:

Green_Wave_20_32_Fed_State_Com_16H_ACCESS_RD_20181022072850.pdf

Existing Road Purpose: ACCESS

Row(s) Exist? NO

ROW ID(s)

ID:

Do the existing roads need to be improved? YES

Existing Road Improvement Description: Improve road to accommodate Drilling and Completion operations.

Existing Road Improvement Attachment:

Section 2 - New or Reconstructed Access Roads

Will new roads be needed? YES

New Road Map:

Green_Wave_20_32_Fed_State_Com_16H_NEW_ACCESS_RD_20181022073116.pdf

 $Green_Wave_20_32_Fed_State_Com_RS_MDP_20_PADS_CTBS_ACC_RDS1_20181022073125.pdf$

 $Green_Wave_20_32_Fed_State_Com_RS_MDP_20_PADS_CTBS_ACC_RDS2_20181022073135.pdf$

New road type: LOCAL

Length: 786

Feet

Width (ft.): 30

Max slope (%): 6

Max grade (%): 4

Army Corp of Engineers (ACOE) permit required? NO

ACOE Permit Number(s):

New road travel width: 14

New road access erosion control: Water Drainage Ditch

New road access plan or profile prepared? YES

New road access plan attachment:

Well Name: GREEN WAVE 20-32 FED STATE COM Well Number: 16H

Green_Wave_20_32_Fed_State_Com_RS_MDP_20_PADS_CTBS_ACC_RDS1_20181022073214.pdf
Green_Wave_20_32_Fed_State_Com_RS_MDP_20_PADS_CTBS_ACC_RDS2_20181022073222.pdf
Green_Wave_20_32_Fed_State_Com_16H_NEW_ACCESS_RD_20181022073222.pdf

Green_Wave_20_32_Fed_State_Com_16H_NEW_ACCESS_RD_20181022073207.pdf

Access road engineering design? YES

Access road engineering design attachment:

Green_Wave_20_32_Fed_State_Com_16H_NEW_ACCESS_RD_20181022073233.pdf
Green_Wave_20_32_Fed_State_Com_RS_MDP_20_PADS_CTBS_ACC_RDS1_20181022073244.pdf
Green_Wave_20_32_Fed_State_Com_RS_MDP_20_PADS_CTBS_ACC_RDS2_20181022073255.pdf

Access surfacing type: NONE

Access topsoil source: ONSITE

Access surfacing type description:

Access onsite topsoil source depth: 6

Offsite topsoil source description:

Onsite topsoil removal process: See attached Interim reclamation diagram.

Access other construction information:

Access miscellaneous information: Attached road map for well pad and a plat with the overall proposed MDP road system.

Number of access turnouts:

Access turnout map:

Drainage Control

New road drainage crossing: OTHER

Drainage Control comments: N/A

Road Drainage Control Structures (DCS) description: N/A

Road Drainage Control Structures (DCS) attachment:

Access Additional Attachments

Additional Attachment(s):

Section 3 - Location of Existing Wells

Existing Wells Map? YES

Attach Well map:

Green_Wave_20_32_Fed_State_Com_16H_OneMileBuffer_20181022073310.pdf

Existing Wells description:

Well Name: GREEN WAVE 20-32 FED STATE COM Well Number: 16H

Section 4 - Location of Existing and/or Proposed Production Facilities

Submit or defer a Proposed Production Facilities plan? SUBMIT

Production Facilities description: Part of Rattlesnake 2 MDP. SIX PLATS ATTACHED - 3 ELECTRIC, CTB 20-9 PAD PLAT, WELLPAD PLAT, FLOWLINE PLAT. POWER AND ROADS ARE APPROVED IN EXISTING EASEMENTS - ROADS 138036, POWER 138037. CONNECTS HANDLED BY THIRD PARTY **Production Facilities map:**

Green_Wave_20_32_Fed_State_Com_CTB_20_9_PAD_20181018170815.pdf

Green_Wave_20_32_Fed_State_Com_RS_MDP2_20_9_CTB_ELE_20181018170825.PDF

Green_Wave_20_32_Fed_State_Com_S_LAT_ELE_20181018170838.PDF

Green_Wave_20_32_Fed_State_Com_20_8_WP_ELE_20181022073502.PDF

Green_Wave_20_32_Fed_State_Com_RS_MDP1_WP_20_8_20181022073504.pdf

Green_Wave_20_32_Fed_State_Com_RS_PAD_20_8_TO_CTB_20_9_FL_20181022154951.pdf

Section 5 - Location and Types of Water Supply

Water Source Table

Water source use type: STIMULATION Water source type: RECYCLED

Describe type:

Source latitude: Source longitude:

Source datum:

Water source permit type: OTHER Source land ownership: FEDERAL

Water source transport method: PIPELINE

Source transportation land ownership: FEDERAL

Water source volume (barrels): 320000 Source volume (acre-feet): 41.245792

Source volume (gai): 13440000

Water source and transportation map:

GREEN_WAVE_20_32_FED_STATE_COM_WP_20_8_WATER_MAP_20181022073600.pdf

Water source comments: The attached Water Transfer Map is a proposal only and the final route and documentation will be provided by a Devon contractor prior to installation. When available Devon will always follow existing disturbance. New water well? NO

New	Water	اامW	Info
IACAA	TTOLE	44611	11110

Well latitude:

Well Longitude:

Well datum:

Well target aguifer:

Est. depth to top of aquifer(ft):

Est thickness of aquifer:

Well Name: GREEN WAVE 20-32 FED STATE COM Well Number: 16H

Aquifer comments:

Aquifer documentation:

Well depth (ft):

Well casing type:

Well casing outside diameter (in.):

Well casing inside diameter (in.):

New water well casing?

Used casing source:

Drilling method:

Drill material:

Grout material:

Grout depth:

Casing length (ft.):

Casing top depth (ft.):

Well Production type:

Completion Method:

Water well additional information:

State appropriation permit:

Additional information attachment:

Section 6 - Construction Materials

Construction Materials description: Part of Rattlesnake 2 MDP. Dirt fill and caliche will be used to construct well pad. See attached map.

Construction Materials source location attachment:

RS_MDP_1_Pad_20_8_Caliche_Map_20181022073706.pdf

Section 7 - Methods for Handling Waste

Waste type: DRILLING

Waste content description: Water Based and Oil Based Cuttings

Amount of waste: 1740

barrels

Waste disposal frequency: Daily

Safe containment description: N/A

Safe containment attachment:

Waste disposal type: HAUL TO COMMERCIAL

Disposal location ownership: COMMERCIAL

FACILITY

Disposal type description:

Disposal location description: All cuttings will disposed of at R360, Sundance, or equivalent.

Waste type: COMPLETIONS/STIMULATION

Waste content description: Flow back water during completion operations.

Amount of waste: 3000

barrels

Waste disposal frequency: One Time Only

Safe containment description: n/a

Safe containment attachment:

Well Name: GREEN WAVE 20-32 FED STATE COM Well Number: 16H

Waste disposal type: HAUL TO COMMERCIAL Disposal location ownership: COMMERCIAL

FACILITY

Disposal type description:

Disposal location description: Various disposal locations in Lea and Eddy counties.

Waste type: PRODUCED WATER

Waste content description: Produced water during flowback will be disposed of at our Rattlesnake 16 SWD.

Amount of waste: 4100

barrels

Waste disposal frequency: Daily Safe containment description: n/a

Safe containment attachment:

Waste disposal type: OFF-LEASE INJECTION

Disposal location ownership: STATE

Disposal type description:

Disposal location description: Produced water will be primarily disposed of at our Rattlesnake 16 SWD. Portions of this water will be recycled and used for stimulations (recycle facility co-located with SWD). Surplus produced water will be sent to third party suppliers for disposal.

Waste type: FLOWBACK

Waste content description: Average produced BWPD over the flowback period (first 30 days of production).

Amount of waste: 11500

barrels

Waste disposal frequency : Daily
Safe containment description: n/a

Safe containment attachment:

Waste disposal type: OFF-LEASE INJECTION

Disposal location ownership: STATE

Disposal type description:

Disposal location description: Produced water will be primarily disposed of at our Rattlesnake 16 SWD. Portions of this water will be recycled and used for stimulations (recycle facility co-located with SWD). Surplus produced water will be sent to third party suppliers for disposal.

Reserve Pit

Reserve Pit being used? NO

Temporary disposal of produced water into reserve pit?

Reserve pit length (ft.)

Reserve pit width (ft.)

Reserve pit depth (ft.)

Reserve pit volume (cu. yd.)

Is at least 50% of the reserve pit in cut?

Reserve pit liner

Reserve pit liner specifications and installation description

Well Name: GREEN WAVE 20-32 FED STATE COM

Well Number: 16H

Cuttings Area

Cuttings Area being used? NO

Are you storing cuttings on location? NO

Description of cuttings location

Cuttings area length (ft.)

Cuttings area width (ft.)

Cuttings area depth (ft.)

Cuttings area volume (cu. yd.)

Is at least 50% of the cuttings area in cut?

WCuttings area liner

Cuttings area liner specifications and installation description

Section 8 - Ancillary Facilities

Are you requesting any Ancillary Facilities?: NO

Ancillary Facilities attachment:

Comments:

Section 9 - Well Site Layout

Well Site Layout Diagram:

Green_Wave_20_32_Fed_State_Com_16H_WELL_LAYOUT_20181022073727.pdf

Comments:

Section 10 - Plans for Surface Reclamation

Type of disturbance: New Surface Disturbance

Multiple Well Pad Name: RATTLESNAKE MDP 1 PAD

Multiple Well Pad Number: 20-08

Recontouring attachment:

Green_Wave_20_32_Fed_State_Com_16H_INTERIM_RECL_20181022073741.pdf

Drainage/Erosion control construction: n/a **Drainage/Erosion control reclamation:** n/a

Well Name: GREEN WAVE 20-32 FED STATE COM Well Number: 16H

Well pad proposed disturbance

(acres): 8.271

Road proposed disturbance (acres):

0.542

Powerline proposed disturbance

(acres): 4.35

Pipeline proposed disturbance

(acres): 1.355

Other proposed disturbance (acres): 0

Total proposed disturbance: 14.518

Well pad interim reclamation (acres): Well pad long term disturbance

5.676

Road interim reclamation (acres): 0

Powerline interim reclamation (acres):

Pipeline interim reclamation (acres): 0

Other interim reclamation (acres): 0

Total interim reclamation: 5.676

(acres): 2.595

Road long term disturbance (acres):

0.542

Powerline long term disturbance

(acres): 4.35

Pipeline long term disturbance

(acres): 1.355

Other long term disturbance (acres): 0

Total long term disturbance: 8.842

Disturbance Comments:

Reconstruction method: Operator will use Best Management Practices"BMP" to mechanically recontour to obtain the desired outcome.

Topsoil redistribution: Topsoils shall be replaced to their original relative positions and contoured so as to achieve erosion control, long-term stability and preservation of surface water flow patterns.

Soil treatment: Topsoils shall be replaced to their original relative positions and contoured so as to achieve erosion control, long-term stability and preservation of surface water flow patterns.

Existing Vegetation at the well pad: Shinnery, yucca, grasses and mesquite.

Existing Vegetation at the well pad attachment:

Existing Vegetation Community at the road: Shinnery, yucca, grasses and mesquite.

Existing Vegetation Community at the road attachment:

Existing Vegetation Community at the pipeline: Shinnery, yucca, grasses and mesquite.

Existing Vegetation Community at the pipeline attachment:

Existing Vegetation Community at other disturbances: Shinnery, yucca, grasses and mesquite.

Existing Vegetation Community at other disturbances attachment:

Non native seed used? NO

Non native seed description:

Seedling transplant description:

Will seedlings be transplanted for this project? NO

Seedling transplant description attachment:

Will seed be harvested for use in site reclamation? NO

Seed harvest description:

Seed harvest description attachment:

Well Name: GREEN WAVE 20-32 FED STATE COM

Well Number: 16H

Seed Management

Seed Table

Seed type:

Seed source:

Seed name:

Source name:

Source address:

Total pounds/Acre:

Source phone:

Seed cultivar:

Seed use location:

PLS pounds per acre:

Proposed seeding season:

Seed Summary

Seed Type

Pounds/Acre

Seed reclamation attachment:

Operator Contact/Responsible Official Contact Info

First Name: TRAVIS

Last Name: PHIBBS

Phone: (575)748-9929

Email: TRAVIS.PHIBBS@DVN.COM

Seedbed prep:

Seed BMP:

Seed method:

Existing invasive species? NO

Existing invasive species treatment description:

Existing invasive species treatment attachment:

Weed treatment plan description: Maintain weeds on an as need basis.

Weed treatment plan attachment:

Monitoring plan description: Monitor as needed.

Monitoring plan attachment:

Success standards: N/A

Pit closure description: N/A

Pit closure attachment:

Well Name: GREEN WAVE 20-32 FED STATE COM

Well Number: 16H

Section 11 - Surface Ownership	
Disturbance type: NEW ACCESS ROAD	
Describe:	
Surface Owner: BUREAU OF LAND MANAGEMENT	ī
Other surface owner description:	
BIA Local Office:	
BOR Local Office:	
COE Local Office:	
DOD Local Office:	
NPS Local Office:	
State Local Office:	•
Military Local Office:	
USFWS Local Office:	
Other Local Office:	•
USFS Region:	
USFS Forest/Grassland:	USFS Ranger District:
	•
Disturbance type: EXISTING ACCESS ROAD	
Describe:	
Surface Owner: BUREAU OF LAND MANAGEMENT	ī

Other surface owner description:

BIA Local Office:

BOR Local Office:

COE Local Office:

DOD Local Office:

NPS Local Office:

State Local Office:

Military Local Office:

USFWS Local Office:

Other Local Office:

USFS Region:

NCFC Forest/Creenland	NOTO Description
USFS Forest/Grassland:	USFS Ranger District:
Disturbance type: WELL PAD	
Describe:	· ·
Surface Owner: BUREAU OF LAND MANAGEMENT	·
Other surface owner description:	
BIA Local Office:	
BOR Local Office:	
COE Local Office:	
DOD Local Office:	
NPS Local Office:	
State Local Office:	
Military Local Office:	
USFWS Local Office:	
Other Local Office:	
USFS Region:	•
USFS Forest/Grassland:	USFS Ranger District:
	-
Marie Carlos de	
Disturbance type: PIPELINE	
Describe:	
Surface Owner: BUREAU OF LAND MANAGEMENT	
Other surface owner description:	
BIA Local Office:	
BOR Local Office:	
COE Local Office:	
DOD Local Office:	

Well Number: 16H

Operator Name: DEVON ENERGY PRODUCTION COMPANY LP

Well Name: GREEN WAVE 20-32 FED STATE COM

NPS Local Office:
State Local Office:

Military Local Office:

Well Name: GREEN WAVE 20-32 FED STATE COM

Well Number: 16H

USFWS Local Office:

Other Local Office:

USFS Region:

USFS Forest/Grassland:

USFS Ranger District:

Section 12 - Other Information

Right of Way needed? YES

Use APD as ROW? YES

ROW Type(s): 281001 ROW - ROADS,288100 ROW - O&G Pipeline,FLPMA (Powerline),Other

ROW Applications

SUPO Additional Information: PART OF RATTLESNAKE MDP 2. SEE SEC. 4 FOR FACILITY, ELECTRIC AND FLOWLINE PLATS.

Use a previously conducted onsite? YES

Previous Onsite information: CONDUCTED 1/272017

Other SUPO Attachment



U.S. Department of the Interior BUREAU OF LAND MANAGEMENT



Section 1 - General

Would you like to address long-term produced water disposal? NO

Section 2 - Lined Pits

Would you like to utilize Lined Pit PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

Lined pit PWD on or off channel:

Lined pit PWD discharge volume (bbl/day):

Lined pit specifications:

Pit liner description:

Pit liner manufacturers information:

Precipitated solids disposal:

Decribe precipitated solids disposal:

Precipitated solids disposal permit:

Lined pit precipitated solids disposal schedule:

Lined pit precipitated solids disposal schedule attachment:

Lined pit reclamation description:

Lined pit reclamation attachment:

Leak detection system description:

Leak detection system attachment:

Lined pit Monitor description:

Lined pit Monitor attachment:

Lined pit: do you have a reclamation bond for the pit?

Is the reclamation bond a rider under the BLM bond?

Lined pit bond number:

Lined pit bond amount:

Additional bond information attachment:

PWD disturbance (acres):

Section 3 - Unlined Pits

Injection PWD discharge volume (bbl/day):

Injection well mineral owner:

Would you like to utilize Unlined Pit PWD options? NO

Produced Water Disposal (PWD) Location	n:
PWD surface owner:	PWD disturbance (acres):
Unlined pit PWD on or off channel:	
Unlined pit PWD discharge volume (bbl/d	lay):
Unlined pit specifications:	
Precipitated solids disposal:	
Decribe precipitated solids disposal:	
Precipitated solids disposal permit:	
Unlined pit precipitated solids disposal s	chedule:
Unlined pit precipitated solids disposal s	chedule attachment:
Unlined pit reclamation description:	
Unlined pit reclamation attachment:	
Unlined pit Monitor description:	
Unlined pit Monitor attachment:	
Do you propose to put the produced water	er to beneficial use?
Beneficial use user confirmation:	
Estimated depth of the shallowest aquifer	r (feet):
Does the produced water have an annual that of the existing water to be protected?	average Total Dissolved Solids (TDS) concentration equal to or less than?
TDS lab results:	
Geologic and hydrologic evidence:	
State authorization:	
Unlined Produced Water Pit Estimated pe	ercolation:
Unlined pit: do you have a reclamation bo	ond for the pit?
Is the reclamation bond a rider under the	BLM bond?
Unlined pit bond number:	
Unlined pit bond amount:	
Additional bond information attachment:	
Section 4 - Injection	
Would you like to utilize Injection PWD or	otions? NO
Produced Water Disposal (PWD) Location	· 1:
PWD surface owner:	PWD disturbance (acres):
	· ··

Injection well type:	
Injection well number:	Injection well name:
Assigned injection well API number?	Injection well API number:
Injection well new surface disturbance (acres):	
Minerals protection information:	
Mineral protection attachment:	
Underground Injection Control (UIC) Permit?	
UIC Permit attachment:	
Section 5 - Surface Discharge	
Would you like to utilize Surface Discharge PWD options? NO	
Produced Water Disposal (PWD) Location:	
PWD surface owner:	PWD disturbance (acres):
Surface discharge PWD discharge volume (bbl/day):	
Surface Discharge NPDES Permit?	
Surface Discharge NPDES Permit attachment:	
Surface Discharge site facilities information:	•
Surface discharge site facilities map:	
Section 6 - Other	
Would you like to utilize Other PWD options? NO	
Produced Water Disposal (PWD) Location:	
PWD surface owner:	PWD disturbance (acres):
Other PWD discharge volume (bbl/day):	
Other PWD type description:	
Other PWD type attachment:	
Have other regulatory requirements been met?	•
Other regulatory requirements attachment:	



U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

Bond Info Data Report

Bond Information

Federal/Indian APD: FED

BLM Bond number: CO1104

BIA Bond number:

Do you have a reclamation bond? NO

Is the reclamation bond a rider under the BLM bond?

Is the reclamation bond BLM or Forest Service?

BLM reclamation bond number:

Forest Service reclamation bond number:

Forest Service reclamation bond attachment:

Reclamation bond number:

Reclamation bond amount:

Reclamation bond rider amount:

Additional reclamation bond information attachment: