UNITED STATES

FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018

DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
SUNDRY NOTICES AND REPORTED FIELD OFFICE ASSESSMENT SUNDRY NOTICES AND REPORTED FIELD FIELD

Do not use this form for proposals to drill or to the proposal or to the proposal

SUBMIT IN TI	RIPLICATE - Other Instru	ections on page 2	S OCD 7. If Unit or CA/Ag	greement, Name and/or No.	
1. Type of Well	· · · · · · · · · · · · · · · · · · ·		8. Well Name and N		
② Oil Well ☐ Gas Well ☐ Other 2. Name of Operator		MAY MILY FOLLIS	2 0 2019 JAVELINA 30 P	LD 70211	
EOG RESOURCES INCORPO		eogresources.com	30-025-42830)-00-X1	
		3b. Phone No. (include the cod Ph: 432-636-3600		10. Field and Pool or Exploratory Area RED HILLS-BONE SPRING, NORTH	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)			11. County or Paris	11. County or Parish, State	
Sec 30 T25S R34E Lot 3 2191FSL 599FWL			LEA COUNT	LEA COUNTY, NM	
12. CHECK THE API	PROPRIATE BOX(ES) T	O INDICATE NATURE (OF NOTICE, REPORT, OR O	THER DATA	
TYPE OF SUBMISSION		ТҮРЕ С	TYPE OF ACTION		
□ Notice of Intent	☐ Acidize	Deepen	☐ Production (Start/Resume)	☐ Water Shut-Off	
_	☐ Alter Casing	☐ Hydraulic Fracturing	Reclamation	■ Well Integrity	
Subsequent Report ■	Casing Repair	■ New Construction	Recomplete	Other	
☐ Final Abandonment Notice	☐ Change Plans	Plug and Abandon	☐ Temporarily Abandon	Drilling Operations	
	□ Convert to Injection	Plug Back	☐ Water Disposal	11.	
3. Describe Proposed or Completed Oper If the proposal is to deepen directionall Attach the Bond under which the work following completion of the involved o testing has been completed. Final Abadetermined that the site is ready for final COMPLICATION.	ration: Clearly state all pertinent by or recomplete horizontally, given will be performed or provide the operations. If the operation resulundonment Notices must be filed all inspection.	ve subsurface locations and mease e Bond No. on file with BLM/Bl its in a multiple completion or re-	sured and true vertical depths of all per A. Required subsequent reports must completion in a new interval, a Form 3	rtinent markers and zones. be filed within 30 days 160-4 must be filed once	
If the proposal is to deepen directionall Attach the Bond under which the work following completion of the involved o testing has been completed. Final Abadetermined that the site is ready for fine 03/19/19 SPUD CONDUCTOR 03/19/19 12-1/4" HOLE 03/19/19 Surface Casing @ 1,1 Ran 9-5/8" 40# J-55 LTC Lead Cement w/ 520 sx Class 0 (1.36 yld, 14.8 ppg) Test casing to 1,700 psi for 30 to 04/13/19 8-3/4" hole 04/13/19 Intermediate Casing @ Ran 7-5/8". 29.7#, ECP-110 BT	ration: Clearly state all pertinent ty or recomplete horizontally, given the performed or provide the operations. If the operation resulundonment Notices must be filed all inspection. HOLE 20" 125' C (1.64 yld, 13.5 ppg), Tail min - OK. Circ 240 sx cem 2 11,899' C SCC (0' - 1,002')	ve subsurface locations and mease Bond No. on file with BLM/Bl its in a multiple completion or reconly after all requirements, including the completion of the conference of t	sured and true vertical depths of all per A. Required subsequent reports must completion in a new interval, a Form 3	rtinent markers and zones. be filed within 30 days 160-4 must be filed once	
If the proposal is to deepen directionall Attach the Bond under which the work following completion of the involved o testing has been completed. Final Abadetermined that the site is ready for fin. 03/19/19 SPUD CONDUCTOR 03/19/19 12-1/4" HOLE 03/19/19 Surface Casing @ 1,1 Ran 9-5/8" 40# J-55 LTC Lead Cement w/ 520 sx Class (1.36 yld, 14.8 ppg) Test casing to 1,700 psi for 30 to 04/13/19 8-3/4" hole 04/13/19 Intermediate Casing @ Ran 7-5/8", 29.7#, ECP-110 BT Ran 7-5/8", 29.7#, ICYP-110 M	ration: Clearly state all pertinent by or recomplete horizontally, given will be performed or provide the operations. If the operation resuludonment Notices must be filed hal inspection. HOLE 20" 125' C (1.64 yld, 13.5 ppg), Tailmin - OK. Circ 240 sx cemmoders of the complete of the	ve subsurface locations and mease Bond No. on file with BLM/Bl its in a multiple completion or reconly after all requirements, including which will be sufficient to surface. 1465 verified by the BLM W	sured and true vertical depths of all per A. Required subsequent reports must completion in a new interval, a Form 3 iding reclamation, have been complete the subsequent of t	rtinent markers and zones. be filed within 30 days 160-4 must be filed once	
If the proposal is to deepen directionall Attach the Bond under which the work following completion of the involved o testing has been completed. Final Abadetermined that the site is ready for fin. 03/19/19 SPUD CONDUCTOR 03/19/19 12-1/4" HOLE 03/19/19 Surface Casing @ 1,1 Ran 9-5/8" 40# J-55 LTC Lead Cement w/ 520 sx Class 0 (1.36 yld, 14.8 ppg) Test casing to 1,700 psi for 30 in 04/13/19 8-3/4" hole 04/13/19 Intermediate Casing @ Ran 7-5/8", 29.7#, ECP-110 BT Ran 7-5/8", 29.7#, ICYP-110 Mill. I hereby certify that the foregoing is to 14. I hereby certify that the foregoing is to 14. I hereby certify that the foregoing is to 15.	ration: Clearly state all pertinent by or recomplete horizontally, given will be performed or provide the operations. If the operation resuludonment Notices must be filed all inspection. HOLE 20" 125' C (1.64 yld, 13.5 ppg), Tailmin - OK. Circ 240 sx cem 11.899' TC SCC (0' - 1,002') 10-FXL (1,002' - 11,899') True and correct. Electronic Submission #46 For EOG RESOUR	ve subsurface locations and mease Bond No. on file with BLM/Bl its in a multiple completion or re only after all requirements, inclu- liw/ 90 sx Class C ment to surface	sured and true vertical depths of all per A. Required subsequent reports must completion in a new interval, a Form 3 iding reclamation, have been complete the subsequent of t	rtinent markers and zones. be filed within 30 days 160-4 must be filed once	
If the proposal is to deepen directionall Attach the Bond under which the work following completion of the involved o testing has been completed. Final Abadetermined that the site is ready for fin. 03/19/19 SPUD CONDUCTOR 03/19/19 SPUD CONDUCTOR 03/19/19 Surface Casing @ 1,1 Ran 9-5/8" 40# J-55 LTC Lead Cement w/ 520 sx Class 0 (1.36 yld, 14.8 ppg) Test casing to 1,700 psi for 30 in 04/13/19 8-3/4" hole 04/13/19 Intermediate Casing @ Ran 7-5/8", 29.7#, ECP-110 BT Ran 7-5/8", 29.7#, ICYP-110 Minute 14. I hereby certify that the foregoing is to 14. I hereby certify that the foregoing is to 14.	ration: Clearly state all pertinent by or recomplete horizontally, git will be performed or provide the operations. If the operation resuludonment Notices must be filed all inspection. HOLE 20" 125' C (1.64 yld, 13.5 ppg), Tail min - OK. Circ 240 sx cem 11,899' TC SCC (0' - 1,002') O-FXL (1,002' - 11,899') True and correct. Electronic Submission #46 For EOG RESOUR mitted to AFMSS for proces	ve subsurface locations and mease Bond No. on file with BLM/Bl its in a multiple completion or reconly after all requirements, including which was a complete to surface. 1465 verified by the BLM WCES INCORPORATED, sensing by PRISCILLA PEREZ	sured and true vertical depths of all per A. Required subsequent reports must completion in a new interval, a Form 3 iding reclamation, have been complete the subsequent reports and t	rtinent markers and zones. be filed within 30 days 160-4 must be filed once and the operator has	
If the proposal is to deepen directionall Attach the Bond under which the work following completion of the involved o testing has been completed. Final Abadetermined that the site is ready for fin. 03/19/19 SPUD CONDUCTOR 03/19/19 12-1/4" HOLE 03/19/19 Surface Casing @ 1,1 Ran 9-5/8" 40# J-55 LTC Lead Cement w/ 520 sx Class (1.36 yld, 14.8 ppg) Test casing to 1,700 psi for 30 ii 04/13/19 8-3/4" hole 04/13/19 Intermediate Casing @ Ran 7-5/8", 29.7#, ECP-110 BT Ran 7-5/8", 29.7#, ICYP-110 Mi	ation: Clearly state all pertinent by or recomplete horizontally, git will be performed or provide the operations. If the operation resuludonment Notices must be filed all inspection. HOLE 20" 125' C (1.64 yld, 13.5 ppg), Tailmin - OK. Circ 240 sx cemulation of the complete of the c	ve subsurface locations and mease Bond No. on file with BLM/Bl its in a multiple completion or reconly after all requirements, including the substitution of the subst	ell Information System to the Hobbs on 04/17/2019 (19PP1557SE)	rtinent markers and zones. be filed within 30 days 160-4 must be filed once and the operator has	
If the proposal is to deepen directionall Attach the Bond under which the work following completion of the involved o testing has been completed. Final Abadetermined that the site is ready for fin. 03/19/19 SPUD CONDUCTOR 03/19/19 12-1/4" HOLE 03/19/19 Surface Casing @ 1,1 Ran 9-5/8" 40# J-55 LTC Lead Cement w/ 520 sx Class 0 (1.36 yld, 14.8 ppg) Test casing to 1,700 psi for 30 r 04/13/19 8-3/4" hole 04/13/19 Intermediate Casing @ Ran 7-5/8", 29.7#, ECP-110 BT Ran 7-5/8", 29.7#, ICYP-110 Mi	ation: Clearly state all pertinent by or recomplete horizontally, given all performed or provide the perations. If the operation resulution ment Notices must be filed all inspection. HOLE 20" 125' C (1.64 yld, 13.5 ppg), Tail min - OK. Circ 240 sx cem 11,899' C SCC (0' - 1,002') IO-FXL (1,002' - 11,899') The and correct. Electronic Submission #46 For EOG RESOUR mitted to AFMSS for proces LIS LIS LIS LIS LIS LIS LIS LI	ve subsurface locations and mease Bond No. on file with BLM/Bl ts in a multiple completion or reconly after all requirements, including the subsection of th	sured and true vertical depths of all per A. Required subsequent reports must completion in a new interval, a Form 3 iding reclamation, have been complete and the subsequent of the Hobbs on 04/17/2019 (19PP1557SE) EGULATORY ADMINISTRATO	rtinent markers and zones. be filed within 30 days 160-4 must be filed once and the operator has	
If the proposal is to deepen directionall Attach the Bond under which the work following completion of the involved o testing has been completed. Final Abadetermined that the site is ready for fin. 03/19/19 SPUD CONDUCTOR 03/19/19 12-1/4" HOLE 03/19/19 Surface Casing @ 1,1 Ran 9-5/8" 40# J-55 LTC Lead Cement w/ 520 sx Class 0 (1.36 yld, 14.8 ppg) Test casing to 1,700 psi for 30 ii 04/13/19 8-3/4" hole 04/13/19 Intermediate Casing @ Ran 7-5/8", 29.7#, ECP-110 BT Ran 7-5/8", 29.7#, ICYP-110 Mi	ation: Clearly state all pertinent by or recomplete horizontally, given all performed or provide the perations. If the operation resulution ment Notices must be filed all inspection. HOLE 20" 125' C (1.64 yld, 13.5 ppg), Tail min - OK. Circ 240 sx cem 11,899' C SCC (0' - 1,002') IO-FXL (1,002' - 11,899') The and correct. Electronic Submission #46 For EOG RESOUR mitted to AFMSS for proces LIS LIS LIS LIS LIS LIS LIS LI	ve subsurface locations and mease Bond No. on file with BLM/Bl its in a multiple completion or reconly after all requirements, including the substitution of the subst	sured and true vertical depths of all per A. Required subsequent reports must completion in a new interval, a Form 3 iding reclamation, have been complete and the subsequent of the Hobbs on 04/17/2019 (19PP1557SE) EGULATORY ADMINISTRATO	rtinent markers and zones. be filed within 30 days 1160-4 must be filed once and the operator has	
If the proposal is to deepen directionall Attach the Bond under which the work following completion of the involved o testing has been completed. Final Abadetermined that the site is ready for fin. 03/19/19 SPUD CONDUCTOR 03/19/19 12-1/4" HOLE 03/19/19 Surface Casing @ 1,1 Ran 9-5/8" 40# J-55 LTC Lead Cement w/ 520 sx Class 0 (1.36 yld, 14.8 ppg) Test casing to 1,700 psi for 30 ii 04/13/19 8-3/4" hole 04/13/19 Intermediate Casing @ Ran 7-5/8", 29.7#, ECP-110 BT Ran 7-5/8", 29.7#, ICYP-110 Mi	ation: Clearly state all pertinent by or recomplete horizontally, given all performed or provide the perations. If the operation resulution ment Notices must be filed all inspection. HOLE 20" 125' C (1.64 yld, 13.5 ppg), Tail min - OK. Circ 240 sx cem 11,899' C SCC (0' - 1,002') IO-FXL (1,002' - 11,899') The and correct. Electronic Submission #46 For EOG RESOUR mitted to AFMSS for proces LIS LIS LIS LIS LIS LIS LIS LI	ve subsurface locations and mease Bond No. on file with BLM/Bl ts in a multiple completion or reconly after all requirements, including the substitution of the substi	sured and true vertical depths of all per A. Required subsequent reports must completion in a new interval, a Form 3 iding reclamation, have been complete and the subsequent of the Hobbs on 04/17/2019 (19PP1557SE) EGULATORY ADMINISTRATO	rtinent markers and zones. be filed within 30 days 160-4 must be filed once and the operator has	

Additional data for EC transaction #461465 that would not fit on the form

32. Additional remarks, continued

Stage 1: Lead Cement w/ 390 sx Class H(1.23 yld, 15.6 ppg)
Test casing to 2,500 psi for 30 min - Good. Did not circ cement to surface, TOC @ 7,200' by Est Stage 2: Bradenhead squeeze w/ 1,000 sx Class C (1.53 yld, 14.8 ppg)
Stage 3: Top out w/ 41 sx Class C + 2% CaCl2 (1.36 yld, 14.8 ppg) Flushed lines w/ 3 bbls fresh water TOC @ Surface Resume Drilling 6-3/4" hole