CLINIDDA	DEPARTMENT OF THE I BUREAU OF LAND MANA (NOTICES AND REPO		OC	Expires: J Lease Serial No. 4 NMLC062269A	
Do not use t	his form for proposals to ell. Use form 3160-3 (AP	drill or to re-enter an	6	5. If Indian, Allottee	
SUBMIT IN	TRIPLICATE - Other inst	tructions HOBBS O		7. If Unit or CA/Agre	eement, Name and/or No.
1. Type of Well		JUL 0 3 201	9 8	3. Well Name and No GHOST RIDER 2	22-15 FEDERAL COM 2
2. Name of Operator APACHE CORPORATION		LINDA LUCE Dapachecorp.co	ED 9	D. API Well No. 30-025-45645-0	00-X1
 3a. Address 303 VETERANS AIRPARK LANE SUITE 3000 MIDLAND, TX 79705 		3b. Phone No. (include area code) Ph: 432-818-1826		10. Field and Pool or Exploratory Area WILDCAT BONE SPRING	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description,))	1	1. County or Parish,	State
Sec 22 T24S R32E SESE 400FSL 676FEL 32.196918 N Lat, 103.656166 W Lon				LEA COUNTY, NM	
12. CHECK THE A	PPROPRIATE BOX(ES)	TO INDICATE NATURE OI	NOTICE, R	EPORT, OR OT	HER DATA
TYPE OF SUBMISSION		TYPE OF	ACTION		
□ Notice of Intent	C Acidize	Deepen	Production	n (Start/Resume)	□ Water Shut-Off
Subsequent Report	Alter Casing	Hydraulic Fracturing			Well Integrity
	 Casing Repair Change Plans 	New Construction			Other
Final Abandonment Notice	Convert to Injection	Plug and Abandon Plug Back	Temporari Water Disponential	-	
Attach the Bond under which the work following completion of the involve testing has been completed. Final A determined that the site is ready for Move satellite from Northwes located in the SW/4 SE/4 Se depicted in the attached plat, run from each well on associ	nally or recomplete horizontally, ork will be performed or provide ed operations. If the operation re- bandonment Notices must be fil- final inspection. It side of well pads to a ser- ction 22, T24S, R32E betw. Boone Arch survey and S ated drill pads to central sa	give subsurface locations and measure the Bond No. on file with BLM/BIA. sults in a multiple completion or recor- ed only after all requirements, includi parate 500' x 500' central satel veen Middle Drill Pad and East atellite Layout. All production 1 atellite with a common emulsio	ed and true vertic Required subse npletion in a new ng reclamation, h lite pad Drill Pad as ines will n line	cal depths of all pertin quent reports must be v interval, a Form 316	nent markers and zones. tiled within 30 days 50-4 must be filed once
If the proposal is to deepen direction Attach the Bond under which the wi following completion of the involve testing has been completed. Final A determined that the site is ready for Move satellite from Northwess located in the SW/4 SE/4 Se depicted in the attached plat, run from each well on associ running from central satellite in a common trench and rout of previously approved trencl pad being located at the NW 126 feet. An additional accer	nally or recomplete horizontally, ork will be performed or provide ed operations. If the operation re- boundomment Notices must be fil- final inspection. It side of well pads to a ser- ction 22, T24S, R32E betw. Boone Arch survey and S ated drill pads to central sa facility to Central Tank Bat e as approved under APD h will be replaced with the Corner, Center of West sig ss road from existing lease	give subsurface locations and measure the Bond No. on file with BLM/BIA. sults in a multiple completion or recor- ed only after all requirements, includi operate 500' x 500' central satel veen Middle Drill Pad and East atellite Layout. All production 1	ed and true vertic Required subse mpletion in a new ng reclamation, h Drill Pad as ines will n line e laid e. Approx. 550 satellite d for approx. 72 feet and	cal depths of all pertin quent reports must be v interval, a Form 316 have been completed a	nent markers and zones. filed within 30 days 50-4 must be filed once
If the proposal is to deepen direction Attach the Bond under which the with following completion of the involve testing has been completed. Final A determined that the site is ready for Move satellite from Northwess located in the SW/4 SE/4 Set depicted in the attached plat, run from each well on associ running from central satellite in a common trench and rout of previously approved trench pad being located at the NW 126 feet. An additional access additional electric from previously size of pipe below:	nally or recomplete horizontally, ork will be performed or provide ed operations. If the operation re- boandonment Notices must be fil- final inspection. It side of well pads to a sep- ction 22, T24S, R32E betw. Boone Arch survey and S ated drill pads to central sa facility to Central Tank Bat e as approved under APD' h will be replaced with the Corner, Center of West sides so road from existing lease busly approved route of 10	give subsurface locations and measure the Bond No. on file with BLM/BIA. sults in a multiple completion or recor- ed only after all requirements, includi operate 500' x 500' central satel veen Middle Drill Pad and East atellite Layout. All production I atellite with a common emulsio ttery. All production lines will b 's from each drill pad to satellit following points of entry to the de of pad, and SE corner of pad a road to SW Corner of pad for	ed and true vertic Required subse npletion in a new ng reclamation, h Drill Pad as ines will n line e laid e. Approx. 556 satellite d for approx. 72 feet and ngth and	cal depths of all pertin quent reports must be v interval, a Form 316 have been completed a	nent markers and zones. tiled within 30 days 50-4 must be filed once
If the proposal is to deepen direction Attach the Bond under which the w following completion of the involve testing has been completed. Final A determined that the site is ready for Move satellite from Northwess located in the SW/4 SE/4 Set depicted in the SW/4 SE/4 Set depicted in the attached plat, run from each well on associ running from central satellite in a common trench and rout of previously approved trench pad being located at the NW 126 feet. An additional access additional electric from previous size of pipe below:	hally or recomplete horizontally, ork will be performed or provide ed operations. If the operation re- boandonment Notices must be fil- final inspection. If side of well pads to a sep- ction 22, T24S, R32E betw Boone Arch survey and S ated drill pads to central sa facility to Central Tank Balle e as approved under APD' h will be replaced with the Corner, Center of West sides so road from existing lease busly approved route of 10 <u>DOT-BUN-NM-PS20</u> is true and correct. Electronic Submission #	give subsurface locations and measure the Bond No. on file with BLM/BIA. sults in a multiple completion or recor- ed only after all requirements, includi parate 500' x 500' central satel veen Middle Drill Pad and East atellite Layout. All production I atellite with a common emulsio tatellite ayout. All production lines will b 's from each drill pad to satellit following points of entry to the de of pad, and SE corner of pad or road to SW Corner of pad for 1 feet. The following details ler	ed and true vertic Required subse npletion in a new ng reclamation, h lite pad Drill Pad as ines will n line e laid e. Approx. 556 satellite d for approx. 72 feet and ngth and	cal depths of all pertin quent reports must be v interval, a Form 316 have been completed a 0'	nent markers and zones. tiled within 30 days 50-4 must be filed once
If the proposal is to deepen direction Attach the Bond under which the w following completion of the involve testing has been completed. Final A determined that the site is ready for Move satellite from Northwess located in the SW/4 SE/4 Set depicted in the attached plat, run from each well on associ running from central satellite in a common trench and rout of previously approved trench pad being located at the NW 126 feet. An additional access additional electric from previous size of pipe below: <u>EVEC JAC 06/A/A</u> 14. I hereby certify that the foregoing to Common termine the the foregoing to	hally or recomplete horizontally, ork will be performed or provide ed operations. If the operation re- bhandonment Notices must be fil- final inspection. If side of well pads to a sep- ction 22, T24S, R32E betw. Boone Arch survey and S ated drill pads to central sa facility to Central Tank Bat e as approved under APD' h will be replaced with the Corner, Center of West sides so road from existing lease busly approved route of 10 <u>DOT-BUN-MM-Po20</u> is true and correct. Electronic Submission #- For APACH mmitted to AFMSS for proce	give subsurface locations and measure the Bond No. on file with BLM/BIA. sults in a multiple completion or recor- ed only after all requirements, includi parate 500' x 500' central satel veen Middle Drill Pad and East atellite Layout. All production I atellite with a common emulsio tatellite ayout. All production I atellite ayout. All production I atellite Layout. All production f atellite with a common emulsio tatellite ayout. All production f atellite with a common emulsio tatellite ayout. All production f atellite ayout. All production f atellite ayout. All production f atellite by the substance and the assing by JUANA MEDRANO on	ed and true vertic Required subse npletion in a new ng reclamation, b lite pad Drill Pad as ines will n line e laid e. Approx. 550 satellite d for approx. 72 feet and ngth and <u>pulutions of</u> 100bs 06/12/2019 (15	cal depths of all pertin quent reports must be v interval, a Form 316 have been completed a 0' 0' 0' 0' 0' 0' 0' 0' 0' 0'	nent markers and zones. tiled within 30 days 50-4 must be filed once
If the proposal is to deepen direction Attach the Bond under which the w following completion of the involve testing has been completed. Final A determined that the site is ready for Move satellite from Northwess located in the SW/4 SE/4 Set depicted in the SW/4 SE/4 Set depicted in the attached plat, run from each well on associ running from central satellite in a common trench and rout of previously approved trench pad being located at the NW 126 feet. An additional access additional electric from previous size of pipe below:	hally or recomplete horizontally, ork will be performed or provide ed operations. If the operation re- bhandonment Notices must be fil- final inspection. If side of well pads to a sep- ction 22, T24S, R32E betw. Boone Arch survey and S ated drill pads to central sa facility to Central Tank Bat e as approved under APD' h will be replaced with the Corner, Center of West sides so road from existing lease busly approved route of 10 <u>DOT-BUN-MM-Po20</u> is true and correct. Electronic Submission #- For APACH mmitted to AFMSS for proce	give subsurface locations and measure the Bond No. on file with BLM/BIA. sults in a multiple completion or recor- ed only after all requirements, includi parate 500' x 500' central satel veen Middle Drill Pad and East atellite Layout. All production I atellite with a common emulsio tatellite ayout. All production I atellite ayout. All production I atellite Layout. All production f atellite with a common emulsio tatellite ayout. All production f atellite with a common emulsio tatellite ayout. All production f atellite ayout. All production f atellite ayout. All production f atellite by the substance and the assing by JUANA MEDRANO on	ed and true vertic Required subse npletion in a new ng reclamation, h lite pad Drill Pad as ines will n line e laid e. Approx. 556 satellite d for approx. 72 feet and ngth and	cal depths of all pertin quent reports must be v interval, a Form 316 have been completed a 0' 0' 0' 0' 0' 0' 0' 0' 0' 0'	nent markers and zones. tiled within 30 days 50-4 must be filed once
If the proposal is to deepen direction Attach the Bond under which the w following completion of the involve testing has been completed. Final A determined that the site is ready for Move satellite from Northwess located in the SW/4 SE/4 Set depicted in the stached plat, run from each well on associ running from central satellite in a common trench and rout of previously approved trench pad being located at the NW 126 feet. An additional accet additional electric from previo size of pipe below: <u>EVEC JAC 06 (A/19</u> 14. I hereby certify that the foregoing Name(Printed/Typed) LINDA LU	hally or recomplete horizontally, ork will be performed or provide ed operations. If the operation re- boandonment Notices must be fil- final inspection. If side of well pads to a ser- ction 22, T24S, R32E betw Boone Arch survey and S ated drill pads to central sa facility to Central Tank Bat e as approved under APD' h will be replaced with the Corner, Center of West sid ss road from existing lease busly approved route of 10 <u>DCT-BUN-NM-PS20</u> is true and correct. Electronic Submission # For APACH mmitted to AFMSS for proce JCE	give subsurface locations and measure the Bond No. on file with BLM/BIA. sults in a multiple completion or recor- ed only after all requirements, includi parate 500' x 500' central satel veen Middle Drill Pad and East atellite Layout. All production I atellite with a common emulsio tatellite ayout. All production I atellite with a common emulsio tatellite ayout. All production lines will b 's from each drill pad to satellit following points of entry to the de of pad, and SE corner of pad or oad to SW Corner of pad for 1 feet. The following details ler <u>0-7019-059 w-CA</u> SH 468217 verified by the BLM Well E CORPORATION, sent to the assing by JUANA MEDRANO on Title SURFAC	ed and true vertic Required subse mpletion in a new ng reclamation, h lite pad Drill Pad as ines will n line e laid e. Approx. 550 satellite d for approx. 72 feet and ngth and <u>out which of</u> Information S 100bs 06/12/2019 (19 CE LANDMAN	cal depths of all pertin quent reports must be v interval, a Form 316 have been completed a 0' 0' 0' 0 uttate a b JM0058SE)	nent markers and zones. tiled within 30 days 50-4 must be filed once
If the proposal is to deepen direction Attach the Bond under which the w following completion of the involve testing has been completed. Final A determined that the site is ready for Move satellite from Northwess located in the SW/4 SE/4 Set depicted in the SW/4 SE/4 Set depicted in the attached plat, run from each well on associ running from central satellite in a common trench and rout of previously approved trench pad being located at the NW 126 feet. An additional access additional electric from previous size of pipe below: <u>EVEC JAC 06 (A/19</u> 14. I hereby certify that the foregoing Name (Printed/Typed) LINDA LU	hally or recomplete horizontally, ork will be performed or provide ed operations. If the operation re- boandonment Notices must be fil- final inspection. If side of well pads to a ser- ction 22, T24S, R32E betw Boone Arch survey and S ated drill pads to central sa facility to Central Tank Bat e as approved under APD' h will be replaced with the Corner, Center of West sid ss road from existing lease busly approved route of 10 <u>DCT-BUN-NM-PS20</u> is true and correct. Electronic Submission # For APACH mmitted to AFMSS for proce JCE	give subsurface locations and measure the Bond No. on file with BLM/BIA. sults in a multiple completion or recor- ed only after all requirements, includi parate 500' x 500' central satel veen Middle Drill Pad and East atellite Layout. All production I atellite with a common emulsio tatellite Jayout. All production lines will b 's from each drill pad to satellit following points of entry to the de of pad, and SE corner of pad or road to SW Corner of pad for 1 feet. The following details ler <u>0-7019-0596-209 SH</u> 468217 verified by the BLM Well IE CORPORATION, sent to the assing by JUANA MEDRANO on Title SURFAC	ed and true vertic Required subse mpletion in a new ng reclamation, h lite pad Drill Pad as ines will n line e laid e. Approx. 550 satellite d for approx. 72 feet and ngth and <u>out which of</u> Information S 100bs 06/12/2019 (19 CE LANDMAN	cal depths of all pertin quent reports must be v interval, a Form 316 have been completed a 0' 0' 0' 0 uttate a b JM0058SE)	nent markers and zones. tiled within 30 days 50-4 must be filed once
If the proposal is to deepen direction Attach the Bond under which the w following completion of the involve testing has been completed. Final A determined that the site is ready for Move satellite from Northwess located in the SW/4 SE/4 Se depicted in the SW/4 SE/4 Se depicted in the attached plat, run from each well on associ running from central satellite in a common trench and rout of previously approved trench pad being located at the NW 126 feet. An additional acce additional electric from previo size of pipe below: <u>Wed JAC 06/A/19</u> 14. I hereby certify that the foregoing Con Name (Printed/Typed) LINDA LU Signature (Electronic	hally or recomplete horizontally, ork will be performed or provide ed operations. If the operation re- shandonment Notices must be fil- final inspection. St side of well pads to a ser- ction 22, T24S, R32E betw Boone Arch survey and S ated drill pads to central sa facility to Central Tank Bat e as approved under APD' h will be replaced with the Corner, Center of West sid ss road from existing lease busly approved route of 10 <u>DOT-BUN-MM-Po20</u> is true and correct. Electronic Submission # mmitted to AFMSS for proce JCE Submission)	give subsurface locations and measure the Bond No. on file with BLM/BIA. sults in a multiple completion or recor- ed only after all requirements, includion bearate 500' x 500' central satel veen Middle Drill Pad and East inatellite Layout. All production lines inatellite with a common emulsion thery. All production lines will b is from each drill pad to satellite following points of entry to the de of pad, and SE corner of pad aroad to SW Corner of pad for 1 feet. The following details ler <u>0-7019-0596-204</u> Sta 468217 verified by the BLM Well the CORPORATION, sent to the essing by JUANA MEDRANO on Title SURFAC Date 06/08/20	ed and true vertic Required subse mpletion in a new ng reclamation, h lite pad Drill Pad as ines will n line e laid e. Approx. 550 satellite d for approx. 72 feet and ngth and <u>out which of</u> Information S 100bs 06/12/2019 (19 CE LANDMAN	cal depths of all pertin quent reports must be v interval, a Form 316 have been completed a 0' 0' 0' 0 uttate a b JM0058SE)	nent markers and zones. tiled within 30 days 50-4 must be filed once
If the proposal is to deepen direction Attach the Bond under which the w following completion of the involve testing has been completed. Final A determined that the site is ready for Move satellite from Northwess located in the SW/4 SE/4 See depicted in the SW/4 SE/4 See depicted in the attached plat, run from each well on associ running from central satellite in a common trench and rout of previously approved trench pad being located at the NW 126 feet. An additional acce additional electric from previo size of pipe below: <u>EVEL JAC 06 (M/19</u> 14. I hereby certify that the foregoing Con Name (Printed/Typed) LINDA LU Signature (Electronic	nally or recomplete horizontally, ork will be performed or provide ed operations. If the operation re- bbandonment Notices must be fil- final inspection. It side of well pads to a ser- ction 22, T24S, R32E betw Boone Arch survey and S ated drill pads to central sa facility to Central Tank Bat e as approved under APD' h will be replaced with the Corner, Center of West sid ss road from existing lease busly approved route of 10 <u>DCT-BCM-NM-PS20</u> is true and correct. Electronic Submission # For APACH mmitted to AFMSS for proce JCE Submission) THIS SPACE FO	give subsurface locations and measure the Bond No. on file with BLM/BIA. sults in a multiple completion or recor- ed only after all requirements, includi parate 500' x 500' central satel veen Middle Drill Pad and East inatellite Layout. All production lines that a common emulsion thery. All production lines will b 's from each drill pad to satellit following points of entry to the de of pad, and SE corner of pad a road to SW Corner of pad for 1 feet. The following details ler <u>0-7019-6596-EAS</u> 468217 verified by the BLM Well the CORPORATION, sent to the passing by JUANA MEDRANO on Title SURFAC Date 06/08/20 DR FEDERAL OR STATE C	ed and true vertic Required subse mpletion in a new ng reclamation, h lite pad Drill Pad as ines will n line e laid e. Approx. 550 satellite d for approx. 72 feet and ngth and <u>out which of</u> Information S 100bs 06/12/2019 (19 CE LANDMAN	cal depths of all pertin quent reports must be v interval, a Form 316 have been completed a 0' 0' 0' 0 uttate a b JM0058SE)	nent markers and zones. tiled within 30 days 50-4 must be filed once
If the proposal is to deepen direction Attach the Bond under which the w following completion of the involve testing has been completed. Final A determined that the site is ready for Move satellite from Northwess located in the SW/4 SE/4 Sec depicted in the SW/4 SE/4 Sec depicted in the attached plat, run from each well on associ running from central satellite in a common trench and rout of previously approved trench pad being located at the NW 126 feet. An additional access additional electric from previo size of pipe below: <u>EVEC JAC 06/19/19</u> 14. I hereby certify that the foregoing Con Name (Printed/Typed) LINDA LU Signature (Electronic Approved By	hally or recomplete horizontally, ork will be performed or provide ed operations. If the operation re- solution of the operation of the section of the secti	give subsurface locations and measure the Bond No. on file with BLM/BIA. sults in a multiple completion or recor- ed only after all requirements, includi operate 500' x 500' central satel veen Middle Drill Pad and East inatellite Layout. All production lines that a common emulsion thery. All production lines will b 's from each drill pad to satellit following points of entry to the de of pad, and SE corner of pad a road to SW Corner of pad for 1 feet. The following details ler <u>0-7019-0596-264</u> Sto 468217 verified by the BLM Well the CORPORATION, sent to the assing by JUANA MEDRANO on Title SURFAC Date 06/08/20 DR FEDERAL OR STATE C 	ed and true vertic Required subsee mpletion in a new ng reclamation, h Drill Pad as ines will n line e laid e. Approx. 550 satellite d for approx. 72 feet and ngth and <u>gu. (utiv) S of</u> lobbs CE LANDMAN 19 DFFICE USE	cal depths of all pertin quent reports must be v interval, a Form 316 have been completed a 0' 0' cuttamed, ystem bJM0058SE) 1	nent markers and zones. e filed within 30 days 50-4 must be filed once and the operator has begin to the operator has 0-4 must be filed once and the operator has 0-4 must be filed once and the operator has
If the proposal is to deepen direction Attach the Bond under which the w following completion of the involve testing has been completed. Final A determined that the site is ready for Move satellite from Northwess located in the SW/4 SE/4 Sed depicted in the SW/4 SE/4 Sed depicted in the attached plat, run from each well on associ running from central satellite in a common trench and rout of previously approved trench pad being located at the NW 126 feet. An additional access additional electric from previo size of pipe below: <u>EVED JAC 06 (A/19</u> 14. I hereby certify that the foregoing Con Name (Printed/Typed) LINDA LU Signature (Electronic Approved By Conditions of approval, if any, are attach ertify that the applicant holds legal or ec- which would entitle the applicant to cond Fitte 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent Instructions on page 2)	hally or recomplete horizontally, ork will be performed or provide ed operations. If the operation re- shandonment Notices must be fil- final inspection. St side of well pads to a ser- ction 22, T24S, R32E betw. Boone Arch survey and S ated drill pads to central sa facility to Central Tank Bat e as approved under APD' h will be replaced with the Corner, Center of West sid ss road from existing lease busly approved route of 10 <u>DOT-BUM-MM-Po2U</u> is true and correct. Electronic Submission # For APACH mmitted to AFMSS for proce JCE Submission) THIS SPACE FO	give subsurface locations and measure the Bond No. on file with BLM/BIA. sults in a multiple completion or recor- ed only after all requirements, includi operate 500' x 500' central satel veen Middle Drill Pad and East inatellite Layout. All production lines that a common emulsion thery. All production lines will b 's from each drill pad to satellit following points of entry to the de of pad, and SE corner of pad a road to SW Corner of pad for 1 feet. The following details ler <u>0-7019-0596-264</u> Sto 468217 verified by the BLM Well the CORPORATION, sent to the assing by JUANA MEDRANO on Title SURFAC Date 06/08/20 DR FEDERAL OR STATE C 	ed and true vertic Required subse mpletion in a new ng reclamation, h lite pad Drill Pad as ines will n line e laid e. Approx. 550 satellite d for approx. 72 feet and ngth and <u>pulutions</u> 06/12/2019 (19 2E LANDMAN 19 DFFICE USE	cal depths of all pertin quent reports must be v interval, a Form 316 have been completed a o' o' cuttamed. ystem bJM0058SE) i to any department or	nent markers and zones. e filed within 30 days 50-4 must be filed once and the operator has

Additional data for EC transaction #468217 that would not fit on the form

32. Additional remarks, continued

1 - 4000 feet 12" SDR 7 Poly Emulsion Line rated 265 psi from Satellite to Central Tank Battery 30- 4" FP 301 Flex Pipe Flowlines rated at 750 psi from West Pad to Satellite, approx. 1600 feet each

30- 4" FP 301 Flex Pipe Flowlines rated at 750 psi from Central Pad to Satellite approx. 920 feet each

30- 4" FP 302 Flex Pipe Flowlines rated at 750 psi from East Pad to Satellite approx. 950 feet each

Expand the West side of the Central Tank Battery (CTB) Pad an additional 180 feet. APD's were approved at a dimension of 320' x 525' to 500' X 525'. The skimmer tank will increase from 1,000 bbl to 3,000 bbl to handle forecasted production. Attached are plat, Boone Arch Survey, and CTB Layout.

Revisions to Operator-Submitted EC Data for Sundry Notice #468217

	Operator Submitted	BLM Revised (AFMSS)
Sundry Type:	NEWCON SR	NEWCON SR
Lease:	NMLC062269A	NMLC062269A
Agreement:		
Operator:	APACHE CORPORATION 303 VETERANS AIRPARK LANE SUITE 3000 MIDLAND, TX 79705 Ph: 432-818-1826	APACHE CORPORATION 303 VETERANS AIRPARK LANE SUITE 3000 MIDLAND, TX 79705 Ph: 432.818.1000 Fx: 432-818-1190
Admin Contact:	LINDA LUCE SURFACE LANDMAN E-Mail: linda.luce@apachecorp.com Cell: 432-813-9953 Ph: 432-818-1826	LINDA LUCE SURFACE LANDMAN E-Mail: linda.luce@apachecorp.com Cell: 432-813-9953 Ph: 432-818-1826
Tech Contact:	LINDA LUCE SURFACE LANDMAN E-Mail: linda.luce@apachecorp.com Cell: 432-813-9953 Ph: 432-818-1826	LINDA LUCE SURFACE LANDMAN E-Mail: linda.luce@apachecorp.com Cell: 432-813-9953 Ph: 432-818-1826
Location: State: County:	NM LEA COUNTY	NM LEA
Field/Pool:	TRISTE DRAW;BONESPRING	WILDCAT BONE SPRING
Well/Facility:	GHOST RIDER 22 FEDERAL COM 201H Sec 22 T24S R32E SESE 400FSL 676FEL 32.196918 N Lat, 103.656160 W Lon	GHOST RIDER 22-15 FEDERAL COM 201H Sec 22 T24S R32E SESE 400FSL 676FEL 32.196918 N Lat, 103.656166 W Lon

BLM Lease Number: NMLC062269A Company Reference: Apache Corporation Well Name & Number: Ghost Rider 22-15 Federal Com 201H

STANDARD STIPULATIONS FOR OIL AND GAS RELATED SITES

A copy of the application (Grant/Sundry Notice) and attachments, including stipulations and map, will be on location during construction. BLM personnel may request to view a copy of your permit during construction to ensure compliance with all stipulations.

The holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer, BLM.

1. The holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant and for all response costs, penalties, damages, claims, and other costs arising from the provisions of the Resource Conservation and Recovery Act (RCRA), 42 U.S.C. Chap. 82, Section 6901 et. seq., from the Comprehensive Environmental Response, Compensation and Liability Act (CERCLA), 42 U.S.C. Chap. 109, Section 9601 et. seq., and from other applicable environmental statues.

2. The holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976, as amended (15 U.S.C. 2601, et. seq.) with regard to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized by this grant. (See 40 CFR, Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR, Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation and Liability Act, Section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the Authorized Officer concurrent with the filing of the reports to the involved Federal agency or State government.

3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, et. seq. or the Resource Conservation and Recovery Act, 42 U.S.C. 6901, et. seq.) on the right-of-way (unless the release or threatened release is wholly unrelated to the right-of-way holder's activity on the right-of-way). This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

4. If, during any phase of the construction, operation, maintenance, or termination of the site or related pipeline(s), any oil or other pollutant should be discharged from site facilities, the pipeline(s) or from containers or vehicles impacting Federal lands, the control and total removal, disposal, and cleanup of such oil of other pollutant, wherever found, shall be the responsibility of the holder, regardless of fault. Upon failure of the holder to control, dispose of, or clean up such

discharge on or affecting Federal lands, or to repair all damages to Federal lands resulting therefrom, the Authorized Officer may take such measures as deemed necessary to control and cleanup the discharge and restore the area, including, where appropriate, the aquatic environment and fish and wildlife habitats, at the full expense of the holder. Such action by the Authorized Officer shall not relieve the holder of any liability or responsibility.

5. Sites shall be maintained in an orderly, sanitary condition at all times. Waste materials, both liquid and solid, shall be disposed of promptly at an appropriate, authorized waste disposal facility in accordance with all applicable State and Federal laws. "Waste" means all discarded matter including, but not limited to, human waste, trash, garbage, refuse, petroleum products, brines, chemicals, oil drums, ashes, and equipment.

6. The operator will notify the Bureau of Land Management (BLM) authorized officer and nearest Fish and Wildlife Service (FWS) Law Enforcement office within 24 hours, if the operator discovers a dead or injured federally protected species (i.e., migratory bird species, bald or golden eagle, or species listed by the FWS as threatened or endangered) in or adjacent to a pit, trench, tank, exhaust stack, or fence. (If the operator is unable to contact the FWS Law Enforcement office, the operator must contact the nearest FWS Ecological Services office.)

7. All above-ground structures not subject to safety requirements shall be painted by the holder to blend with the natural color of the landscape. The paint used shall be a color which simulates "Standard Environmental Colors" designated by the Rocky Mountain Five-State Interagency Committee. The color selected for this project is **Shale Green**, Munsell Soil Color Chart Number 5Y 4/2.

8. Any cultural and/or paleontological resource (historic or prehistoric site or object) discovered by the holder, or any person working on the holder's behalf, on public or Federal land shall be immediately reported to the Authorized Officer. The holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the " Authorized Officer. An evaluation of the discovery will be made by the Authorized Officer to determine appropriate actions to prevent the loss of significant cultural or scientific values. The holder will be responsible for the cost of evaluation and any decision as to the proper mitigation measures will be made by the Authorized Officer after consulting with the holder.

9. A sales contract for removal of mineral material (caliche, sand, gravel, fill dirt) from an authorized pit, site, or on location must be obtained from the BLM prior to commencing construction. There are several options available for purchasing mineral material: contact the BLM office (575-234-5972).

10. The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

11. Once the site is no longer in service or use, the site must undergo final abandonment. At final abandonment, the site and access roads must undergo "final" reclamation so that the character and productivity of the land are restored. Earthwork for final reclamation must be completed within six (6) months of the abandonment of the site. All pads and facility locations and roads must be reclaimed to a satisfactory revegetated, safe, and stable condition, unless an agreement is made with the landowner or BLM to keep the road and/or pad intact. After all disturbed areas have been satisfactorily prepared, these areas need to be revegetated with the seed mixture provided. Seeding should be accomplished by drilling on the contour whenever practical or by other approved methods. Seeding may need to be repeated until revegetation is successful, as determined by the BLM.

Operators shall contact a BLM surface protection specialist prior to surface abandonment operations for site specific objectives (Jim Amos: 575-234-5909).

12. The holder shall stockpile an adequate amount of topsoil where blading occurs. The topsoil to be stripped is approximately 6 inches in depth. The topsoil will be segregated from other spoil piles. The topsoil will be used for final reclamation.

13. The holder will reseed all disturbed areas. Seeding will be done according to the attached seeding requirements, using the following seed mix.

() seed mixture 1	() seed mixture 3
() seed mixture 2	() seed mixture 4
(X) seed mixture 2/LPC	() Aplomado Falcon Mixture

14. In those areas where erosion control structures are required to stabilize soil conditions, the holder shall install such structures as are suitable for the specific soil conditions being encountered and which are in accordance with sound management practices. Any earth work will require prior approval by the Authorized Officer.

15. Open-topped Tanks - The operator will take actions necessary to prevent wildlife and livestock access, including avian wildlife, to all open-topped tanks that contain or have the potential to contain salinity sufficient to cause harm to wildlife or livestock, hydrocarbons, or Resource Conservation and Recovery Act of 1976-exempt hazardous substances. At a minimum, the operator will net, screen, or cover open-topped tanks to exclude wildlife and livestock and prevent mortality. If the operator uses netting, the operator will cover and secure the open portion of the tank to prevent wildlife entry. The operator will net, screen, or cover the tanks until the operator removes the tanks from the location or the tanks no longer contain substances that could be harmful to wildlife or livestock. Use a maximum netting mesh size of 1 ½ inches. The netting must not be in contact with fluids and must not have holes or gaps

16. The operator will prevent all hazardous, poisonous, flammable, and toxic substances from coming into contact with soil and water. At a minimum, the operator will install and maintain an impervious secondary containment system for any tank or barrel containing hazardous, poisonous, flammable, or toxic substances sufficient to contain the contents of the tank or barrel and any drips, leaks, and anticipated precipitation. The operator will dispose of fluids within the containment system that do not meet applicable state or U. S. Environmental Protection Agency

livestock water standards in accordance with state law; the operator must not drain the fluids to the soil or ground. The operator will design, construct, and maintain all secondary containment systems to prevent wildlife and livestock exposure to harmful substances. At a minimum, the operator will install effective wildlife and livestock exclosure systems such as fencing, netting, expanded metal mesh, lids, and grate covers. Use a maximum netting mesh size of 1 ½ inches.

17. Open-Vent Exhaust Stack Exclosures – The operator will construct, modify, equip, and maintain all open-vent exhaust stacks on production equipment to prevent birds and bats from entering, and to discourage perching, roosting, and nesting. (Recommended exclosure structures on open-vent exhaust stacks are in the shape of a cone.) Production equipment includes, but may not be limited to, tanks, heater-treaters, separators, dehydrators, flare stacks, in-line units, and compressor mufflers.

18. Containment Structures - Proposed production facilities such as storage tanks and other vessels will have a secondary containment structure that is constructed to hold the capacity of 1.5 times the largest tank, plus freeboard to account for precipitation, unless more stringent protective requirements are deemed necessary.

19. Special Stipulations:

Rangeland Management:

Any damage to structures that provide water to livestock throughout the life of the well, caused by operations from the well site, must be immediately corrected by the operator. The operator must notify the BLM office (575-234-5972) and the private surface landowner or the grazing allotment holder if any damage occurs to structures that provide water to livestock.

Watershed Management:

Tank battery locations will be lined and bermed. A 20 mil permanent liner will be installed with a 4 oz. felt backing to prevent tears or punctures. Tank battery berms must be large enough to contain 1 ½ times the content of the largest tank or 24 hour production, whichever is greater. Automatic shut off, check valves, or similar systems will be installed for tanks to minimize the effects of catastrophic line failures used in production or drilling.

When crossing ephemeral drainages the pipeline(s) will be buried to a minimum depth of 48 inches from the top of pipe to ground level. Erosion control methods such as gabions and/or rock aprons should be placed on both up and downstream sides of the pipeline crossing. In addition, curled (weed free) wood/straw fiber wattles/logs and/or silt fences should be placed on the downstream side for sediment control during construction and maintained until soils and vegetation have stabilized. Water bars should be placed within the ROW to divert and dissipate surface runoff. A pipeline access road is not permitted to cross these ephemeral drainages. Traffic should be diverted to a preexisting route. Additional seeding may be required in floodplains and drainages to restore energy dissipating vegetation.

Prior to pipeline installation/construction a leak detection plan will be developed. The method(s) could incorporate gauges to detect pressure drops, situating valves and lines so they can be visually inspected periodically or installing electronic sensors to alarm when a leak is present. The leak

detection plan will incorporate an automatic shut off system that will be installed for proposed pipelines to minimize the effects of an undesirable event.

Any water erosion that may occur due to the construction of overhead electric line and during the life of the power line will be quickly corrected and proper measures will be taken to prevent future erosion. A power pole should not be placed in drainages, playas, wetlands, riparian areas, or floodplains and must span across the features at a distance away that would not promote further erosion.

Wildlife Management:

Timing Limitation Stipulation/Condition of Approval for Lesser Prairie-Chicken: Oil and gas activities including 3-D geophysical exploration, and drilling will not be allowed in lesser prairie-chicken habitat during the period from March 1st through June 15th annually. During that period, other activities that produce noise or involve human activity, such as the maintenance of oil and gas facilities, geophysical exploration other than 3-D operations, and pipeline, road, and well pad construction, will be allowed except between 3:00 am and 9:00 am. The 3:00 am to 9:00 am restriction will not apply to normal, around-the-clock operations, such as venting, flaring, or pumping, which do not require a human presence during this period. Additionally, no new drilling will be allowed within up to 200 meters of leks known at the time of permitting. Normal vehicle use on existing roads will not be restricted. Exhaust noise from pump jack engines must be muffled or otherwise controlled so as not to exceed 75 db measured at 30 ft. from the source of the noise.

Timing Limitation Exceptions:

The Carlsbad Field Office will publish an annual map of where the LPC timing and noise stipulations and conditions of approval (Limitations) will apply for the identified year (between March 1 and June 15) based on the latest survey information. The LPC Timing Area map will identify areas which are Habitat Areas (HA), Isolated Population Area (IPA), and Primary Population Area (PPA). The LPC Timing Area map will also have an area in red crosshatch. The red crosshatch area is the only area where an operator is required to submit a request for exception to the LPC Limitations. If an operator is operating outside the red crosshatch area, the LPC Limitations do not apply for that year and an exception to LPC Limitations is not required.

BURIED PIPELINE STIPULATIONS

A copy of the application (Grant, APD, or Sundry Notice) and attachments, including conditions of approval, survey plat and/or map, will be on location during construction. BLM personnel may request to you a copy of your permit during construction to ensure compliance with all stipulations.

Holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer:

1. The Holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant.

2. The Holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976 as amended, 15 USC 2601 et seq. (1982) with regards to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized under this right-of-way grant. (See 40 CFR Part 702-

799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation, and Liability Act, section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the authorized officer concurrent with the filing of the reports to the involved Federal agency or State government.

3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, et seq. or the Resource Conservation and Recovery Act, 42 U.S.C.6901, et seq.) on the Right-of-Way (unless the release or threatened release is wholly unrelated to the Right-of-Way holder's activity on the Right-of-Way), or resulting from the activity of the Right-of-Way holder on the Right-of-Way. This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

4. If, during any phase of the construction, operation, maintenance, or termination of the pipeline, any oil or other pollutant should be discharged from the pipeline system, impacting Federal lands, the control and total removal, disposal, and cleaning up of such oil or other pollutant, wherever found, shall be the responsibility of holder, regardless of fault. Upon failure of holder to control, dispose of, or clean up such discharge on or affecting Federal lands, or to repair all damages resulting therefrom, on the Federal lands, the Authorized Officer may take such measures as he deems necessary to control and clean up the discharge and restore the area, including where appropriate, the aquatic environment and fish and wildlife habitats, at the full expense of the holder. Such action by the Authorized Officer shall not relieve holder of any responsibility as provided herein.

5. All construction and maintenance activity will be confined to the authorized right-of-way.

6. The pipeline will be buried with a minimum cover of 36 inches between the top of the pipe and ground level.

7. The maximum allowable disturbance for construction in this right-of-way will be $\underline{30}$ feet:

- Blading of vegetation within the right-of-way will be allowed: maximum width of blading operations will not exceed <u>30</u> feet. The trench is included in this area. (*Blading is defined as the complete removal of brush and ground vegetation.*)
- Clearing of brush species within the right-of-way will be allowed: maximum width of clearing operations will not exceed <u>30</u> feet. The trench and bladed area are included in this area. (Clearing is defined as the removal of brush while leaving ground vegetation (grasses, weeds, etc.) intact. Clearing is best accomplished by holding the blade 4 to 6 inches above the ground surface.)
- The remaining area of the right-of-way (if any) shall only be disturbed by compressing the vegetation. (Compressing can be caused by vehicle tires, placement of equipment, etc.)

8. The holder shall stockpile an adequate amount of topsoil where blading is allowed. The topsoil to be stripped is approximately <u>6</u> inches in depth. The topsoil will be segregated from other spoil piles from trench construction. The topsoil will be evenly distributed over the bladed area for the preparation of seeding.

9. The holder shall minimize disturbance to existing fences and other improvements on public lands. The holder is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the owner of any improvements prior to disturbing them. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting of the fence. No permanent gates will be allowed unless approved by the Authorized Officer.

10. Vegetation, soil, and rocks left as a result of construction or maintenance activity will be randomly scattered on this right-of-way and will not be left in rows, piles, or berms, unless otherwise approved by the Authorized Officer. The entire right-of-way shall be recontoured to match the surrounding landscape. The backfilled soil shall be compacted and a 6 inch berm will be left over the ditch line to allow for settling back to grade.

11. In those areas where erosion control structures are required to stabilize soil conditions, the holder will install such structures as are suitable for the specific soil conditions being encountered and which are in accordance with sound resource management practices.

12. The holder will reseed all disturbed areas. Seeding will be done according to the attached seeding requirements, using the following seed mix.

() seed mixture 1	() seed mixture 3
() seed mixture 2	() seed mixture 4
(X) seed mixture 2/LPC	() Aplomado Falcon Mixture

13. All above-ground structures not subject to safety requirements shall be painted by the holder to blend with the natural color of the landscape. The paint used shall be color which simulates "Standard Environmental Colors" – Shale Green, Munsell Soil Color No. 5Y 4/2.

14. The pipeline will be identified by signs at the point of origin and completion of the right-of-way and at all road crossings. At a minimum, signs will state the holder's name, BLM serial number, and the product being transported. All signs and information thereon will be posted in a permanent, conspicuous manner, and will be maintained in a legible condition for the life of the pipeline.

15. The holder shall not use the pipeline route as a road for purposes other than routine maintenance as determined necessary by the Authorized Officer in consultation with the holder before maintenance begins. The holder will take whatever steps are necessary to ensure that the pipeline route is not used as a roadway. As determined necessary during the life of the pipeline, the Authorized Officer may ask the holder to construct temporary deterrence structures.

16. Any cultural and/or paleontological resources (historic or prehistoric site or object) discovered by the holder, or any person working on his behalf, on public or Federal land shall be immediately reported to the Authorized Officer. Holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery will be made by the Authorized Officer to determine appropriate actions to prevent the loss of significant cultural or scientific values. The holder will be responsible for the cost of evaluation and any decision as to proper mitigation measures will be made by the Authorized Officer after consulting with the holder.

17. The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes associated roads, pipeline corridor and adjacent land affected by the establishment of weeds due to this

action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

18. <u>Escape Ramps</u> - The operator will construct and maintain pipeline/utility trenches [that are not otherwise fenced, screened, or netted] to prevent livestock, wildlife, and humans from becoming entrapped. At a minimum, the operator will construct and maintain escape ramps, ladders, or other methods of avian and terrestrial wildlife escape in the trenches according to the following criteria:

- a. Any trench left open for eight (8) hours or less is not required to have escape ramps; however, before the trench is backfilled, the contractor/operator shall inspect the trench for wildlife, remove all trapped wildlife, and release them at least 100 yards from the trench.
- b. For trenches left open for eight (8) hours or more, earthen escape ramps (built at no more than a 30 degree slope and spaced no more than 500 feet apart) shall be placed in the trench.

STANDARD STIPULATIONS FOR OVERHEAD ELECTRIC DISTRIBUTION LINES

A copy of the grant and attachments, including stipulations, survey plat and/or map, will be on location during construction. BLM personnel may request to you a copy of your permit during construction to ensure compliance with all stipulations.

Holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer:

1. The holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant.

2. The holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976 as amended, 15 USC 2601 et seq. (1982) with regards to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized under this right-of-way grant. (See 40 CFR, Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR, Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation, and Liability Act, section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the authorized officer concurrent with the filing of the reports to the involved Federal agency or State government.

3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, et seq. or the Resource Conservation and Recovery Act, 42 U.S.C. 6901, et seq.) on the Right-of-Way (unless the release or threatened release is wholly unrelated to the Right-of-Way holder's activity on the Right-of-Way), or resulting from the activity of the Right-of-Way holder on the Right-of-Way. This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

4. There will be no clearing or blading of the right-of-way unless otherwise agreed to in writing by the Authorized Officer.

5. Power lines shall be constructed and designed in accordance to standards outlined in "Suggested Practices for Avian Protection on Power lines: The State of the Art in 2006" Edison Electric Institute, APLIC, and the California Energy Commission 2006. The holder shall assume the burden and expense of proving that pole designs not shown in the above publication deter raptor perching, roosting, and nesting. Such proof shall be provided by a raptor expert approved by the Authorized Officer. The BLM reserves the right to require modification or additions to all powerline structures placed on this right-of-way, should they be necessary to ensure the safety of large perching birds. Such modifications and/or additions shall be made by the holder without liability or expense to the United States.

Raptor deterrence will consist of but not limited to the following: triangle perch discouragers shall be placed on each side of the cross arms and a nonconductive perching deterrence shall be placed on all vertical poles that extend past the cross arms.

6. The holder shall minimize disturbance to existing fences and other improvements on public lands. The holder is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the owner of any improvements prior to disturbing them. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting the fence. No permanent gates will be allowed unless approved by the Authorized Officer.

7. The BLM serial number assigned to this authorization shall be posted in a permanent, conspicuous manner where the power line crosses roads and at all serviced facilities. Numbers will be at least two inches high and will be affixed to the pole nearest the road crossing and at the facilities served.

8. Upon cancellation, relinquishment, or expiration of this grant, the holder shall comply with those abandonment procedures as prescribed by the Authorized Officer.

9. All surface structures (poles, lines, transformers, etc.) shall be removed within 180 days of abandonment, relinquishment, or termination of use of the serviced facility or facilities or within 180 days of abandonment, relinquishment, cancellation, or expiration of this grant, whichever comes first. This will not apply where the power line extends service to an active, adjoining facility or facilities.

10. Any cultural and/or paleontological resource (historic or prehistoric site or object) discovered by the holder, or any person working on his behalf, on public or Federal land shall be immediately reported to the Authorized Officer. Holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery will be made by the Authorized Officer to determine appropriate actions to prevent the loss of significant cultural or scientific values. The holder will be responsible for the cost of evaluation and any decision as to proper mitigation measures will be made by the Authorized Officer after consulting with the holder.

- 11. Special Stipulations:
 - For reclamation remove poles, lines, transformer, etc. and dispose of properly.
 - Fill in any holes from the poles removed.

Timing Limitation Stipulation/Condition of Approval for Lesser Prairie-Chicken:

Oil and gas activities including 3-D geophysical exploration, and drilling will not be allowed in lesser prairie-chicken habitat during the period from March 1st through June 15th annually. During that period, other activities that produce noise or involve human activity, such as the maintenance of oil and gas facilities, geophysical exploration other than 3-D operations, and pipeline, road, and well pad construction, will be allowed except between 3:00 am and 9:00 am. The 3:00 am to 9:00 am restriction will not apply to normal, around-the-clock operations, such as venting, flaring, or pumping, which do not require a human presence during this period. Additionally, no new drilling will be allowed within up to 200 meters of leks known at the time of permitting. Normal vehicle use on existing roads will not be restricted. Exhaust noise from pump jack engines must be muffled or otherwise controlled so as not to exceed 75 db measured at 30 ft. from the source of the noise.

Seed Mixture for LPC Sand/Shinnery Sites

Holder shall seed all disturbed areas with the seed mixture listed below. The seed mixture shall be planted in the amounts specified in pounds of pure live seed (PLS)* per acre. There shall be <u>no</u> primary or secondary noxious weeds in the seed mixture. Seed will be tested and the viability testing of seed shall be done in accordance with State law(s) and within nine (9) months prior to purchase. Commercial seed shall be either certified or registered seed. The seed container shall be tagged in accordance with State law(s) and available for inspection by the Authorized Officer.

Seed will be planted using a drill equipped with a depth regulator to ensure proper depth of planting where drilling is possible. The seed mixture will be evenly and uniformly planted over the disturbed area (smaller/heavier seeds have a tendency to drop the bottom of the drill and are planted first). Holder shall take appropriate measures to ensure this does not occur. Where drilling is not possible, seed will be broadcast and the area shall be raked or chained to cover the seed. When broadcasting the seed, the pounds per acre are to be doubled. Seeding shall be repeated until a satisfactory stand is established as determined by the Authorized Officer. Evaluation of growth may not be made before completion of at least one full growing season after seeding.

Species to be planted in pounds of pure live seed* per acre:

Species	<u>lb/acre</u>
Plains Bristlegrass	5lbs/A
Sand Bluestem	5lbs/A
Little Bluestem	3lbs/A
Big Bluestem	6lbs/A
Plains Coreopsis	2lbs/A
Sand Dropseed	1lbs/A

*Pounds of pure live seed:

Pounds of seed x percent purity x percent germination = pounds pure live seed