

## **UNITED STATES**

SUNDRY NOTICES AND REPORTS ON WELL'S

Do not use this form for proposals to drill or to re-enter an

DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018

Lease Serial No. NMNM15091 ✔

6. If Indian, Allottee or Tribe Name

abandoned wel		such proposals	200	?		
	ns on page 2	0350	7. If Unit or CA/Agree	ment, Name and/or No.		
1. Type of Well	•	ECEN	6. Well Name and No. ROJO 7811 22 FEDERAL COM 15H			
2. Name of Operator	REDDELL	For	9. API Well No.			
BTA OIL PRODUCERS	m		30-025-45333-00-X1			
		none No. (include area code) 432-682-3753 Ext: 139		10. Field and Pool or Exploratory Area BOBCAT DRAW-UPR WOLFCAMP		
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		-		11. County or Parish, State		
Sec 22 T25S R33E SESE 220 32.109386 N Lat, 103.555794			LEA COUNTY, NM			
12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA						
TYPE OF SUBMISSION	TYPE OF ACTION					
□ Notice of Intent	☐ Acidize	Deepen	☐ Production (Start/Resume)		■ Water Shut-Off	
_	☐ Alter Casing	☐ Hydraulic Fracturing	☐ Reclam	ation	■ Well Integrity	
Subsequent Report	☐ Casing Repair	■ New Construction	☐ Recomplete		Other	
☐ Final Abandonment Notice	☐ Change Plans	<del>-</del> -		arily Abandon		
	☐ Convert to Injection	☐ Plug Back	<b>⊠</b> Water I	Disposal		
testing has been completed. Final Abdetermined that the site is ready for final Abdetermined that the site is ready for final PRODUCERS, LLC FEDERAL COM 15H.	operations. If the operation results in a pandonment Notices must be filed only a inal inspection.  RESPECTFULLY REQUESTS TO THE WATER IS UPPER WATER IS UPP	after all requiréments, includi	ing reclamation	n, have been completed a	nd the operator has	
THE AMOUNT OF WATER PRODUCED FROM THE BOBCAT DRAW UPPER WOLFCAMP IS 1,500 BBL/DAY. $m \sim$						
THE WATER IS STORED ADJACENT TO THE CENTRAL TANK BATTERY IN FOUR WATER TANKS						
THE WATER IS THEN PIPED TO THE MESQUITE VACA DRAW FED SWD #1 WELL. THE VACA DRAW FEDERAL SWD WELL NO. 1 (API 30-025-23895)IS LOCATED 657.5 FEET FROM THE SOUTH LINE AND 661.5 FEET FROM THE EAST LINE, UNIT P OF SECTION 21, TOWNSHIP 25 SOUTH AND RANGE 33 EAST, NMPM, LEA COUNTY NM.						
14. I hereby certify that the foregoing is true and correct.  Electronic Submission #469599 verified by the BLM Well Information System  For BTA OIL PRODUCERS, sent to the Hobbs  Committed to AFMSS for processing by PRISCILLA PEREZ on 06/18/2019 (19PP2239SE)  Name (Printed/Typed) KATY REDDELL  Title REGULATORY ANALYST						
				·		
Signature (Electronic S	Submission)	Date 06/18/20	- RUCE IEU FUR RECARD			
THIS SPACE FOR FEDERAL OR STATE OFFICE USE						
Approved By		Title	J	UN 2 0 2019	Date	
Conditions of approval, if any, are attache certify that the applicant holds legal or equ which would entitle the applicant to condu		BUREAU	OF LAND MANAGEM	ST. ENT		

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department of agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2) \*\*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED



## IT IS FURTHER ORDERED THAT:

The operator shall take all steps necessary to ensure that the disposed water enters only the approved disposal interval and is not permitted to escape to other formations or onto the surface. This includes the completion and construction of the well as proposed in the application, and as modified by this Order.

Within two years after commencing disposal, the operator shall conduct an injection survey, consisting of a temperature log or equivalent, over the entire injection interval using representative disposal rates. Copies of the survey results shall be provided to the Division's District I office and Santa Fe Engineering Bureau office.

After installing tubing, the casing-tubing annulus shall be loaded with an inert fluid and equipped with a pressure gauge or an approved leak detection device in order to determine leakage in the casing, tubing, or packer. The casing shall be pressure tested from the surface to the packer setting depth to assure casing integrity.

The well shall pass an initial mechanical integrity test ("MIT") prior to initially commencing disposal and prior to resuming disposal each time the disposal packer is unseated. All MIT procedures and schedules shall follow the requirements in Division Rule 19.15.26.11A. NMAC. The Division Director retains the right to require at any time wireline verification of completion and packer setting depths in this well.

The wellhead injection pressure on the well shall be limited to **no more than 3493 psi**. In addition, the disposal well or system shall be equipped with a pressure limiting device in workable condition which shall, at all times, limit surface tubing pressure to the maximum allowable pressure for this well.

The Director of the Division may authorize an increase in tubing pressure upon a proper showing by the operator of said well that such higher pressure will not result in migration of the disposed fluid from the target formation. Such proper showing shall be demonstrated by sufficient evidence including but not limited to an acceptable Step-Rate Test.

The operator shall notify the supervisor of the Division's District I office of the date and time of the installation of disposal equipment and of any MIT so that the same may be inspected and witnessed. The operator shall provide written notice of the date of commencement of disposal to the Division's District office. The operator shall submit monthly reports of the disposal operations on Division Form C-115, in accordance with Division Rules 19.15.26.13 and 19.15.7.24 NMAC.

Without limitation on the duties of the operator as provided in Division Rules 19.15.29 and 19.15.30 NMAC, or otherwise, the operator shall immediately notify the Division's District I office of any failure of the tubing, casing or packer in the well, or of any leakage or release of water, oil or gas from around any produced or plugged and abandoned well in the area, and shall take such measures as may be timely and necessary to correct such failure or leakage.

Administrative Order SWD-1571-C Mesquite SWD. Inc. February 22, 2017 Page 3 of 3

The injection authority granted under this order is not transferable except upon Division approval. The Division may require the operator to demonstrate mechanical integrity of any injection well that will be transferred prior to approving transfer of authority to inject.

The Division may revoke this injection order after notice and hearing if the operator is in violation of Rule 19.15.5.9 NMAC.

The disposal authority granted herein shall terminate two (2) years after the effective date of this Order if the operator has not commenced injection operations into the subject well. One year after the last date of reported disposal into this well, the Division shall consider the well abandoned, and the authority to dispose will terminate *ipso facto*. The Division, upon written request mailed by the operator prior to the termination date, may grant an extension thereof for good cause.

Compliance with this Order does not relieve the operator of the obligation to comply with other applicable federal, state or local laws or rules, or to exercise due care for the protection of fresh water, public health and safety and the environment.

Jurisdiction is retained by the Division for the entry of such further orders as may be necessary for the prevention of waste and/or protection of correlative rights or upon failure of the operator to conduct operations (1) to protect fresh or protectable waters or (2) consistent with the requirements in this order, whereupon the Division may, after notice and hearing, terminate the disposal authority granted herein.

DAVID R. CATANACH

Director

DRC/mam

cc: Oil Conservation Division – Hobbs District Office Bureau of Land Management – Carlsbad Well File - 30-025-23895