Submit ! Copy To Appropriate District Office	State of New Mexico	Form C-103
District I – (575) 393-6161	Energy, Minerals and Natural Resources	Revised July 18, 2013
1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> – (575) 748-1283		WELL API NO. 30-025-46032
911 C First St. Artesia NM 99210	OIL CONSERVATION DIVISION	5. Indicate Type of Lease
District III – (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 87410	BBS 2006 with St. Francis Dr.	STATE FEE
D' - ' - TT - (505) 456 0460	Santa Fe NM 87505	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM AU 87505	G 2 9 2019	325728
SUNDRY NOTICES AND REPORTS ON WELLS		7. Lease Name or Unit Agreement Name
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPONED TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR YELL" (FORM C-101) FOR SUCH		ADDER 31 STATE
PROPOSALS.) 1. Type of Well: Oil Well Gas	Well 🔲 Other	8. Well Number 504H
2. Name of Operator EOG RESOURCES		9. OGRID Number 7377
3. Address of Operator		10. Pool name or Wildcat
<u>-</u>	7, MIDLAND TX 79702	97964 WC-025 G-07 S243225C; LWR BONE SPRIN
4. Well Location		
Unit Letter O : 311	feet from the SOUTH line and 19	63feet from the EASTline
Section 31	Township 24S Range 33E	NMPM County LEA
11.	Elevation (Show whether DR, RKB, RT, GR, etc.)
	3502 GL	
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data		
12. Check Appropriate Box to indicate Nature of Notice, Report of Other Data		
NOTICE OF INTER	NTION TO: SUB	SEQUENT REPORT OF:
	UG AND ABANDON 🔲 REMEDIAL WOR	
	ANGE PLANS COMMENCE DR	
	ILTIPLE COMPL	T JOB 🗵
DOWNHOLE COMMINGLE CLOSED-LOOP SYSTEM		
OTHER:	OTHER: DRII	L CSG 🔀
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date		
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of		
proposed completion or recompletion.		
08/07/19 CONDUCTOR 20" @ 120' 🔑		
08/17/19 17-1/2" HOLE		
08/17/19 Surface Casing @ 1,213'		
Ran 13-3/8" 54.5# J-55 STC		
Lead Cement w/ 885 sx Class C (1.79 yld, 13.5 ppg), Trail w/190 sx Class C (1.34 yld, 14.8 ppg) Test casing to 1,500 psi for 30 min - good Circ 615 sx cement to surface Resume drilling 12-1/4" hole		
rest casing to 1,000 psi for 50 min 9 good One 615 sx certient to surface resultie drilling 12-1/4 fible		
•		
•		
08/00/20		
Spud Date: 08/16/19	Rig Release Date:	
I hereby certify that the information abov	is true and complete to the best of my knowledg	ge and belief.
\mathcal{I}		•
SIGNATURE (UN)	TITLE Sr. Regulatory Admin	istrator DATE 08/27/19
()	/	
Type or print name Emily Follis	E-mail address: emily_follis@e	eogresources.comONE: 432-848-9163
For State Use Only	_	/ /
APPROVED BY:	TITLE	DATE 09/06/19
Conditions of Approval (if any):		