

Submit 1 Copy To Appropriate District
Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-025-44072

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

319585

7. Lease Name or Unit Agreement Name

DATE 14 STATE COM

8. Well Number

#602H

9. OGRID Number

7377

10. Pool name or Wildcat

5535 BERRY; BONE SPRING, NORTH

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

EOG RESOURCES

3. Address of Operator

P O BOX 2267, MIDLAND TX 79702

4. Well Location

Unit Letter O 230 feet from the SOUTH line and 1370 feet from the EAST line
Section 14 Township 21S Range 33E NMPM County LEA CO., NM

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3786 GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

DOWNHOLE COMMINGLE ☐

CLOSED-LOOP SYSTEM ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ P AND A ☐

CASING/CEMENT JOB ☒

OTHER: DRILL CSG ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

06/14/19 20" Conductor @115'

08/26/19 Surface Casing @ 1,976'

Ran 13-3/8" 54.5# J-55 STC

Lead Cement w/ 1,400 sx Class C (1.76 yld, 13.5 ppg), Trail w/265 sx Class C (1.36 yld, 14.8 ppg)

Test casing to 1,500 psi for 30 min - Good. Circ 765 sx cement to surface Resume Drilling 12-1/4" hole

Spud Date:

06/14/19
08/26/19

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE Sr. Regulatory Administrator

DATE 08/28/19

Type or print name Emily Follis

E-mail address: emily_follis@eogresources.com PHONE: 432-848-9163

For State Use Only

APPROVED BY:

TITLE

Petroleum Engineer

DATE

09/17/19

Conditions of Approval (if any):

Responsible Engineer