

HOBBS OCD  
OCT 08 2019

FORM APPROVED  
OMB No. 1004-0137  
Expires: January 31, 2018

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
**APPLICATION FOR PERMIT TO DRILL OR REENTER**

1a. Type of work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		5. Lease Serial No. NMLC0061374A
1b. Type of Well: <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other		6. If Indian, Allottee or Tribe Name
1c. Type of Completion: <input type="checkbox"/> Hydraulic Fracturing <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		7. If Unit or CA Agreement, Name and No. BELL LAKE / NMNM068292X
2. Name of Operator KAISER FRANCIS OIL COMPANY (12361)		8. Lease Name and Well No. BELL LAKE UNIT SOUTH 213H (716706)
3a. Address 6733 S. Yale Ave. Tulsa OK 74121	3b. Phone No. (include area code) (918)491-0000	9. API Well No. 30-025 46421 (98264)
4. Location of Well (Report location clearly and in accordance with any State requirements. *) At surface SENE / 2276 FNL / 307 FEL / LAT 32.2475812 / LONG -103.5015434 At proposed prod. zone SWSW / 330 FSL / 350 FWL / LAT 32.2257374 / LONG -103.4993642		10. Field and Pool, or Exploratory BELL LAKE SOUTH / BONE SPRING
11. Sec., T. R. M. or Blk. and Survey or Area SEC 6 / T24S / R34E / NMP		
14. Distance in miles and direction from nearest town or post office* 20 miles		12. County or Parish LEA
13. State NM		
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) 307 feet	16. No of acres in lease 440	17. Spacing Unit dedicated to this well 480
18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. 30 feet	19. Proposed Depth 10862 feet / 18735 feet	20. BLM/BIA Bond No. in file FED: WYB000055
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 3597 feet	22. Approximate date work will start* 06/01/2019	23. Estimated duration 40 days
24. Attachments		

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, and the Hydraulic Fracturing rule per 43 CFR 3162.3-3 (as applicable)

- |  |   |
|--|---|
| 1. Well plat certified by a registered surveyor.   | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above). |
| 2. A Drilling Plan.  | 5. Operator certification.  |
| 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office). | 6. Such other site specific information and/or plans as may be requested by the BLM.            |

25. Signature (Electronic Submission)	Name (Printed/Typed) Stormi Davis / Ph: (575)308-3765	Date 02/21/2019
Title Regulatory Analyst		
Approved by (Signature) (Electronic Submission)	Name (Printed/Typed) Christopher Walls / Ph: (575)234-2234	Date 07/09/2019
Title Petroleum Engineer		

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Reg GCP 10/10/19

**APPROVED WITH CONDITIONS**  
Approval Date: 07/09/2019

K2  
10/10/19

## INSTRUCTIONS

**GENERAL:** This form is designed for submitting proposals to perform certain well operations, as indicated on Federal and Indian lands and leases for action by appropriate Federal agencies, pursuant to applicable Federal laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from local Federal offices.

**ITEM I:** If the proposal is to redrill to the same reservoir at a different subsurface location or to a new reservoir, use this form with appropriate notations. Consult applicable Federal regulations concerning subsequent work proposals or reports on the well.

**ITEM 4:** Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local Federal offices for specific instructions.

**ITEM 14:** Needed only when location of well cannot readily be found by road from the land or lease description. A plat, or plats, separate or on the reverse side, showing the roads to, and the surveyed location of, the well, and any other required information, should be furnished when required by Federal agency offices.

**ITEMS 15 AND 18:** If well is to be, or has been directionally drilled, give distances for subsurface location of hole in any present or objective productive zone.

**ITEM 22:** Consult applicable Federal regulations, or appropriate officials, concerning approval of the proposal before operations are started.

**ITEM 24:** If the proposal will involve hydraulic fracturing operations, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

## NOTICES

The Privacy Act of 1974 and regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

**AUTHORITY:** 30 U.S.C. 181 et seq., 25 U.S.C. 396; 43 CFR 3160

**PRINCIPAL PURPOSES:** The information will be used to: (1) process and evaluate your application for a permit to drill a new oil, gas, or service well or to reenter a plugged and abandoned well; and (2) document, for administrative use, information for the management, disposal and use of National Resource Lands and resources including (a) analyzing your proposal to discover and extract the Federal or Indian resources encountered; (b) reviewing procedures and equipment and the projected impact on the land involved; and (c) evaluating the effects of the proposed operation on the surface and subsurface water and other environmental impacts.

**ROUTINE USE:** Information from the record and/or the record will be transferred to appropriate Federal, State, and local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecution, in connection with congressional inquiries and for regulatory responsibilities.

**EFFECT OF NOT PROVIDING INFORMATION:** Filing of this application and disclosure of the information is mandatory only if you elect to initiate a drilling or reentry operation on an oil and gas lease.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM connects this information to an evaluation of the technical, safety, and environmental factors involved with drilling for oil and/or gas on Federal and Indian oil and gas leases. This information will be used to analyze and approve applications. Response to this request is mandatory only if the operator elects to initiate drilling or reentry operations on an oil and gas lease. The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

**BURDEN HOURS STATEMENT:** Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Connection Clearance Officer (WO-630), 1849 C Street, N.W., Mail Stop 401 LS, Washington, D.C. 20240.

## Additional Operator Remarks

### Location of Well

- I. SHL: SENE / 2276 FNL / 307 FEL / TWSP: 24S / RANGE: 34E / SECTION: 6 / LAT: 32.2475812 / LONG: -103.5015434 ( TVD: 0 feet, MD: 0 feet )  
PPP: NWSW / 2600 FSL / 470 FWL / TWSP: 24S / RANGE: 34E / SECTION: 5 / LAT: 32.2464816 / LONG: -103.4990262 ( TVD: 10862 feet, MD: 11188 feet )  
PPP: SWNW / 1320 FNL / 447 FWL / TWSP: 24S / RANGE: 34E / SECTION: 8 / LAT: 32.2357063 / LONG: -103.4992005 ( TVD: 10862 feet, MD: 15100 feet )  
PPP: NWSW / 2640 FNL / 365 FWL / TWSP: 24S / RANGE: 34E / SECTION: 8 / LAT: 32.2320783 / LONG: -103.4992596 ( TVD: 10862 feet, MD: 16400 feet )  
BHL: SWSW / 330 FSL / 350 FWL / TWSP: 24S / RANGE: 34E / SECTION: 8 / LAT: 32.2257374 / LONG: -103.4993642 ( TVD: 10862 feet, MD: 18735 feet )

### BLM Point of Contact

Name: Tanja Baca  
Title: Admin Support Assistant  
Phone: 5752345940  
Email: tabaca@blm.gov

CONFIDENTIAL

### **Review and Appeal Rights**

A person contesting a decision shall request a State Director review. This request must be filed within 20 working days of receipt of the Notice with the appropriate State Director (see 43 CFR 3165.3). The State Director review decision may be appealed to the Interior Board of Land Appeals, 801 North Quincy Street, Suite 300, Arlington, VA 22203 (see 43 CFR 3165.4). Contact the above listed Bureau of Land Management office for further information.

**CONFIDENTIAL**

# PECOS DISTRICT DRILLING OPERATIONS CONDITIONS OF APPROVAL

OPERATOR'S NAME:	Kaiser Francis Oil Company
LEASE NO.:	NMNM0061374A
WELL NAME & NO.:	Bell Lake Unit South 213H
SURFACE HOLE FOOTAGE:	2276'/N & 307'/E
BOTTOM HOLE FOOTAGE:	330'/S & 350'/W
LOCATION:	Section 6, T.24 S., R.34 E., NMPM
COUNTY:	Lea County, New Mexico

H2S	<input type="radio"/> Yes	<input checked="" type="radio"/> No	
Potash	<input checked="" type="radio"/> None	<input type="radio"/> Secretary	<input type="radio"/> R-111-P
Cave/Karst Potential	<input checked="" type="radio"/> Low	<input type="radio"/> Medium	<input type="radio"/> High
Variance	<input type="radio"/> None	<input checked="" type="radio"/> Flex Hose	<input type="radio"/> Other
Wellhead	<input checked="" type="radio"/> Conventional	<input type="radio"/> Multibowl	<input type="radio"/> Both
Other	<input type="checkbox"/> 4 String Area	<input type="checkbox"/> Capitan Reef	<input type="checkbox"/> WIPP
Other	<input type="checkbox"/> Fluid Filled	<input type="checkbox"/> Cement Squeeze	<input type="checkbox"/> Pilot Hole
Special Requirements	<input type="checkbox"/> Water Disposal	<input type="checkbox"/> COM	<input checked="" type="checkbox"/> Unit

## A. HYDROGEN SULFIDE

1. Hydrogen Sulfide (H2S) monitors shall be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the Hydrogen Sulfide area shall meet Onshore Order 6 requirements, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, provide measured values and formations to the BLM.

## B. CASING

1. The 13-3/8" surface casing shall be set at approximately 1350' (a minimum of 25' into the Rustler Anhydrite and above the salt) and cemented to surface.
  - a. **If cement does not circulate to surface**, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of **6 hours** after pumping cement, ideally between 8-10 hours after completing the cement job.
  - b. WOC time for a primary cement job will be a minimum of **8 hours** or **500 psi** compressive strength, whichever is greater. This is to include the lead cement.
  - c. If cement falls back, remedial cementing will be done prior to drilling out that string.
  - d. WOC time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 psi compressive strength, whichever is greater.

2. The 9-5/8" intermediate casing shall cemented to surface.
  - a. If cement does not circulate to surface, see B.1.a, b & d.
3. The 5-1/2" production casing shall be cemented with 200 feet tie back into the previous casing. Operator shall provide method of verification.

**C. PRESSURE CONTROL**

1. Variance approved to use flex line from BOP to choke manifold. Manufacturer's specification to be readily available. No external damage to flex line. Flex line to be installed as straight as possible (no hard bends).
2. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **5000 (5M)** psi.

**D. SPECIAL REQUIREMENTS**

1. The well sign for a unit well shall include the unit number in addition to the surface and bottom hole lease numbers. This also applies to participating area numbers. If a participating area has not been established, the operator can use the general unit designation, but will replace the unit number with the participating area number once it has been established.
2. A commercial well determination shall be submitted after production has been established for at least six months.

**DR 5/23/2019**

## GENERAL REQUIREMENTS

1. The BLM is to be notified in advance for a representative to witness:
  - a. Spudding well (minimum of 24 hours)
  - b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
  - c. BOPE tests (minimum of 4 hours)
    - ☒ Chaves and Roosevelt Counties  
Call the Roswell Field Office, 2909 West Second St., Roswell NM 88201.  
During office hours call (575) 627-0272.  
After office hours call (575)
    - ☒ Eddy County  
Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220,  
(575) 361-2822
    - ☒ Lea County  
Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240, (575)  
393-3612
2. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
  - a. In the event the operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).
  - b. When the operator proposes to set surface casing with Spudder Rig
    - Notify the BLM when moving in and removing the Spudder Rig.
    - Notify the BLM when moving in the 2<sup>nd</sup> Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
    - BOP/BOPE test to be conducted per Onshore Oil and Gas Order No. 2 as soon as 2nd Rig is rigged up on well.
3. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.
4. The record of the drilling rate along with the GR/N well log (one log per well pad is acceptable) run from TD to surface (horizontal well – vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.

## A. CASING

1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.
2. Wait on cement (WOC) for Potash Areas: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends, 2) until cement has been in place at least 24 hours. WOC time will be recorded in the driller's log. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
3. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.
6. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.
7. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.
8. Whenever a casing string is cemented in the R-111-P potash area, the NMOCD requirements shall be followed.



## **B. PRESSURE CONTROL**

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.
2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: The flex line must meet the requirements of API 16C. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.
3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:
  - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
  - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
  - c. Manufacturer representative shall install the test plug for the initial BOP test.
  - d. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
  - e. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.
5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
  - a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead when specified), whichever is greater. However, if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).

- b. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the plug. However, **no tests** shall commence until the cement has had a minimum of 24 hours setup time, except the casing pressure test can be initiated immediately after bumping the plug (only applies to single stage cement jobs).
- c. The tests shall be done by an independent service company utilizing a test plug. The results of the test shall be reported to the appropriate BLM office.
- d. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
- e. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
- f. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes. This test shall be performed prior to the test at full stack pressure.
- g. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per Onshore Order No. 2.

#### **C. DRILLING MUD**

- 1. Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

#### **D. WASTE MATERIAL AND FLUIDS**

- 2. All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.
- 3. Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.



U.S. Department of the Interior  
BUREAU OF LAND MANAGEMENT

## APD Print Report

08/20/2019

APD ID: 10400039280

Submission Date: 02/21/2019

Highlighted data  
reflects the most  
recent changes

Operator Name: KAISER FRANCIS OIL COMPANY

Federal/Indian APD: FED

Well Name: BELL LAKE UNIT SOUTH

Well Number: 213H

[Show Final Text](#)

Well Type: OIL WELL

Well Work Type: Drill

### Application

#### Section 1 - General

APD ID: 10400039280

Tie to previous NOS?

Submission Date: 02/21/2019

BLM Office: CARLSBAD

User: Stormi Davis

Title: Regulatory Analyst

Federal/Indian APD: FED

Is the first lease penetrated for production Federal or Indian? FED

Lease number: NMLC0061374A

Lease Acres: 440

Surface access agreement in place?

Allotted?

Reservation:

Agreement in place? YES

Federal or Indian agreement: FEDERAL

Agreement number: NMNM068292X

Agreement name:

Keep application confidential? YES

Permitting Agent? NO

APD Operator: KAISER FRANCIS OIL COMPANY

Operator letter of designation:

#### Operator Info

Operator Organization Name: KAISER FRANCIS OIL COMPANY

Operator Address: 6733 S. Yale Ave.

Zip: 74121

Operator PO Box: PO Box 21468

Operator City: Tulsa

State: OK

Operator Phone: (918)491-0000

Operator Internet Address:

#### Section 2 - Well Information

Well in Master Development Plan? NO

Master Development Plan name:

Well in Master SUPO? NO

Master SUPO name:

Well in Master Drilling Plan? NO

Master Drilling Plan name:

Approval Date: 07/09/2019

Page 1 of 23

**Operator Name:** KAISER FRANCIS OIL COMPANY

**Well Name:** BELL LAKE UNIT SOUTH

**Well Number:** 213H

**Well Name:** BELL LAKE UNIT SOUTH

**Well Number:** 213H

**Well API Number:**

**Field/Pool or Exploratory?** Field and Pool

**Field Name:** BELL LAKE SOUTH **Pool Name:** BONE SPRING

**Is the proposed well in an area containing other mineral resources?** NONE

**Describe other minerals:**

**Is the proposed well in a Helium production area?** N

**Use Existing Well Pad?** NO

**New surface disturbance?**

**Type of Well Pad:** MULTIPLE WELL

**Multiple Well Pad Name:**

**Number:** 10

**Well Class:** HORIZONTAL

**SOUTH BELL LAKE UNIT**

**Number of Legs:** 1

**Well Work Type:** Drill

**Well Type:** OIL WELL

**Describe Well Type:**

**Well sub-Type:** EXPLORATORY (WILDCAT)

**Describe sub-type:**

**Distance to town:** 20 Miles

**Distance to nearest well:** 30 FT

**Distance to lease line:** 307 FT

**Reservoir well spacing assigned acres Measurement:** 480 Acres

**Well plat:** BLUS\_213H\_C102\_20190220151255.pdf

BLUS\_213H\_Pymt\_Rec\_20190221084654.pdf

**Well work start Date:** 06/01/2019

**Duration:** 40 DAYS

### Section 3 - Well Location Table

**Survey Type:** RECTANGULAR

**Describe Survey Type:**

**Datum:** NAD83

**Vertical Datum:** NAVD88

**Survey number:** 6744

**Reference Datum:**

	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	MD	TVD
SHL Leg #1	227 6	FNL	307	FEL	24S	34E	6	Aliquot SENE	32.24758 12	- 103.5015 434	LEA	NEW MEXI CO	NEW MEXI CO	S	STATE	359 7	0	0
KOP Leg #1	219 3	FNL	477	FWL	24S	34E	5	Aliquot SWN W	32.24779 3	- 103.4990 04	LEA	NEW MEXI CO	NEW MEXI CO	F	NMLC0 061374 A	- 678 8	104 38	103 85

**Operator Name:** KAISER FRANCIS OIL COMPANY

**Well Name:** BELL LAKE UNIT SOUTH

**Well Number:** 213H

	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	MD	TVD
PPP Leg #1	2600	FSL	470	FWL	24S	34E	5	Aliquot NWS W	32.2464816	-103.4990262	LEA	NEW MEXI CO	NEW MEXI CO	F	NMLC0061374A	-7265	11188	10862
PPP Leg #1	1320	FNL	447	FWL	24S	34E	8	Aliquot SWN W	32.2357063	-103.4992005	LEA	NEW MEXI CO	NEW MEXI CO	F	NMNM100594	-7265	15100	10862
PPP Leg #1	2640	FNL	365	FWL	24S	34E	8	Aliquot NWS W	32.2320783	-103.4992596	LEA	NEW MEXI CO	NEW MEXI CO	F	NMLC0069109	-7265	16400	10862
EXIT Leg #1	330	FSL	350	FWL	24S	34E	8	Aliquot SWS W	32.2257374	-103.4993642	LEA	NEW MEXI CO	NEW MEXI CO	F	NMLC0069109	-7265	18735	10862
BHL Leg #1	330	FSL	350	FWL	24S	34E	8	Aliquot SWS W	32.2257374	-103.4993642	LEA	NEW MEXI CO	NEW MEXI CQ	F	NMLC0069109	-7265	18735	10862

### Drilling Plan

#### Section 1 - Geologic Formations

Formation ID	Formation Name	Elevation	True Vertical Depth	Measured Depth	Lithologies	Mineral Resources	Producing Formation
1	—	3597	0	0		NONE	N
2	RUSTLER	2197	1400	1400		NONE	N
3	SALADO	1797	1800	1800		NONE	N
4	TOP SALT	1472	2125	2125		NONE	N
5	BASE OF SALT	-1503	5100	5100		NONE	N
6	LAMAR	-1678	5275	5275		NATURAL GAS,OIL	N
7	BELL CANYON	-1753	5350	5350		NATURAL GAS,OIL	N
8	CHERRY CANYON	-2628	6225	6225		NATURAL GAS,OIL	N
9	BRUSHY CANYON	-4103	7700	7700		NATURAL GAS,OIL	N

Approval Date: 07/09/2019

Page 3 of 23

**Operator Name:** KAISER FRANCIS OIL COMPANY

**Well Name:** BELL LAKE UNIT SOUTH

**Well Number:** 213H

Formation ID	Formation Name	Elevation	True Vertical Depth	Measured Depth	Lithologies	Mineral Resources	Producing Formation
10	BONE SPRING	-5203	8800	8800		NATURAL GAS,OIL	N
11	AVALON SAND	-5376	8973	8973		NATURAL GAS,OIL	N
12	BONE SPRING 1ST	-6303	9900	9900		NATURAL GAS,OIL	N
13	BONE SPRING 2ND	-6877	10485	10485		NATURAL GAS,OIL	Y
14	BONE SPRING LIME	-7363	10960	10960		NATURAL GAS,OIL	N
15	BONE SPRING 3RD	-7673	11270	11270		NATURAL GAS,OIL	N
16	WOLFCAMP	-7778	11375	11375		NATURAL GAS,OIL	N

## Section 2 - Blowout Prevention

**Pressure Rating (PSI):** 5M

**Rating Depth:** 18000

**Equipment:** A 10M system will be installed according to Onshore Order #2 consisting of an Annular Preventer, BOP with two rams and a blind ram. BOP will be equipped with 2 side outlets (choke side shall be a minimum 3" line, and kill side will be a minimum 2" line). Kill line will be installed with (2) valves and a check valve (2" min) of proper pressure rating for the system. Remote kill line (2' min) will be installed and ran to the outer edge of the substructure and be unobstructed. A manual and hydraulic valve (3" min) will be installed on the choke line, 3 chokes will be used with one being remotely controlled. Fill up line will be installed above the uppermost preventer. Pressure gauge of proper pressure rating will be installed on choke manifold. Upper and lower kelly cocks will be utilized with handles readily available in plain sight. A float sub will be available at all times. All connections subject to well pressure will be flanged, welded, or clamped.

**Requesting Variance?** YES

**Variance request:** Flex Hose Variance

**Testing Procedure:** BOP/BOPE will be tested by an independent service company to 250 psi low and the high pressure indicated above per Onshore Order 2 requirements. The System may be upgraded to a higher pressure but still tested to the working pressure listed in the table above. If the system is upgraded all of the components installed will be functional and tested.

**Choke Diagram Attachment:**

BLUS\_213H\_Choke\_Manifold\_20190220135316.pdf

**BOP Diagram Attachment:**

BLUS\_213H\_Wellhead\_Diagram\_20190220135508.pdf

BLUS\_213H\_BOP\_20190220135511.pdf

BLUS\_213H\_FlexHose\_Data\_20190220135513.pdf

Operator Name: KAISER FRANCIS OIL COMPANY

Well Name: BELL LAKE UNIT SOUTH

Well Number: 213H

### Section 3 - Casing

Casing ID	String Type	Hole Size	Csg Size	Condition	Standard	Tapered String	Top Set MD	Bottom Set MD	Top Set TVD	Bottom Set TVD	Top Set MSL	Bottom Set MSL	Calculated casing length MD	Grade	Weight	Joint Type	Collapse SF	Burst SF	Joint SF Type	Joint SF	Body SF Type	Body SF
1	SURFACE	17.5	13.375	NEW	API	N	0	1350	0	1350			1350	J-55	54.5	ST&C	1.8	4.3	DRY	12.4	DRY	11
2	INTERMEDIATE	12.25	9.625	NEW	API	N	0	5200	0	5200			5200	HCP-110	40	LT&C	1.8	3.3	DRY	6.1	DRY	6
3	PRODUCTION	8.75	5.5	NEW	API	N	0	18735	0	10862			18735	P-110	20	OTHER - GBCD	2.2	2.5	DRY	3	DRY	3

#### Casing Attachments

Casing ID: 1 String Type: SURFACE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

BLUS\_213H\_Casing\_Assumptions\_20190220135717.pdf

**Operator Name:** KAISER FRANCIS OIL COMPANY

**Well Name:** BELL LAKE UNIT SOUTH

**Well Number:** 213H

#### Casing Attachments

**Casing ID:** 2      **String Type:** INTERMEDIATE

**Inspection Document:**

**Spec Document:**

**Tapered String Spec:**

**Casing Design Assumptions and Worksheet(s):**

BLUS\_213H\_Casing\_Assumptions\_20190220135728.pdf

**Casing ID:** 3      **String Type:** PRODUCTION

**Inspection Document:**

**Spec Document:**

**Tapered String Spec:**

**Casing Design Assumptions and Worksheet(s):**

BLUS\_213H\_Casing\_Assumptions\_20190220135737.pdf

BLUS\_213H\_5.5\_P110\_GBCD\_20190220135749.pdf

#### Section 4 - Cement

String Type	Lead/Tail	Stage Tool Depth	Top MD	Bottom MD	Quantity(sx)	Yield	Density	Cu Ft	Excess%	Cement type	Additives
SURFACE	Lead		0	1350	730	1.75	13.5	1275	75	Halcem	4% Bentonite
SURFACE	Tail		0	1350	300	1.33	14.8	400	75	Halcem	Poly Flake
INTERMEDIATE	Lead		0	5200	1000	2.09	12.5	2089	75	Econocem	KolSeal



**Operator Name:** KAISER FRANCIS OIL COMPANY

**Well Name:** BELL LAKE UNIT SOUTH

**Well Number:** 213H

String Type	Lead/Tail	Stage Tool Depth	Top MD	Bottom MD	Quantity(sx)	Yield	Density	Cu Ft	Excess%	Cement type	Additives
INTERMEDIATE	Tail		0	5200	380	1.33	14.8	506	75	Halcem	none
PRODUCTION	Lead		4000	1873 5	228	3.49	10.5	795	10	Class H	KolSeal
PRODUCTION	Tail		4000	1873 5	2698	1.22	14.5	3300	10	Class H	none

### Section 5 - Circulating Medium

**Mud System Type:** Closed

**Will an air or gas system be Used?** NO

**Description of the equipment for the circulating system in accordance with Onshore Order #2:**

**Diagram of the equipment for the circulating system in accordance with Onshore Order #2:**

**Describe what will be on location to control well or mitigate other conditions:** Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times

**Describe the mud monitoring system utilized:** PVT/Pason/Visual Monitoring

### Circulating Medium Table

Top Depth	Bottom Depth	Mud Type	Min Weight (lbs/gal)	Max Weight (lbs/gal)	Density (lbs/cu ft)	Gel Strength (lbs/100 sqft)	PH	Viscosity (CP)	Salinity (ppm)	Filtration (cc)	Additional Characteristics
5200	1873 5	OIL-BASED MUD	8.7	8.9							
1350	5200	OIL-BASED MUD	8.7	8.9							
0	1350	OTHER : Fresh Water	8.4	9							

**Operator Name:** KAISER FRANCIS OIL COMPANY

**Well Name:** BELL LAKE UNIT SOUTH

**Well Number:** 213H

### Section 6 - Test, Logging, Coring

**List of production tests including testing procedures, equipment and safety measures:**

Top of cement on production casing will be determined by calculation.

**List of open and cased hole logs run in the well:**

GR,MUDLOG

**Coring operation description for the well:**

None planned

### Section 7 - Pressure

**Anticipated Bottom Hole Pressure:** 5045

**Anticipated Surface Pressure:** 2655.36

**Anticipated Bottom Hole Temperature(F):** 165

**Anticipated abnormal pressures, temperatures, or potential geologic hazards?** NO

**Describe:**

**Contingency Plans geohazards description:**

**Contingency Plans geohazards attachment:**

**Hydrogen Sulfide drilling operations plan required?** YES

**Hydrogen sulfide drilling operations plan:**

BLUS\_213H\_H2S\_Contingency\_Plan\_20190220140413.pdf

### Section 8 - Other Information

**Proposed horizontal/directional/multi-lateral plan submission:**

BLUS\_213H\_\_Well\_Plan\_v1\_20190220140516.pdf

**Other proposed operations facets description:**

Gas Capture Plan attached

**Other proposed operations facets attachment:**

BLUS\_213H\_GCP\_20190220140528.pdf

**Other Variance attachment:**

SUPO

**Operator Name:** KAISER FRANCIS OIL COMPANY

**Well Name:** BELL LAKE UNIT SOUTH

**Well Number:** 213H

### Section 1 - Existing Roads

**Will existing roads be used?** YES

**Existing Road Map:**

BLUS\_213H\_Existing\_Roads\_20190220140713.pdf

**Existing Road Purpose:** ACCESS,FLUID TRANSPORT

**Row(s) Exist?** NO

**ROW ID(s)**

**ID:**

**Do the existing roads need to be improved?** NO

**Existing Road Improvement Description:**

**Existing Road Improvement Attachment:**

### Section 2 - New or Reconstructed Access Roads

**Will new roads be needed?** YES

**New Road Map:**

BLUS\_213H\_Access\_Roads\_20190220140937.pdf

**New road type:** RESOURCE

**Length:** 765

**Feet**

**Width (ft.):** 25

**Max slope (%):** 2

**Max grade (%):** 2

**Army Corp of Engineers (ACOE) permit required?** NO

**ACOE Permit Number(s):**

**New road travel width:** 15

**New road access erosion control:** Road construction requirements and regular maintenance would alleviate potential impacts to the access road from water erosion damage.

**New road access plan or profile prepared?** NO

**New road access plan attachment:**

**Access road engineering design?** NO

**Access road engineering design attachment:**

**Turnout?** N

**Access surfacing type:** OTHER

**Operator Name:** KAISER FRANCIS OIL COMPANY

**Well Name:** BELL LAKE UNIT SOUTH

**Well Number:** 213H

**Access topsoil source:** BOTH

**Access surfacing type description:** Native caliche

**Access onsite topsoil source depth:** 6

**Offsite topsoil source description:** Material will be obtained from BLM caliche pit in SWSW Section 22-T24S-R34E or NENE Section 20-T23S-R33E

**Onsite topsoil removal process:** The top 6 inches of topsoil is pushed off and stockpiled along the side of the location. An approximate 160' X 160' area is used within the proposed well site to remove caliche. Subsoil is removed and stockpiled within the pad site to build the location and road. Then subsoil is pushed back in the hole and caliche is spread accordingly across proposed access road.

**Access other construction information:**

**Access miscellaneous information:**

**Number of access turnouts:**

**Access turnout map:**

### Drainage Control

**New road drainage crossing:** OTHER

**Drainage Control comments:** Proposed access road will be crowned and ditched and constructed of 6 inch rolled and compacted caliche. Water will be diverted where necessary to avoid ponding, maintain good drainage, and to be consistent with local drainage patterns.

**Road Drainage Control Structures (DCS) description:** The ditches will be 3' wide with 3:1 slopes

**Road Drainage Control Structures (DCS) attachment:**

### Access Additional Attachments

**Additional Attachment(s):**

### Section 3 - Location of Existing Wells

**Existing Wells Map?** YES

**Attach Well map:**

BLUS\_213H\_1\_Mile\_Wells\_20190220141745.pdf

**Existing Wells description:**

### Section 4 - Location of Existing and/or Proposed Production Facilities

**Submit or defer a Proposed Production Facilities plan?** DEFER

**Estimated Production Facilities description:** Production facilities are planned for the east side of pad. Plan for initial wells: 2-1000 bbl water tanks and 5-1000 bbl oil tanks, a temporary 6X20 horizontal 3-phase sep, a 48" X 10' 3-phase sep, a 8 X 20' heater treater and a 48"X 10' 2-phase sep

**Operator Name:** KAISER FRANCIS OIL COMPANY

**Well Name:** BELL LAKE UNIT SOUTH

**Well Number:** 213H

## Section 5 - Location and Types of Water Supply

### Water Source Table

**Water source use type:** INTERMEDIATE/PRODUCTION CASING

**Water source type:** OTHER

**Describe type:** BRINE WATER

**Source latitude:**

**Source longitude:**

**Source datum:**

**Water source permit type:** PRIVATE CONTRACT

**Source land ownership:** PRIVATE

**Water source transport method:** TRUCKING

**Source transportation land ownership:** OTHER

**Describe transportation land ownership:**

**Water source volume (barrels):** 20000

**Source volume (acre-feet):** 2.577862

**Source volume (gal):** 840000

**Water source use type:** OTHER, STIMULATION, SURFACE CASING **Water source type:** OTHER

**Describe type:** FRESH WATER

**Source latitude:**

**Source longitude:**

**Source datum:**

**Water source permit type:** PRIVATE CONTRACT

**Source land ownership:** PRIVATE

**Water source transport method:** TRUCKING

**Source transportation land ownership:** OTHER

**Describe transportation land ownership:**

**Water source volume (barrels):** 250000

**Source volume (acre-feet):** 32.223274

**Source volume (gal):** 10500000

**Water source and transportation map:**

BLUS\_213H\_Water\_Source\_Map\_20190220142151.pdf

**Water source comments:** Source transportation land ownership is a mixture of Federal, State and County.

**New water well?** NO

### New Water Well Info

**Well latitude:**

**Well Longitude:**

**Well datum:**

**Well target aquifer:**

**Est. depth to top of aquifer(ft):**

**Est thickness of aquifer:**

**Operator Name:** KAISER FRANCIS OIL COMPANY

**Well Name:** BELL LAKE UNIT SOUTH

**Well Number:** 213H

**Aquifer comments:**

**Aquifer documentation:**

**Well depth (ft):**

**Well casing type:**

**Well casing outside diameter (in.):**

**Well casing inside diameter (in.):**

**New water well casing?**

**Used casing source:**

**Drilling method:**

**Drill material:**

**Grout material:**

**Grout depth:**

**Casing length (ft.):**

**Casing top depth (ft.):**

**Well Production type:**

**Completion Method:**

**Water well additional information:**

**State appropriation permit:**

**Additional information attachment:**

### Section 6 - Construction Materials

**Using any construction materials:** YES

**Construction Materials description:** On site caliche will be used for construction if sufficient. In the event insufficient quantities of caliche are available onsite, caliche will be trucked in from BLM's caliche pit in SWSW Section 22-T24-R34E or NENE Section 20-T23S-R33E.

**Construction Materials source location attachment:**

### Section 7 - Methods for Handling Waste

**Waste type:** DRILLING

**Waste content description:** Drilling fluids and cuttings

**Amount of waste:** 3900 barrels

**Waste disposal frequency :** One Time Only

**Safe containment description:** All drilling fluids will be stored safely and disposed of properly

**Safe containmant attachment:**

**Waste disposal type:** HAUL TO COMMERCIAL FACILITY **Disposal location ownership:** COMMERCIAL

**Disposal type description:**

**Disposal location description:** Cuttings will be hauled to R360's facility on US 62/180 at Halfway, NM

**Waste type:** SEWAGE

**Waste content description:** Human waste and grey water

**Amount of waste:** 1000 gallons

**Waste disposal frequency :** One Time Only

**Operator Name:** KAISER FRANCIS OIL COMPANY

**Well Name:** BELL LAKE UNIT SOUTH

**Well Number:** 213H

**Safe containment description:** Waste material will be stored safely and disposed of properly

**Safe containmant attachment:**

**Waste disposal type:** HAUL TO COMMERCIAL FACILITY      **Disposal location ownership:** COMMERCIAL

**Disposal type description:**

**Disposal location description:** Trucked to an approved disposal facility

**Waste type:** GARBAGE

**Waste content description:** Miscellaneous trash

**Amount of waste:** 500                      pounds

**Waste disposal frequency :** One Time Only

**Safe containment description:** Trash produced during drilling and completion operations will be collected in a trash container and disposed of properly

**Safe containmant attachment:**

**Waste disposal type:** HAUL TO COMMERCIAL FACILITY      **Disposal location ownership:** COMMERCIAL

**Disposal type description:**

**Disposal location description:** Trucked to an approved disposal facility

### Reserve Pit

**Reserve Pit being used?** NO

**Temporary disposal of produced water into reserve pit?**

**Reserve pit length (ft.)**                      **Reserve pit width (ft.)**

**Reserve pit depth (ft.)**    **Reserve pit volume (cu. yd.)**

**Is at least 50% of the reserve pit in cut?**

**Reserve pit liner**

**Reserve pit liner specifications and installation description**

### Cuttings Area

**Cuttings Area being used?** NO

**Are you storing cuttings on location?** YES

**Description of cuttings location** Cuttings will be stored in roll off bins and hauled to R360 on US 62/180 near Halfway.

**Cuttings area length (ft.)**    **Cuttings area width (ft.)**

**Cuttings area depth (ft.)**    **Cuttings area volume (cu. yd.)**

**Operator Name:** KAISER FRANCIS OIL COMPANY

**Well Name:** BELL LAKE UNIT SOUTH

**Well Number:** 213H

**Is at least 50% of the cuttings area in cut?**

**WCuttings area liner**

**Cuttings area liner specifications and installation description**

## Section 8 - Ancillary Facilities

**Are you requesting any Ancillary Facilities?:** NO

**Ancillary Facilities attachment:**

**Comments:**

## Section 9 - Well Site Layout

**Well Site Layout Diagram:**

BLUS\_213H\_Pad\_10\_Drilling\_Layout\_20190220142446.pdf

BLUS\_213H\_Well\_Pad\_Layout\_20190220142447.pdf

**Comments:**

## Section 10 - Plans for Surface Reclamation

**Type of disturbance:** New Surface Disturbance

**Multiple Well Pad Name:** SOUTH BELL LAKE UNIT

**Multiple Well Pad Number:** 10

**Recontouring attachment:**

**Drainage/Erosion control construction:** During construction proper erosion control methods will be used to control erosion, runoff and siltation of the surrounding area. As per request of rancher, a berm will be constructed along the east side of well pad.

**Drainage/Erosion control reclamation:** Proper erosion control methods will be used on the area to control erosion, runoff and siltation of the surrounding area.

**Wellpad long term disturbance (acres):** 5.969

**Wellpad short term disturbance (acres):** 0

**Access road long term disturbance (acres):** 0.43905

**Access road short term disturbance (acres):** 0

**Pipeline long term disturbance (acres):** 0

**Pipeline short term disturbance (acres):** 0

**Other long term disturbance (acres):** 0

**Other short term disturbance (acres):** 0

**Total long term disturbance:** 6.40805

**Total short term disturbance:** 0

**Disturbance Comments:** Plan to reclaim 130' on the north side and 80' on the west side of well pad.

**Reconstruction method:** The areas planned for interim reclamation will then be recontoured to the original contour if feasible, or if not feasible, to an interim contour that blends with the surrounding topography as much as possible. Where applicable, the fill material of the well pad will be backfilled into the cut to bring the area back to the original contour. The interim cut and fill slopes prior to re-seeding will not be steeper than a 3:1 ratio, unless the adjacent native topography is



**Operator Name:** KAISER FRANCIS OIL COMPANY

**Well Name:** BELL LAKE UNIT SOUTH

**Well Number:** 213H

steeper. Note: Constructed slopes may be much steeper during drilling, but will be recontoured to the above ratios during interim reclamation.

**Topsoil redistribution:** Topsoil will be evenly respread and aggressively revegetated over the entire disturbed area not needed for all-weather operations

**Soil treatment:** To seed the area, the proper BLM seed mixture, free of noxious weeds, will be used. Final seedbed preparation will consist of contour cultivating to a depth of 4 to 6 inches within 24 hours prior to seeding, dozer tracking, or other imprinting in order to break the soil crust and create seed germination micro-sites.

**Existing Vegetation at the well pad:** The historic climax plant community is a grassland dominated by black grama, dropseeds, and blue stems with sand sage and shinnery oak distributed evenly throughout. Current landscape displays mesquite, shinnery oak, yucca, desert sage, fourwing saltbush, snakeweed, and bunch grasses

**Existing Vegetation at the well pad attachment:**

**Existing Vegetation Community at the road:** Refer to "Existing Vegetation at the well pad"

**Existing Vegetation Community at the road attachment:**

**Existing Vegetation Community at the pipeline:**

**Existing Vegetation Community at the pipeline attachment:**

**Existing Vegetation Community at other disturbances:**

**Existing Vegetation Community at other disturbances attachment:**

**Non native seed used?** NO

**Non native seed description:**

**Seedling transplant description:**

**Will seedlings be transplanted for this project?** NO

**Seedling transplant description attachment:**

**Will seed be harvested for use in site reclamation?** NO

**Seed harvest description:**

**Seed harvest description attachment:**

## Seed Management

### Seed Table

**Seed type:**

**Seed source:**

**Seed name:**

**Source name:**

**Source address:**

**Operator Name:** KAISER FRANCIS OIL COMPANY

**Well Name:** BELL LAKE UNIT SOUTH

**Well Number:** 213H

**Source phone:**

**Seed cultivar:**

**Seed use location:**

**PLS pounds per acre:**

**Proposed seeding season:**

Seed Summary	
Seed Type	Pounds/Acre

**Total pounds/Acre:**

**Seed reclamation attachment:**

**Operator Contact/Responsible Official Contact Info**

**First Name:**

**Last Name:**

**Phone:**

**Email:**

**Seedbed prep:**

**Seed BMP:**

**Seed method:**

**Existing invasive species?** NO

**Existing invasive species treatment description:**

**Existing invasive species treatment attachment:**

**Weed treatment plan description:** No invasive species present. Standard regular maintenance to maintain a clear location and road.

**Weed treatment plan attachment:**

**Monitoring plan description:** Identify areas supporting weeds prior to construction; prevent the introduction and spread of weeds from construction equipment during construction; and contain weed seeds and propagules by preventing segregated topsoil from being spread to adjacent areas. No invasive species present. Standard regular maintenance to maintain a clear location and road.

**Monitoring plan attachment:**

**Success standards:** To maintain all disturbed areas as per Gold Book standards

**Pit closure description:** N/A

**Pit closure attachment:**

**Section 11 - Surface Ownership**

**Operator Name:** KAISER FRANCIS OIL COMPANY

**Well Name:** BELL LAKE UNIT SOUTH

**Well Number:** 213H

**Disturbance type:** WELL PAD

**Describe:**

**Surface Owner:** STATE GOVERNMENT

**Other surface owner description:**

**BIA Local Office:**

**BOR Local Office:**

**COE Local Office:**

**DOD Local Office:**

**NPS Local Office:**

**State Local Office:** COMMISSIONER OF PUBLIC LANDS, PO BOX 1148, SANTA FE, NM 87504

**Military Local Office:**

**USFWS Local Office:**

**Other Local Office:**

**USFS Region:**

**USFS Forest/Grassland:**

**USFS Ranger District:**

**Fee Owner:** Mark T. McCloy & Annette E McCloy

**Fee Owner Address:**

**Phone:** (432)940-4459

**Email:**

**Surface use plan certification:** NO

**Surface use plan certification document:**

**Surface access agreement or bond:** Agreement

**Surface Access Agreement Need description:** Surface Use and Compensation Agreement dated October 4, 2016 between Mark T McCloy and Annette E McCloy Revocable Living Trust and Kaiser-Francis Oil Company

**Surface Access Bond BLM or Forest Service:**

**BLM Surface Access Bond number:**

**USFS Surface access bond number:**

**Operator Name:** KAISER FRANCIS OIL COMPANY

**Well Name:** BELL LAKE UNIT SOUTH

**Well Number:** 213H

**Disturbance type:** NEW ACCESS ROAD

**Describe:**

**Surface Owner:** STATE GOVERNMENT

**Other surface owner description:**

**BIA Local Office:**

**BOR Local Office:**

**COE Local Office:**

**DOD Local Office:**

**NPS Local Office:**

**State Local Office:** COMMISSIONER OF PUBLIC LANDS, PO BOX 1148, SANTA FE, NM 87504-1148

**Military Local Office:**

**USFWS Local Office:**

**Other Local Office:**

**USFS Region:**

**USFS Forest/Grassland:**

**USFS Ranger District:**

## Section 12 - Other Information

**Right of Way needed?** NO

**Use APD as ROW?**

**ROW Type(s):**

### ROW Applications

**SUPO Additional Information:**

**Use a previously conducted onsite?** NO

**Previous Onsite information:**

### Other SUPO Attachment

BLUS\_213H\_SPCC\_Pad\_10\_20190220142527.pdf

PWD

Approval Date: 07/09/2019

Page 18 of 23

**Operator Name:** KAISER FRANCIS OIL COMPANY

**Well Name:** BELL LAKE UNIT SOUTH

**Well Number:** 213H

### Section 1 - General

**Would you like to address long-term produced water disposal?** NO

### Section 2 - Lined Pits

**Would you like to utilize Lined Pit PWD options?** NO

**Produced Water Disposal (PWD) Location:**

**PWD surface owner:**

**PWD disturbance (acres):**

**Lined pit PWD on or off channel:**

**Lined pit PWD discharge volume (bbl/day):**

**Lined pit specifications:**

**Pit liner description:**

**Pit liner manufacturers information:**

**Precipitated solids disposal:**

**Describe precipitated solids disposal:**

**Precipitated solids disposal permit:**

**Lined pit precipitated solids disposal schedule:**

**Lined pit precipitated solids disposal schedule attachment:**

**Lined pit reclamation description:**

**Lined pit reclamation attachment:**

**Leak detection system description:**

**Leak detection system attachment:**

**Lined pit Monitor description:**

**Lined pit Monitor attachment:**

**Lined pit: do you have a reclamation bond for the pit?**

**Is the reclamation bond a rider under the BLM bond?**

**Operator Name:** KAISER FRANCIS OIL COMPANY

**Well Name:** BELL LAKE UNIT SOUTH

**Well Number:** 213H

**Lined pit bond number:**

**Lined pit bond amount:**

**Additional bond information attachment:**

### **Section 3 - Unlined Pits**

**Would you like to utilize Unlined Pit PWD options?** NO

**Produced Water Disposal (PWD) Location:**

**PWD disturbance (acres):**

**PWD surface owner:**

**Unlined pit PWD on or off channel:**

**Unlined pit PWD discharge volume (bbl/day):**

**Unlined pit specifications:**

**Precipitated solids disposal:**

**Describe precipitated solids disposal:**

**Precipitated solids disposal permit:**

**Unlined pit precipitated solids disposal schedule:**

**Unlined pit precipitated solids disposal schedule attachment:**

**Unlined pit reclamation description:**

**Unlined pit reclamation attachment:**

**Unlined pit Monitor description:**

**Unlined pit Monitor attachment:**

**Do you propose to put the produced water to beneficial use?**

**Beneficial use user confirmation:**

**Estimated depth of the shallowest aquifer (feet):**

**Does the produced water have an annual average Total Dissolved Solids (TDS) concentration equal to or less than that of the existing water to be protected?**

**TDS lab results:**

**Geologic and hydrologic evidence:**

**State authorization:**

**Unlined Produced Water Pit Estimated percolation:**

**Unlined pit: do you have a reclamation bond for the pit?**

**Is the reclamation bond a rider under the BLM bond?**

**Unlined pit bond number:**

**Unlined pit bond amount:**

**Additional bond information attachment:**

**Operator Name:** KAISER FRANCIS OIL COMPANY

**Well Name:** BELL LAKE UNIT SOUTH

**Well Number:** 213H

#### **Section 4 - Injection**

**Would you like to utilize Injection PWD options?** NO

**Produced Water Disposal (PWD) Location:**

**PWD surface owner:**

**PWD disturbance (acres):**

**Injection PWD discharge volume (bbl/day):**

**Injection well mineral owner:**

**Injection well type:**

**Injection well number:**

**Injection well name:**

**Assigned injection well API number?**

**Injection well API number:**

**Injection well new surface disturbance (acres):**

**Minerals protection information:**

**Mineral protection attachment:**

**Underground Injection Control (UIC) Permit?**

**UIC Permit attachment:**

#### **Section 5 - Surface Discharge**

**Would you like to utilize Surface Discharge PWD options?** NO

**Produced Water Disposal (PWD) Location:**

**PWD surface owner:**

**PWD disturbance (acres):**

**Surface discharge PWD discharge volume (bbl/day):**

**Surface Discharge NPDES Permit?**

**Surface Discharge NPDES Permit attachment:**

**Surface Discharge site facilities information:**

**Surface discharge site facilities map:**

#### **Section 6 - Other**

**Would you like to utilize Other PWD options?** NO

**Produced Water Disposal (PWD) Location:**

**PWD surface owner:**

**PWD disturbance (acres):**

**Other PWD discharge volume (bbl/day):**

**Other PWD type description:**

**Operator Name:** KAISER FRANCIS OIL COMPANY

**Well Name:** BELL LAKE UNIT SOUTH

**Well Number:** 213H

**Other PWD type attachment:**

**Have other regulatory requirements been met?**

**Other regulatory requirements attachment:**

## Bond Info

### Bond Information

**Federal/Indian APD:** FED

**BLM Bond number:** WYB000055

**BIA Bond number:**

**Do you have a reclamation bond?** NO

**Is the reclamation bond a rider under the BLM bond?**

**Is the reclamation bond BLM or Forest Service?**

**BLM reclamation bond number:**

**Forest Service reclamation bond number:**

**Forest Service reclamation bond attachment:**

**Reclamation bond number:**

**Reclamation bond amount:**

**Reclamation bond rider amount:**

**Additional reclamation bond information attachment:**

## Operator Certification

### Operator Certification

*I hereby certify that I, or someone under my direct supervision, have inspected the drill site and access route proposed herein; that I am familiar with the conditions which currently exist; that I have full knowledge of state and Federal laws applicable to this operation; that the statements made in this APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for the operations conducted under this application. These statements are subject to the provisions of 18 U.S.C. 1001 for the filing of false statements.*

**NAME:** Stormi Davis

**Signed on:** 12/07/2018

**Title:** Regulatory Analyst

**Street Address:** 106 W. Riverside Drive

**City:** Carlsbad

**State:** NM

**Zip:** 88220

**Phone:** (575)308-3765

**Email address:** nmogrservices@gmail.com

**Approval Date:** 07/09/2019

**Page 22 of 23**



**Operator Name:** KAISER FRANCIS OIL COMPANY

**Well Name:** BELL LAKE UNIT SOUTH

**Well Number:** 213H

**Field Representative**

**Representative Name:** Eric Hansen

**Street Address:** P.O. Box 21468

**City:** Tulsa

**State:** OK

**Zip:** 74121-1468

**Phone:** (918)527-5260

**Email address:** erich@kfoc.net

**Payment Info**

**Payment**

**APD Fee Payment Method:** PAY.GOV

**pay.gov Tracking ID:** 26FIPUSC

Kaiser-Francis Oil Company

## **Kaiser-Francis**

Lea County, New Mexico (NAD 83)

Bell Lake Unit South 213H

Bell Lake Unit South 213H

Wellbore #1

Plan: Design #1

## **Standard Planning Report**

16 January, 2019

**MS** *Directional*

<b>Database:</b>	EDM 5000.14 Conroe Db	<b>Local Co-ordinate Reference:</b>	Well Bell Lake Unit South 213H
<b>Company:</b>	Kaiser-Francis	<b>TVD Reference:</b>	WELL @ 3619.40usft (Cactus 171)
<b>Project:</b>	Lea County, New Mexico (NAD 83)	<b>MD Reference:</b>	WELL @ 3619.40usft (Cactus 171)
<b>Site:</b>	Bell Lake Unit South 213H	<b>North Reference:</b>	Grid
<b>Well:</b>	Bell Lake Unit South 213H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1		

<b>Project</b>	Lea County, New Mexico (NAD 83)		
<b>Map System:</b>	US State Plane 1983	<b>System Datum:</b>	Mean Sea Level
<b>Geo Datum:</b>	North American Datum 1983		
<b>Map Zone:</b>	New Mexico Eastern Zone		

<b>Site</b>	Bell Lake Unit South 213H
-------------	---------------------------

<b>Site Position:</b>		<b>Northing:</b>	454,799.45 usft	<b>Latitude:</b>	32° 14' 51.292 N
<b>From:</b>	Map	<b>Easting:</b>	798,491.11 usft	<b>Longitude:</b>	103° 30' 5.556 W
<b>Position Uncertainty:</b>	0.00 usft	<b>Slot Radius:</b>	13-3/16 "		

<b>Well</b>	Bell Lake Unit South 213H				
<b>Well Position</b>	<b>+N/-S</b>	0.00 usft	<b>Northing:</b>	454,799.45 usft	<b>Latitude:</b> 32° 14' 51.292 N
	<b>+E/-W</b>	0.00 usft	<b>Easting:</b>	798,491.11 usft	<b>Longitude:</b> 103° 30' 5.556 W
<b>Position Uncertainty</b>	0.00 usft	<b>Wellhead Elevation:</b>	usft	<b>Ground Level:</b>	3,597.40 usft
<b>Grid Convergence:</b>	0.444 °				

<b>Wellbore</b>	Wellbore #1
-----------------	-------------

<b>Magnetics</b>	<b>Model Name</b>	<b>Sample Date</b>	<b>Declination (°)</b>	<b>Dip Angle (°)</b>	<b>Field Strength (nT)</b>
	BGGM2018	5/29/2019	6.785	60.015	47,792.96

<b>Design</b>	Design #1
---------------	-----------

**Audit Notes:**

<b>Version:</b>	<b>Phase:</b>	PLAN	<b>Tie On Depth:</b>	0.00
-----------------	---------------	------	----------------------	------

<b>Vertical Section:</b>	<b>Depth From (TVD) (usft)</b>	<b>+N/-S (usft)</b>	<b>+E/-W (usft)</b>	<b>Direction (°)</b>
	0.00	0.00	0.00	174.71

<b>Plan Survey Tool Program</b>	<b>Date</b>	1/16/2019
---------------------------------	-------------	-----------

Depth From (usft)	Depth To (usft)	Survey (Wellbore)	Tool Name	Remarks
1 0.00	18,735.99	Design #1 (Wellbore #1)	MWD	
			OWSG MWD - Standard	

**Plan Sections**

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	
4,170.00	0.00	0.00	4,170.00	0.00	0.00	0.00	0.00	0.00	0.000	
4,569.84	8.00	83.93	4,568.54	2.95	27.70	2.00	2.00	0.00	83.927	
9,838.53	8.00	83.93	9,786.00	80.49	756.55	0.00	0.00	0.00	0.000	
10,238.37	0.00	0.00	10,184.54	83.44	784.25	2.00	-2.00	0.00	180.000	
10,438.37	0.00	0.00	10,384.54	83.44	784.25	0.00	0.00	0.00	0.000	VP - Bell Lake Unit
11,188.37	90.00	180.35	10,862.01	-394.02	781.35	12.00	12.00	-23.95	180.348	
18,735.99	90.00	180.35	10,862.00	-7,941.50	735.45	0.00	0.00	0.00	0.000	PBHL - Bell Lake U

<b>Database:</b>	EDM 5000.14 Conroe Db	<b>Local Co-ordinate Reference:</b>	Well Bell Lake Unit South 213H
<b>Company:</b>	Kaiser-Francis	<b>TVD Reference:</b>	WELL @ 3619.40usft (Cactus 171)
<b>Project:</b>	Lea County, New Mexico (NAD 83)	<b>MD Reference:</b>	WELL @ 3619.40usft (Cactus 171)
<b>Site:</b>	Bell Lake Unit South 213H	<b>North Reference:</b>	Grid
<b>Well:</b>	Bell Lake Unit South 213H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1		

## Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
100.00	0.00	0.00	100.00	0.00	0.00	0.00	0.00	0.00	0.00
200.00	0.00	0.00	200.00	0.00	0.00	0.00	0.00	0.00	0.00
300.00	0.00	0.00	300.00	0.00	0.00	0.00	0.00	0.00	0.00
400.00	0.00	0.00	400.00	0.00	0.00	0.00	0.00	0.00	0.00
500.00	0.00	0.00	500.00	0.00	0.00	0.00	0.00	0.00	0.00
600.00	0.00	0.00	600.00	0.00	0.00	0.00	0.00	0.00	0.00
700.00	0.00	0.00	700.00	0.00	0.00	0.00	0.00	0.00	0.00
800.00	0.00	0.00	800.00	0.00	0.00	0.00	0.00	0.00	0.00
900.00	0.00	0.00	900.00	0.00	0.00	0.00	0.00	0.00	0.00
1,000.00	0.00	0.00	1,000.00	0.00	0.00	0.00	0.00	0.00	0.00
1,100.00	0.00	0.00	1,100.00	0.00	0.00	0.00	0.00	0.00	0.00
1,200.00	0.00	0.00	1,200.00	0.00	0.00	0.00	0.00	0.00	0.00
1,300.00	0.00	0.00	1,300.00	0.00	0.00	0.00	0.00	0.00	0.00
1,400.00	0.00	0.00	1,400.00	0.00	0.00	0.00	0.00	0.00	0.00
1,500.00	0.00	0.00	1,500.00	0.00	0.00	0.00	0.00	0.00	0.00
1,600.00	0.00	0.00	1,600.00	0.00	0.00	0.00	0.00	0.00	0.00
1,700.00	0.00	0.00	1,700.00	0.00	0.00	0.00	0.00	0.00	0.00
1,800.00	0.00	0.00	1,800.00	0.00	0.00	0.00	0.00	0.00	0.00
1,900.00	0.00	0.00	1,900.00	0.00	0.00	0.00	0.00	0.00	0.00
2,000.00	0.00	0.00	2,000.00	0.00	0.00	0.00	0.00	0.00	0.00
2,100.00	0.00	0.00	2,100.00	0.00	0.00	0.00	0.00	0.00	0.00
2,200.00	0.00	0.00	2,200.00	0.00	0.00	0.00	0.00	0.00	0.00
2,300.00	0.00	0.00	2,300.00	0.00	0.00	0.00	0.00	0.00	0.00
2,400.00	0.00	0.00	2,400.00	0.00	0.00	0.00	0.00	0.00	0.00
2,500.00	0.00	0.00	2,500.00	0.00	0.00	0.00	0.00	0.00	0.00
2,600.00	0.00	0.00	2,600.00	0.00	0.00	0.00	0.00	0.00	0.00
2,700.00	0.00	0.00	2,700.00	0.00	0.00	0.00	0.00	0.00	0.00
2,800.00	0.00	0.00	2,800.00	0.00	0.00	0.00	0.00	0.00	0.00
2,900.00	0.00	0.00	2,900.00	0.00	0.00	0.00	0.00	0.00	0.00
3,000.00	0.00	0.00	3,000.00	0.00	0.00	0.00	0.00	0.00	0.00
3,100.00	0.00	0.00	3,100.00	0.00	0.00	0.00	0.00	0.00	0.00
3,200.00	0.00	0.00	3,200.00	0.00	0.00	0.00	0.00	0.00	0.00
3,300.00	0.00	0.00	3,300.00	0.00	0.00	0.00	0.00	0.00	0.00
3,400.00	0.00	0.00	3,400.00	0.00	0.00	0.00	0.00	0.00	0.00
3,500.00	0.00	0.00	3,500.00	0.00	0.00	0.00	0.00	0.00	0.00
3,600.00	0.00	0.00	3,600.00	0.00	0.00	0.00	0.00	0.00	0.00
3,700.00	0.00	0.00	3,700.00	0.00	0.00	0.00	0.00	0.00	0.00
3,800.00	0.00	0.00	3,800.00	0.00	0.00	0.00	0.00	0.00	0.00
3,900.00	0.00	0.00	3,900.00	0.00	0.00	0.00	0.00	0.00	0.00
4,000.00	0.00	0.00	4,000.00	0.00	0.00	0.00	0.00	0.00	0.00
4,100.00	0.00	0.00	4,100.00	0.00	0.00	0.00	0.00	0.00	0.00
4,170.00	0.00	0.00	4,170.00	0.00	0.00	0.00	0.00	0.00	0.00
<b>KOP, 2.00°/100' Build</b>									
4,200.00	0.60	83.93	4,200.00	0.02	0.16	0.00	2.00	2.00	0.00
4,300.00	2.60	83.93	4,299.96	0.31	2.93	-0.04	2.00	2.00	0.00
4,400.00	4.60	83.93	4,399.75	0.98	9.18	-0.13	2.00	2.00	0.00
4,500.00	6.60	83.93	4,499.27	2.01	18.88	-0.26	2.00	2.00	0.00
4,569.84	8.00	83.93	4,568.54	2.95	27.70	-0.38	2.00	2.00	0.00
<b>Hold 8.00° Inc, 83.93° Azm</b>									
4,600.00	8.00	83.93	4,598.41	3.39	31.87	-0.44	0.00	0.00	0.00
4,700.00	8.00	83.93	4,697.44	4.86	45.71	-0.63	0.00	0.00	0.00
4,800.00	8.00	83.93	4,796.47	6.33	59.54	-0.82	0.00	0.00	0.00

# MS Directional Planning Report



<b>Database:</b>	EDM 5000.14 Conroe Db	<b>Local Co-ordinate Reference:</b>	Well Bell Lake Unit South 213H
<b>Company:</b>	Kaiser-Francis	<b>TVD Reference:</b>	WELL @ 3619.40usft (Cactus 171)
<b>Project:</b>	Lea County, New Mexico (NAD 83)	<b>MD Reference:</b>	WELL @ 3619.40usft (Cactus 171)
<b>Site:</b>	Bell Lake Unit South 213H	<b>North Reference:</b>	Grid
<b>Well:</b>	Bell Lake Unit South 213H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1		

## Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
4,900.00	8.00	83.93	4,895.49	7.81	73.37	-1.01	0.00	0.00	0.00
5,000.00	8.00	83.93	4,994.52	9.28	87.21	-1.20	0.00	0.00	0.00
5,100.00	8.00	83.93	5,093.55	10.75	101.04	-1.39	0.00	0.00	0.00
5,200.00	8.00	83.93	5,192.58	12.22	114.88	-1.58	0.00	0.00	0.00
5,300.00	8.00	83.93	5,291.60	13.69	128.71	-1.77	0.00	0.00	0.00
5,400.00	8.00	83.93	5,390.63	15.17	142.54	-1.96	0.00	0.00	0.00
5,500.00	8.00	83.93	5,489.66	16.64	156.38	-2.15	0.00	0.00	0.00
5,600.00	8.00	83.93	5,588.69	18.11	170.21	-2.34	0.00	0.00	0.00
5,700.00	8.00	83.93	5,687.71	19.58	184.04	-2.53	0.00	0.00	0.00
5,800.00	8.00	83.93	5,786.74	21.05	197.88	-2.72	0.00	0.00	0.00
5,900.00	8.00	83.93	5,885.77	22.53	211.71	-2.91	0.00	0.00	0.00
6,000.00	8.00	83.93	5,984.80	24.00	225.54	-3.10	0.00	0.00	0.00
6,100.00	8.00	83.93	6,083.82	25.47	239.38	-3.29	0.00	0.00	0.00
6,200.00	8.00	83.93	6,182.85	26.94	253.21	-3.48	0.00	0.00	0.00
6,300.00	8.00	83.93	6,281.88	28.41	267.05	-3.67	0.00	0.00	0.00
6,400.00	8.00	83.93	6,380.91	29.88	280.88	-3.86	0.00	0.00	0.00
6,500.00	8.00	83.93	6,479.93	31.36	294.71	-4.05	0.00	0.00	0.00
6,600.00	8.00	83.93	6,578.96	32.83	308.55	-4.24	0.00	0.00	0.00
6,700.00	8.00	83.93	6,677.99	34.30	322.38	-4.43	0.00	0.00	0.00
6,800.00	8.00	83.93	6,777.02	35.77	336.21	-4.62	0.00	0.00	0.00
6,900.00	8.00	83.93	6,876.04	37.24	350.05	-4.81	0.00	0.00	0.00
7,000.00	8.00	83.93	6,975.07	38.72	363.88	-5.00	0.00	0.00	0.00
7,100.00	8.00	83.93	7,074.10	40.19	377.71	-5.19	0.00	0.00	0.00
7,200.00	8.00	83.93	7,173.13	41.66	391.55	-5.38	0.00	0.00	0.00
7,300.00	8.00	83.93	7,272.16	43.13	405.38	-5.57	0.00	0.00	0.00
7,400.00	8.00	83.93	7,371.18	44.60	419.22	-5.76	0.00	0.00	0.00
7,500.00	8.00	83.93	7,470.21	46.07	433.05	-5.95	0.00	0.00	0.00
7,600.00	8.00	83.93	7,569.24	47.55	446.88	-6.14	0.00	0.00	0.00
7,700.00	8.00	83.93	7,668.27	49.02	460.72	-6.32	0.00	0.00	0.00
7,800.00	8.00	83.93	7,767.29	50.49	474.55	-6.51	0.00	0.00	0.00
7,900.00	8.00	83.93	7,866.32	51.96	488.38	-6.70	0.00	0.00	0.00
8,000.00	8.00	83.93	7,965.35	53.43	502.22	-6.89	0.00	0.00	0.00
8,100.00	8.00	83.93	8,064.38	54.91	516.05	-7.08	0.00	0.00	0.00
8,200.00	8.00	83.93	8,163.40	56.38	529.88	-7.27	0.00	0.00	0.00
8,300.00	8.00	83.93	8,262.43	57.85	543.72	-7.46	0.00	0.00	0.00
8,400.00	8.00	83.93	8,361.46	59.32	557.55	-7.65	0.00	0.00	0.00
8,500.00	8.00	83.93	8,460.49	60.79	571.39	-7.84	0.00	0.00	0.00
8,600.00	8.00	83.93	8,559.51	62.26	585.22	-8.03	0.00	0.00	0.00
8,700.00	8.00	83.93	8,658.54	63.74	599.05	-8.22	0.00	0.00	0.00
8,800.00	8.00	83.93	8,757.57	65.21	612.89	-8.41	0.00	0.00	0.00
8,900.00	8.00	83.93	8,856.60	66.68	626.72	-8.60	0.00	0.00	0.00
9,000.00	8.00	83.93	8,955.62	68.15	640.55	-8.79	0.00	0.00	0.00
9,100.00	8.00	83.93	9,054.65	69.62	654.39	-8.98	0.00	0.00	0.00
9,200.00	8.00	83.93	9,153.68	71.10	668.22	-9.17	0.00	0.00	0.00
9,300.00	8.00	83.93	9,252.71	72.57	682.05	-9.36	0.00	0.00	0.00
9,400.00	8.00	83.93	9,351.73	74.04	695.89	-9.55	0.00	0.00	0.00
9,500.00	8.00	83.93	9,450.76	75.51	709.72	-9.74	0.00	0.00	0.00
9,600.00	8.00	83.93	9,549.79	76.98	723.56	-9.93	0.00	0.00	0.00
9,700.00	8.00	83.93	9,648.82	78.46	737.39	-10.12	0.00	0.00	0.00
9,800.00	8.00	83.93	9,747.84	79.93	751.22	-10.31	0.00	0.00	0.00
9,838.53	8.00	83.93	9,786.00	80.49	756.55	-10.39	0.00	0.00	0.00
Begin 2.00°/100' Drop									
9,900.00	6.77	83.93	9,846.96	81.33	764.41	-10.49	2.00	-2.00	0.00
10,000.00	4.77	83.93	9,946.45	82.39	774.40	-10.63	2.00	-2.00	0.00

# MS Directional Planning Report



<b>Database:</b>	EDM 5000.14 Conroe Db	<b>Local Co-ordinate Reference:</b>	Well Bell Lake Unit South 213H
<b>Company:</b>	Kaiser-Francis	<b>TVD Reference:</b>	WELL @ 3619.40usft (Cactus 171)
<b>Project:</b>	Lea County, New Mexico (NAD 83)	<b>MD Reference:</b>	WELL @ 3619.40usft (Cactus 171)
<b>Site:</b>	Bell Lake Unit South 213H	<b>North Reference:</b>	Grid
<b>Well:</b>	Bell Lake Unit South 213H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1		

## Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
10,100.00	2.77	83.93	10,046.23	83.09	780.93	-10.72	2.00	-2.00	0.00
10,200.00	0.77	83.93	10,146.17	83.41	784.00	-10.76	2.00	-2.00	0.00
10,238.37	0.00	0.00	10,184.54	83.44	784.25	-10.77	2.00	-2.00	0.00
<b>Begin Vertical Hold</b>									
10,300.00	0.00	0.00	10,246.17	83.44	784.25	-10.77	0.00	0.00	0.00
10,400.00	0.00	0.00	10,346.17	83.44	784.25	-10.77	0.00	0.00	0.00
10,438.37	0.00	0.00	10,384.54	83.44	784.25	-10.77	0.00	0.00	0.00
<b>Begin 12.00°/100' Build</b>									
10,500.00	7.40	180.35	10,446.00	79.47	784.23	-6.81	12.00	12.00	0.00
10,600.00	19.40	180.35	10,543.10	56.34	784.09	16.20	12.00	12.00	0.00
10,700.00	31.40	180.35	10,633.28	13.54	783.83	58.80	12.00	12.00	0.00
10,800.00	43.40	180.35	10,712.58	-47.08	783.46	119.13	12.00	12.00	0.00
10,900.00	55.40	180.35	10,777.54	-122.87	783.00	194.55	12.00	12.00	0.00
11,000.00	67.40	180.35	10,825.33	-210.50	782.47	281.76	12.00	12.00	0.00
11,100.00	79.40	180.35	10,853.85	-306.15	781.88	376.95	12.00	12.00	0.00
11,188.37	90.00	180.35	10,862.01	-394.02	781.35	464.39	12.00	12.00	0.00
<b>Begin 90.00° Lateral</b>									
11,200.00	90.00	180.35	10,862.01	-405.65	781.28	475.96	0.00	0.00	0.00
11,300.00	90.00	180.35	10,862.00	-505.65	780.67	575.48	0.00	0.00	0.00
11,400.00	90.00	180.35	10,862.00	-605.64	780.06	675.00	0.00	0.00	0.00
11,500.00	90.00	180.35	10,862.00	-705.64	779.45	774.51	0.00	0.00	0.00
11,600.00	90.00	180.35	10,862.00	-805.64	778.85	874.03	0.00	0.00	0.00
11,700.00	90.00	180.35	10,862.00	-905.64	778.24	973.54	0.00	0.00	0.00
11,800.00	90.00	180.35	10,862.00	-1,005.64	777.63	1,073.06	0.00	0.00	0.00
11,900.00	90.00	180.35	10,862.00	-1,105.63	777.02	1,172.58	0.00	0.00	0.00
12,000.00	90.00	180.35	10,862.00	-1,205.63	776.41	1,272.09	0.00	0.00	0.00
12,100.00	90.00	180.35	10,862.00	-1,305.63	775.81	1,371.61	0.00	0.00	0.00
12,200.00	90.00	180.35	10,862.00	-1,405.63	775.20	1,471.12	0.00	0.00	0.00
12,300.00	90.00	180.35	10,862.00	-1,505.63	774.59	1,570.64	0.00	0.00	0.00
12,400.00	90.00	180.35	10,862.00	-1,605.63	773.98	1,670.16	0.00	0.00	0.00
12,500.00	90.00	180.35	10,862.00	-1,705.62	773.37	1,769.67	0.00	0.00	0.00
12,600.00	90.00	180.35	10,862.00	-1,805.62	772.77	1,869.19	0.00	0.00	0.00
12,700.00	90.00	180.35	10,862.00	-1,905.62	772.16	1,968.70	0.00	0.00	0.00
12,800.00	90.00	180.35	10,862.00	-2,005.62	771.55	2,068.22	0.00	0.00	0.00
12,900.00	90.00	180.35	10,862.00	-2,105.62	770.94	2,167.74	0.00	0.00	0.00
13,000.00	90.00	180.35	10,862.00	-2,205.61	770.33	2,267.25	0.00	0.00	0.00
13,100.00	90.00	180.35	10,862.00	-2,305.61	769.72	2,366.77	0.00	0.00	0.00
13,200.00	90.00	180.35	10,862.00	-2,405.61	769.12	2,466.28	0.00	0.00	0.00
13,300.00	90.00	180.35	10,862.00	-2,505.61	768.51	2,565.80	0.00	0.00	0.00
13,400.00	90.00	180.35	10,862.00	-2,605.61	767.90	2,665.32	0.00	0.00	0.00
13,500.00	90.00	180.35	10,862.00	-2,705.61	767.29	2,764.83	0.00	0.00	0.00
13,600.00	90.00	180.35	10,862.00	-2,805.60	766.68	2,864.35	0.00	0.00	0.00
13,700.00	90.00	180.35	10,862.00	-2,905.60	766.08	2,963.86	0.00	0.00	0.00
13,800.00	90.00	180.35	10,862.00	-3,005.60	765.47	3,063.38	0.00	0.00	0.00
13,900.00	90.00	180.35	10,862.00	-3,105.60	764.86	3,162.90	0.00	0.00	0.00
14,000.00	90.00	180.35	10,862.00	-3,205.60	764.25	3,262.41	0.00	0.00	0.00
14,100.00	90.00	180.35	10,862.00	-3,305.59	763.64	3,361.93	0.00	0.00	0.00
14,200.00	90.00	180.35	10,862.00	-3,405.59	763.04	3,461.44	0.00	0.00	0.00
14,300.00	90.00	180.35	10,862.00	-3,505.59	762.43	3,560.96	0.00	0.00	0.00
14,400.00	90.00	180.35	10,862.00	-3,605.59	761.82	3,660.48	0.00	0.00	0.00
14,500.00	90.00	180.35	10,862.00	-3,705.59	761.21	3,759.99	0.00	0.00	0.00
14,600.00	90.00	180.35	10,862.00	-3,805.58	760.60	3,859.51	0.00	0.00	0.00
14,700.00	90.00	180.35	10,862.00	-3,905.58	759.99	3,959.02	0.00	0.00	0.00

# MS Directional Planning Report



<b>Database:</b>	EDM 5000.14 Conroe Db	<b>Local Co-ordinate Reference:</b>	Well Bell Lake Unit South 213H
<b>Company:</b>	Kaiser-Francis	<b>TVD Reference:</b>	WELL @ 3619.40usft (Cactus 171)
<b>Project:</b>	Lea County, New Mexico (NAD 83)	<b>MD Reference:</b>	WELL @ 3619.40usft (Cactus 171)
<b>Site:</b>	Bell Lake Unit South 213H	<b>North Reference:</b>	Grid
<b>Well:</b>	Bell Lake Unit South 213H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1		

## Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
14,800.00	90.00	180.35	10,862.00	-4,005.58	759.39	4,058.54	0.00	0.00	0.00
14,900.00	90.00	180.35	10,862.00	-4,105.58	758.78	4,158.06	0.00	0.00	0.00
15,000.00	90.00	180.35	10,862.00	-4,205.58	758.17	4,257.57	0.00	0.00	0.00
15,100.00	90.00	180.35	10,862.00	-4,305.58	757.56	4,357.09	0.00	0.00	0.00
15,200.00	90.00	180.35	10,862.00	-4,405.57	756.95	4,456.60	0.00	0.00	0.00
15,300.00	90.00	180.35	10,862.00	-4,505.57	756.35	4,556.12	0.00	0.00	0.00
15,400.00	90.00	180.35	10,862.00	-4,605.57	755.74	4,655.64	0.00	0.00	0.00
15,500.00	90.00	180.35	10,862.00	-4,705.57	755.13	4,755.15	0.00	0.00	0.00
15,600.00	90.00	180.35	10,862.00	-4,805.57	754.52	4,854.67	0.00	0.00	0.00
15,700.00	90.00	180.35	10,862.00	-4,905.56	753.91	4,954.18	0.00	0.00	0.00
15,800.00	90.00	180.35	10,862.00	-5,005.56	753.30	5,053.70	0.00	0.00	0.00
15,900.00	90.00	180.35	10,862.00	-5,105.56	752.70	5,153.22	0.00	0.00	0.00
16,000.00	90.00	180.35	10,862.00	-5,205.56	752.09	5,252.73	0.00	0.00	0.00
16,100.00	90.00	180.35	10,862.00	-5,305.56	751.48	5,352.25	0.00	0.00	0.00
16,200.00	90.00	180.35	10,862.00	-5,405.56	750.87	5,451.76	0.00	0.00	0.00
16,300.00	90.00	180.35	10,862.00	-5,505.55	750.26	5,551.28	0.00	0.00	0.00
16,400.00	90.00	180.35	10,862.00	-5,605.55	749.66	5,650.80	0.00	0.00	0.00
16,500.00	90.00	180.35	10,862.00	-5,705.55	749.05	5,750.31	0.00	0.00	0.00
16,600.00	90.00	180.35	10,862.00	-5,805.55	748.44	5,849.83	0.00	0.00	0.00
16,700.00	90.00	180.35	10,862.00	-5,905.55	747.83	5,949.34	0.00	0.00	0.00
16,800.00	90.00	180.35	10,862.00	-6,005.54	747.22	6,048.86	0.00	0.00	0.00
16,900.00	90.00	180.35	10,862.00	-6,105.54	746.62	6,148.38	0.00	0.00	0.00
17,000.00	90.00	180.35	10,862.00	-6,205.54	746.01	6,247.89	0.00	0.00	0.00
17,100.00	90.00	180.35	10,862.00	-6,305.54	745.40	6,347.41	0.00	0.00	0.00
17,200.00	90.00	180.35	10,862.00	-6,405.54	744.79	6,446.92	0.00	0.00	0.00
17,300.00	90.00	180.35	10,862.00	-6,505.54	744.18	6,546.44	0.00	0.00	0.00
17,400.00	90.00	180.35	10,862.00	-6,605.53	743.57	6,645.96	0.00	0.00	0.00
17,500.00	90.00	180.35	10,862.00	-6,705.53	742.97	6,745.47	0.00	0.00	0.00
17,600.00	90.00	180.35	10,862.00	-6,805.53	742.36	6,844.99	0.00	0.00	0.00
17,700.00	90.00	180.35	10,862.00	-6,905.53	741.75	6,944.50	0.00	0.00	0.00
17,800.00	90.00	180.35	10,862.00	-7,005.53	741.14	7,044.02	0.00	0.00	0.00
17,900.00	90.00	180.35	10,862.00	-7,105.52	740.53	7,143.54	0.00	0.00	0.00
18,000.00	90.00	180.35	10,862.00	-7,205.52	739.93	7,243.05	0.00	0.00	0.00
18,100.00	90.00	180.35	10,862.00	-7,305.52	739.32	7,342.57	0.00	0.00	0.00
18,200.00	90.00	180.35	10,862.00	-7,405.52	738.71	7,442.08	0.00	0.00	0.00
18,300.00	90.00	180.35	10,862.00	-7,505.52	738.10	7,541.60	0.00	0.00	0.00
18,400.00	90.00	180.35	10,862.00	-7,605.51	737.49	7,641.12	0.00	0.00	0.00
18,500.00	90.00	180.35	10,862.00	-7,705.51	736.89	7,740.63	0.00	0.00	0.00
18,600.00	90.00	180.35	10,862.00	-7,805.51	736.28	7,840.15	0.00	0.00	0.00
18,700.00	90.00	180.35	10,862.00	-7,905.51	735.67	7,939.66	0.00	0.00	0.00
18,735.99	90.00	180.35	10,862.00	-7,941.50	735.45	7,975.48	0.00	0.00	0.00

PBHL

# MS Directional Planning Report



<b>Database:</b>	EDM 5000.14 Conroe Db	<b>Local Co-ordinate Reference:</b>	Well Bell Lake Unit South 213H
<b>Company:</b>	Kaiser-Francis	<b>TVD Reference:</b>	WELL @ 3619.40usft (Cactus 171)
<b>Project:</b>	Lea County, New Mexico (NAD 83)	<b>MD Reference:</b>	WELL @ 3619.40usft (Cactus 171)
<b>Site:</b>	Bell Lake Unit South 213H	<b>North Reference:</b>	Grid
<b>Well:</b>	Bell Lake Unit South 213H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1		

## Design Targets

Target Name - hit/miss target - Shape	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
VP - Bell Lake Unit Sc - plan hits target center - Point	0.00	0.00	10,384.54	83.44	784.25	454,882.89	799,275.36	32° 14' 52.058 N	103° 29' 56.417 W
PBHL - Bell Lake Unit - plan hits target center - Point	0.00	0.00	10,862.00	-7,941.50	735.45	446,857.95	799,226.56	32° 13' 32.655 N	103° 29' 57.711 W
FTP - Bell Lake Unit S - plan hits target center - Point	0.00	0.00	10,862.00	-394.01	781.35	454,405.44	799,272.46	32° 14' 47.334 N	103° 29' 56.494 W

## Plan Annotations

Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment
		+N/-S (usft)	+E/-W (usft)	
4,170.00	4,170.00	0.00	0.00	KOP, 2.00°/100' Build
4,569.84	4,568.54	2.95	27.70	Hold 8.00° Inc, 83.93° Azm
9,838.53	9,786.00	80.49	756.55	Begin 2.00°/100' Drop
10,238.37	10,184.54	83.44	784.25	Begin Vertical Hold
10,438.37	10,384.54	83.44	784.25	Begin 12.00°/100' Build
11,188.37	10,862.01	-394.02	781.35	Begin 90.00° Lateral
18,735.99	10,862.00	-7,941.50	735.45	PBHL