Office	State of New Mexico	Form C-103
<u>District I</u> – (575) 393-6161	Energy, Minerals and Natural Resources	Revised July 18, 2013
1625 N. French Dr., Hobbs, NM 88240	-00	WELL API NO.
<u>District II</u> – (575) 748-1283 811 S. First St., Artesia, NM 88210	OIL CONSERVATIONS WORK	30-025-32955
District III - (505) 334-6178	1220 South St. Francis Dr.	5. Indicate Type of Lease  STATE ⊠ FEE □
1000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u> – (505) 476-3460	Santa Fe, N <b>M 273052019</b>	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM	3, 001, 0 3% 4.	10712
87505		· · · · · · · · · · · · · · · · · · ·
	TICES AND REPORTS ON WELL STATES OF THE POSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A	7. Lease Name or Unit Agreement Name
	LICATION FOR PERMIT" (FORM C-101) FOR SUCH	New Mexico DW State
PROPOSALS.)		8. Well Number 3
1. Type of Well: Oil Well	Gas Well Other	
2. Name of Operator		9. OGRID Number
COG Operating, LLC  3. Address of Operator		229137 10. Pool name or Wildcat
2208 W. Main Street Artesia, N	NM 88210	Wildcat 96032
4. Well Location		Whiteat 70032
	C 4 N 4 P 1770 C 6 4 N 4 P	
<u> </u>	from the North line and 660 feet from the West line	
Section 6		NMPM County Lea
	11. Elevation (Show whether DR, RKB, RT, GR, etc.	:.)
	3647' GL	
12 Charle	Ammonwiata Day to Indicate Nations of Nation	Demont on Other Date
12. Clieck	Appropriate Box to Indicate Nature of Notice,	, Report or Other Data
NOTICE OF	INTENTION TO: SUE	SSEQUENT REPORT OF:
PERFORM REMEDIAL WORK		
	_	RILLING OPNS. P AND A
	MULTIPLE COMPL   CASING/CEMEN	<u> </u>
_	<u> </u>	
_		
OTHER:	OTHER:	
13. Describe proposed or con	npleted operations. (Clearly state all pertinent details, ar	nd give pertinent dates, including estimated date
of starting any proposed	work). SEE RULE 19.15.7.14 NMAC. For Multiple Co	ompletions: Attach wellbore diagram of
proposed completion or r	ecompletion.	
	uipment. POH w/ rods & pump. 08/27/19 Dug out cel	
tbg anchor. Set 5 1/2" CIBP	@ 5040'. Circulated hole w/ MLF. Pressure tested cs	g, held 600 PSI. 08/28/19 Spotted 50 sx class
tbg anchor. Set 5 ½" CIBP C cmt @ 5040-4535'. Spotte	@ 5040'. Circulated hole w/ MLF. Pressure tested cs d 25 sx class C cmt w/ 2% CACL @ 2150-1899'. WO	g, held 600 PSI. 08/28/19 Spotted 50 sx class C. Tagged plug @ 1950'. Perf'd csg @ 692'.
tbg anchor. Set 5 ½" CIBP C cmt @ 5040-4535'. Spotte Pressured up on perfs to 100	@ 5040'. Circulated hole w/ MLF. Pressure tested cs d 25 sx class C cmt w/ 2% CACL @ 2150-1899'. WO 00 PSI. Perf'd csg @ 100'. Broke circulation on the 5	g, held 600 PSI. 08/28/19 Spotted 50 sx class C. Tagged plug @ 1950'. Perf'd csg @ 692'. ½" & 8 5/8" csg. Spotted 30 sx class C cmt @
tbg anchor. Set 5 ½" CIBP C cmt @ 5040-4535'. Spotte Pressured up on perfs to 100 740-437'. WOC. 08/28/19 Ta	@ 5040'. Circulated hole w/ MLF. Pressure tested cs d 25 sx class C cmt w/ 2% CACL @ 2150-1899'. WO 00 PSI. Perf'd csg @ 100'. Broke circulation on the 5 agged plug @ 450'. ND BOP. Squeezed 40 sx class C o	g, held 600 PSI. 08/28/19 Spotted 50 sx class PC. Tagged plug @ 1950'. Perf'd csg @ 692'. 1/2" & 8 5/8" csg. Spotted 30 sx class C cmt @ cmt through perfs @ 100' & circulated to
tbg anchor. Set 5 ½" CIBP C cmt @ 5040-4535'. Spotte Pressured up on perfs to 100 740-437'. WOC. 08/28/19 Ta surface up the 5 ½" & 8 5/8'	@ 5040'. Circulated hole w/ MLF. Pressure tested cs/d 25 sx class C cmt w/ 2% CACL @ 2150-1899'. WO 00 PSI. Perf'd csg @ 100'. Broke circulation on the 5 agged plug @ 450'. ND BOP. Squeezed 40 sx class C o'. Rigged down & moved off. 09/06/19 Moved in back	g, held 600 PSI. 08/28/19 Spotted 50 sx class PC. Tagged plug @ 1950'. Perf'd csg @ 692'. 1/2" & 8 5/8" csg. Spotted 30 sx class C cmt @ cmt through perfs @ 100' & circulated to choe and welder, dug out cellar, cut off well
tbg anchor. Set 5 ½" CIBP C cmt @ 5040-4535'. Spotte Pressured up on perfs to 100 740-437'. WOC. 08/28/19 Ta surface up the 5 ½" & 8 5/8' head, and Kerry Fortner w/	@ 5040'. Circulated hole w/ MLF. Pressure tested cs/d 25 sx class C cmt w/ 2% CACL @ 2150-1899'. WO 00 PSI. Perf'd csg @ 100'. Broke circulation on the 5 agged plug @ 450'. ND BOP. Squeezed 40 sx class C o'. Rigged down & moved off. 09/06/19 Moved in back NM OCD verified cement to surface. Welded on "Al	g, held 600 PSI. 08/28/19 Spotted 50 sx class PC. Tagged plug @ 1950'. Perf'd csg @ 692'. 1/2" & 8 5/8" csg. Spotted 30 sx class C cmt @ cmt through perfs @ 100' & circulated to choe and welder, dug out cellar, cut off well
tbg anchor. Set 5 ½" CIBP C cmt @ 5040-4535'. Spotte Pressured up on perfs to 100 740-437'. WOC. 08/28/19 Ta surface up the 5 ½" & 8 5/8' head, and Kerry Fortner w/	@ 5040'. Circulated hole w/ MLF. Pressure tested cs/d 25 sx class C cmt w/ 2% CACL @ 2150-1899'. WO 00 PSI. Perf'd csg @ 100'. Broke circulation on the 5 agged plug @ 450'. ND BOP. Squeezed 40 sx class C o'. Rigged down & moved off. 09/06/19 Moved in back	g, held 600 PSI. 08/28/19 Spotted 50 sx class PC. Tagged plug @ 1950'. Perf'd csg @ 692'. 1/2" & 8 5/8" csg. Spotted 30 sx class C cmt @ cmt through perfs @ 100' & circulated to choe and welder, dug out cellar, cut off well
tbg anchor. Set 5 ½" CIBP C cmt @ 5040-4535'. Spotte Pressured up on perfs to 100 740-437'. WOC. 08/28/19 Ta surface up the 5 ½" & 8 5/8' head, and Kerry Fortner w/	@ 5040'. Circulated hole w/ MLF. Pressure tested cs/d 25 sx class C cmt w/ 2% CACL @ 2150-1899'. WO 00 PSI. Perf'd csg @ 100'. Broke circulation on the 5 agged plug @ 450'. ND BOP. Squeezed 40 sx class C o'. Rigged down & moved off. 09/06/19 Moved in back NM OCD verified cement to surface. Welded on "Al	g, held 600 PSI. 08/28/19 Spotted 50 sx class PC. Tagged plug @ 1950'. Perf'd csg @ 692'. 1/2" & 8 5/8" csg. Spotted 30 sx class C cmt @ cmt through perfs @ 100' & circulated to choe and welder, dug out cellar, cut off well
tbg anchor. Set 5 ½" CIBP C cmt @ 5040-4535'. Spotte Pressured up on perfs to 100 740-437'. WOC. 08/28/19 Ta surface up the 5 ½" & 8 5/8' head, and Kerry Fortner w/	@ 5040'. Circulated hole w/ MLF. Pressure tested cs/d 25 sx class C cmt w/ 2% CACL @ 2150-1899'. WO 00 PSI. Perf'd csg @ 100'. Broke circulation on the 5 agged plug @ 450'. ND BOP. Squeezed 40 sx class C o'. Rigged down & moved off. 09/06/19 Moved in back NM OCD verified cement to surface. Welded on "Al	g, held 600 PSI. 08/28/19 Spotted 50 sx class PC. Tagged plug @ 1950'. Perf'd csg @ 692'. 1/2" & 8 5/8" csg. Spotted 30 sx class C cmt @ cmt through perfs @ 100' & circulated to choe and welder, dug out cellar, cut off well
tbg anchor. Set 5 ½" CIBP C cmt @ 5040-4535'. Spotte Pressured up on perfs to 100 740-437'. WOC. 08/28/19 Ta surface up the 5 ½" & 8 5/8' head, and Kerry Fortner w/	@ 5040'. Circulated hole w/ MLF. Pressure tested cs/d 25 sx class C cmt w/ 2% CACL @ 2150-1899'. WO 00 PSI. Perf'd csg @ 100'. Broke circulation on the 5 agged plug @ 450'. ND BOP. Squeezed 40 sx class C o'. Rigged down & moved off. 09/06/19 Moved in back NM OCD verified cement to surface. Welded on "Al	g, held 600 PSI. 08/28/19 Spotted 50 sx class PC. Tagged plug @ 1950'. Perf'd csg @ 692'. 1/2" & 8 5/8" csg. Spotted 30 sx class C cmt @ cmt through perfs @ 100' & circulated to choe and welder, dug out cellar, cut off well
tbg anchor. Set 5 ½" CIBP C cmt @ 5040-4535'. Spotte Pressured up on perfs to 100 740-437'. WOC. 08/28/19 Ta surface up the 5 ½" & 8 5/8' head, and Kerry Fortner w/ cellar, cut off deadmen, clea	@ 5040'. Circulated hole w/ MLF. Pressure tested csd 25 sx class C cmt w/ 2% CACL @ 2150-1899'. WO 00 PSI. Perf'd csg @ 100'. Broke circulation on the 5 agged plug @ 450'. ND BOP. Squeezed 40 sx class C o'. Rigged down & moved off. 09/06/19 Moved in back NM OCD verified cement to surface. Welded on "Al ned location, and moved off.	g, held 600 PSI. 08/28/19 Spotted 50 sx class PC. Tagged plug @ 1950'. Perf'd csg @ 692'. 1/2" & 8 5/8" csg. Spotted 30 sx class C cmt @ cmt through perfs @ 100' & circulated to choe and welder, dug out cellar, cut off well
tbg anchor. Set 5 ½" CIBP C cmt @ 5040-4535'. Spotte Pressured up on perfs to 100 740-437'. WOC. 08/28/19 Ta surface up the 5 ½" & 8 5/8' head, and Kerry Fortner w/	@ 5040'. Circulated hole w/ MLF. Pressure tested cs/d 25 sx class C cmt w/ 2% CACL @ 2150-1899'. WO 00 PSI. Perf'd csg @ 100'. Broke circulation on the 5 agged plug @ 450'. ND BOP. Squeezed 40 sx class C o'. Rigged down & moved off. 09/06/19 Moved in back NM OCD verified cement to surface. Welded on "Al	g, held 600 PSI. 08/28/19 Spotted 50 sx class PC. Tagged plug @ 1950'. Perf'd csg @ 692'. 1/2" & 8 5/8" csg. Spotted 30 sx class C cmt @ cmt through perfs @ 100' & circulated to choe and welder, dug out cellar, cut off well
tbg anchor. Set 5 ½" CIBP C cmt @ 5040-4535'. Spotte Pressured up on perfs to 100 740-437'. WOC. 08/28/19 Ta surface up the 5 ½" & 8 5/8' head, and Kerry Fortner w/ cellar, cut off deadmen, clea	@ 5040'. Circulated hole w/ MLF. Pressure tested csd 25 sx class C cmt w/ 2% CACL @ 2150-1899'. WO 00 PSI. Perf'd csg @ 100'. Broke circulation on the 5 agged plug @ 450'. ND BOP. Squeezed 40 sx class C o'. Rigged down & moved off. 09/06/19 Moved in back NM OCD verified cement to surface. Welded on "Al ned location, and moved off.	g, held 600 PSI. 08/28/19 Spotted 50 sx class PC. Tagged plug @ 1950'. Perf'd csg @ 692'. 1/2" & 8 5/8" csg. Spotted 30 sx class C cmt @ cmt through perfs @ 100' & circulated to choe and welder, dug out cellar, cut off well
tbg anchor. Set 5 ½" CIBP C cmt @ 5040-4535'. Spotte Pressured up on perfs to 100 740-437'. WOC. 08/28/19 Ta surface up the 5 ½" & 8 5/8' head, and Kerry Fortner w/ cellar, cut off deadmen, clea	@ 5040'. Circulated hole w/ MLF. Pressure tested csd 25 sx class C cmt w/ 2% CACL @ 2150-1899'. WO DO PSI. Perf'd csg @ 100'. Broke circulation on the 5 agged plug @ 450'. ND BOP. Squeezed 40 sx class C o'. Rigged down & moved off. 09/06/19 Moved in back NM OCD verified cement to surface. Welded on "Al ned location, and moved off.  Rig Release Date:	g, held 600 PSI. 08/28/19 Spotted 50 sx class PC. Tagged plug @ 1950'. Perf'd csg @ 692'.   "" & 8 5/8" csg. Spotted 30 sx class C cmt @ cmt through perfs @ 100' & circulated to choe and welder, dug out cellar, cut off well bove Ground Dry Hole Marker". Backfilled
tbg anchor. Set 5 ½" CIBP C cmt @ 5040-4535'. Spotte Pressured up on perfs to 100 740-437'. WOC. 08/28/19 Ta surface up the 5 ½" & 8 5/8' head, and Kerry Fortner w/ cellar, cut off deadmen, clea	@ 5040'. Circulated hole w/ MLF. Pressure tested csd 25 sx class C cmt w/ 2% CACL @ 2150-1899'. WO 00 PSI. Perf'd csg @ 100'. Broke circulation on the 5 agged plug @ 450'. ND BOP. Squeezed 40 sx class C o'. Rigged down & moved off. 09/06/19 Moved in back NM OCD verified cement to surface. Welded on "Al ned location, and moved off.	g, held 600 PSI. 08/28/19 Spotted 50 sx class PC. Tagged plug @ 1950'. Perf'd csg @ 692'.   "" & 8 5/8" csg. Spotted 30 sx class C cmt @ cmt through perfs @ 100' & circulated to choe and welder, dug out cellar, cut off well bove Ground Dry Hole Marker". Backfilled
tbg anchor. Set 5 ½" CIBP C cmt @ 5040-4535'. Spotte Pressured up on perfs to 100 740-437'. WOC. 08/28/19 Ta surface up the 5 ½" & 8 5/8' head, and Kerry Fortner w/ cellar, cut off deadmen, clea	@ 5040'. Circulated hole w/ MLF. Pressure tested csd 25 sx class C cmt w/ 2% CACL @ 2150-1899'. WO DO PSI. Perf'd csg @ 100'. Broke circulation on the 5 agged plug @ 450'. ND BOP. Squeezed 40 sx class C o'. Rigged down & moved off. 09/06/19 Moved in back NM OCD verified cement to surface. Welded on "Al ned location, and moved off.  Rig Release Date:	g, held 600 PSI. 08/28/19 Spotted 50 sx class PC. Tagged plug @ 1950'. Perf'd csg @ 692'.   "" & 8 5/8" csg. Spotted 30 sx class C cmt @ cmt through perfs @ 100' & circulated to choe and welder, dug out cellar, cut off well bove Ground Dry Hole Marker". Backfilled
tbg anchor. Set 5 ½" CIBP C cmt @ 5040-4535'. Spotte Pressured up on perfs to 100 740-437'. WOC. 08/28/19 Ta surface up the 5 ½" & 8 5/8' head, and Kerry Fortner w/ cellar, cut off deadmen, clea	@ 5040'. Circulated hole w/ MLF. Pressure tested csd 25 sx class C cmt w/ 2% CACL @ 2150-1899'. WO DO PSI. Perf'd csg @ 100'. Broke circulation on the 5 agged plug @ 450'. ND BOP. Squeezed 40 sx class C o'. Rigged down & moved off. 09/06/19 Moved in back NM OCD verified cement to surface. Welded on "Al ned location, and moved off.  Rig Release Date:	g, held 600 PSI. 08/28/19 Spotted 50 sx class PC. Tagged plug @ 1950'. Perf'd csg @ 692'.   "" & 8 5/8" csg. Spotted 30 sx class C cmt @ cmt through perfs @ 100' & circulated to choe and welder, dug out cellar, cut off well bove Ground Dry Hole Marker". Backfilled
tbg anchor. Set 5 ½" CIBP C cmt @ 5040-4535'. Spotte Pressured up on perfs to 100 740-437'. WOC. 08/28/19 Ta surface up the 5 ½" & 8 5/8' head, and Kerry Fortner w/ cellar, cut off deadmen, clea	@ 5040'. Circulated hole w/ MLF. Pressure tested csd d 25 sx class C cmt w/ 2% CACL @ 2150-1899'. WO DO PSI. Perf'd csg @ 100'. Broke circulation on the 5 agged plug @ 450'. ND BOP. Squeezed 40 sx class C o'. Rigged down & moved off. 09/06/19 Moved in back NM OCD verified cement to surface. Welded on "Almed location, and moved off.  Rig Release Date:	g, held 600 PSI. 08/28/19 Spotted 50 sx class PC. Tagged plug @ 1950'. Perf'd csg @ 692'. 1/2" & 8 5/8" csg. Spotted 30 sx class C cmt @ cmt through perfs @ 100' & circulated to choe and welder, dug out cellar, cut off well bove Ground Dry Hole Marker". Backfilled
tbg anchor. Set 5 ½" CIBP C cmt @ 5040-4535'. Spotte Pressured up on perfs to 100 740-437'. WOC. 08/28/19 Ta surface up the 5 ½" & 8 5/8' head, and Kerry Fortner w/ cellar, cut off deadmen, clea	@ 5040'. Circulated hole w/ MLF. Pressure tested cs/d 25 sx class C cmt w/ 2% CACL @ 2150-1899'. WO 00 PSI. Perf'd csg @ 100'. Broke circulation on the 5 agged plug @ 450'. ND BOP. Squeezed 40 sx class C o'. Rigged down & moved off. 09/06/19 Moved in back NM OCD verified cement to surface. Welded on "Al ned location, and moved off.  Rig Release Date:  Rig Release Date:  TITLE: Regulatory Technician	g, held 600 PSI. 08/28/19 Spotted 50 sx class PC. Tagged plug @ 1950'. Perf'd csg @ 692'.  ½" & 8 5/8" csg. Spotted 30 sx class C cmt @ cmt through perfs @ 100' & circulated to choe and welder, dug out cellar, cut off well bove Ground Dry Hole Marker". Backfilled
tbg anchor. Set 5 ½" CIBP C cmt @ 5040-4535'. Spotte Pressured up on perfs to 100 740-437'. WOC. 08/28/19 Ta surface up the 5 ½" & 8 5/8' head, and Kerry Fortner w/ cellar, cut off deadmen, clear Spud Date:	@ 5040'. Circulated hole w/ MLF. Pressure tested cs/d 25 sx class C cmt w/ 2% CACL @ 2150-1899'. WO 00 PSI. Perf'd csg @ 100'. Broke circulation on the 5 agged plug @ 450'. ND BOP. Squeezed 40 sx class C o'. Rigged down & moved off. 09/06/19 Moved in back NM OCD verified cement to surface. Welded on "Al ned location, and moved off.  Rig Release Date:  Rig Release Date:  TITLE: Regulatory Technician	g, held 600 PSI. 08/28/19 Spotted 50 sx class PC. Tagged plug @ 1950'. Perf'd csg @ 692'.  ½" & 8 5/8" csg. Spotted 30 sx class C cmt @ cmt through perfs @ 100' & circulated to choe and welder, dug out cellar, cut off well bove Ground Dry Hole Marker". Backfilled
tbg anchor. Set 5 ½" CIBP C cmt @ 5040-4535'. Spotte Pressured up on perfs to 100 740-437'. WOC. 08/28/19 Ta surface up the 5 ½" & 8 5/8' head, and Kerry Fortner w/ cellar, cut off deadmen, clear Spud Date:  I hereby certify that the information of the surface	@ 5040'. Circulated hole w/ MLF. Pressure tested cs/d 25 sx class C cmt w/ 2% CACL @ 2150-1899'. WO 00 PSI. Perf'd csg @ 100'. Broke circulation on the 5 agged plug @ 450'. ND BOP. Squeezed 40 sx class C o'. Rigged down & moved off. 09/06/19 Moved in back NM OCD verified cement to surface. Welded on "Al ned location, and moved off.  Rig Release Date:  Rig Release Date:  TITLE: Regulatory Technician  E-mail address: dflores2@concho.c	g, held 600 PSI. 08/28/19 Spotted 50 sx class PC. Tagged plug @ 1950'. Perf'd csg @ 692'.  "" & 8 5/8" csg. Spotted 30 sx class C cmt @ cmt through perfs @ 100' & circulated to choe and welder, dug out cellar, cut off well bove Ground Dry Hole Marker". Backfilled  DATE: 10/28/19  PHONE: 575-748-6946
tbg anchor. Set 5 ½" CIBP C cmt @ 5040-4535'. Spotte Pressured up on perfs to 100 740-437'. WOC. 08/28/19 Ta surface up the 5 ½" & 8 5/8' head, and Kerry Fortner w/ cellar, cut off deadmen, clea  Spud Date:  I hereby certify that the information  SIGNATURE  Type or print name: Delilah Flores	@ 5040'. Circulated hole w/ MLF. Pressure tested cs/d 25 sx class C cmt w/ 2% CACL @ 2150-1899'. WO 00 PSI. Perf'd csg @ 100'. Broke circulation on the 5 agged plug @ 450'. ND BOP. Squeezed 40 sx class C o'. Rigged down & moved off. 09/06/19 Moved in back NM OCD verified cement to surface. Welded on "Al ned location, and moved off.  Rig Release Date:  Rig Release Date:  TITLE: Regulatory Technician	g, held 600 PSI. 08/28/19 Spotted 50 sx class PC. Tagged plug @ 1950'. Perf'd csg @ 692'.  ½" & 8 5/8" csg. Spotted 30 sx class C cmt @ cmt through perfs @ 100' & circulated to choe and welder, dug out cellar, cut off well bove Ground Dry Hole Marker". Backfilled