

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Carlsbad Field Office

FORM APPROVED
OMB NO. 1004-0137
Expires: January 31, 2018**SUNDRY NOTICES AND REPORTS ON WELLS**
*Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.*5. Lease Serial No.
NMNM97153

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.

8. Well Name and No.
VACA DRAW 9418 10 FED 12H9. API Well No.
30-025-45495-00-X110. Field and Pool or Exploratory Area
RED HILLS11. County or Parish, State
LEA COUNTY, NM

SUBMIT IN TRIPLICATE - Other Instructions on page 2

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

BTA OIL PRODUCERS

Contact: KATY REDDELL

E-Mail: kreddell@btaoil.com

3a. Address

104 SOUTH PECOS STREET
MIDLAND, TX 79701

3b. Phone No. (include area code)

Ph: 432-682-3753 Ext: 139

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Sec 10 T25S R33E SWSW 220FSL 1275FWL
32.138416 N Lat, 103.564659 W Lon

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☐ Notice of Intent☒ Subsequent Report☐ Final Abandonment Notice☐ Acidize☐ Alter Casing☐ Casing Repair☐ Change Plans☐ Convert to Injection☐ Deepen☐ Hydraulic Fracturing☐ New Construction☐ Plug and Abandon☐ Plug Back☐ Production (Start/Resume)☐ Reclamation☐ Recomplete☐ Temporarily Abandon☐ Water Disposal☐ Water Shut-Off☐ Well Integrity☒ Other
Drilling Operations

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompletable horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletable in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.

05/30/2019: SPUD WELL ✓

05/31/2019: DRILLED 14-3/4" HOLE. SET 10-3/4" 40.5#J-55 CASING @1,265' WITH 840 SX CEMENT. CEMENT TO SURFACE.

06/01/2019: TEST 10-3/4" CSG TO 1,500 PSI FOR 30 MIN. GOOD TEST.

06/11/2019: DRILLED 9-7/8 HOLE. SET 7-5/8" 29.7#P-110 CSG @12,007' WITH 980 SX CEMENT. CEMENT TO SURFACE. SUSPEND OPERATION FOR BATCH DRILLING.

08/25/2019: TEST 7-5/8 SHOE TO 13.5 ppg. GOOD TEST.

14. I hereby certify that the foregoing is true and correct.

Electronic Submission #490295 verified by the BLM Well Information System
For BTA OIL PRODUCERS, sent to the Hobbs
Committed to AFMSS for processing by PRISCILLA PEREZ on 10/31/2019 (20PP0264SE)

Name (Printed/Typed) KATY REDDELL

Title REGULATORY ANALYST

Signature (Electronic Submission)

Date 10/29/2019

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved By

Title Accepted for Record

NOV 05 2019

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office Jonathon Shepard
Carlsbad Field Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED **

Additional data for EC transaction #490295 that would not fit on the form

32. Additional remarks, continued

08/31/2019: SIDETRACK DEPTH 12,170' DRILLING 6-3/4" HOLE.

09/10/2019 RUN 5-1/2"X5" CSG TAPERED STRING. 5-1/2" 18#P-110 Wedge 521 17,540' - 11,730') (5-1/2" 20# P-110 ICY TXP-BTC to surface)] with 1345 sx. CEMENT CIRCULATED TO SURFACE.

09/09/2019: RIG RELEASED.