District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 1000 Rio Brazos Road, Aztec, NM 87410 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy, Minerals and Natural Resources Department

to Appropriate District Office HOBBS OCD

Submit Original

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

GAS CAPTURE PLAN

RECEIVED

X Original	Operator & OGRID No.: _	CHEVRON USAINC 4323			
☐ Amended			Date:_	04/18/2019	
Reason	n for Amendment:				

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity.

Note: A C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule 19.15.18.12.A

Well(s)/Production Facility - Dagger Lake CTB #4

The well(s) that will be located at the production facility are shown in the table below.

ie wents) mat win be locat	ee at ale pro	, 	O D110 W11 111 C	10 10010 0010	****	
Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
DL 4 33 LOCH NESS FED COM P1 4H	Pending	UL:O, SEC 4, T22S-R33E	264' FSL, 1347' FEL	4,800	0	
DL 4 33 LOCH NESS FED COM P1 5H	Pending	UL:P, SEC 4, T22S-R33E	264' FSL, 1297' FEL	4,800	0	
DL 4 33 LOCH NESS FED COM P1 6H	Pending	UL:P, SEC 4, T22S-R33E	264' FSL, 1247' FEL	4,800	0	
DL 9 16 LOCH NESS FED COM P1 16H	Pending	UL:O, SEC 4, T22S-R33E	263' FSL, 1372' FEL	4,800	0	
DL 9 16 LOCH NESS FED COM P1 17H	Pending	UL:O, SEC 4, T22S-R33E	264' FSL, 1322' FEL	4,800	0	
DL 9 16 LOCH NESS FED COM P1 18H	Pending	UL:P, SEC 4, T22S-R33E	264' FSL, 1272' FEL	4,800	0	

Gathering System and Pipeline Notification

These wells will be connected to Chevron's Dagger Lake CTB #4 production facility located in Sec 4, T22S-R33E, Lea County, New Mexico during flowback and production. A vendor to handle gas produced from the production facility is to be determined. An amendment will be submitted to the NMOCD once a determination has be made.

Flowback Strategy

After the fracture treatment/completion operations, wells will be turned to permanent production facilities. Wells will have temporary sand catchers (separators) that will be installed at the well location to prevent sand from getting into the flowlines. These sand separators will be blown down periodically which will result in minimal venting of gas. Gas sales will start as soon as the wells start flowing through the production facilities unless there are operational issues with Enterprise's system at that time. Based on current information, it is Chevron's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- NGL Removal On lease and trucked from condensate tanks
 - o Plants are expensive and uneconomical to operate when gas volume declines.
 - o Any residue gas that results in the future may be flared.