

Submit 1 Copy To Appropriate District Office

District I - (575) 393-6161

1625 N. French Dr., Hobbs, NM 88240

District II - (575) 748-1283

811 S. First St., Artesia, NM 88210

District III - (505) 334-6178

1000 Rio Brazos Rd., Aztec, NM 87410

District IV - (505) 476-3460

1220 S. St. Francis Dr., Santa Fe, NM

87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

Form C-103
Revised July 18, 2013

WELL API NO.

30-025-46263

5. Indicate Type of Lease

STATE ☒ FFE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name
Rebel 9/16 B2IP St Com

8. Well Number 1H

9. OGRID Number 14744

10. Pool name or Wildcat
Berry; Bone Spring, South

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Mewbourne Oil Company

3. Address of Operator
PO Box 5270, Hobbs NM 88241

4. Well Location

Unit Letter I: 2195 feet from the South line and 590 feet from the East line

Section 9 Township 21S Range 34E NMPM Lea County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3703' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

DOWNHOLE COMMINGLE ☐

CLOSED-LOOP SYSTEM ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ P AND A ☐

CASING/CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

12/31/19

Spud 17 1/2" hole @ 1955'. Ran 1940' of 13 3/8" 54.5# J55 ST&C Csg. Cemented with 1150 sks Class C w/additives. Mixed @ 12.5#/g w/2.12 yd. Tail w/200 sks Class C w/0.5% CaCl2. Mixed @ 14.8#/g w/1.33 yd. Displaced w/294 bbls FW. Plug down @ 4:15 PM 01/02/20. Circ 461 sks of cmt to the pit. Test BOPE to 5000# & Annular to 3500#. At 10:45 P.M. 1/03/20, tested csg to 1500# for 30 mins, held OK. FIT to 10.5 PPG EMW. Drilled out with 12 1/4" bit.

Spud Date: 12/31/2019

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Ruby Caballero TITLE Regulatory DATE 1/09/20

Type or print name Ruby Caballero E-mail address: rcaballero@mewbourne.com PHONE: 575-393-5905

For State Use Only

APPROVED BY: [Signature] TITLE Petroleum Engineer DATE 01/17/20

Conditions of Approval (if any):