Office	State of New 1	Mexico	Form C-103
<u>District I</u> – (575) 393-6161	Energy, Minerals and N	atural Resources	Revised July 18, 2013
1625 N. French Dr., Hobbs, NM 88240 District II – (575) 748-1283			WELL API NO. 30-025-45569
811 S. First St., Artesia, NM 88210	OIL CONSERVATION		C T 1' + TC CT
District III - (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. F	rancis Dr.	CO STATE ⊠ FEE □
District IV - (505) 476-3460	Santa Fe, NM	87505 ARS U	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505		rancis Dr. 87505 HOBBS 00	20
87505 SUNDRY NOTIC (DO NOT USE THIS FORM FOR PROPOS. DIFFERENT RESERVOIR. USE "APPLICATION PROPOSALS.)	ES AND REPORTS ON WEL	LS CR 24	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOS	ALS TO DRILL OR TO DEEPEN OR	PLUG BACK PO A	He ord 29/20 B1PA State Com
DIFFERENT RESERVOIR. USE "APPLICA PROPOSALS.)	ATION FOR PERMIT" (FORM C-101	FOR SUCH RECE!	8. Well Number 1/H
1. Type of Well: Oil Well 🔀 🤇	Gas Well 🔲 Other	RES	art -
2. Name of Operator			9. OGRID Number
Mewbourne Oil Company			14744
3. Address of Operator PO Box 5270, Hobbs NM 88240			10. Pool name or Wildcat Scharb; Bone Spring
<u> </u>			Scharo, Bone Spring
4. Well Location Unit Letter P : 205	Control No. 1	1:1 12001	Cont Constitution Front
		line and1300'_	-
Section 29	Township 19S	Range 35E	NMPM Lea County
	11. Elevation (Show whether I	DK, KKB, KI, GK, etc.,	,
	3743 GE		
12 Check A	ppropriate Box to Indicate	Nature of Notice	Penart or Other Data
12. Check A	ppropriate Box to indicate	nature of notice,	Report of Other Data
NOTICE OF INT	TENTION TO:	SUB	SEQUENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WOR	K ☐ ALTERING CASING ☐
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRI	ILLING OPNS. P AND A
PULL OR ALTER CASING	MULTIPLE COMPL	CASING/CEMENT	T JOB 🛛
DOWNHOLE COMMINGLE			
CLOSED-LOOP SYSTEM			
			_
OTHER:		OTHER:	
OTHER: 13. Describe proposed or comple		all pertinent details, and	d give pertinent dates, including estimated date
OTHER: 13. Describe proposed or complete of starting any proposed work.	k). SEE RULE 19.15.7.14 NM	all pertinent details, and	d give pertinent dates, including estimated date mpletions: Attach wellbore diagram of
OTHER: 13. Describe proposed or comple	k). SEE RULE 19.15.7.14 NM	all pertinent details, and	
OTHER: 13. Describe proposed or complete of starting any proposed worth proposed completion or recomplete to the complete of	k). SEE RULE 19.15.7.14 NM	all pertinent details, and	
OTHER: 13. Describe proposed or complete of starting any proposed worth proposed completion or recomplete of the proposed completion or recomplete or proposed complete or recomplete o	k). SEE RULE 19.15.7.14 NM mpletion.	all pertinent details, and IAC. For Multiple Cor	mpletions: Attach wellbore diagram of
OTHER: 13. Describe proposed or complete of starting any proposed work proposed completion or recomplete of the proposed completion of the proposed or completion of the proposed work proposed work proposed completion or recompletion or recompletion or proposed completion or proposed work proposed work proposed completion or recompletion or proposed work proposed work proposed work proposed completion or recompletion or proposed work proposed	k). SEE RULE 19.15.7.14 NM mpletion. ' of 13 3/8" 54.5# J55 ST&C cs	all pertinent details, and IAC. For Multiple Cor	mpletions: Attach wellbore diagram of sks Class C w/additives. Mixed @ 13.5#/g
OTHER: 13. Describe proposed or comple of starting any proposed wor proposed completion or reco 02/04/2020 Spud 17 1/2" hole @ 1975'. Ran 1960 w/1.77 yd. Tail w/200 sks Class C w/0	k). SEE RULE 19.15.7.14 NM mpletion. of 13 3/8" 54.5# J55 ST&C cs 0.5% CaCl2. Mixed @ 14.8#/g	all pertinent details, and IAC. For Multiple Cores. Seg. Cemented w/1375 sw/1.33 yd. Displaced w/1394.	mpletions: Attach wellbore diagram of
OTHER: 13. Describe proposed or comple of starting any proposed wor proposed completion or reco 02/04/2020 Spud 17 1/2" hole @ 1975'. Ran 1960 w/1.77 yd. Tail w/200 sks Class C w/0	k). SEE RULE 19.15.7.14 NM mpletion. of 13 3/8" 54.5# J55 ST&C cs 0.5% CaCl2. Mixed @ 14.8#/g e pits. Test BOPE to 5000# & A	all pertinent details, and IAC. For Multiple Cores. Seg. Cemented w/1375 sw/1.33 yd. Displaced w/1394.	sks Class C w/additives. Mixed @ 13.5#/g w/296 bbls of BW. Plug down @ 5:00 P.M.
OTHER: 13. Describe proposed or complete of starting any proposed worth proposed completion or reconcept of the proposed completion of the proposed completion of the proposed completion of the proposed completion or reconcept of the proposed com	k). SEE RULE 19.15.7.14 NM mpletion. of 13 3/8" 54.5# J55 ST&C cs 0.5% CaCl2. Mixed @ 14.8#/g e pits. Test BOPE to 5000# & A	all pertinent details, and IAC. For Multiple Cores. Seg. Cemented w/1375 sw/1.33 yd. Displaced w/1394.	sks Class C w/additives. Mixed @ 13.5#/g w/296 bbls of BW. Plug down @ 5:00 P.M.
OTHER: 13. Describe proposed or complete of starting any proposed worth proposed completion or recomplete of starting any proposed worth proposed completion or recomplete of the starting any proposed worth proposed completion or recomplete of the starting any proposed worth proposed completion or recomplete of the starting any proposed worth propos	k). SEE RULE 19.15.7.14 NM mpletion. Of of 13 3/8" 54.5# J55 ST&C cs 0.5% CaCl2. Mixed @ 14.8#/g e pits. Test BOPE to 5000# & A W. Drilled out with 12 1/4" bit.	all pertinent details, and IAC. For Multiple Consider Sp. Cemented w/1375 sw/1.33 yd. Displaced Annular to 3500#. At 4	mpletions: Attach wellbore diagram of sks Class C w/additives. Mixed @ 13.5#/g w/296 bbls of BW. Plug down @ 5:00 P.M. :00 P.M. 02/08/20, tested csg to 1500# for 30
OTHER: 13. Describe proposed or completed of starting any proposed worth proposed completion or recompleted of starting any proposed worth proposed completion or recompleted 17 1/2" hole @ 1975'. Ran 1960 w/1.77 yd. Tail w/200 sks Class C w/02/07/2020. Circ 570 sks of cmt to the mins, held OK. FIT to 10.5 PPG EMV 02/10/2020 TD'ed 12 1/4" hole @ 3650'. Ran 363	k). SEE RULE 19.15.7.14 NM mpletion. Of of 13 3/8" 54.5# J55 ST&C cs 0.5% CaCl2. Mixed @ 14.8#/g e pits. Test BOPE to 5000# & AV. Drilled out with 12 1/4" bit. Of of 9 5/8" 40# HCL80 LT&C	all pertinent details, and IAC. For Multiple Consider. Sign Cemented w/1375 s w/1.33 yd. Displaced w/1.33 yd. Annular to 3500#. At 4. Csg. Cemented with 8	mpletions: Attach wellbore diagram of sks Class C w/additives. Mixed @ 13.5#/g w/296 bbls of BW. Plug down @ 5:00 P.M.:00 P.M. 02/08/20, tested csg to 1500# for 30
OTHER: 13. Describe proposed or completed of starting any proposed worth proposed completion or recompleted of starting any proposed worth proposed completion or recompleted 17 1/2" hole @ 1975'. Ran 1960 w/1.77 yd. Tail w/200 sks Class C w/02/07/2020. Circ 570 sks of cmt to the mins, held OK. FIT to 10.5 PPG EMV 02/10/2020 TD'ed 12 1/4" hole @ 3650'. Ran 363 w/1.77 yd. Tail w/200 sks Class C w/1.77 yd. Tail w/200 sks Class C w/1.77 yd. Tail w/200 sks Class C w/1.75 w/1.7	k). SEE RULE 19.15.7.14 NM mpletion. Tof 13 3/8" 54.5# J55 ST&C cs 0.5% CaCl2. Mixed @ 14.8#/g e pits. Test BOPE to 5000# & AV. Drilled out with 12 1/4" bit. O' of 9 5/8" 40# HCL80 LT&C additives. Mixed @ 14.8#/g w/	all pertinent details, and IAC. For Multiple Consider. Sig. Cemented w/1375 s w/1.33 yd. Displaced w/1.33 yd. Annular to 3500#. At 4. Csg. Cemented with 8 1.33 yd. Displaced w/2	mpletions: Attach wellbore diagram of sks Class C w/additives. Mixed @ 13.5#/g w/296 bbls of BW. Plug down @ 5:00 P.M.:00 P.M. 02/08/20, tested csg to 1500# for 30 850 sks Class C w/additives. Mixed @ 13.5#/g 171 bbl of FW. Plug down @ 9:00 P.M.
OTHER: 13. Describe proposed or completed of starting any proposed work proposed completion or recologous proposed	k). SEE RULE 19.15.7.14 NM mpletion. Of of 13 3/8" 54.5# J55 ST&C cs 0.5% CaCl2. Mixed @ 14.8#/g e pits. Test BOPE to 5000# & AW. Drilled out with 12 1/4" bit. Of of 9 5/8" 40# HCL80 LT&C additives. Mixed @ 14.8#/g w/ bits. Set Cameron mandrel hang	all pertinent details, and IAC. For Multiple Cores. Cemented w/1375 s w/1.33 yd. Displaced w/1375 s Annular to 3500#. At 4 Cass. Cemented with 8 1.33 yd. Displaced w/2 er through BOP w/90k	mpletions: Attach wellbore diagram of sks Class C w/additives. Mixed @ 13.5#/g w/296 bbls of BW. Plug down @ 5:00 P.M.:00 P.M. 02/08/20, tested csg to 1500# for 30
OTHER: 13. Describe proposed or completed of starting any proposed worth proposed completion or recompleted of starting any proposed worth proposed completion or recompleted 17 1/2" hole @ 1975'. Ran 1960 w/1.77 yd. Tail w/200 sks Class C w/02/07/2020. Circ 570 sks of cmt to the mins, held OK. FIT to 10.5 PPG EMV 02/10/2020 TD'ed 12 1/4" hole @ 3650'. Ran 363 w/1.77 yd. Tail w/200 sks Class C w/1.77 yd. Tail w/200 sks Class C w/1.77 yd. Tail w/200 sks Class C w/1.75 w/1.7	k). SEE RULE 19.15.7.14 NM mpletion. Of of 13 3/8" 54.5# J55 ST&C cs 0.5% CaCl2. Mixed @ 14.8#/g e pits. Test BOPE to 5000# & AW. Drilled out with 12 1/4" bit. Of of 9 5/8" 40# HCL80 LT&C additives. Mixed @ 14.8#/g w/ bits. Set Cameron mandrel hang	all pertinent details, and IAC. For Multiple Cores. Cemented w/1375 s w/1.33 yd. Displaced w/1375 s Annular to 3500#. At 4 Cass. Cemented with 8 1.33 yd. Displaced w/2 er through BOP w/90k	mpletions: Attach wellbore diagram of sks Class C w/additives. Mixed @ 13.5#/g w/296 bbls of BW. Plug down @ 5:00 P.M.:00 P.M. 02/08/20, tested csg to 1500# for 30 850 sks Class C w/additives. Mixed @ 13.5#/g 171 bbl of FW. Plug down @ 9:00 P.M.
OTHER: 13. Describe proposed or comple of starting any proposed wor proposed completion or reco 02/04/2020 Spud 17 1/2" hole @ 1975'. Ran 1960 w/1.77 yd. Tail w/200 sks Class C w/02/07/2020. Circ 570 sks of cmt to the mins, held OK. FIT to 10.5 PPG EMV 02/10/2020 TD'ed 12 1/4" hole @ 3650'. Ran 363 w/1.77 yd. Tail w/200 sks Class C w/02/10/20. Circ 149 sks of cmt to the p 1500# for 30 mins, held OK. FIT test	k). SEE RULE 19.15.7.14 NM mpletion. Of of 13 3/8" 54.5# J55 ST&C cs 0.5% CaCl2. Mixed @ 14.8#/g e pits. Test BOPE to 5000# & AW. Drilled out with 12 1/4" bit. Of of 9 5/8" 40# HCL80 LT&C additives. Mixed @ 14.8#/g w/ bits. Set Cameron mandrel hang to EMW of 10.5 PPG. Drilled of	all pertinent details, and IAC. For Multiple Cores. Cemented w/1375 s w/1.33 yd. Displaced w/1.33 yd. Displaced w/2 cer through BOP w/90k out with 8 3/4" bit.	mpletions: Attach wellbore diagram of sks Class C w/additives. Mixed @ 13.5#/g w/296 bbls of BW. Plug down @ 5:00 P.M.:00 P.M. 02/08/20, tested csg to 1500# for 30 850 sks Class C w/additives. Mixed @ 13.5#/g 171 bbl of FW. Plug down @ 9:00 P.M.
OTHER: 13. Describe proposed or completed of starting any proposed work proposed completion or recologous proposed	k). SEE RULE 19.15.7.14 NM mpletion. Of of 13 3/8" 54.5# J55 ST&C cs 0.5% CaCl2. Mixed @ 14.8#/g e pits. Test BOPE to 5000# & AW. Drilled out with 12 1/4" bit. Of of 9 5/8" 40# HCL80 LT&C additives. Mixed @ 14.8#/g w/ bits. Set Cameron mandrel hang	all pertinent details, and IAC. For Multiple Cores. Cemented w/1375 s w/1.33 yd. Displaced w/1.33 yd. Displaced w/2 cer through BOP w/90k out with 8 3/4" bit.	mpletions: Attach wellbore diagram of sks Class C w/additives. Mixed @ 13.5#/g w/296 bbls of BW. Plug down @ 5:00 P.M.:00 P.M. 02/08/20, tested csg to 1500# for 30 850 sks Class C w/additives. Mixed @ 13.5#/g 171 bbl of FW. Plug down @ 9:00 P.M.
OTHER: 13. Describe proposed or comple of starting any proposed wor proposed completion or reco 02/04/2020 Spud 17 1/2" hole @ 1975'. Ran 1960 w/1.77 yd. Tail w/200 sks Class C w/02/07/2020. Circ 570 sks of cmt to the mins, held OK. FIT to 10.5 PPG EMV 02/10/2020 TD'ed 12 1/4" hole @ 3650'. Ran 363 w/1.77 yd. Tail w/200 sks Class C w/02/10/20. Circ 149 sks of cmt to the p 1500# for 30 mins, held OK. FIT test	k). SEE RULE 19.15.7.14 NM mpletion. Of of 13 3/8" 54.5# J55 ST&C cs 0.5% CaCl2. Mixed @ 14.8#/g e pits. Test BOPE to 5000# & AW. Drilled out with 12 1/4" bit. Of of 9 5/8" 40# HCL80 LT&C additives. Mixed @ 14.8#/g w/ bits. Set Cameron mandrel hang to EMW of 10.5 PPG. Drilled of	all pertinent details, and IAC. For Multiple Cores. Cemented w/1375 s w/1.33 yd. Displaced w/1.33 yd. Displaced w/2 cer through BOP w/90k out with 8 3/4" bit.	mpletions: Attach wellbore diagram of sks Class C w/additives. Mixed @ 13.5#/g w/296 bbls of BW. Plug down @ 5:00 P.M.:00 P.M. 02/08/20, tested csg to 1500# for 30 850 sks Class C w/additives. Mixed @ 13.5#/g 171 bbl of FW. Plug down @ 9:00 P.M.
OTHER: 13. Describe proposed or comple of starting any proposed wor proposed completion or reco 02/04/2020 Spud 17 1/2" hole @ 1975'. Ran 1960 w/1.77 yd. Tail w/200 sks Class C w/02/07/2020. Circ 570 sks of cmt to the mins, held OK. FIT to 10.5 PPG EMV 02/10/2020 TD'ed 12 1/4" hole @ 3650'. Ran 363 w/1.77 yd. Tail w/200 sks Class C w/02/10/20. Circ 149 sks of cmt to the p 1500# for 30 mins, held OK. FIT test	k). SEE RULE 19.15.7.14 NM mpletion. Of of 13 3/8" 54.5# J55 ST&C cs 0.5% CaCl2. Mixed @ 14.8#/g e pits. Test BOPE to 5000# & AW. Drilled out with 12 1/4" bit. Of of 9 5/8" 40# HCL80 LT&C additives. Mixed @ 14.8#/g w/ pits. Set Cameron mandrel hang to EMW of 10.5 PPG. Drilled or Rig Relea	all pertinent details, and IAC. For Multiple Corseg. Cemented w/1375 s w/1.33 yd. Displaced w/2 Annular to 3500#. At 4 Csg. Cemented with 8 1.33 yd. Displaced w/2 er through BOP w/90k out with 8 3/4" bit.	sks Class C w/additives. Mixed @ 13.5#/g w/296 bbls of BW. Plug down @ 5:00 P.M.:00 P.M. 02/08/20, tested csg to 1500# for 30 850 sks Class C w/additives. Mixed @ 13.5#/g 271 bbl of FW. Plug down @ 9:00 P.M.:#. At 11:30 A.M. 02/11/20, tested csg to
OTHER: 13. Describe proposed or completed of starting any proposed worth proposed completion or reconcept of the proposed completion of the proposed complete of the propo	k). SEE RULE 19.15.7.14 NM mpletion. Of of 13 3/8" 54.5# J55 ST&C cs 0.5% CaCl2. Mixed @ 14.8#/g e pits. Test BOPE to 5000# & AW. Drilled out with 12 1/4" bit. Of of 9 5/8" 40# HCL80 LT&C additives. Mixed @ 14.8#/g w/ pits. Set Cameron mandrel hang to EMW of 10.5 PPG. Drilled or Rig Relea	all pertinent details, and IAC. For Multiple Corseg. Cemented w/1375 s w/1.33 yd. Displaced w/2 Annular to 3500#. At 4 Csg. Cemented with 8 1.33 yd. Displaced w/2 er through BOP w/90k out with 8 3/4" bit.	sks Class C w/additives. Mixed @ 13.5#/g w/296 bbls of BW. Plug down @ 5:00 P.M.:00 P.M. 02/08/20, tested csg to 1500# for 30 850 sks Class C w/additives. Mixed @ 13.5#/g 271 bbl of FW. Plug down @ 9:00 P.M.:#. At 11:30 A.M. 02/11/20, tested csg to
OTHER: 13. Describe proposed or completed of starting any proposed work proposed completion or recologous proposed completion proposed completion proposed completion proposed completion proposed completion proposed completion proposed completi	k). SEE RULE 19.15.7.14 NM mpletion. Of of 13 3/8" 54.5# J55 ST&C cs 0.5% CaCl2. Mixed @ 14.8#/g e pits. Test BOPE to 5000# & AW. Drilled out with 12 1/4" bit. Of of 9 5/8" 40# HCL80 LT&C additives. Mixed @ 14.8#/g w/ bits. Set Cameron mandrel hang to EMW of 10.5 PPG. Drilled on Rig Release bove is true and complete to the	all pertinent details, and IAC. For Multiple Corses. Cemented w/1375 s w/1.33 yd. Displaced w/1.33 yd. Displaced w/2. Csg. Cemented with 8 1.33 yd. Displaced w/2 er through BOP w/90k out with 8 3/4" bit. ase Date:	sks Class C w/additives. Mixed @ 13.5#/g w/296 bbls of BW. Plug down @ 5:00 P.M.:00 P.M. 02/08/20, tested csg to 1500# for 30 850 sks Class C w/additives. Mixed @ 13.5#/g 271 bbl of FW. Plug down @ 9:00 P.M. #. At 11:30 A.M. 02/11/20, tested csg to
OTHER: 13. Describe proposed or completed of starting any proposed worth proposed completion or reconcept of the proposed completion of the proposed complete of the propo	k). SEE RULE 19.15.7.14 NM mpletion. Of of 13 3/8" 54.5# J55 ST&C cs 0.5% CaCl2. Mixed @ 14.8#/g e pits. Test BOPE to 5000# & AW. Drilled out with 12 1/4" bit. Of of 9 5/8" 40# HCL80 LT&C additives. Mixed @ 14.8#/g w/ pits. Set Cameron mandrel hang to EMW of 10.5 PPG. Drilled or Rig Relea	all pertinent details, and IAC. For Multiple Corses. Cemented w/1375 s w/1.33 yd. Displaced w/1.33 yd. Displaced w/2. Csg. Cemented with 8 1.33 yd. Displaced w/2 er through BOP w/90k out with 8 3/4" bit. ase Date:	sks Class C w/additives. Mixed @ 13.5#/g w/296 bbls of BW. Plug down @ 5:00 P.M.:00 P.M. 02/08/20, tested csg to 1500# for 30 850 sks Class C w/additives. Mixed @ 13.5#/g 271 bbl of FW. Plug down @ 9:00 P.M.:#. At 11:30 A.M. 02/11/20, tested csg to
OTHER: 13. Describe proposed or completed of starting any proposed work proposed completion or recologous described by the proposed described by the pr	k). SEE RULE 19.15.7.14 NM mpletion. Of of 13 3/8" 54.5# J55 ST&C cs 0.5% CaCl2. Mixed @ 14.8#/g e pits. Test BOPE to 5000# & AW. Drilled out with 12 1/4" bit. Of of 9 5/8" 40# HCL80 LT&C additives. Mixed @ 14.8#/g w/oits. Set Cameron mandrel hang to EMW of 10.5 PPG. Drilled on Rig Releated bove is true and complete to the TITLE_Regard.	all pertinent details, and IAC. For Multiple Consider. Sign Cemented w/1375 s w/1.33 yd. Displaced w/2 annular to 3500#. At 4 Csg. Cemented with 8 1.33 yd. Displaced w/2 er through BOP w/90k out with 8 3/4" bit. Sign Cemented with 8 assertion between the best of my knowledge gulatory	sks Class C w/additives. Mixed @ 13.5#/g w/296 bbls of BW. Plug down @ 5:00 P.M.:00 P.M. 02/08/20, tested csg to 1500# for 30 850 sks Class C w/additives. Mixed @ 13.5#/g 271 bbl of FW. Plug down @ 9:00 P.M.:#. At 11:30 A.M. 02/11/20, tested csg to
OTHER: 13. Describe proposed or completed of starting any proposed worth proposed completion or recologory	k). SEE RULE 19.15.7.14 NM mpletion. Of of 13 3/8" 54.5# J55 ST&C cs 0.5% CaCl2. Mixed @ 14.8#/g e pits. Test BOPE to 5000# & AW. Drilled out with 12 1/4" bit. Of of 9 5/8" 40# HCL80 LT&C additives. Mixed @ 14.8#/g w/oits. Set Cameron mandrel hang to EMW of 10.5 PPG. Drilled on Rig Releated bove is true and complete to the TITLE_Regard.	all pertinent details, and IAC. For Multiple Consider. Sign Cemented w/1375 s w/1.33 yd. Displaced w/2 annular to 3500#. At 4 Csg. Cemented with 8 1.33 yd. Displaced w/2 er through BOP w/90k out with 8 3/4" bit. Sign Cemented with 8 assertion between the best of my knowledge gulatory	sks Class C w/additives. Mixed @ 13.5#/g w/296 bbls of BW. Plug down @ 5:00 P.M.:00 P.M. 02/08/20, tested csg to 1500# for 30 850 sks Class C w/additives. Mixed @ 13.5#/g 271 bbl of FW. Plug down @ 9:00 P.M. #. At 11:30 A.M. 02/11/20, tested csg to
OTHER: 13. Describe proposed or completed of starting any proposed work proposed completion or recologous described by the proposed described by the pr	k). SEE RULE 19.15.7.14 NM mpletion. Of of 13 3/8" 54.5# J55 ST&C cs 0.5% CaCl2. Mixed @ 14.8#/g e pits. Test BOPE to 5000# & AW. Drilled out with 12 1/4" bit. Of of 9 5/8" 40# HCL80 LT&C additives. Mixed @ 14.8#/g w/oits. Set Cameron mandrel hang to EMW of 10.5 PPG. Drilled on Rig Releated bove is true and complete to the TITLE_Regard.	all pertinent details, and IAC. For Multiple Consider. Sign Cemented w/1375 s w/1.33 yd. Displaced w/2 annular to 3500#. At 4 Csg. Cemented with 8 1.33 yd. Displaced w/2 er through BOP w/90k out with 8 3/4" bit. Sign Cemented with 8 assertion between the best of my knowledge gulatory	mpletions: Attach wellbore diagram of sks Class C w/additives. Mixed @ 13.5#/g w/296 bbls of BW. Plug down @ 5:00 P.M. :00 P.M. 02/08/20, tested csg to 1500# for 30 850 sks Class C w/additives. Mixed @ 13.5#/g 271 bbl of FW. Plug down @ 9:00 P.M. :#. At 11:30 A.M. 02/11/20, tested csg to e and belief. DATE02/19/2020 PHONE: _575-393-5905
OTHER: 13. Describe proposed or completed of starting any proposed worth proposed completion or recologory	k). SEE RULE 19.15.7.14 NM mpletion. Of of 13 3/8" 54.5# J55 ST&C cs 0.5% CaCl2. Mixed @ 14.8#/g e pits. Test BOPE to 5000# & AW. Drilled out with 12 1/4" bit. Of of 9 5/8" 40# HCL80 LT&C additives. Mixed @ 14.8#/g w/oits. Set Cameron mandrel hang to EMW of 10.5 PPG. Drilled on Rig Releated bove is true and complete to the TITLE_Regard.	all pertinent details, and IAC. For Multiple Consider. Sign Cemented w/1375 s w/1.33 yd. Displaced w/2 annular to 3500#. At 4 Csg. Cemented with 8 1.33 yd. Displaced w/2 er through BOP w/90k out with 8 3/4" bit. Sign Cemented with 8 assertion between the best of my knowledge gulatory	### sks Class C w/additives. Mixed @ 13.5#/g w/296 bbls of BW. Plug down @ 5:00 P.M. :00 P.M. 02/08/20, tested csg to 1500# for 30 B50 sks Class C w/additives. Mixed @ 13.5#/g 171 bbl of FW. Plug down @ 9:00 P.M. :#. At 11:30 A.M. 02/11/20, tested csg to be and belief. ### DATE02/19/2020 PHONE: _575-393-5905