Submit 1 Copy To Appropriate District Office	State of New Mexico	Form C-103
<u>District 1</u> – (575) 393-6161 1625 N. French Dr., Hobbs, NM 88240	Energy, Minerals and Natural Resources	Revised July 18, 2013 WELL API NO.
District II - (575) 748-1283	OIL CONSERVATION DIVISION	30-025-46736
811 S. First St., Artesia, NM 88210 <u>District III</u> – (505) 334-6178	1220 South St. Francis Day	5. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u> – (505) 476-3460	Santa Fe, NM 356	STATE FEE 6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM	Santa Fe, NM 8500 2020	313956
87505 SUNDRY NOT	TICES AND REPORTS ON WELLS 9. 4 L	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROP DIFFERENT RESERVOIR. USE "APPL	OSALS TO DRILL OR TO DEEPEN OF PLUG BACK TED ICATION FOR PERMIT" (FORM C-101) FOR SUCTION Gas Well Other	NEPTUNE 10 STATE COM
PROPOSALS.) 1. Type of Well: Oil Well 🗖	Gas Well Other	8. Well Number 303H
2. Name of Operator		9. OGRID Number
	SOURCES	7377
3. Address of Operator	V 2267 MIDI AND TV 70702	10. Pool name or Wildcat 59900 TRIPLE X; BONE SPRING
4 Well Location	X 2267, MIDLAND TX 79702	L
Unit Letter P :870 feet from the SOUTH line and 931 feet from the EAST line		
Section 10	Township 24S Range 33E	NMPM County
	11. Elevation (Show whether DR, RKB, RT, GR, etc.)	
3608 GL		
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data		
· · ·		
		SEQUENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WOR	_
TEMPORARILY ABANDON DULL OR ALTER CASING		
DOWNHOLE COMMINGLE		
CLOSED-LOOP SYSTEM		
OTHER:		L CSG D
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of		
proposed completion or recompletion.		
01/30/2020 20" Conductor @ 115'		
01/30/2020 17-1/2" HOLE 01/30/2020 Surface Hole @ 1,360' MD, 1,360' TVD		
Casing shoe @ 1,341' MD		
Ran 13-3/8" 54.5# J-55 STC Lead Cement w/ 875 sx Class C(1.81 yld, 13.5 ppg), Trail w/200 sx Class C (1.35 yld, 14.8 ppg) Test casing to 1,500 psi for 30 min -Good Circ 558 sx cement to surface Resume drilling 12-1/4" hole		
lest casing to 1,500 psi for 30 min -Good Circ 558 sx cement to surface Resume drilling 12-1/4" note		
		•
Smud Date:	Pig Palagea Data:	····]
Spud Date: 01/30/2020	Rig Release Date:	
Spud Date: 01/30/2020	Rig Release Date:	
01/30/2020	Rig Release Date:	e and belief.
01/30/2020		e and belief.
I hereby certify that the information	above is true and complete to the best of my knowledge	
I hereby certify that the information SIGNATURE	TITLE Sr. Regulatory Adminis	stratorDATE_02/18/2020
I hereby certify that the information SIGNATURE Type or print name Emily Follis	TITLE Sr. Regulatory Adminis	
I hereby certify that the information SIGNATURE	TITLE Sr. Regulatory Administration E-mail address: emily_follis@ed	ogresources.comONE: 432-848-9163
I hereby certify that the information SIGNATURE Type or print name Emily Follis	TITLE Sr. Regulatory Adminis	ogresources.comONE: 432-848-9163