Office			State of New Me		Form C-103		
District I - (57		Energy, N	inerals and Nati	Iral Resources	WELL API N		sed July 18, 2013
District II - (57	5 N. French Dr., Hobbs, NM 88240 rict II – (575) 748-1283				20 025 46752		
	CHII - (5/5) /48-1283 OIL CONSERVATION DIVISION First St., Artesia, NM 88210 0IL CONSERVATION DIVISION CHIII - (505) 334-6178 1220 South St. Francisco Bio Brizos Rd. Actes NM 87410 1220 South St. Francisco				5. Indicate Type of Lease		
1000 Rio Brazo					STATE FEE 6. State Oil & Gas Lease No.		
<u>District IV</u> – (5 1220 S. St. Fra	05) 476-3460 ncis Dr., Santa Fe, NM	L		FEB 2 4 2020).
87505				FEB		0561	
(DO NOT USE	SUNDRY NO	OSALS TO DRILL O	ORTS ON WELLS R TO DEEPEN OR PL	UG BACKENVEL	7. Lease Nan	ne or Unit Agre	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG PARTEEN DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SECURIT PROPOSALS.)					a		
1. Type of Well: Oil Well 🛛 Gas Well 🗌 Other					#20211		
2. Name of Operator EOG RESOURCES					9. OGRID Number 7377		
3. Address of Operator					10. Pool name or Wildcat		
P O BOX 2267, MIDLAND TX 79702					59900 TRIPLE X; BONE SPRING		
4. Well Location Unit Letter M : 304 feet from the SOUTH line and 534 feet from the WEST line							
Sec	tion 32			ange 33E	NMPM	County	LEA CO
11. Elevation (Show whether DR, RKB, RT, GR, etc.)							
3661 GL							
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data							
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:							
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK							
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRIL							
OTHER:		_		*	L CSG		
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date							
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.							
02/02/2020 20" Conductor @ 115'							
02/18/2020 17-1/2" HOLE							
Casing shoe @ 1,380' MD							
Ran 13-3/8" 54.5# J-55 STC Load Compart w/ 860 cx Class C/1 76 vld, 13 5 ppg), Trail w/ 200 cx Class C /1 36 vld, 14 8 ppg)							
Lead Cement w/ 860 sx Class C(1.76 yld, 13.5 ppg), Trail w/ 200 sx Class C (1.36 yld, 14.8 ppg) Test casing to 1,500 psi for 30 min -Good. Circ 386 sx cement to surface Resume drilling 12-1/4" hole							
Spud Date:	02/02/202	20	Rig Release D	ate:			
				L			
Therefore and if the table information above in two and a second to the base of multiples and by the first							
I hereby certify that the information above is true and complete to the best of my knowledge and belief.							
SIGNATURE MA TITLE Sr. Regulatory Administrator DATE 02/20/2020							
Type or print name Emily Føllis E-mail address: emily_follis@eogresources.comONE: 432-848-9163 For State Use Only Engineer							
TUI STALE US		·/~~		Petroleum En	gineer		la u. l
APPROVED		tech -	TITLE			DATE 02	124/2020
Conditions of Approval (If any):							

K5 220-20