<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico

Energy, Minerals and Natural Resources Department Oil Conservation Division HOBBS

1220 South St. Francis Dr. Santa Fe, NM 87505

MAR 0 3 2020

Submit Original to Appropriate District Office

GAS CAPTURE PLAN

	Date:	1-2	1 - 20	19
--	-------	-----	--------	----

RECEIVED

 □ Original Operator & OGRID No.: OXY USA INC. - 16696 ☐ Amended - Reason for Amendment:

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity.

Note: Form C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15.18.12 NMAC). Well(s)/Production Facility - Red Tank 27-28 CTB

The well(s) that will be located at the production facility are shown in the table below.

The well(s) that will be loca	ited at the produc	don facility are si	lown in the table beig	T	Flared	1
Well Name	API	Well Location (ULSTR)	Footages	Expecte d	or	Comments
				MCF/D	Vented	Comments
T C-4 27 24 F-1		II'A D. C	2002577	MCF/D	vented	
Taco Cat 27_34 Fed	d Pending	Unit B Sec.	280'FNL	4,400	0	
Com #12H		27 T22S R32E	2380'FEL			
Taco Cat 27_34 Fed	Pending	Unit B Sec.	280'FNL	4,400	0	
Com #13H		27 T22S R32E	2345'FEL			
Taco Cat 27_34 Fed	Pending	Unit C Sec.	520'FNL	2,200	0	
Com #22H 30-02-9	Pending — 46933	27 T22S R32E	1880'FWL		<u> </u>	l
Taco Cat 27_34 Fed	Pending	Unit C Sec.	520'FNL	2,200	0	
Com #23H	Pending	27 T22S R32E	1915'FWL			
Taco Cat 27_34 Fed	Dandina	Unit C Sec. 27	340'FNL	4 200	0	
Com #32H	Pending	T22S R32E	1880'FWL	4,300		
Taco Cat 27 34 Fed	D 1	Unit C Sec. 27	340'FNL	4 200	0	
Com #33H	Pending	T22S R32E	1915'FWL	4,300		
Taco Cat 27 34 Fed	30-025-44933	Unit D Sec. 27	260'FNL	3,000	0	
Com #11H		T22S R32E	855'FWL			
Taco Cat 27 34 Fed	30-025-44934	Unit D Sec. 27	260'FNL	1,300	0	
Com #21H		T22S R32E	785'FWL			
Taco Cat 27 34 Fed	30-025-44935	Unit D Sec. 27	260'FNL	1,300	0	
Com #31H		T22S R32E	820'FWL)
Lion Oil 28 33 Fed Com		Unit A Sec. 28	911'FNL			
# 24H	Pending	T22S R32E	1155'FEL	2,200	0	
Lion Oil 28 33 Fed Com	Pending	Unit A Sec. 28	919'FNL	2,200	0	
# 25H		T22S R32E	1121'FEL			
Lion Oil 28_33 Fed Com	Pending	Unit B Sec. 28	225'FNL	4,300	0	
# 34H		T22S R32E	1550'FEL			
Lion Oil 28 33 Fed Com		Unit B Sec. 28	255'FNL	 		
# 35H	Pending	T22S R32E	1515'FEL	4,300	0	
			*	4,400	0	
Lion Oil 28_33 Fed Com	¹ Pending	Unit B Sec. 28	835'FNL			
# 14H		T22S R32E	1456'FEL			
Lion Oil 28_33 Fed Com	Pending	Unit B Sec. 28	844'FNL	4,400	0	
# 15H		T22S R32E	1422'FEL			
Lion Oil 28_33 Fed Com	Pending	Unit B Sec. 28	852'FNL	4,400	0	
# 16H		T22S R32E	1388'FEL			

Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, where a gas transporter system is in place. The gas produced from production facility is dedicated to <u>DCP Midstream</u>, <u>LP ("DCP")</u> and is connected to <u>DCP's</u> low pressure gathering system located in Lea, New Mexico. <u>OXY USA INC. ("OXY")</u> provides (periodically) to <u>DCP</u> a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, <u>OXY</u> and <u>DCP</u> have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at DCP's Processing Plant located in Sec. 30, 31 T22S R32E Lea County, New Mexico. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on <u>DCP's</u> system at that time. Based on current information, it is <u>OXY's</u> belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines