

District I

1625 N. French Dr., Hobbs, NM 87402
District II
1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Diazos Rd., Artec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

RECEIVED

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

MAR 06 2008

HOBBS OCD

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well Gas Well Other

2. Name of Operator

Pogo Producing Company

3. Address of Operator

P.O. Box 10340 Midland, Texas 79702

4. Well Location

Unit letter G 1980 feet from the North line and 1980 feet from the East line
Section 8 Township 20S Range 37E NMPM NM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc)

Pit or Below-grade Tank Application or Closure

Pit type Steel Depth to Groundwater 30' Distance from nearest fresh water well 1000' Distance from nearest surface water 71,000'

Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK
- PLUG AND ABANDON
- TEMPORARILY ABANDON
- CHANGE PLANS
- PULL OR ALTER CASING
- MULTIPLE COMPLETIONS

SUBSEQUENT REPORT OF:

- REMEDIATION WORK
- ALTERING CASING
- COMMENCE DRILLING OPS
- PLUG AND ABANDON
- CASING/CEMENT JOB

OTHER: _____

OTHER: _____

13. Describe proposed or completed operations: (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

- 12/27/07 - 1. Tagged existing CIBP at 2,591'.
- 12/28/07 - 2. Attempted to squeeze Cement at 2,550' w/no success PSI to 1,000#, spot 25 sx of Cement at 2,591' (no tag required).
- 1/2/08 - 3. Attempted to squeeze Cement at 2,000' w/no success PSI to 1,000#, spot 25 sx of Cement at 2,050', WOC, tagged at 1,795'.
- 1/2/08 - 4. Attempted to squeeze Cement at 1,127' w/no success PSI to 1,000#, spot 25 sx of Cement at 1,177' tagged at 605'.
- 1/3/08 - 5. Attempted to squeeze Cement at 415' w/no success PSI to 1,000#, spot 65 sx of Cement circulate to surface. Cut off Wellhead and install Dry Hole Marker.

Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cimrd.state.nm.us/oed.

JOB COMPLETE/FILE COPY

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCB guidelines or an (attached) alternative OCD-approved plan .

SIGNATURE

TITLE

DATE 2-7-08

Type of print name: For State Use Only

E-mail address: RABAT

Telephone No. 314/08

APPROVED BY:

TITLE

Geologist

DATE APR 11 2008

Conditions of Approval (if any):