

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

HOBBS OFFICE O. C. C.
NEW MEXICO OIL CONSERVATION COMMISSION

Nov 30 11 46 AM '66

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>	
5. State Oil & Gas Lease No. K 2443	
7. Unit Agreement Name	
8. Farm or Lease Name LANE STATE	
9. Well No. 1	
10. Field and Pool, or Wildcat Wildcat	
12. County Lea	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL GAS WELL OTHER

2. Name of Operator
MONSANTO COMPANY

3. Address of Operator
101 North Marienfeld, Midland, Texas

4. Location of Well
UNIT LETTER **M** **660** FEET FROM THE **South** LINE AND **660** FEET FROM
THE **West** LINE, SECTION **30** TOWNSHIP **10-S** RANGE **34-E** NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

At total depth 4030', due to parted 8-5/8" casing and 10-3/4" wash over pipe being stuck in the hole at 1808', this well will be plugged and abandoned as follows:

**1764' of 8-5/8" casing had been pulled while attempting to repair parted casing.
25-sx cement plug at 1764'
25-sx cement plug at 350', base 10-3/4" casing.
10-sx cement plug at surface in 11-3/4" casing.**

Hole will be filled with heavy drilling mud between each plug. Install 4" x 4" steel marker and clean up location. Verbal approval for this plugging procedure was obtained from Mr. J. D. Ramey on 11-28-66 by Mr. Paul Harryman.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED A. W. Wood **A. W. Wood** TITLE Dist. Prod. Supt. DATE 11-29-66

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: