

| | | |
|------------------------|--|--|
| NO. OF COPIES RECEIVED | | |
| DISTRIBUTION | | |
| SANTA FE | | |
| FILE | | |
| U.S.G.S. | | |
| LAND OFFICE | | |
| OPERATOR | | |

NEW MEXICO OIL CONSERVATION COMMISSION

JUL 30 11 29 AM '65

Form C-100
Supersedes Old
C-102 and C-103
Effective 1-1-65

54. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.
L-3935

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

| | |
|--|---|
| 1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> | 7. Unit Agreement Name |
| 2. Name of Operator Sunray DX Oil Company | 8. Form or Lease Name W. M. State "AZ" |
| 3. Address of Operator P. O. Box 1416, Roswell, New Mexico | 9. Well No. 3 |
| 4. Location of Well C 1980 FEET FROM THE West LINE AND 660 FEET FROM North LINE, SECTION 33 TOWNSHIP 78 RANGE 33E NMPM. | 10. Field and Pool, or Wildcat Undesignated |
| 15. Elevation (Show whether DF, RT, GR, etc.) 4409.5 OL | 12. County Roosevelt |

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

| | | | |
|---|---|--|---|
| PERFORM REMEDIAL WORK <input type="checkbox"/> | PLUG AND ABANDON <input type="checkbox"/> | REMEDIAL WORK <input type="checkbox"/> | ALTERING CASING <input type="checkbox"/> |
| TEMPORARILY ABANDON <input type="checkbox"/> | CHANGE PLANS <input type="checkbox"/> | COMMENCE DRILLING OPNS. <input type="checkbox"/> | PLUG AND ABANDONMENT <input type="checkbox"/> |
| REPAIR OR ALTER CASING <input type="checkbox"/> | | CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/> | OTHER Completion Work <input type="checkbox"/> |

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Drilled to TD 4481'. Ran 4 1/2", J-55, 9.5# csg to csg point 4473'. Cnt'd w/200 sx Incore Pos. WOC 24 hrs. Tested to 1000# 30 min. O.K. Top of cnt by temp. survey 3530'.
2. Perf w/E gum 1 1/2" bullets at 4429, 4438, 4428, 4433, 4477, 4490, 4405, 4325, 4351, 4388, 4398, and 4405. Selectively acidize perfs w/2750 gal Spearhead acid & frac w/20,000 gal ref oil & 20,000# sd.
3. Recovered all lead oil & potential for 252 bbl oil, no wtr., on 2 1/2/6 1/4" ck. GOR 850.

I, I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED B. F. Brawley TITLE District Engineer DATE 7-29-65

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: