

INSTRUCTIONS

This form is to be filled out with the appropriate data at the close of the formation not later than 20 days after the completion of any newly drilled or reworked well. It should be filled out by all owners of an radioactivity log run on the well and a summary of all special tests made on the well. The formation tops should be reported in all measured depths. In the case of directionally drilled wells, true vertical depths shall be reported. The formation thicknesses shall be reported for each zone. The form is to be filed in quadruplicate except on state land, where only two copies are prepared. See Rule 11-9.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____ 2160	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____ 2210	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
H. Salt _____ 2520	T. Anoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____ 2522	T. Mass _____	T. Cliff House _____	T. Leadville _____
T. T. Nixon _____ 2870	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____ 3110	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Gradado _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres _____ 3892	T. Simpson _____	T. Gallup _____	T. Ignacio Qtzite _____
J. Glenora _____ 5337	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Packard _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Banbury _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____ 6000	T. Granite _____	T. Todilto _____	T. _____
T. Brinkard _____ 6960	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abo _____ 7500	T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp _____ 8860	T. _____	T. Chinle _____	T. _____
T. Penn. _____ 9285	T. _____	T. Permian _____	T. _____
T. Cisco (Dough C) _____ 9610	T. _____	T. Penn. "A" _____	T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	2160	2160	Red bed-sand & shale				
2160	2210	50	Anhydrite & dolomite				
2210	2520	310	Salt & anhydrite				
2520	2682	162	Anhydrite & dolomite				
2682	2872	190	Sand & dolomite sand				
2872	3140	268	Dolomite & dolomite sand				
3140	3392	252	Dolomite & anhydritic sand				
3392	5337	1945	Dolomite & anhydritic dolomite				
5337	5422	85	Sand				
5422	6820	1398	Dolomite, sand & shale				
6820	6960	140	sand				
6960	7700	740	Dolomite sand & shale				
7700	8860	1160	Lime and Shale				
8860	9610	750	Lime & shale, chert				
9610	9644	34	Lime & chert				
9644	9665	16	Shale & lime				
TD	9665						