COUNTY CHAVES FIELD Chaveroo STATE NM

OPR CHAMPLIN PETROLEUM COMPANY MAP

7 State "6"

Sec. 6, T-8-S, R-33-E CO-ORD

1980' FNL, 1980' FEL of Sec. MC 10481 [redacted]

Spd 7-16-66 CLASS

Cmp 8-12-66

FORMATION	DATUM	FORMATION	DATUM

CSG & SX - TUBING

8 5/8" 366' 250
4 1/2" 4415' 325

LOGS EL GR RA IND HC A

TD 4415', PBD 4413'

IP San Andres Perfs 4166-4332' Pmpd 19 BOPD + 160 BW. Pot. Based on 24 hr test, TP 20#, CP 50#, Gravity 25.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Sitton & Norton PROP DEPTH 4500' TYPE

DATE

F.R. 7-14-66
PD 4500' - SA
Contractor - Sitton & Norton

7-25-66 Drlg. 4220' lm.

8-1-66 TD 4415', PBD 4413', RU Pump.
Perf @ 4166', 4196', 4218', 4247', 4279', 4289', 4332' W/2 SPI
Perf @ 4176', 4206', 4300', 4308', 4314', 4321' W/1 SPI
Acid (4166-4332') 500 gals.
Frac (4166-4332') 50,000 gals wtr + 40,000# sd.

8-8-66 TD 4415', PBD 4413', pmpg load.

8-15-66 TD 4415', PBD 4413', pmpg load.

8-22-66 TD 4415', PBD 4413', WO Pot.
Pmpd 19 BO + 160 BW/24 hrs.

8-29-66 TD 4415', PBD 4413', COMPLETE.
LOG TOPS: Yates 2341', Queen 3007', San Andres 3573'.