



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Las Cruces  
Lease No. 061051  
Unit \_\_\_\_\_

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

**Federal A Trigg**

**February 13,** 19**53**

Well No. 1 is located 660 ft. from N line and 660 ft. from E line of sec. 20  
NE/4, NE/4 Sec. 20 13E 33E  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Wilcox Lea New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is \_\_\_\_\_ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Plan to drill a Devonian test with company rotary tools. 17 1/2" hole to approximately 350' where 13-3/8" OD 40# Grade N-40 new casing will be set & cemented w/ approximately 300 sks. regular cement, circulate to surface. Then continue drilling w/ 12-1/4" hole to a depth of approximately 4200' where 9-5/8" OD 40# Grade S-95 new casing will be set at 3450' and 9-5/8" OD 40# Grade N-80 new casing will be set at approximately 4200' cemented w/ approx. 3000 sks cement w/ 3% gel. Then continue drilling 8-3/4" hole to approx. 13,500' where 5-1/2" casing will be set at approx. 9200' of 17# Grade N-80 new casing and 4400' of 20# Grade N-80 new casing on top, cement w/ approx. 3000 sks. cement w/ 3% gel. All casing will be cemented and tested by approved method.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company The Ohio Oil Company

Address P. O. Box 2107

Hobbs, New Mexico

By Frank Barrett

Title Superintendent