

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 10000 feet, and from _____ feet to _____ feet.
 Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

PRODUCTION

Put to Producing 11-26-53, 19_____
 OIL WELL: The production during the first 24 hours was 209.76 barrels of liquid of which 99.20% was oil; _____% was emulsion; _____% water; and .80% was sediment. A.P.I. Gravity 13.1 corrected
 GAS WELL: The production during the first 24 hours was _____ M.C.F. plus _____ barrels of liquid Hydrocarbon. Shut in Pressure _____ lbs.
 Length of Time Shut in _____

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy.....	1523'	T. Devonian.....	T. Ojo Alamo.....
T. Salt.....	1612'	T. Silurian.....	T. Kirtland-Fruitland.....
B. Salt.....	2470'	T. Montoya.....	T. Farmington.....
T. Yates.....	2620'	T. Simpson.....	T. Pictured Cliffs.....
T. xxxxxx Artesia Rd. Sd.....	3400'	T. McKee.....	T. Menefee.....
T. Queen.....		T. Ellenburger.....	T. Point Lookout.....
T. Grayburg.....		T. Gr. Wash.....	T. Mancos.....
T. San Andres.....	4119'	T. Granite.....	T. Dakota.....
T. xxxxxx Paddock.....	5975'	T.	T. Morrison.....
T. xxxxxx Clearfork.....	6356'	T.	T. Penn.....
T. Tubbs.....	6997'	T.	T.
T. Abo.....	7737'	T.	T.
T. Penn.....	9358'	T.	T.
T. Miss.....		T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	6	6	Cellar				
6	220	214	Sand & Caliche				
220	300	80	Red Bed, Sand & Shale				
300	1523	1223	Sand & Shale				
1523	1612	89	Sand, Anhydrite & Shale				
1612	2620	1008	Shale, Anhydrite & Salt				
2620	3230	610	Shale, Anhydrite & Sand				
3230	3400	170	Shale & Anhydrite				
3400	3500	100	Shale, Anhydrite & Sand				
3500	4119	619	Shale, Anhydrite, Sand & Salt				
4119	5550	1431	Dolomite w/ Anhydrite Stringers				
5550	5662	112	Limestone & Dolomite				
5662	5775	113	Dolomite & Anhydrite				
5775	6356	581	Dolomite, Sand & Anhydrite				
6356	6997	641	Dolomite w/ Anhydrite Stringers				
6997	7737	740	Dolomite, Sand & Anhydrite				
7737	8340	603	Shale, Dolomite & Anhydrite				
8340	9080	740	Anhydrite & Dolomite				
9080	9150	70	Chert & Dolomite				
9150	9230	80	Chert, Limestone & Dolomite				
9230	9270	40	Lime				
9270	9320	50	Dolomite, Chert & Lime				
9320	9620	500	Chert, Lime & Shale				
9620	10000	380	Lime & Shale				
	10000		Total Depth				
	9990		Drilled Out Depth				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

December 9, 1953 (Date)
 Company or Operator Amerada Petroleum Corporation Address Box 636 - Lovington, New Mexico
 Name *[Signature]* Position or Title Farm Boss