

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

RECEIVED
JUL 9 1953
OIL CONSERVATION COMMISSION
HOBBBS OFFICE

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELLS	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

July 8, 1953

Odessa, Texas

(Date)

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Forest Oil Corporation & Houston Oil Company

State (No. 10291)

(Company or Operator)

(Lease)

Llane Drilling Company

(Contractor)

Well No. **1** in the **SW** 1/4 **NW** 1/4 of Sec. **26**

T. **13-S**, R. **37-E**, NMPM., **King-Wolfe Camp** Pool, **Lee** County.

The Dates of this work were as follows: **July 4, 5, 6, 7, 1953**

Notice of intention to do the work (was) ~~(was not)~~ submitted on Form **C-101** on **June 11,** 19**53**,
(Cross out incorrect words)

and approval of the proposed plan (was) ~~(was not)~~ obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

On July 4, 1953 this well reached a depth of 4,735' in limestone. On July 5, 1953, 9 5/8" O.D. 3/4 36 & 3/4 40 casing was cemented at 4,730' with 1,300 sks. of 1 1/2 gal cement, 250 sks. Strata Crete and 200 sks. neat cement.

A temperature survey by Halliburton showed the top of the cement to be at 2,300' which was above the top of the salt section which was topped at 2,310'.

On July 7, 1953 prior to drilling the cement plug, a pressure of 1000 was held for 30 minutes on the casing. The plug, cement and shoe was drilled out, and 800 pressure was held for 30 minutes on the open hole with no drop which indicated no channeling of cement.

Witnessed by **Lee Dean** (Name) **Llane Drilling Company** (Company) **Tool Pusher** (Title)

Approved: OIL CONSERVATION COMMISSION

Roy Yurkovich (Name)
Oil & Gas Inspector (Title)

JUL 9 1953 (Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: **J.R. Knight**
Position: **District Production Superintendent**
Representing: **Forest Oil Corporation**
Address: **Box 4106, Odessa, Texas**

Handwritten signature or scribble at the bottom right of the page.