

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

5a. Indicate Type of Lease  
State  Fee

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Newhall Resources	8. Farm or Lease Name Speight
3. Address of Operator P.O. Box 8629 Midland, TX 79708	9. Well No. 1
4. Location of Well UNIT LETTER <u>A</u> <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>15</u> TOWNSHIP <u>13-S</u> RANGE <u>38-E</u> NMPM.	10. Field and Pool, or Wildcat Bronco Siluro/Devonian
15. Elevation (Show whether DF, RT, GR, etc.) 3806.5	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Sidetracked hole @ 10,440'. Drilled a 6" hole from 10,391 to TD (11,890') Reached TD on 10/2/86. Ran a DST in the Devonian formation from 11,858 to 11,890'. Ran a 5" 18#/ft S-95 flush Jt. liner from 11,890 to 9983. Set a 5" x 7" Baker Simplex liner hanger @ 9983 and cemented liner in place. Halliburton cemented w/170 sx of Class "H" cement w/3# per sack salt, .5% CFR-2, .6% Halad 22-A. Cement circulated to liner top.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED: J E Brusenhan TITLE: Production Manager DATE: 10/8/86

APPROVED BY: \_\_\_\_\_ TITLE: \_\_\_\_\_ DATE: \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: