

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPlicate
(Other instructions on reverse side)

1. Form approved by
Budget Bureau No. 1004-0-10
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

LC-030437A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL GAS WELL OTHER Injection

2. NAME OF OPERATOR
Conoco Inc.

3. ADDRESS OF OPERATOR
P.O. Box 460 - Hobbs, NM 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface
1980' FNL & 660' FEL

14. PERMIT NO. 30-025-00697

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4001 DF

7. UNIT AGREEMENT NAME

MCA Unit #1, 4

8. FARM OR LEASE NAME

9. WELL NO.

#141

10. FIELD AND POOL OR WILDCAT

Maljamar G-5A

11. SEC., T./R., M., OR BLK. AND SURVEY OR AREA

Sec. 26, T17S, R32E

12. COUNTY OR PARISH 13. STATE

Lea NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other) Convert to Cased Hole

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

C.O. to 4276'. Drill new hole to 4295'. Run 20 jts. 2-7/8" fiberglass liner in hole on 2-3/8" workstring. Establish circ. of 2 BPM. Pump (volume to be determined based on new caliper) 50/50 Pozmix Class C cement w/.45 gps D604 and .7% CaCl2 at 1-2 BPM. Reverse out cement above liner. w/o cement 24-36 hours. Drill out to 4295'. Run CBL-GR-CCL log from 3600'-4295'. Spot 3 bbls acid in fiberglass. Perf. 10SPF: 4282'-44', 4212'-4192', 4174'-60', 4142'-24', 4112'-4092', 4078'-72', 4057'-52', 4043'-4036'. Acidize Grayburg 6th & S-A 7th w/140 wbls 15% HCL-NE-FE. Return to inj.

18. I hereby certify that the foregoing is true and correct

SIGNED W.W. Baker W.W. Baker

TITLE Administrative Supervisor

DATE October 2, 1989

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

Adan

*See Instructions on Reverse Side