

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

INDEXED - 1000000000

MISCELLANEOUS REPORTS ON WELLS

1954 AUG 27 PM 3:27

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other) ACID TREATMENT	X

August 24, 1954

(Date)

Hobbs, New Mexico

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

John J. Christmann

(Company or Operator)

Tennaco

(Lease)

Clarke Oil Well Servicing Co.

(Contractor)

Well No. 3

in the SE 1/4 SW 1/4 of Sec. 4

T-16-S, R-35-E, NMPM.

Tennaco Wolfcamp

Pool,

Lee

County.

The Dates of this work were as follows: August 9-23, 1954

Notice of intention to do the work (was) ~~REMOVED~~ submitted on Form C-102 on August 6, 1954

(Cross out incorrect words)

and approval of the proposed plan (was) ~~REMOVED~~ obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Loaded well with 300 barrels oil. Then, using The Chemical Process Company, treated through casing perforations 10,340 - 10,352 and 10,360 - 10,436 feet with 1000 gallons Formjel followed by 8000 gallons 15% LST acid. Acid injection pressures: maximum 4200 psi, final 3400 psi. Total oil and acid load 643 barrels. Recovered load and flowed well one week. Well then flowed 203 barrels clean oil in 24 hours through 1 5/8-inch tubing choke. Flowing casing pressure 1570 psi. Flowing tubing pressure 875 psi. Gas-oil ratio 1482.

Witnessed by L. O. Storn

(Name)

John J. Christmann

(Company)

Engineer

(Title)

Approved: OIL CONSERVATION COMMISSION

L. G. Stanley

(Name)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: L. O. Storn

Position: Engineer

Representing: John J. Christmann

Address: 1114-10th St., Lubbock, Texas

Engineer District I

(Title)

AUG 25 1954

(Date)

THE UNIVERSITY OF CHICAGO
DEPARTMENT OF CHEMISTRY

PHYSICAL CHEMISTRY LABORATORY

REPORT ON THE EXPERIMENT DETERMINATION OF THE RATE OF REACTION OF
HYDROGEN PEROXIDE WITH POTASSIUM IODIDE

BY [Name]

ADVISOR: [Name]

DATE: [Date]

1. INTRODUCTION

2. THEORY

3. EXPERIMENTAL PROCEDURE

4. RESULTS AND DISCUSSION

5. CONCLUSIONS

6. REFERENCES

7. APPENDICES

8. ACKNOWLEDGMENTS

9. BIBLIOGRAPHY

10. SUMMARY

11. INDEX