

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO.
30-025-31229

5. Indicate Type of Lease
STATE FEE

6. State Oil & Gas Lease No.
V-2032

7. Lease Name or Unit Agreement Name

Hondo State

8. Well No.
#1

9. Pool name or Wildcat
North Sanmal Penn

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE 'APPLICATION FOR PERMIT' (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL GAS WELL OTHER

2. Name of Operator
Hondo Drilling Company

3. Address of Operator
P.O. Drawer 2516 Midland, TX 79702

4. Well Location
Unit Letter 0 : 810' Feet From The South Line and 1,980' Feet From The East Line
Section 18 Township 16-S Range 33-E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
4,248' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER: <input type="checkbox"/>	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12-9-92 Pulled 2 3/8" tubing & Guiberson Packer out of hole.
Run 2 3/8" tubing back in hole. Set cement plug @ 5,703'.

12-10-92 Tag cement plug at 5,542', 161' cement plug.
Displaced hole with 10 lb. mud, laid down 136 joints 2 3/8" tubing. Set 100 ft. cement plug from 1,400' to 1,500'.

12-11-92 Cut off wellhead, set 10' cement plug top of 8 5/8" casing & dry hole marker.

Approved as to plugging of the Well Bore.
Liability under bond is retained until
surface restoration is completed.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Nathan W. Outlaw TITLE President DATE 12/14/92

TYPE OR PRINT NAME Nathan W. Outlaw TELEPHONE NO.

(This space for State Use)

APPROVED BY Gary W. Wink TITLE OC FIELD REPRESENTATIVE II/STAFF MANAGER DATE JAN 23 1993

CONDITIONS OF APPROVAL, IF ANY:

Handwritten initials or mark.