Form 3160-5 (June 1990)

1. Type of Well

2. Name of Operator

Oil Gas Well

3. Address and Telephone No.

X Other

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

105 South 4th St., Artesia, NM 88210

YATES PETROLEUM CORPORATION

SWD

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPRO	OVI	ED
Budget Bureau No.	100	04-0135
Expires: March	31	1993

5. Lease Designation and Serial No.

SUNDRY NOTICES	AND REPORTS	S ON WELLS
----------------	-------------	------------

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

NM 59392 6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Lusk SWD #1

11. County or Parish, State

30-025-31051

10. Field and Pool, or Exploratory Area

East Lusk Delaware

9. API Well No.

Unit C, 660' FNL, 2310' FWL, CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPOR	Lea, NM T, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent Subsequent Report Final Abandonment Notice	Abandonment Recompletion Plugging Back Casing Repair Altering Casing X Other WORKOVER, Add perfs & treat perfs & frac unfraced zones	

8-5-92. POH w/packer and 2-7/8" plastic-coated tubing from 4600'. RU wireline. Perforated as follows: 7284-7344' (1 SPF) 61 holes; 6920-6972' (1 SPF) 53 holes; and 6407-6474' (1 SPF) 68 holes. Acidized perfs 7284-7344' w/2000g. 7½% NEFE. Frac'd 7284-7344' w/24500g. 35# XL and 60000# 20/40 sand. Acidized perfs 6920-6972' w/2000g. 7½% NEFE. Frac'd 6920-72' w/24500g. 35# XL and 60000# 20/40 sand. Acidized perforations 6384-6474' w/2000g. 7½%. Frac'd perfs 6384-6474'

w/36750g. 35# XL and 90000# 20/40 sand. Acidized perfs 5121-5138 w/750g. 7½% NEFE. Frac'd perfs 5121-5138' w/6125g. 35# XL and 15000# 20/40 sand. Acidized perfs 4733-4742' w/500g. 7½%

8-11-92. WIH w/nickel-plated packer and plastic lined 2-7/8" tubing to 4650'. Circulated packer fluid. Set packer. Flanged wellhead up. Tested annulus to 450 psi for 15 minutes.

8-1-92. Acidized existing perfs 4733-7678' (120 holes) w/10000g. 15% NEFE acid.

NEFE. Frac'd perfs 4733-4742' w/6125g. 35# XL and 15000# 20/40 sand.

(505) 748-1471)

Tested good. Witnessed by L. W. Hill, NMOCD, Hobbs, NM. Returned to injection.

14. I hereby certify that the foregoing is true and correct Signed A Garda Day: All III	Title Production Supervisor	8-14-92
(This space for Federal or State office use) Approved by Conditions of approval, if any:	Title	Date