

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELL

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-offs, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON DEEPENING WELL
REPORT ON RESULT OF PLUGGING OF WELL		

Monument, New Mexico. July 3, 1939.

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation

State LA

C of NE $\frac{1}{4}$ of SW $\frac{1}{4}$

Company or Operator

Lease

Well No. 2

in the

of Sec. 1

T.

17s

36s

N. M. P. M.,

South Lovington

Field,

Lea

County

The dates of this work were as follows:

July 1, 1939.

Notice of intention to do the work was (was not) submitted on Form C-102 on June 29, 1939.
and approval of the proposed plan was (was not) obtained. (Cross out incorrect words) 19

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

With the well drilled to a TD of 4630', 5 $\frac{1}{2}$ " OD Seamless casing was set at 4620' and cemented with 230 sacks of El Toro cement. The plug was pumped to 4554 @ 7 p.m. 6-28-39.

The well was allowed to stand undisturbed for a period of 72 hours. Pump pressure of 1400# was applied to the pipe and fittings, the valves closed, and the pressure within observed for a period of 30 minutes. There was no drop in pressure. The cement plug was then drilled and the same test again applied with like result. Drilling was resumed on the night of July 1, 1939.

Witnessed by L.E. Stuart Noble Drilling Company Tool Pusher.
Name Company Title

Subscribed and sworn to before me this

3

day of

July

19 39

Lewis A. Manne

Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name

Position

Representing

Address

J. O. Michael

Foreman

Amerada Petroleum Corporation

Monument, New Mexico.

My Commission expires

December 21, 1940.

Remarks:

Roy Harkrath

Name

Title

VSP