

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Hondo Oil & Gas Company

3. Address and Telephone No.

P. O. Box 2208, Roswell, NM 88202 (505)625-6732

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2310' FSL & 990' FEL; Sec.35-T19S-R34E

5. Lease Designation and Serial No.

NM 052

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

#891007465C

Mescalero Ridge Unit 35

8. Well Name and No.

~~Mescalero Ridge 35~~ #9

9. API Well No.

30-025-2126400S1

10. Field and Pool, or Exploratory Area

Pearl Seven Rivers

11. County or Parish, State

Lea Co., NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Sqz old perfs. & perf.
7 Rivers higher.
- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5/04/91 POH w/tbg & pkr. RIH w/ tbg & cement retainer, set cmt. retainer @ 3976'.
5/05/91 RU cmt co. & press. annulus to 500 psi. Establish injection into 7 Rivers "C" perfs 4003'-4015' @ 3 BPM & 1400 psi. Squeezed perfs w/ 100 sx Class "C". Displaced hole w/ 2% KCL wtr + 1 gal/1000 LST Surfactant. SD. WOC.
5/06/91 SI, WOC.
5/07/91 Perf'd 5 1/2" csg from 3926'-3944' w/ 1 JSPF = 19 holes = .528 hole, acidized w/ 3000 gals 7 1/2% NeFe, ISIP 1300 psi.
5/09/91 Frac'd 7 Rivers "B" perfs 3926'-3944' w/ 30,000 gals Crosslinked gelled 2% KCL wtr & 41,000# 12/20 sand & 12,000# 12/20 curable resin coated sd. ISIP 2400psi.
5/29/91 Reperforated 7 Rivers "B" Zone 3927'-3931' (5 holes) & 3936'-3941' (5 holes) for a total of 10 holes @ 1 JSPF.
5/30/91 Acidized 7 Rivers "B" perfs 3926'-3944' w/ 4000 gals 7 1/2% acid in 4 stages using 750# of Rock Salt & 1000 SCF/bbl N2, ISIP 3200 psi.
6/01/91 Refrac'd 3926'-3944' w/ 2000 gals prepad containing 10% mutual solvent & 10,000 gals crosslinked gelled 2% KCL wtr & 17,000# 12/20 sand ramped from 1-4 #/gal, ISIP 2300 psi. (cont.)

14. I hereby certify that the foregoing is true and correct

Signed E. L. B. [Signature]

Title Petroleum Engineer

Date 7/8/91

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date

Form 3160-5

Page 2

Hondo Oil & Gas Company

Mescalero Ridge Unit 35 #9

Pearl Seven Rivers

Lea Co., NM

2310' FSL & 990' FEL; Sec.35-T19S-R34E

July 8, 1991

Part 13. cont.

- 6/04/91 Released pkr @ 3797' & tagged sand @ 3891' (perfs @ 3926'-3944'). TOH & LD pkr. PU 3 3/4" Bulldog railer w/ 2 7/8" notched collar & bailed sand from 3891'-3902', could not go any deeper.
- 6/05/91 Perf'd 7 Rivers @ 3881'-3891' w/ 1 JSPF (11 holes) & 3875'-3885' w/ 1 JSPF (11 holes) for a total of 22 holes.
- 6/13/91 TIH w/ 2"X1 1/2"X12' RWBC pump, hung well on & started pumping.
- 6/25/91 On Potential Test:

Well flowed: 49 MCFPD.

NOTE: Well is pumped 3 hrs. a day to move fluid.

RECEIVED

JUL 26 1991

OK
JUL 26 1991