

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form O-103
Revised 10-1-78

API No. 30-025-26376

5a. Indicate Type of Lease
State Fine
5. State Oil & Gas Lease No.
B-1497

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO PERMIT OR TO OPERATE OR FLOOD BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT TO PERFORM C-101" FOR SUCH PROPOSALS.)

1. OIL WELL GAS WELL OTHER
2. Name of Operator
Phillips Petroleum Company
3. Address of Operator
Room 401, 4001 Penbrook Street, Odessa, Texas 79762
4. Location of Well
UNIT LETTER E 1460 FEET FROM THE North LINE AND 1310 FEET FROM
THE West LINE, SECTION 26 TOWNSHIP 17-S RANGE 35-E
5. Elevation (Show whether DF, RT, GR, etc.)
3911' GR
6. County
Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
FULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	
		OTHER <u>Total Depth</u>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 9-11-79 MI Cactus Drlg. Spudded w/17-1/2" bit @ 4:15 p.m. 9-11-79 Drld to 369'. Ran 13-3/8" 48#, H-40, 8 rd, ST&C csg set @ 369'. Cmtd w/675 sms Cl H w/2% CaCl₂, 1/4# Cello flakes. Circ 150 sms to surface. WOC 24+ hrs.
- 9-13-79 NU BOP's test ok. Drld. out 30' cmt. and 536' formation w/11" bit.
- 9-14-79 Drld ahead w/8-3/4" bit.
- 9-25-79 Reached TD 4800'. C&CM for logging.
- 9-27-79 Ran 126 jts 7", 23#, K-55, LT&C and ST&C csg set @ 4798' cmt w/1,000 sms TLW, 12# salt, 10% D.D., 1/4#/sx Flocele, 3#/sx Gilsonite. Tail in w/400 sms Cl H, 8# salt. Circ 216 sms TLW. Release rig. Prep perf.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed by W. J. Mueller TITLE Sr. Engineering Specialist DATE 9-28-79

APPROVED BY John Ranyo TITLE _____ DATE OCT - 4 1979
Geologist

CONDITIONS OF APPROVAL, IF ANY: