

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPPLICATE  
(Other instructions  
reverse side)

Budget Bureau No. 1004-4.3  
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐ Drilling Well

2. NAME OF OPERATOR  
Barbara Fasken

3. ADDRESS OF OPERATOR  
303 W. Wall, Suite 1900, Midland, Texas 79701-5116

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)  
1980' FSL & 660' FWL  
3604.2' GR

5. LEASE DESIGNATION AND SERIAL NO.  
NM-14496

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Ling Federal

9. WELL NO.  
2

10. FIELD AND POOL OR WILDCAT  
Quail Ridge (Morrow)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
31, T-19-S, R-34-E

12. COUNTY OR PARISH  
Lea

13. STATE  
New Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

16. NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASING
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	ABANDONMENT*
REPAIR WELL	CHANGE PLANS	(Other) Run & cement intermediate csg.	X

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- May 10 to 20, 1988, drilling 12 1/4" hole to 5160' with brine water and mud.
- May 20, 1988 ran in hole as follows: 1 8-5/8" Trico notched guide shoe 1.50', 1 jt. 8-5/8" K-55 32#/ft. casing 39.33', 1 Trico float collar 1.90', 72 jts. 8-5/8" K-55 32#/ft. casing 2854.20', 56 jts. 8-5/8" K-55 24# casing 2272.00', less cut off 22.36'. Total 5,146.57'.
- May 20, 1988, cemented w/500 gals. floguard, 2000 sx BJ lite w/15#/fk, 1/2# celloflake/sk, s.w. 12.8 ppg, yield 2.05 cuft/sk + 300 sx Class "C" neat, s.w. 14.8 ppg, yield 1.32 cuft/sk. Plug down at 7:30 p.m. C.D.T., circ 542 sx excess cement.
- WOC & NU BOP 17 1/2 hrs. before drill out.
- Tested 8-5/8" casing to 1500# for 1/2 hr., held OK.
- Drilled cement and plug.
- May 21, 1988, drilling 7-7/8" hole @ 5400' with fresh water.

18. I hereby certify that the foregoing is true and correct

SIGNED C. Lynn Smith

TITLE Agent

DATE 5-23-88

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

JUN 7 1988

\*See Instructions on Reverse Side

SJS  
CARLSBAD, NEW MEXICO