

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO.
30-025-31834 ✓

5. Indicate Type of Lease
STATE FEE

6. State Oil & Gas Lease No.
B-1520-1

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

7. Lease Name or Unit Agreement Name
VACUUM GLORIETA WEST UNIT

1. Type of Well:
OIL WELL GAS WELL OTHER WATER INJECTION

8. Well No.
5

2. Name of Operator
TEXACO EXPLORATION AND PRODUCTION INC.

3. Address of Operator
P. O. Box 3109 Midland, Texas 79702

9. Pool name or Wildcat
VACUUM GLORIETA

4. Well Location
Unit Letter N : 1209 Feet From The SOUTH Line and 2582 Feet From The WEST Line
Section 24 Township 17-SOUTH Range 34-EAST NMPM LEA County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
GR-4001', KB-4015'

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	
OTHER: _____ <input type="checkbox"/>		OTHER: PRODUCTION CASING <input checked="" type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. DRILLED 7 7/8 HOLE TO 6475'. TD @ 4:00 PM 04-28-93.
2. HLS RAN GR-DLL-MSFL, GR-DSN-SDL-CAL FROM 6460' TO 4460'. PULLED GR-DSN TO SURFACE.
3. RAN 23 JOINTS OF 5 1/2, 17# WC-50 AND 131 JTS OF 15.5#, LTC CASING SET @ 6475'.
4. DOWELL CEMENTED WITH 1550 SACKS 35/65 POZ CLASS H W/ 6% GEL, 5% SALT, 1/4# FLOCELE (12.8 PPG, 1.94 CF/S). F/B 200 SACKS CLASS H (15.6 PPG, 1.18 CF/S). PLUG DOWN @ 5:00 AM 04-29-93. DID NOT CIRCULATE CEMENT.
5. RAN TEMPERATURE SURVEY. TOP OF CEMENT @ 800'.
6. ND. RELEASE RIG @ 8:00 AM 04-29-93.
7. PREP TO COMPLETE.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE C.P. Basham / SDH TITLE DRILLING OPERATIONS MANAGER DATE 05-03-93

TYPE OR PRINT NAME C.P. BASHAM TELEPHONE NO. 915-6884620

(This space for State Use)

orig. Signed by
Paul Kautz
Geologist

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

MAY 06 1993