

District I
PO Box 1980, Hobbs, NM 88241-1980
District II
PO Drawer DD, Artesia, NM 88211-0719
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
PO Box 2088, Santa Fe, NM 87504-2088

State of New Mexico
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, NM 87504-2088

Form C-101
Revised February 10, 1994
Instructions on back
Submit to Appropriate District Office
State Lease - 6 Copies
Fee Lease - 5 Copies

☐ AMENDED REPORT

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

¹ Operator name and Address Amerada Hess Corporation P.O. Box 2040 Houston, TX 77252-2040		² OGRID Number 000495
⁴ Property Code 000135	⁵ Property Name NORTH MONUMENT GRAYBURG SAN ANDRES UNIT	³ API Number 30-0 25-33996
		⁶ Well Number 292

⁷ Surface Location									
UL or lot no.	Section	Township	Range	Lot. Idn	Feet from the	North/South Line	Feet from the	East/West line	County
D	32	19 S	37 E		1270	NORTH	1245	WEST	LEA

⁸ Proposed Bottom Hole Location If Different From Surface									
UL or lot no.	Section	Township	Range	Lot. Idn	Feet from the	North/South Line	Feet from the	East/West line	County
⁹ Proposed Pool 1					¹⁰ Proposed Pool 2				
EUNICE-MONUMENT/GRAYBURG-SAN ANDRES									

¹¹ Work Type Code N	¹² Well Type Code O	¹³ Cable/Rotary R	¹⁴ Lease Type Code P	¹⁵ Ground Level Elevation 3589'
¹⁶ Multiple NO	¹⁷ Proposed Depth 4100'	¹⁸ Formations GRYBRG-S. ANDRES	¹⁹ Contractor PATTERSON	²⁰ Spud Date 06-09-97

²¹ Proposed Casing and Cement Program					
Hole Size	Casing Size	Casing weight/foot	Setting Depth	Sacks of Cement	Estimated TOC
12-1/4"	9-5/8"	36#	1200'	650	SURFACE
8-3/4"	7"	20#	3900'	920	SURFACE
Permit Expires 1 Year From Approval Date Unless Drilling Underway					

²² Describe the proposed program. If this application is to DEEPEN or PLUG BACK give the data on the present productive zone and proposed new productive zone. Describe the blowout prevention program, if any. Use additional sheets if necessary.

1. DRILL AN 12-1/4" HOLE TO 1200' AND SET 1200' OF 36#, 9-5/8" SURFACE CASING. CEMENT W/ 650 SX. OF 65/35 POZ AND CIRCULATE TO SURFACE.
2. DRILL AN 8-3/4" HOLE TO 3900' AND SET 3900' OF 20#, 7" PRODUCTION CASING. CEMENT W/ 920 SX. OF CLASS 'C' AND CIRCULATE TO SURFACE.
3. DRILL AN 6-1/4" HOLE FROM 3900' TO TD AT 4100'. OPEN HOLE COMPLETION FROM 3900' TO 4100'.

²³ I hereby certify that the information given above is true and complete to the best of my knowledge and belief.

Signature: *Mike Jumper*

Printed name: MIKE JUMPER

Title: ADM. SUPERVISOR DRILLING SERVICES

Date: 05-27-97 Phone: (713) 609-4846

OIL CONSERVATION DIVISION	
Approved by: <i>Chris Williams</i>	
Title: DISTRICT I SUPERVISOR	
Approval Date: JUN 03 1997	Expiration Date:
Conditions of Approval: Attached <input type="checkbox"/>	

FOR RECORD ONLY