Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

N.M. Oil Cons. Division 1625 N. French Dr. Hobbs, NM 88240 FORM APPROVED Budget Bureau No. 1004-0135

0440	Expires: March 31, 1993
5. Le	ase Designation and Serial No.

0/4/25// 1/25/25/2	LC-031621-A	
SUNDRY NOTICES AND Do not use this form for proposals to drill of Use "APPLICATION FOR	6. If Indian, Allottee or Tribe Name	
SUBMIT IN	7. If Unit or CA, Agreement Designation	
Oil Gas Well Other 2. Name of Operator	8. Well Name and No. H.M. Britt #14	
Doyle Hartman 3. Address and Telephone No.	9. API Well No. 30-025-35152	
500 N. Main St., Midland, Texas 79701 (915-68 4. Location of Well (Footage, Sec., T., R., M., or Survey Descrip	10. Field and Pool, or Exploratory Area Eumont (Y-7R-Qn) Gas	
1400' FSL & 2310' FEL Section 7, T-20-S, R-37-E, NMPM (J-7-20S-37E)	11. County or Parish, State	
12. CHECK APPROPRIATE BOX(s) To	O INDICATE NATURE OF NOTICE, REPORT, C	Lea County, NM OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
☐ Notice of Intent ☐ Subsequent Report ☐ Final Abandonment Notice	Abandonment Recompletion Plugging Back Casing Repair Altering Casing Other Set 7" Production Casing	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion or Recompletion Report and Log form.)
Type S-4 centralizers. Cemented casing, at a rate Class-C cement containing 2% Econolite, 0.5 lbs Class-C cement and Pozmix "A" containing 0.5 lb	D-CNL-GR-CAL log and AzLL-MCFL-GR log. casing equipped with 7" Super Seal Float Shoe, 7" Super 8.5 BPM, with 1793 cu.ft. of cement slurry consisting logical states of 8.5 BPM, with 1793 cu.ft. of cement slurry consisting logical states of 8.5 BPM, with 1793 cu.ft. of cement slurry consisting logical states of 8.5 BPM, with 1793 cu.ft. of 2.30 Fessure logical states of 8.5 BPM, with 1793 cu.ft. of 8.5 BPM, with 1793 cu	g of 675 sx of 12.4 lb/gal API a 14.2 lb/gal 50-50 blend of API P.M., CDT. 10-6-00. Circulated
Installed 7" slip x 8 Rd collar. Installed B&M Oil T Pressure held okay.	ool 7" x 2 3/8" x 3" Type MR tubinghead. Pressure test	ted 7" O.D. casing to 3150 psi.
Tressure field okay.		
····-	:	
14. I hereby certify that the foregoing is true and correct Signed Live Dunck (This space for Federal or State office use)	Title Tricia Barnes, Production Analyst	Date 10/09/00
Approved by	Title 50 2000 2000 2000 2000 2000 2000 2000	. Date

