

TRIPPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

NOTICE OF INTENTION TO DRILL

RECEIVED SEP 8 1947 HOBB'S OFFICE

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing the changes must be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Hobbs, New Mexico

September 5, 1947

Place


Date

OIL CONSERVATION COMMISSION, Santa Fe, New Mexico,

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as Pacific Western Oil Corp. - D. C. Hardy. Well No. 4 in SW/4 SE/4

Company or Operator Lease of Sec. 20, T 21S, R 37E, N. M., P. M., Drinkard Field, Lea County.



AREA 640 ACRES

The well is 510 feet (N.) (X) of the South line and 1980 feet (E) (W.) of the East line of Sec. 20

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. Assignment No.

If patented land the owner is Virgil Linam

Address Hobbs, New Mexico

If government land the permittee is

Address

The lessee is Pacific Western Oil Corp.

Address c/o Skelly Oil Co., Tulsa, Oklahoma

LOCATE WELL CORRECTLY

We propose to drill well with drilling equipment as follows: Rotary tools from top to total depth. Contractor - Coats & Foster Drlg. Co.

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows:

We propose to use the following strings of casing and to land or cement them as indicated:

Table with 7 columns: Size of Hole, Size of Casing, Weight Per Foot, New or Second Hand, Depth, Landed or Cemented, Sacks Cement. It lists three casing strings: 16" hole with 13-3/8" casing, 10 1/4" hole with 8-5/8" casing, and 6 1/4" hole with 5-1/2" casing.

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 6575 feet.

Additional information: In cementing above casing strings Halliburton Process shall be used. Cement shall be allowed sufficient time to thoroughly set before drilling plug and testing.

Approved SEP 8 1947, 19 except as follows:

Sincerely yours, Skelly Oil Co., Operator for Pacific Western Oil Corp.

By [Signature] Position Dist. Supt.

Send communications regarding well to

Name Skelly Oil Company

Address Hobbs, New Mexico

OIL CONSERVATION COMMISSION, By Roy [Signature] Title Oil & Gas Inspector